



CANADA

LOCKS AND BUILDERS HARDWARE

Catalog No. 2

CORBIN LOCK Company of Canada Limited

Locks and
Builders' Hardware

Good Buildings Deserve Good Hardware



DESIGNED in direct response to the expressed wishes of representative hardware men, we believe this new CORBIN Catalogue contains the most complete line of builders' hardware in existence. Numerous features have been incorporated which enable the catalogue user to find complete information about CORBIN products quickly and easily.

As new products appear, or as lines are changed from time to time, you will receive new pages for insertion in this binder. The careful hardware man will appreciate the importance of inserting such changes promptly and accurately in their proper place in order that this catalogue will continue to serve as a valuable, dependable aid to building more hardware business.

Corbin Lock Company of Canada Limited

BELLEVILLE

ONTARIO - CANADA

COPYRIGHT 1954 THE CORBIN LOCK COMPANY OF CANADA LIMITED

All rights reserved including the right of translating into foreign languages. No part of this book may be reproduced in any manner whatsoever without permission.

Good

Buildings

Deserve

Good

Hardware





CORBIN LOCK COMPANY OF CANADA LIMITED, BELLEVILLE, ONTARIO

Established 1931.

The largest factory in the Dominion of Canada devoted exclusively to the manufacture of Locks and Builders' Hardware.

The Corbin Trade Mark



THE Corbin statement above is more than a slogan. It is a fact—a fundamental principle, the meaning of which is appreciated more and more daily. It not only expresses the ideal of Corbin design and workmanship, but it reminds the architect, builder, home owner and hardware dealer that the choice of hardware for the building is a feature that deserves careful thought and consideration.

"GOOD BUILDINGS DESERVE GOOD HARDWARE"—appears on every Corbin advertisement, on all Corbin circulars, catalogues, booklets, packages and instruction sheets. It has been translated into foreign languages and the Corbin Trade Mark is known in every foreign country. Corbin has steadily publicized the important fact that good hardware is an essential of a good building; the one complements the other.

"GOOD BUILDINGS DESERVE GOOD HARDWARE"—this statement to you as a Corbin Dealer has a definite value in terms of sales volume and profits. It is your privilege to enjoy a substantial share of the prestige which has been created by this trade mark. To gain the full advantages of this profitable, lasting tie-up for your store, we offer you many valuable forms of advertising co-operation. Colorful, artistic and well-written series of sales helps feature merchandise that you sell every day. They feature the Corbin Trade Mark too, and help to make home owners and builders decide.

Because Corbin advertising material is offered on such a liberal basis, its value is sometimes overlooked by individual dealers who could profit by it most. When you consider how carefully Corbin dealerships are allotted it is obvious that the use of specially prepared Corbin advertising material is bound to promote business right over your own counter.

Corbin, therefore, is not only the maker of a fine line of hardware products, but an organization so developed and perfected that through your association with it you can turn Corbin products into profits. For Corbin recognizes that only through co-operation with authorized dealers can products be merchandised—profitably and in large volume.

Corbin Lock Company of Canada Limited

BELLEVILLE

ONTARIO - CANADA

Numerical and Alphabetical Indexes

The first section of the catalogue contains alphabetical and numerical indexes covering every item in the line and showing the number of the page on which it can be found. As new items are added, additional index pages will also be furnished from time to time for insertion in the catalogue.

How to find catalogued items in the Price Book

A notation at the bottom of each page shows the Price Book Section in which its items are listed.

Weights and Measurements

The Weights given in this book are supplied as a guide in estimating transportation and tariff charges. They include the weight of the individual boxes and of any wrapping material, but do not include the weight of wooden cases, cartons or packing material. All weights are subject to ordinary variations of manufacture and to changes which may be made in methods of manufacturing.

The Measurements are subject to ordinary variations caused by grinding and finishing.

Template Goods

When so ordered, goods are made "to template," for use on hollow metal doors and other places where accurate measurements are required for mortising and reinforcements. Blue print templates are furnished showing exact dimensions of articles to be supplied.

Return of Goods. No goods will be accepted if returned without permission. Finished goods made to order and not carried in regular stock cannot be returned. All returned goods require inspection, repapering and repacking. Frequently it is necessary to refinish them due to damage done to the appearance through handling. All expense incurred in restoring the goods to their original saleable condition will be deducted from any allowance for credit.

Cancellations: After process of manufacture has begun, there can be no cancellation of orders for goods which are not carried in our stock. No cancellation of orders can be made without our consent.

Claims for Lost Goods. When goods are accepted by the carriers they cease to be our property and belong to the purchaser. Any claim for loss or damage in transit should be made by him.

Guaranty. We guarantee our product against fault in workmanship and material. Claims for defects must be made immediately upon receipt of the goods.

Corbin Scientific Packaging

Promotes Sales . . . Protects Products

For many years Corbin has given careful study and attention to the proper packaging of its products and the packing of shipments. Careful inspection is maintained to make certain that

every order will leave the plant in a safe and secure manner and arrive at its destination in the same good condition. Reproductions of Corbin package labels are shown below.



The "Red" Label Means Brass or Bronze Metal



The "Blue" Label Means Iron or Steel Metal



The "Green" Label Means Aluminum Metal



The Red, White and Black Label Means Cabinet Lock Hardware
Also furnished with "Red" Labels for Cabinet Locks.

ALPHABETICAL INDEX

01

A	Page
Adapta Lock	299
Adjusters, Casement	76, 77
" Concealed Transom	82
" Window Stop	72
Aligning Tool	231
Automatic Coordinating Device, for Double doors ...	116
" Door Holders	66
" Exit Fixtures	97-117
" Key Duplicating Machine	343
Auxiliary Handle	249
Auxiliary Spring Attachment for Lever Handles	199

B	
Ball Bearing Butts	9-12
" " Cylinders	191, 192
" " Pivots	14, 15
Bar Sash Lifts	73
Barre Design, Wrought Brass or Bronze	267-269
" " Wrought Steel	267-269
Bars, Closet	89
" Exit Push	97-117
" Push	131-135
Bathroom Door Locksets	See Locksets
Bead Screws and Washer, Stop	72
Bell Turns	92
Bells, Rotary Stroke for Bell Turns	92
" Rotary Stroke in sets	92
Bits	231, 243, 249
Bolts, Automatic Exit	97-117
" Barrel	50
" Bottom	55
" Chain	55
" Cremone	51
" Extension Flush	49
" Flush	50
" Foot	55
" Lever Flush	49
" Mortise Door	54
" Side Flush	50
" Surface Door	52
" Top	55
Boring Jig	231, 243, 249, 253
Box Hinges	333
Box Pulls	331
Boxes, Wrought for use with Lock Strikes	198
Brackets	27-31
" Door Closers	27-31
" Hand Rail	93
Bumpers, Door	65
Button Indicators	167
Buttons, Electric Push	141
" Turn	91

B	Page
Butts, Cabinet	13
" Full Surface	12
" Half-Mortise	12
" Half-Surface	12
" Loose Pin, Ball Bearing	9, 10
" " " Cast Iron	11
" " " Half-Surface	12
" " " Template	10, 12
" " " Wrought Aluminum	9, 10
" " " Wrought Brass or Bronze	9, 10, 12
" Wrought Brass	9-13
" " " Broad	13
" " " Middle	13
" " " Narrow	13

C	
Cabinet Catches	84, 85
" Locks	190, 299, 307
" Spindle Nut	199
Cabinet Lock Merchandisers	296
Canada Design, Cast Brass or Bronze	274, 275
" " Wrought Brass or Bronze	261, 262
" " Wrought Steel	261, 262
Canada Turns	75
Canterbury Design, Cast Brass or Bronze	283
Card Holders	328-330
Card Holders and Pulls	330
Card Plates	328
Casement Adjusters	76, 77
" Fasteners	75
Catches, Cabinet	84, 85
" Cupboard	85
" Elbow	84
" Friction	84, 336
" Screen Door	87
" Secret Gate	85
" Showcase	84
" Suitcase	335
" Transom	86
Chain Door Fasteners	59
Chains, Transom	83
Chest Locks	297
Closers, Door	21-45
" " (Brackets for)	27-31
" " for Coupon Booths	24
" " for Fire Doors	24
" " for Hospital Doors	25
" " Parts	32, 33, 35
" " Screen Door	36
" " with Fusible Release	24
" " with Holdback Attachments	23
" " with Key Valve	22

C

	Page
Closers, Door, "400" Semi-Concealed	37-45
Closet Bars	89
Coat and Hat Hooks	88
Collars, Cylinder	200
Communicating Door Locksets	See Locksets
Comparative Finish Symbols	3
Comparative List Cabinet Locks	313
Coordinating Device for Double Doors	116
Corbin Unit Locks "900" Series	213-217
Corners, Case	334
Coupon Booth Door Closer	24
Cremone Bolts	51
Crestwood Design, Cast Brass, Bronze or Aluminum	225, 239
Cup and Drop Ring	210
Cup Handles, Flush	210
Cupboard Catches	85
" Locks	190, 307
" Turns	85
Cylinder Assembly Tools	193
" Collars	200
Cylinder Pins and Parts	193
Cylinders	192, 229, 241, 249
" Description of	191
" Thumb Knob	199
Cylindrical Locksets, Heavy Duty	218-233
" " Standard Duty	234-244
" " Light Duty	245-250

D

Description of Finishes	1, 2
Defender, Cylindrical	234-244
Desk Locks	298
Discs, Thumb Knob	199
Door Bells	92
" Bell Sets	92
" Bolts	See Bolts
" Bumpers	65
" Closers	21-45
" Closer Brackets	27-31
" Closers, "400" Semi-Concealed	37-45
" Fasteners	59
" Guards	131-135
" Handles	136-140
" Holders	63, 64
Door Holders, Automatic	66
" Knobs	204, 206, 278, 285
" Method of Mounting	203
" Knockers	141
" Locksets	See Locksets
" Openers, Electric	198
" Pulls	121-128
" Flush Sliding	121
" Hook	121
" On Plates	126-128

D

	Page
Door Sets, Mortise Screen	87
" Stops	60, 61
" " and Holders	62, 63
Doors, Hand of	4
Drawer Handles	90
" Knobs	91
" Locks	300-305
" Pulls	90
Drop Escutcheons	209
" Handles and Flush Cup	210
Drops, Letter	142, 143

E

Elbow Catches	84
Electric Door Openers	198
" Push Buttons	141
Escutcheons	261-285
" Drop	209
" Flush Cup	210
" Key	209
Exit Fixtures, Automatic	97-117
" " Instructions for Ordering	97
Extension Unit	230, 241
Eyes, Transom	83

F

Fasteners, Casement	75
" Chain Door	59
" Door	59
" Sash	74
Fidelity Design, Cast Brass or Bronze	280, 281
Figures	93
Finishes, Description of	1, 2
" Comparative Table	3
Fire Exit Bolts	97-117
Floor Spring Hinges	16
Flush Bolts	50
" " Extension	49
Flush Cup Handles	210
" Door Pulls	121
" Rings	92
" Sash Lifts	73
Friction Catches	84
" Latches	180

G

Gate Catches	85
Glass Door Knobs	205
" Push Plates	129
Gotham Design, Cast Brass or Bronze	278, 279
Gravity Pivot Hinges	17
Grips	124, 125
Guard Bars	131-135
Guardian, Cylindrical	245-250

ALPHABETICAL INDEX (Cont'd)

03

H	Page
Handles, Cup	210
" Door	136-140
" Drawer	90
" Flush Cup	210
" Lever	207
" Sectional	136-138
" Store Door	139, 140
Hand of Door Locks	4
Hand Rail Brackets	93
Hangers, Pole	71
Hinge Hasps	332
Hinge Plates	282, 285
Hinges, Box	333
" Floor Spring	16
" Gravity Pivot	17
" Pivot, Adjustable Ball-Bearing	14, 15
Holder, Automatic Door	66
" Card	328, 329
" Card and Pull	330
" Door	63, 64
" Overhead Door	67-70
Holders, Door Stop and	62, 63
Hook Door Pulls	121
" Sash Lifts	72
Hooks, Arm	121
" Ceiling	88
" Coat and Hat	88
" Hospital Arm	121
" Pew	88
" Lavatory, for Marble	92
" School House	88
" Wardrobe	88
Hotel Locks	154, 160
House Numbers	93

I

Indicator Button	167
Inside Door Sets	See Locksets

J

Jig, for Boring Door for Tubular and Cylindrical Locks	231, 243, 249, 253
--	--------------------

K

Key Duplicating Machine	343
Key Information, Cabinet Locks	295
Keys	194-196, 337-342
Kick Plates	131
Knob Parts	200-202
" Plates	200
" Roses	208
" Screws	200
" Spindles	201, 202
" Thimbles	202
" Washers	200

K

K	Page
Knobs, Door	204-206, 278-285
" " Glass	205
" " Method of Mounting	203
" Drawer	91
" Screwless	204
" Thumb	209, 278, 282
Knockers, Door	141

L

Label Plates	328
Latches, Bored in Type	See Tubular Latches
" Corbin Unit "900" Series	214
" Corbin Unit Office "900" Series	215
" Cylindrical, Passage Door	226, 240, 243
" " Closet	226
" " Exit	227, 240
" Flush Panel	311
" Friction	180
" Mortise	154-163, 168-181
" " Exit	168
" " Knob	154-163, 179, 180
" " Night	185
" " Office	154-163
" " Passage Door	179, 180
" " Sliding Door	181
" " Store Door	172
" " Vestibule Door	154-163
" Rim Night	186-188
" Thumb	254
" Tubular	251
Lavatory Gravity Pivot Hinges	17
Hook and Bumper	92
Letter Drop Plates	142, 143
Lever Handles	207
" " Auxiliary Spring Attachment for ...	199
Lifters, Transom	78-81
Lifts, Bar Sash	73
" Flush Sash	73
" Hook Sash	72
Lock Springs	199
" Strikes	197
Locks, Adapta	299
Locks, (By Type)	147
" Bored in Type — See Cylindrical & Tubular locks	
" Box	312
" Cabinet	190, 299, 307
" Chest	297
" Cupboard	190, 307
" Cylindrical	See Cylindrical Locks
" Desk	293
" Drawer	300-305
" Flush Panel	311
" Hand of	4

L	Page
Locks, Locker	310, 311
" Mortise	147-178
" Standardized 7000 Line	151-158
" 7200 Line	151-158
" 7300 Line	159-164
" 7400 Line	151-158
" 7500 Line	159-164
" 7600 Line	151-158
" 7700 Line	159-164
" 7900 Line	159-164
" Template Details	149
Rim	177
" Bar Bolt Dead Locks	184
" Exit Locks	98-100
Sliding Door	306
Tubular	251
Unit "900" Series	213-217
Utility	190
Wardrobe	308-310
Locks (By End Use)	
" Apartment Corridor Door, Cylindrical	227, 228, 241
" " " Mortise	154-163
" " " "900 Series Unit ..	215
" Entrance Vestibule, Cylindrical	227, 240
" " " Mortise	154-163, 166
" " " "900" Series Unit	215
" Bathroom, Cylindrical	226, 240, 248
" Mortise	154-163, 178
" Tubular	251
" "900" Series Unit	215
" Bedroom, Cylindrical	227, 240, 248
" Mortise	178
" Tubular	251
" "900" Series Unit	215
" Cabinet	190, 229, 307
" Classroom, Cylindrical	227, 240
" Mortise	154-163, 177
" "900" Series Unit	215
" Closet, Cylindrical	226
" Mortise	154-163, 173-176
" Tubular	251
" "900" Series Unit	214, 215
" Communicating, Cylindrical	226, 240
" Mortise	154-163, 178
" "900" Series Unit	214
" Dead Lock Mortise	154-163, 182, 183
" " Rim	184, 187
" Dormitory Bedroom, Cylindrical	228
" Entrance, Cylindrical	227, 240, 248
" (Knob) Mortise	154-163, 165, 171
" (Handle) Mortise	158, 164, 167
" "900" Series Unit	215
" Exit, Cylindrical	227, 240
" (Exit Bar) Mortise	169, 170
" (Knob) Mortise	170
" Rim	98-100

L	Page
Locks, Exit ¾" Throw Unit "900" Series	215
" Fixed Knob Lock, Cylindrical	227, 240
" Front Door, Cylindrical	227, 240, 248
" " (Handle) Mortise	158, 164, 166
" " (Knobs) Mortise	154-163, 165, 171
" " "900" Series Unit	215
" Hotel Corridor, Cylindrical	227
" " Mortise	154-163
" Inside Door (Bit Keyed) Mortise	173-176
" " " Rim	177
" Office, Cylindrical	227, 228, 240
" Mortise	154-163
" "900" Series Unit	215
" Passage Door, Cylindrical	226, 240, 248
" " Mortise	154-163
" " Tubular	251
" " "900" Series Unit	214
" Pipe or Wire Shaft Door, Cylindrical	228
" " " Mortise	154-163
" Privacy Locks, Cylindrical	226, 227, 240, 248
" " Mortise	178
" " Tubular	251
" " "900" Series Unit	214, 215
" Rest Room, Cylindrical	228, 241
" " Mortise	154-163
" " "900" Series Unit	215
" Service Station, Cylindrical	228, 241
" Sliding Door, Mortise	170
" " Cabinet	190, 306
" Store Entrance, Cylindrical	228
" " (Handle) Mortise	158, 164, 166, 167, 172
" " (Dead Lock) Mortise	182, 183
" " (Knob) Mortise	154-163
" Store Room, Cylindrical	228, 241
" " Mortise	154-163
" " "900" Series Unit	215
" Utility, Cabinet	190
" Cylindrical	228, 241
" Mortise	154-163
" "900" Series Unit	215
" Vestibule, Cylindrical	227
" Mortise	154-163
" "900" Series Unit	215
Locksets, Bathroom Door, Mortise	256, 262-284
" Colonial Knob	256
" Combination	254, 255
" Front Door	255
" Store Door	254
" Cylindrical, Heavy Duty	218-233
" Standard "Defender"	234-244
" Light "Guardian"	245-250

S	Page
Sash Locks	74
“ Poles	71
“ Pull Plates	71
“ Pulleys	94
“ Sockets	71
Screen Door Catches	87
“ “ Checks	34-36
Screwless Knobs	203, 204
“ Roses	208
“ Spindles	201
Screws and Washers, Window and Door Stop	72
“ Knob	200
Sectional Handles	136-138
“ Handle Locksets	136-138
Semi-Concealed Door Closers “400”	37-45
Sets, Latch	See Locksets
“ Lock	See Locksets
Shelf Supports	91
Sockets, Sash	71
Somerset Design, Cast Brass or Bronze	282
Spindle Nut, Cabinet	199
Spindles, Knob	201, 202
Spring, Auxiliary for Lever Handles	199
“ Closer	32, 33
“ Hinges, Surface Floor	16
Springs, Lock	199
Standard Design, Cast Brass or Bronze	276, 277
Stays, Transom	83
Steel Mullion, Removable	101
Stops and Holders, Door	60-63
Stop Bead Screws and Washers	72
Stops, Door	60, 61
Store Door Handles	139, 140
“ “ Locksets	139, 140
Strikes, Cabinet Lock	312
“ Dust-Proof for Ext. Flush Bolts	53
“ for Cement for Ext. Flush Bolts	53
“ for Cremone Bolts	53
“ for Exit Fixtures	116, 117
“ for Marble	53
“ for Mortise Lock	197
“ Open Back, for Exit Locks	116
“ Unit Lock	214
Suitcase Catches	335

S	Page
Sull Sash Strikes	74
Supports or Stays	331
“ Shelf	91
Symbols for Ordering	5

T

Thimbles, Knob	202
Thresholds	118
Thumb Knobs	209
Thumb Latches	254
Titan Design, Cast Brass, Bronze or Aluminum	284
Tools, Cylinder Assembly	193
“ Cylindrical Lock	231, 243, 249
Transom Adjusters, Concealed	82
“ Catches	86
“ Chains	83
“ Eyes	83
“ Lifters	78-81
“ Openers	78-81
“ Stays	83
Tubular Locks and Latches	251-253
Turn Buttons	91
“ Bell	92
“ Canada	75
“ Cupboard	85
“ Quebec	75
“ Thumb	209

U

Unit Extension	230, 241
Unit Locks	213-217
“ Reinforcing	230
Utility Locks	190

W

Warden Design, Colonium Metal	285
“ “ Cast Iron	257
Wardrobe Locks	308-310
Washers, and Stop Bead Screws	72
“ Knob	200
Window Pole and Hook	71
“ Stop Adjusters	72
Windsor Design, Cast Brass, Bronze or Aluminum	224, 238
Wrought Box for use with Strikes	198

ALPHABETICAL INDEX (Cont'd)

05

L	Page
Locksets, Designs, Cast Brass or Bronze	273-285
" " "900" Series Unit	213-217
" " Wrought Brass or Bronze	261-269
" " Steel	262-269
Exit Fixture	97-113
Front Door, with Handles	136-138
Mortise	256, 257, 261-285
" Colonial Knob	256
" Glass Knob	256, 265-269
Plain, Cast Brass or Bronze	273-277
" Corbin Unit "900" Series	213-217
" Wrought Brass or Bronze	261-264
" Wrought Steel	261-269
Residence Unit	213-217
Rim	257
Sectional Handle	136-138
" Trim	256
Store Door	139, 140
Tubular	253

M

Master-Keyed Ball Bearing Cylinders	191, 192
" " " " " Description ..	191
Merchandisers	020
Miami Design, Wrought Brass or Bronze	265, 266
" " Wrought Steel	265, 266
Mortise Locks and Latches	147-185
Mounts for Samples	019, 020
Mullion, Steel for Rim Exit Fixtures	101

N

Name Plates	328
Night Latches, Mortise	185
" " Rim	186-188
Numerals	93
Nut, Cabinet Spindle	199

O

Office Door Locksets	See Locksets
Openers, Electric Door	193
" Transom	78-81
Operators, Transom	78-81
Overhead Door Holders	67-70

P

Padlock Chain Assemblies	327
Padlocks	189, 317-326
Panic Bolts	97-117
Parts, Door Check	32-35
Pivot Hinges, Adjustable Ball-Bearing	14, 15
" " Gravity	17
Plate Escutcheons	209
Plates, Card	328, 329
" Hinge	282, 285
" Kick	131

P

P	Page
Plates, Knob	200
" Letter Drop	142, 143
" Name	328
" Push	129, 130
" " and Pull	128
" " Glass	129
" Sash Pull	71
Plaza Design, Cast Brass or Bronze	273
Pliers, Tru-Arc	229
Pole Hangers	71
Poles, Sash	71
" Window	71
Portland Design, Wrought Brass or Bronze	263, 264
" " Wrought Steel	263, 264
Pulleys, Sash	94
Pushes, Box	331
" Door	121-128
" " Flush	121
" " on Plates	126-128
" Drawer	90
" Flush Sliding Door	121
" Hook Door	121
" Sash	71
Push and Pull Plates	128
" Bars	131-135
" " Exit	98-113
" Buttons, Electric	141
" Levers, Exit	108-109
Push Plates	129, 130
" " Glass	129

Q

Quebec Turns	75
--------------------	----

R

Rabbetted Front, Cylindrical	230, 243
Removable Steel Mullion	101
Reinforcing Unit	230, 243
Reverse Bevel Door Lock	4
Rim Exit Bars and Locks	98-100
Rim Locks and Latches	177, 184-188
" Night Latches	186-188
Rings, Flush	92
Roses, Knob	208, 230, 242
" Lever	207
" Screwless	208
Roses, for Cylindrical sets	220-247
" for Tubular sets	251
Rotary Stroke Bells	92
Rubber Bumpers	65

S

Sample Mounts	019, 020
Sash Fasteners	74
" Lifts, Bar	73
" " Flush	73
" " Hook	72

NUMERICAL INDEX

07

	Page		Page		Page
A	53	010	328	30 1/4	202
A	type lock 147	K10	020, 186	030	253
AA	53	11	35	030 1/4	202
B	53	K11	020	31	30
B	indicator 167	11S	312	K31	019
C	bushing 231	011	328	K32	019
C	strike 53	011 1/4	196, 338	032	201
C	type lock 147	12	35	K33	020
CT1 to CT8	193	K12	020	033	201
D	53	012	328	34	297
D	type lock 147	13	35	K34	020
DC	192	K13	020	034	201
E	53	14	35	36	201
E	type lock 147	14	200	K36	020
FT1	242	K14	020	K37	019
LH	203	14 1/2	200	37 1/2	31
PY	203	15	35	K38	019
TS	203	15	200	K39	019
RAB	230, 243	K15	020	K40	019
WBX	198	16	35	040	231
0	34	16	200	40 1/4	202
1	part 35	K16	020	040 1/4	202
1	rubber tip 64	16 1/2	200	41S	312
K1	019	17	36	K41	020
01	179	17	35	041	231
001	199	17	200	K42	019
002	199	18	35	042	231
2	closer 22	18	200	43	30
2	part 35	018	328	K43	020
2	tru-arc plier 229	18A to 18D	74	43 1/4	202
K2	019	018A to 018D	74	044	201
3	closer 22	19	35	45	180
3	part 35	20	200	45 1/2	201
3	tru-arc plier 229	20	35	045 1/2	201
K3	019	20	201	046	298
003	199	020	328	47 3/4 C	298
4	closer 22	21	36	48	199
4	part 35	21	35	49	31
K4	019	22	35	49S	312
004	199	22	199	49 1/2 S	312
5	closer 22	K22	020	50	020, 296
5	part 35	022 1/2	199	52S	312
5	rubber tip 64	23	35	53 1/4	195, 337
5	thimble 202	K23	020	053 1/4	195
K5	019	24	32, 33	54	195, 337
6	closer 22	24	35	56	201
6	part 35	K24	020	056	201
6	thimble 202	25	27	056 1/4	201
K6	020	25	35	56 1/2	202
006	199	25	201	57	195, 337
7	part 35	25	199	057	195
7	thimble 202	26	28	60	sample board 020
7S	312	26	35	060	243
K7	019	26S	312	061	243, 249
007	199	26 1/2	28	062	11
8	part 35	26 1/2 S	312	63 1/4	194, 337
8	thimble 202	26 3/4	28	063 1/4	194
008	199	27	35	64	194, 337
9	part 35	28	27	064	194
9	thimble 202	28	35	67	194, 337
09	328	29	179	067	194
009	199	29	35	70	display 020, 296
10	latch 179	K29	019	70	panic bolts 111
10	part 35	30	30	70 x 76	112
10S	312	K30	019	70 x 76 1/2	112

	Page		Page		Page
70 x 76¼	112	110A	32, 33	136B	33
70 x 78	112	111A	32, 33	137A	32, 33
71	111	112	32, 33	137B	33
71 x 77	112	116B	32	138	exit fixture 105
71 x 77½	112	116D	33	138	part 32, 33
71 x 77¾	112	117	32	139	32, 33
71 x 79	112	117A	32	140	exit fixture 199
072	11	117C	33	140	part 32
73¼	194, 337	118	numeral 93	140B	33
073¼	194	118	part 32	0140	297
74	strike 53	119	32, 33	141	32
74	key 194, 337	120	exit fixture 104	142	exit fixture 109
074	194	120	part 32, 33	142	part 32
074¼	194	120 x 120	104	142A	33
074½	194	120 x 124	104	0142P	297
75	53	120 x 125	104	143	32
76	strike 53	120 x 126	107	143A	33
76	exit fixture 110	120 x 126½	107	144	32
76½	110	120 x 126NT	107	144A	33
76¾	110	120 x 127	107	145	32, 33
77	exit fixture 110	120 x 127½	107	146	108
77	key 194, 337	120 x 129	107	146½	108
77½	110	120 x 134	104	147	108
77¾	110	120 x 135	104	147½	108
077	194	121	32	149	exit fixture 108
78	110	122	105	149	part 32, 33
79	110	122 x 122	105	150	32, 33
80	butt 9	122 x 128	105	151	collar 200
80	chest lock 297	122 x 138	105	151	part 32, 33
080	249	122A	32, 33	153	collar 200
80½	9	122FT	117	153	part 32, 33
80⅞	196	122S	117	154	32
080⅞	196, 338	123	lock 182	154B	33
083	78	123	part 32, 33	155B	32, 33
084	78	124	exit fixture 104	157	32
85	27	124	part 32	157A	33
085	78	125	exit fixture 104	157W	32, 33
86	28	125	part 32	158	32, 33
90	butt 10	126	exit fixture 102, 103	159	32
90	latch 180	126NT	102, 103	159A	33
90½	10	126	part 32, 33	159½	178
91	181	126A	33	159¾	178
091	181	126½	102, 103	163A	33
093	80	127	exit fixture 102, 103	167	33
094	80	127	part 32	0168	298
095	80	127A	33	0170	93
P95	324	127AK	33	0176	93
P95C	324	127K	32	177	172
P95E	323	127½	102, 103	0177	93
P95H	323	128	105	179¼	196, 338
P95L	323	129	102, 103	179¾	196, 338
P95¼	324	130	93	180	butt 9
P95¼C	324	131	lock 182	180	lock 168
P95¼E	323	131	part 32, 33	180	stopbead 72
P95¼H	323	131B	33	0180	72
P95¼L	323	132	lock 182	180½	9
96¼	196, 338	132	part 32, 33	183	72
100	230	133	lock 182	0183	72
102	23	133	part 32, 33	185	168
102¾	24	134	exit fixture 104	0186	172
103	23	134	part 32, 33	190	10
104	23	135	exit fixture 104	190½	10
105	23	135	part 32, 33	195	196
106	23	135A	33	197	83
110	32, 33	136A	32, 33	198	83

NUMERICAL INDEX (Cont'd)

09

	Page		Page		Page
201	83	343½	65	0406	16
0201	83	0343½	65	DD406	16
203	lock 176	356	188	410	226
203	tran. chain 83	359	178	415	226
208	12	0359	178	418	205
210	12	359½	196, 338	419	226
212	12	360	184	420	226
L215A	299	364	174	423	25
L215B	299	365	175	424	25
L215C	299	0370B	307	427	226
216	12	0370½B	307	429	227
0223	50	0371CX	190	430	design 236
0223½	50	0371DX	190	430	opener 198
230	design 247	376	188	430A	242
232H	249	383	175	430B	242
250	55	400	function 226	430C	242
0250	55	400	hinge 16	432	227
251	192	0400	hinge 16	436	design 237
0251	171	DO400	16	441	227
252	bolt 55	400	bracket 41	444	227
252	cyl. 192	400	closer 37, 45	445	219
0252	55	400MT	231	0445	219
253	152, 192	400-1	41	451	227
260½	192	400-2	41	454	227
0261	171	400-3	41	455	227
263	bolt 54	400-4	41	455¼	227
263	cyl. 152, 192	400-5	41	455¾	227
264	54	400-7	41	456	227
266	54	400-8	41	456¾	188
0266	54	400-9	41	457	228
274	177	400M-2	38	459	228
274A	177	400M-3	38	460	192
285	173	400M-4	38	460A	229
0285	173	400M-5	38	460B	229
291	181	400M-6	38	460C	229
0291	181	400MH-2	38	460D	229
303	176	400MH-3	38	460E	229
3A6	186	400MH-4	38	460F	229
3D6	187	400MH-5	38	460½	192
3R6	187	400MH-6	38	461	228
306	196, 338	400W-2	38	462	228
0306	196	400W-3	38	463	228
321	15	400W-4	38	465	228
322	15	400W-5	38	469	228
323	15	400W-6	38	488	228
0321	15	400WH-2	38	491 x 5"	230
0322	15	400WH-3	38	491 x 7"	230
0323	15	400WH-4	38	491 x 10"	230
326	113	400WH-5	38	492	230, 243
326 x 6087	113	400WH-6	38	500	17
329	113	400S-2	38	501	17
329 x 6087	113	400S-3	38	520	92
330	29	400S-4	38	523	24
331	29	400S-5	38	524	24
332	29	400S-6	38	530	93
333	29	400SH-2	38	553	200
334½	65	400SH-3	38	553¼	200
0334½	65	400SH-4	38	581X	310
335	28	400SH-5	38	582X	311
336	65	400SH-6	38	585	304
337	65	402	226	0585	304
0337	65	403	design 238	590	302
338	65	404	226	0590	302
339	65	405	design 239	590¾	304
340	65	405	function 226	0590¾	304

	Page		Page		Page
592½	302	689	115	820 A to F	69
0592½	302	691 x 5"	241	821	function 248
600	240	693	117	821 A to F	69
0601	303	695	235	822 A to F	69
602	197	695¼	235	823 A to F	69
0602	197	0695	235	830	design 220
603	197	0695¼	235	831	dcsign 222
0603	197	697	117	831	function 248
604	197	698	117	836	design 221
606	116	699	303	838	design 233
0606	197	0699	303	840 A to F	69
607	116	700	214	841	function 248
608	116	701	152	841 A to F	69
610	240	701B	310	845	246
612	197	702	118	845¼	246
614	197	702B	310	0845	246
0614	197	703	214	842 A to F	69
615	function 240	704	118	843 A to F	69
615	strike 197	704L	310	850 A to F	69
616	197	705	118	851	function 248
0618	197	706	118	851 A to F	69
620	function 240	710U	214	852 A to F	69
620	strike 197	711	152	853 A to F	69
621	240	712	91	860 A to F	70
625	305	720	215	861 A to F	70
630	198	721	152	862 A to F	70
631	function 240	723	25	870	cylinder 192
631	strike 198	724	25	870 A to F	67
634	197	727	152	871 A to F	67
0636	197	0737	308	872 A to F	67
640	197	0738	301	873 A to F	67
641	function 240	741	215	878	305
641	strike 197	744	215	890 A to F	68
642	197	749	309	891 A to F	68
644	240	0749	309	892 A to F	68
645	251	750	309	900	design 213, 216
651	240	0750	309	900	padlock 320
655	function 240	751	215	900C	320
655	strike 115	0751	309	0900	320
657	241	751¾	215	0900C	320
659	251	754	215	902	320
661	241	754¾	215	902C	320
662	241	755	215	0902	320
663	241	755	function 215	0902C	320
666	115	0755	wardrobe lock 308	904	dcsign 217, 218
0666	300	757	308	904	padlock 320
0666½	300	761	215	904C	320
670	192	761 A to F	70	904¼	320
676	116	762 A to F	70	904¼C	320
0676	303	764	215	0904	320
678	116	770 A to F	70	0904C	320
681	117	771 A to F	70	0904¼	320
682	117	772 A to F	70	0904¼C	320
683	117	0792	254	904H	323
684	98	800	design 220	904W	323
684½	115	801	design 222	904X	323
684¾	115	803	design 224	906	321
684⅝	115	803	drawer lock 305	906C	321
685	174	803A	224	906¼	321
685¾	174	803B	224	906¼C	321
0686X	190	805	design 225	0906	321
687	115	806	design 221	0906C	321
688½	115	808	design 223	0906¼	321
688¾	115	810	248	0906¼C	321
688⅝	115	820	function 248	906H	323

NUMERICAL INDEX (Cont'd)

011

	Page		Page		Page
908	321	01235C	89	1914¼H	329
908C	321	1236	89	1918	206
908¼	321	01236	89	1919¼	331
908¼C	321	01239	88	1925A	330
0908	321	01240	88	1925¼H	330
0908C	321	1285	173	1929¼	331
0908¼	321	01285	173	1932	206
0908¼C	321	1344	90	1932¼H	328
0909	94	1345	90	1935A	328
910 A to H	82	1346	90	1935¼H	328
915 C to H	82	1355	90	1950	210
0929	94	1357	90	1952	210
0949	94	1358	90	1953	210
961	177	1365	175	1954	206
01043	76	01366	90	1960	206
1046	77	1385	170	1961	206
1047	76	1385½	170	1962	206
1055	77	1419	204	1963	206
01058	76	1419W	204	1970	52
01059	83	1419½	204	01970	52
1106	208	01419½	204	1971	52
1108	208	1422	204	01971	52
01108	208	01422	204	1990	51
1109	208	1425	205	1992	51
01109	208	01425	205	2009	207
1110	208	1446	184	2020	207
01110	208	1447	184	2021	207
1118	208	1490	267	2022	207
1119	208	01490	267	2024	207
1120	208	1492	267	02024	207
1121	208	01492	267	2025	207
1122	208	1519½	204	02065	301
1125	208	1621	204	02065¼	302
01125	208	01621	204	02066	301
1127	208	01623½	204	02067	308
1129	208	1719	204	2102	121
1130	208	1719½	204	2103	121
01138	208	1719¾	204	02103	121
1147	206	1751	331	02109	333
1150	206	1771½	335	02111	333
1157	251	1771¾	335	02112	333
1158	251	1778½	335	2114	333
1159	251	1778¾	335	02114	333
1160	206	1809½	335	2138	209
1161	206	1809¾	335	2140	209
1162	206	1825	180	2145	209
1163	206	1829	74	2147	209
01203	88	01829	74	2148	209
01204	88	1830	205	2202	132
01206	88	1831	74	2203	132
1210	88	01831	74	2209	131
01210	88	1835	312	2220	132
1211	88	1835	box lock	2223	133
01211	88	1840	cancelled	2224	133
1212	88	1893¼H	74	2225	133
01212	88	1894¼H	329	2231	134
01217	88	01897	92	2232	134
01217½	88	1902¼H	330	2233	134
1220	92	1903¼H	330	2234	134
1232	88	1906¼H	330	2236	134
01232	88	1909¼	331	2231A	134
01232½	88	1911¼H	329	2231B	134
1235	89	1912¼H	328	2231BS	134
01235	89	1913A	329	2232G	134
1235C	89	1913¼H	329	2232S	134

	Page		Page		Page
2233G	134	2825½	66	2886AC	319
2237	135	2826	exit fixture	100	2886¼A
2238	135	2826	holder	66	2886¼AC
2240	135	2826½	66	2926	98, 99
2248	209	2827	66	2926½	98, 99
2250	135	2827½	66	2926NT	98, 99
2265	59	2829	100	2927	98, 99
02265	59	2829¼	100	2927½	98, 99
2266	59	2834	50	2929	98, 99
02266	59	2850	49	2929¼	98, 99
2280	71	2851	49	2951G	326
02285	306	2856	49	2951GC	326
02290S	312	2857	49	2990	267
02291	306	2858	49	2991	267
02291S	190	2859	49	03002	332
2300	129	2863¼	189	3004	332
2305	142	2863¼A	189	03004	332
2306	142	2863¼C	189	3005	332
2316	131	2863¼AC	189	03005	332
2318	142	2879	317	03023	91
2319	142	2879A	317	03024	91
2320	142	2879C	317	03025	91
2321	142	2879AC	317	3028	91
2324	128	2880	317	3032	332
2334	142	2880A	317	03032	332
2335	142	2880AC	317	3038	85
2336	130	2880C	317	3046	85
2337	130	2880¼	317	03046	85
2343	129, 274	2880¼A	317	3048	85
2352	130	2880¼AC	317	03048	85
02352	130	2880¼C	317	3156M	75
2353	130	2880AH	322	3156R	75
02353	130	2881	317	3156S	75
2354	130	2881A	317	03162M	75
2359	116	2881AC	317	03162R	75
2446	184	2881C	317	03162S	75
2447	184	2881¼	317	3168M	75
2531	91	2881¼A	317	3168R	75
2537	91	2881¼AC	317	3168S	75
2538	91	2881¼C	317	03168M	75
2560	209	2881AH	322	03168R	75
02560	209	2881AW	322	03168S	75
2565	101	2881AX	322	3174M	75
2575	336	2882	189, 318	3174R	75
2578	336	2882¼	189, 318	3175M	75
2614	312	2882A	189, 318	3175R	75
2620	265	2882AC	189, 318	3186	71
2621	265	2882C	189, 318	03186	71
2652	312	2882¼A	189, 318	3187	71
2660	209	2882¼AC	189, 318	03187	71
2662	209	2882¼C	189, 318	3190	71
2782	207	2883	189, 318	03190	71
2784	207	2883AH	322	3196	71
2813	50	2883¼	189, 318	03196	71
2820	66	2883A	189, 318	3213	85
2820½	66	2883AC	189, 318	03213	85
2822	66	2883C	189, 318	3220	84
2822½	66	2883¼A	189, 318	3222	84
02823	50	2883¼AC	189, 318	03222	84
2823	bolt	2883¼C	189, 318	3232	84
2823	holder	2885A	319	03234	84, 336
2823½	66	2885AC	319	3236	84, 336
2824	66	2885¼A	319	3237	84, 336
2824½	66	2885¼AC	319	3238	84, 336
2825	66	2886A	319	3239	84, 336

	Page		Page		Page
03253	85	3768	60	4408½	124
03259	85	3769	60	4409	122
3273	86	3770	61	4409K	342
3275	86	3771	61	4410	124
03275	86	3778	62	04410	124
3277	86	3779	62	4412	124
03277	86	3780	62	4414	122
3302	72	3781	62	4416	124
3308	72	3790	60	4419	124
03308	72	3791	60	4420	124
3315	73	3861	64	04421	124
03315	73	03861	64	4436	125
3316	73	3864	64	4451	125
03316	73	03864	64	4454	125
3318	257	3865	64	4455	124
3319	73	03865	64	04455	124
3366	257	03875	63	4456	124
3367	257	3990	267	4457	124
3394	73	3991	267	4462	128
03394	73	4103B	340	4463	128
3395	73	4106	340	4464	128
03395	73	4116B	340	4466	128
3396	73	4120B	340	4467	128
03396	73	4120T	340	4470	127
3457	87	4122½	340	04470	127
03457	87	4122½B	340	4472	127
3463	87	4127B	340	04472	127
03463	87	4127½B	340	4475	127
3620	265	4128B	340	04475	127
3621	265	4130B	340	4476	127
03700	334	4131A	341	04476	127
03703	334	4131B	341	4485	126, 274
03715	334	4132A	341	4486	126, 274
3740	62	4140T	341	4487	126, 274
03740	62	4141B	341	4491	342
3741	62	4144B	341	4544	91
03741	62	4145½B	340	4740	341
3742	62	4145½C	341	4773	341
03742	62	4151	341	4780	342
3743	62	4152	341	4784	342
03743	62	4163½	339	5111	183
3750	60	4179	339	5112	183
03750	60	4197½AC	339	5113	183
3751	60	4202	342	5192	185
03751	60	4292	181	5193	185
3752	61	04328	121	5211	183
03752	61	4330	122	5212	183
3753	61	4331	122	5213	183
03753	61	4332	122	5243	165
3754	61	4333	122	5255	181
03754	61	4334	125	5256	181
3756	61	4335	121	5262	167
3757	61	4337	121	5372	166
3758	61	4359K	342	5443	165
3759	61	4370	123	5558	339
3760	63	4371	123	5565	101
03760	63	4372	123	5584	170
3761	63	4373	123	5585	170
03761	63	4374	123	5592	185
3763	60	4375	123	5593	185
03763	60	4376	123	5597	185
3765	60	4382	90	5598	185
03765	60	04398	121	5683	169
3766	60	04398½	121	5683½	169
03766	60	4408	122	5683¾	169

	Page		Page		Page
5743	166	7235	156	7522	160
5784	170	7237	156	7523	160
5785	170	7242	154	7523 $\frac{1}{4}$	160
5862	339	7243	154	7525	160
6031	341	7247	158	7527	160
6087	113	7248	158	7531	162
6168M	75	7251	156	7533	162
6168R	75	7254	156	7534	162
6168S	75	7255	156	7535	162
6170	93	7257	156	7537	162
6232	88	7271	158	7542	160
6373	61	7272	158	7543	160
6387	60	7273	158	7547	164
6396	73	7288	158	7548	164
6756	61	7300	159, 164	7551	162
6757	61	7300	160	7554	162
6758	61	7310	162	7555	162
6759	61	7311	160	7557	162
6829	74	7312	160	7571	164
7000	series locks . . . 149, 164	7313	160	7572	164
7000	153, 158	7320	160	7573	164
7000	154	7321	160	7588	164
7010	156	7322	160	7600	153, 159
7011	154	7323	160	7621	154
7012	154	7323 $\frac{1}{4}$	160	7622	154
7013	154	7325	160	7623	154
7020	154	7327	160	7623 $\frac{1}{4}$	154
7021	154	7331	162	7625	154
7022	154	7333	162	7627	154
7023	154	7334	162	7642	154
7023 $\frac{1}{4}$	154	7335	162	7643	154
7025	lock . . . 154	7337	162	7648	158
7025	lever . . . 207	7342	160	7672	158
07025	207	7343	160	7673	158
7027	154	7347	164	7688	158
7031	156	7348	164	7700	159, 164
7033	156	7351	162	7711	160
7034	156	7354	162	7712	160
7035	156	7355	162	7713	160
7037	156	7357	162	7721	160
7042	154	7371	164	7722	160
7043	154	7372	164	7723	160
7047	158	7373	164	7723 $\frac{1}{4}$	160
7048	158	7388	164	7725	160
7051	156	7400	153, 158	7727	160
7054	156	7411	154	7742	160
7055	156	7412	154	7743	160
7057	156	7413	154	7748	164
7071	158	7421	154	7772	164
7072	158	7422	154	7773	164
7073	158	7423	154	7788	164
7088	158	7423 $\frac{1}{4}$	154	7900	159, 164
7200	153, 158	7425	154	7921	160
7200	154	7427	154	7922	160
7210	156	7442	154	7923	160
7220	154	7443	154	7923 $\frac{1}{4}$	160
7221	154	7448	158	7925	160
7222	154	7472	158	7927	160
7223	154	7473	158	7942	160
7223 $\frac{1}{4}$	154	7488	158	7943	160
7225	154	7500	159, 164	7948	164
7227	154	7500	160	7972	164
7231	156	7510	162	7973	164
7233	156	7520	160	7988	164
7234	156	7521	160	8201	75


	Page		Page		Page
8206	75	54070	142	74540	278
8292	75	54071	142	74549	278
8618C	339	54113	137, 285	74561	278
8632C	339	54122	285	74570	278
8658BPM	339	54131	285	74571	278
8658BPS	339	54161	141, 285	74580	140
8658BY	339	54168	141, 285	74583	136
8687C	339	54184	137, 285	74586	126, 278
9101A	343	54198	285	74587	278
9913X	324	54270	142	74590	278
9913¼X	324	54271	142	74591	278
9913XC	324	56413	137	75213	200
9913¼XC	324	56484	137	75314	138
9913XH	325	60030	261	75368	141
9913XK	325	60032	261	75369	141
9913XP	325	60033	261	75383	138
9913XR	325	60230	263	75384	138
9914X	324	60231	263	75385	102, 113
9914¼X	324	60233	263	75385¼	98, 100
9914XC	324	60281	139	75385NT	102, 113
9914¼XC	324	64122	257	75385¼NT	98, 100
9954	326	64131	257	76703	284
14613	137	64130	257	76706	284
14684	137	70030	261	76713	284
15111	183	70031	261	76722	284
15112	183	70032	261	76730	284
15113	183	70033	261	76786	126, 284
15192	185	70061	141, 261	76790	129, 284
15193	185	70081	139	78803	280
15443	165	70211	92	78822	280
15630	311	70230	263	78830	140, 280
15631	311	70231	263	78831	280
19613	200	70233	263	78870	280
19613½	200	70261	141	78871	280
34113	136	70264	92	78880	140
34184	136	70281	139	78886	280
36413	136	73930	273	78890	280
36484	136	73932	273	80024	220
40013	138	73986	126, 273	80024DT	220
40070	142	73990	129, 273	80124	222
40071	142	73991	129, 273	80124DT	222
40084	138	74030	274	80324	224
40213	104, 105	74031	274	80324DT	224
40288	104, 105	74070	143	80524	225
40324	238	74071	143	80524DT	225
40324DT	238	74072	143	80605	230
40524	239	74073	143	80624	221
40524DT	239	74074	143	80624DT	221
42013	136	74081	140, 274	80703	282
42084	136	74130	276	80713	136, 282
42113	138	74131	276	80722	282
42184	138	74140	209	80730	282
42213	138	74180	140, 276	80731	282
42284	138	74181	140, 276	80740	282
43024	226	74186	126, 276	80749	282
43024DT	226	74190	129, 276	80761	141, 282
43624	237	74192	129, 276	80768	282
43624DT	237	74193	129, 276	80770	282
50313	137	74194	129, 276	80771	282
50384	137	74505	278	80784	136, 282
50761	141	74513	278	80790	282
52980	139	74514	136	80798	282
52986	127	74522	278	80824	223
52991	130	74530	278	80824DT	223
54068	141	74531	278	83024	220

	Page		Page		Page
83024DT	220	320-048	265	430-631	236
83124	222	320-074	265	430-641	236
83124DT	222	320-806	265	430-644	236
83624	221	320B-806	265	430-651	236
83624DT	221	320-810	265	430-655	236
83824	223	320B-810	265	430-657	236
83824DT	223	329-004	268	430-661	236
86222	283	329-048	268	430-662	236
86229	283	329-074	268	430-663	236
86231	283	329-806	268	436-600	237
86280	140	329B-806	268	436-610	237
86286	283	329-810	268	436-615	237
86290	283	329B-810	268	436-620	237
100-012	256	341-880	136	436-621	237
100-130	256	341-994	136	436-631	237
100-158	256	364-880	136	436-641	237
100-438	256	364-994	136	436-644	237
100-464	256	400-880	138	436-651	237
100-742	256	400-994	138	436-655	237
100-842	256	403-600	238	436-657	237
104-012	256	403-610	238	436-661	237
104-130	256	403-615	238	436-662	237
104-158	256	403-620	238	436-663	237
104-438	256	403-621	238	498-004	269
104-464	256	403-631	238	498-048	269
104-742	256	403-641	238	498-074	269
104-842	256	403-644	238	498-806	269
128-012	266	403-651	238	498B-806	269
128-130	266	403-655	238	498-810	269
128-158	266	403-657	238	498B-810	269
128-438	266	403-661	238	503-880	137
128-742	266	403-662	238	503-994	137
128-806	266	403-663	238	520-012	265
128-842	266	405-600	239	520-045	255
146-880	137	405-610	239	520-130	265
146-994	137	405-615	239	520-158	265
153-012	256	405-620	239	520-3R6	255
153-130	256	405-621	239	520-438	265
153-438	256	405-631	239	520-742	265
198-012	269	405-641	239	520-806	265
198-130	269	405-644	239	520-842	265
198-158	269	405-651	239	529-012	268
198-438	269	405-655	239	529-045	255
198-742	269	405-657	239	529-130	268
198-806	269	405-661	239	529-158	268
198-842	269	405-662	239	529-3R6	255
200F-645	253	405-663	239	529-438	268
200F-645½	253	420-880	136	529-742	268
200F-659	253	420-994	136	529-806	268
202-645	253	421-880	138	529-842	268
202-645½	253	421-994	138	529-990	139
202-659	253	422-880	138	541-158	285
230-810	247	422-994	138	541-880	137
230-820	247	428-004	266	541-994	137
230-821	247	428-048	266	564-880	137
230-831	247	428-074	266	564-994	137
230-841	247	428-806	266	600-004	262
230-851	247	428B-806	266	600-004½	262
300-004	256	428-810	266	600-048	262
300-048	256	428B-810	266	600-048½	262
302-645	253	430-600	236	600-072	262
302-659	253	430-610	236	600-072½	262
304-004	256	430-615	236	600-074	262
304-048	256	430-620	236	600-074½	262
320-004	265	430-621	236	600-806	262

	Page		Page		Page
600-806½	262	741-438	277	800-488	220
600B-806	262	741-438¼	277	801-400	222
600-810	262	741-464	277	801-402	222
600-810½	262	741-464¼	277	801-404	222
600B-810	262	741-522	277	801-405	222
602-004	264	741-522¼	277	801-410	222
602-048	264	741-742	277	801-415	222
602-074	264	741-742¼	277	801-419	222
602-806	264	741-842	277	801-420	222
602B-806	264	741-842¼	277	801-427	222
602-810	264	741-990	140	801-429	222
602B-810	264	741-991	140	801-432	222
602-933	139	745-130	279	801-441	222
641-004	257	745-158	279	801-444	222
641-048	257	745-438	279	801-451	222
641-074	257	745-464	279	801-454	222
641-3R6	257	745-522	279	801-455	222
700-012	262	745-742	279	801-455¼	222
700-130	262	745-842	279	801-455¾	222
700-158	262	745-879	136	801-456	222
700-426	262	745-990	140	801-457	222
700-438	262	745-993	136	801-459	222
700-742	262	753-177	254	801-461	222
700-806	262	753-2R6	254	801-462	222
700-842	262	753-247	254	801-463	222
700-991	139	753-879	138	801-465	222
702-012	264	753-880	138	801-469	222
702-045	255	753-993	138	801-488	222
702-130	264	753-994	138	803-400	224
702-158	264	767-158	284	803-402	224
702-3R6	255	767-438	284	803-404	224
702-438	264	767-464	284	803-405	224
702-742	264	767-522	284	803-410	224
702-806	264	767-742	284	803-415	224
702-842	264	767-842	284	803-419	224
702-991	139	788-130	281	803-420	224
739-130	273	788-158	281	803-427	224
739-130¼	273	788-464	281	803-429	224
739-158	273	788-522	281	803-432	224
739-158¼	273	788-742	281	803-441	224
739-438	273	788-842	281	803-444	224
739-438¼	273	788-990	140	803-451	224
739-464	273	800-400	220	803-454	224
739-464¼	273	800-402	220	803-455	224
739-522	273	800-404	220	803-455¼	224
739-522¼	273	800-405	220	803-456	224
739-742	273	800-410	220	803-457	224
739-742¼	273	800-415	220	803-459	224
739-842	273	800-419	220	803-461	224
739-842¼	273	800-420	220	803-462	224
740-130	275	800-427	220	803-463	224
740-130¼	275	800-429	220	803-465	224
740-158	275	800-432	220	803-469	224
740-158¼	275	800-441	220	803-488	224
740-438	275	800-444	220	805-400	225
740-438¼	275	800-451	220	805-402	225
740-464	275	800-454	220	805-404	225
740-464¼	275	800-455	220	805-405	225
740-522	275	800-455¼	220	805-410	225
740-522¼	275	800-455¾	220	805-415	225
740-742	275	800-456	220	805-419	225
740-742¼	275	800-457	220	805-420	225
740-842	275	800-459	220	805-427	225
740-842¼	275	800-461	220	805-429	225
740-991	140	800-462	220	805-432	225
741-130	277	800-463	220	805-441	225
741-130¼	277	800-465	220	805-444	225
741-158	277	800-469	220	805-451	225
741-158¼	277				

	Page		Page		Page
805-454	225	808-469	223	836-454	221
805-455	225	808-488	223	836-455	221
805-455 $\frac{1}{4}$	225	830-400	220	836-455 $\frac{1}{4}$	221
805-455 $\frac{3}{4}$	225	830-402	220	836-455 $\frac{3}{4}$	221
805-456	225	830-404	220	836-456	221
805-457	225	830-405	220	836-457	221
805-459	225	830-410	220	836-459	221
805-461	225	830-415	220	836-461	221
805-462	225	830-419	220	836-462	221
805-463	225	830-420	220	836-463	221
805-465	225	830-427	220	836-465	221
805-469	225	830-429	220	836-469	221
805-488	225	830-432	220	836-488	221
806-400	221	830-441	220	838-400	223
806-402	221	830-444	220	838-402	223
806-404	221	830-451	220	838-404	223
806-405	221	830-454	220	838-405	223
806-410	221	830-455	220	838-410	223
806-415	221	830-455 $\frac{1}{4}$	220	838-415	223
806-419	221	830-455 $\frac{3}{4}$	220	838-419	223
806-420	221	830-456	220	838-420	223
806-427	221	830-457	220	838-427	223
806-429	221	830-459	220	838-429	223
806-432	221	830-461	220	838-432	223
806-441	221	830-462	220	838-441	223
806-444	221	830-463	220	838-444	223
806-451	221	830-465	220	838-451	223
806-454	221	830-469	220	838-454	223
806-455	221	830-488	220	838-455	223
806-455 $\frac{1}{4}$	221	831-400	222	838-455 $\frac{1}{4}$	223
806-455 $\frac{3}{4}$	221	831-402	222	838-455 $\frac{3}{4}$	223
806-456	221	831-404	222	838-456	223
806-457	221	831-405	222	838-457	223
806-459	221	831-410	222	838-459	223
806-461	221	831-415	222	838-461	223
806-462	221	831-419	222	838-462	223
806-463	221	831-420	222	838-463	223
806-465	221	831-427	222	838-465	223
806-469	221	831-429	222	838-469	223
806-488	221	831-432	222	838-488	223
807-158	282	831-441	222	862-158	283
807-842	282	831-444	222	862-742	283
807-880	136	831-451	222	862-842	283
807-994	136	831-454	222	862-990	140
808-400	223	831-455	222	900-700	216
808-402	223	831-455 $\frac{1}{4}$	222	900-703	216
808-404	223	831-455 $\frac{3}{4}$	222	900-710U	216
808-405	223	831-456	222	900-720	216
808-410	223	831-457	222	900-741	216
808-415	223	831-459	222	900-744	216
808-419	223	831-461	222	900-751	216
808-420	223	831-462	222	900-751 $\frac{3}{4}$	216
808-427	223	831-463	222	900-754	216
808-429	223	831-465	222	900-754 $\frac{3}{4}$	216
808-432	223	831-469	222	900-755	216
808-441	223	831-488	222	900-757	216
808-444	223	836-400	221	900-761	216
808-451	223	836-402	221	900-764	216
808-454	223	836-404	221	904-700	217
808-455	223	836-405	221	904-703	217
808-455 $\frac{1}{4}$	223	836-410	221	904-710U	217
808-455 $\frac{3}{4}$	223	836-415	221	904-720	217
808-456	223	836-419	221	904-741	217
808-457	223	836-420	221	904-744	217
808-459	223	836-427	221	904-751	217
808-461	223	836-429	221	904-751 $\frac{3}{4}$	217
808-462	223	836-432	221	904-754	217
808-463	223	836-441	221	904-754 $\frac{3}{4}$	217
808-465	223	836-444	221	904-755	217
		836-451	221	904-757	217
				904-761	217
				904-764	217

Sample Mounts of Corbin Hardware

**K37****K40**

For use with Corbin Heavy Duty Cylindrical Locksets.

Height 8", Base 4" x 8".

**K31****K30**

Type of K29 and K32

**K38**

Type of K42

For use with Corbin Standard Duty Cylindrical Locksets.

Height 6 1/4"

Base 3 3/4" x 5 1/2"

K42 for use with Corbin Light Duty Cylindrical Locksets.

**K39**

For use with Corbin Light Duty Cylindrical Locksets.

10" high x 14" long
x 4" wide.

Actual samples of CORBIN Hardware are the keynote to selling better quality at bigger profits. They have eye appeal—and enable the prospects to see the goods as they will appear when applied.

In this section are shown the standard type of sample mounts for Corbin Hardware products. Study the following pages carefully and make a selection of the display mounts you feel are needed in your store.

Successful hardware dealers find that good displays of actual hardware influence buying and save much time.

Listing of Mounts Illustrated

K29 to K32—These panels have easel backs and can be mounted with knobs, escutcheons, handles, push plates and other pieces obtainable in the following sizes:

No.	Type	Size
K29	Inside	9x3 1/2 in.
K30	Front Door	12x3 1/2 in.
K31	Sectional	15x4 1/2 in.
K32	Store Door	20x5 in.

Type of **K2**

For mounting all Corbin Locksets. Sizes of blocks vary to suit the individual item and show it to best advantage.

LOCKSET BLOCKS


No.	Type	Size
K1	Inside	11 x 5 x 1 3/4 in.
K2	Inside Tubular	6 x 4 3/4 x 1 3/8 in.
K3	Front Door	16 x 5 x 1 3/4 in.
K4	Sectional Front Door	21 x 5 1/2 x 1 3/4 in.
K5	Store Door	24 x 5 1/2 x 1 3/4 in.
K7	Screen Door	8 x 3 1/2 x 1 1/8 in.

020 Sample Mounts of Corbin Products



K13

For Corbin Surface Floor Hinge
15 x 6½ x 4 in.




K11, K12

For Corbin Screen Door Closers
Nos. 17 and 21

K11 20 x 6½ x 6 in.

K12 22 x 9 x 4 in.



K16

K16 For Four Night Latches with
removable mounts.

19¼ x 9¼ x 1⅝ in.



K10

Counter Demonstrator, Hinged
5 x 9 x 1⅝ in.

For Night Latches


Merchandizers



**No. 70
PADLOCK BOARD**

18 x 4½ in.

Mounted with one each
900, 904, 9913X, 9954, P95



**No. 50
CABINET LOCK BOARD**

11¼ x 17¾ in.

Mounted with

Drawer	Cupboard	Wardrobe	Chest
590	02067	701B	34
592½		702B	0142P
0666		749	
699		750	
02066			



No. 60

**PRESSURE CAST ALUMINUM
HARDWARE**

10 x 4½ in.

Mounted with

EA 6396	Bar Lift
EA 6829	Sash Fastener
EA 6232	Hat and Coat Hook
EA 6170	Hand Rail Bracket
EA 6387	Door Stop


SAMPLE MOUNTS NOT ILLUSTRATED

No.	Type	Size	No.	Type	Size
K6	Door Bell	7½ x 5 x 1⅝ in.	K24	Push Bar	30 x 4 x ⅝ in.
K14	1446 Bar Bolt	6½ x 4½ x 1⅝ in.	K33	Flush Bolt	16 x 2½ x 1⅝ in.
K15	1447 Bar Bolt	7 x 5 x 1⅝ in.	K34	Flush Bolt	12 x 2½ x 1⅝ in.
K22	Rimsets	11 x 5 x 1⅝ in.	K36	Panic Bolt	26½ x 26 in.
K23	Panic Bolt	30 x 15 x 1⅝ in.	K41	Heavy Duty 5 in. B.S.	11¼ x 3¼ x 9 in.
			K43	"Defender" 5 in. B.S.	10 x 3¼ x 8½ in.

Good buildings

deserve

good hardware



Aberhart Memorial Hospital
Edmonton, Alberta



The Hong Kong & Shanghai Banking Corp.
Hong Kong, China



Federal Building
Victoria, British Columbia



Mount Sinai Hospital
Toronto, Ontario



Calgary General Hospital
Calgary, Alberta

Description of Finishes

1

Specify finish by prefixing finish symbol to catalogue number

FOR CAST AND WROUGHT BRONZE

Finish Symbol	Description	Finish Symbol	Description
Bronze Finishes		SKB	Statuary, Medium, Sanded
B	Natural Colour, Polished	R	Antique Copper
DB	Natural Colour, Dull	KF	Sanded, Dull Black
DBOR	Natural Colour, Dull, Oil Rubbed	Nickel Finishes	
KHB	Dull Bronze, Oxidized and Relieved Suitable only for ornamental goods Use DB for plain goods to match	E	Nickel Plated, Polished
KB	Statuary, Medium	DE	Nickel Plated, Dull
RKB	Statuary, Medium, Sanded, High Parts Polished Suitable only for ornamental goods Use SKB for plain goods to match	KE	Nickel Plated, Oxidized and Relieved Suitable only for ornamental goods Use DE for plain goods to match
		SKE	Nickel Plated, Oxidized and Relieved, Sanded
		Chromium Finishes	
		CR	Chromium Plated, Polished
		DCR	Chromium Plated, Dull

FOR CAST AND WROUGHT BRASS

Finish Symbol	Description	Finish Symbol	Description
A	Natural Color, Polished	HPE	Imitation Half Polished Iron, Hammered Suitable only for ornamental goods Use SKE for plain goods to match
EA	Natural Color, Dull		
KA	Oxidized and Relieved Suitable only for ornamental goods Use EA for plain goods to match		

BRASS AND BRONZE WITHOUT LACQUER

NICKELINE

Finish Symbol	Description	Finish Symbol	Description
NL	Indicates "No Lacquer." For example, DBNL	NK	Composition Cast White Metal, Highly Polished
		DNK	Composition Cast White Metal, Dull Finish

ALUMINUM

Furnished only on items described in catalogue as available in Aluminum metal.

Finish Symbol	Description	Finish Symbol	Description
AL	Roll Polished and Lacquered	EA	Brass Plated, Dull, Lacquered
*DA	Dull, Lacquered	DB	Bronze Plated, Dull, Lacquered
DL	Dull Satin, Anodized	E	Nickel Plated
*	Kick Plates only		

Description of Finishes

Specify finish by prefixing finish symbol to catalogue number

FOR STEEL AND IRON

Japanned, Zinc, Coppered and Dead Black finishes are furnished only on articles so described in Catalogue and are applied to unpolished surface.

Finish Symbol	Description	Finish Symbol	Description
Brass Plated Finishes		Miscellaneous Finishes	
EA	Brass Plated, Dull	C	Copper (listed)
KA	Brass Plated, Oxidized and Relieved Suitable only for ornamental goods Use EA for plain goods to match	D	Dead Black (listed)
Bronze Plated Finishes		J	Japanned (listed)
DB	Bronze Plated, Dull	G	Zinc (listed)
KHB	Dull Bronze, Oxidized and Relieved Suitable only for ornamental goods Use DB for plain goods to match	R	Antique Copper
Nickel Plated Finishes		KF	Sanded, Dull Black
E	Nickel Plated, Polished (For Steel Only) For Cast Iron use DE	HPE	Imitation Half Polished Iron, Hammered Suitable only for ornamental goods Use SKE for plain goods to match
DE	Nickel Plated, Dull	For Door Closers Only	
KE	Nickel Plated, Oxidized, and Relieved Suitable only for ornamental goods Use DE for plain goods to match	AL	Aluminum Bronze
SKE	Nickel Plated, Oxidized and Relieved, Sanded	MR	Maroon Bronze
*For Night Latches Only		PC	Prime Coat
DW	Black Wrinkle Japan	D	Dead Black
EAW	Dull Brass Wrinkle Japan	For Iron Exit Fixtures	
HBW	Statuary Bronze Wrinkle Japan	EAL	Sprayed finish, to match EA (listed)
ALW	Aluminum Wrinkle Japan		

*NIGHT LATCHES 3A6 FURNISHED IN METALLESCENT FINISHES

Finish Symbol	Description	Finish Symbol	Description
EA	Brass	GM	Gun Metal
MR	Maroon Bronze	AL	Aluminum

Comparative Finish Symbols


CORBIN WITH OTHER BUILDERS HARDWARE MANUFACTURERS

Corbin Lock Co. of Can. Ltd.	Belleville Lock Co. Ltd.	The Peterborough Lock Mfg. Co. Ltd.	Schlage Lock Co. of Can. Ltd.	The Stanley Works of Can. Ltd.	The Yale and Towne Mfg. Co.
B	Z1	1	9	A	BZ10
DB	Z3	4	10	A5	BY22
KHB	Z6	34	11	A4	BY21
KB	Z16	6	20	B4	BY25
A	R1	12	3	C	AZ10
EA	R3	13	4	F	AY22
KA	R6	15	5	F4	AY21
E	N1	30	N	NZ10
DE	N3	31	15	N5	NY10
KE	N6	32	15A	N3	NY21
CR	CM1	42	26	CM	DZ10
DCR	CM3	43	26D	CMD	DY10
NK	K1	33	25	NM	NZ40
DNK	K3	39	25D	NMD	Y40
HPE	HF	GB32	17A	Y3	NX56
KF	BN	40	19	H	BX90
DL	AL
R	R7	8	...	D2	CZ27
PC	PC	...
C	...	26
D	...	40	...	J1	DJ
J	J	17	...	J	J


Handing of Doors and Windows

ALWAYS TAKE HANDINGS FROM OUTSIDE

Mortise or Rim Locks




Left Hand Lock
(Door, left hand)




Right Hand Lock
(Door, right hand)

Outside




Left Hand Reverse Bevel Lock

Outside




Right Hand Reverse Bevel Lock

Book Case or Cupboard



Left Hand Lock


Outside




Right Hand Lock

Book case and cupboard doors always open out, and the locks are regularly made with reverse bevel latch bolt; it is not necessary to specify reverse bevel.

Casement Windows




Left Hand




Right Hand

OPENING IN




Left Hand

Right Hand




Left Hand



Right Hand

OPENING OUT



Left Hand

Right Hand

Casement windows are handed from inside and it is necessary to state whether they open in or open out.

Symbols

For use in specifying and ordering Corbin locks and builders' hardware

Affix symbol to number of item to which it applies

Symbol	Description	Symbol	Description
	Butts		Locks and Strikes
BT	Button Tip.	BS	Backset or distance from Front of Lock to center of Hub or Keyhole. State size.
FW	Fibre Washer.	BEV.	Bevel of Lock Front. State Bevel required. The usual Bevel is $\frac{1}{8}$ in 2 in.
NRP	Non Rising Pin.	CBX	Cast Box Strike. State Hand.
	Dummy Trim	PX	Protected Strike. State Hand and Thickness of Door.
DC	Dummy Cylinder.	PBX	Protected Box Strike. State Hand and Thickness of Door.
	Finishes	WBX	Wrought Box Strike.
	See pages 1 and 2.	AR	Armored Front.
	Hand of Doors	SLC	Strike Lip to center.
	See page 4.		Machine Screws
	Keys	MS	Furnish with Machine Screws.
MK	Master Key.		Template Work
SMK	Sub Master Key.	FULL TMS	Made to Template and furnished with Machine Screws.
G MK	Grand Master Key.	$\frac{1}{2}$ TMS	Made to Template and furnished with Machine Screws for Metal Frames with Wood Screws for Wood Door.
EM. K	Emergency Key.	ATMS	Arm only of Door Closer made to Template and furnished with Machine Screws.
	Knobs	STMS	Strike only made to Template and furnished with Machine Screws.
NOR	No Rose.	STWBX	Wrought Box Strike only to Template and furnished with Machine Screws.
PY	Knob Shank		
LH	Lever Handle		
SIMPLEX	Knob Shank		
TS	Screwless		
2KS	2 Knob Screws in Each Shank of Knobs		



CANADA

BUTTS AND HINGES

LOOSE PIN BUTTS

TEMPLATE BUTTS

HALF SURFACE BUTTS







FULL SURFACE BUTTS

WROUGHT BRASS BUTTS

ADJUSTABLE
BALL BEARING PIVOT HINGES

SURFACE
FLOOR SPRING HINGES

GRAVITY
PIVOT HINGES





 INDEX OF

Butts, Hinges and Pivots

Item	Page
CABINET:	
Narrow	13
Middle	13
Broad	13
FLOOR HINGES	16
GRAVITY PIVOTS	17
HINGE PIVOTS, ADJUSTABLE	15
MORTISE:	
Half Mortise	12
Regular	9, 11
Template	10, 11
SURFACE:	
Full Surface	12
Half Surface	12

Loose Pin Butts

Heavy Wrought Brass or Bronze

Polished



80

Stainless Steel Bushed
Type of 80½
Not bushed

No. 80 and 180 can also be furnished wrought aluminum DL finish, when so ordered. Prefix DL to number.

Cold Rolled for toughness


Non-rising Stainless Steel Pins

All edges square

Leaves beveled at Knuckles for close fit

Button tipped; Five Knuckles

Finished to match other Corbin Hardware



180, 180½

Two non-detachable
stainless steel ball bearings

Polished designates knuckles polished and buffed and each leaf buffed only.

Highly polished designates complete butt polished and buffed.

Number Polished	Number Highly Polished	Size Open Inches	Gauge of Metal	Wood Screws per Butt	Brass or Bronze Weight Pair Lbs.	Aluminum Weight Pair Lbs.	Packed in a Box, Pair
80½	80	3½ x 3½	.123	6-1 x10	1¼	¾	1
For Residential and other medium weight doors		4 x 4	.130	8-1 x12	1¾	⅞	1
		4½ x 4½	.138	8-1¼x12	2⅞	¾	1
		5 x 4	.146	10-1¼x12	2⅞	1⅜	1
		5 x 4½	.146	10-1¼x12	2⅞	1⅜	1
		5 x 5	.146	10-1¼x12	3⅞	1	1
		6 x 6	.160	10-1½x14	5⅞	1⅞	1
Number Polished	Number Highly Polished	Size Open Inches	Gauge of Metal	Wood Screws per Butt	Brass or Bronze Weight Pair Lbs.	Aluminum Weight Pair Lbs.	Packed in a Box, Pair
180½	180	3½ x 3½	.123	6-1 x10	1⅜	¾	1
For medium weight doors receiving average service and closer equipped doors		4 x 4	.130	8-1 x12	1⅞	½	1
		4½ x 4½	.138	8-1¼x12	2¼	1⅜	1
		5 x 4	.146	10-1¼x12	2⅞	⅞	1
		5 x 4½	.146	10-1¼x12	2⅞	1⅜	1
		5 x 5	.146	10-1¼x12	3⅞	1	1
		6 x 6	.160	10-1½x14	4⅞	1⅞	1

Size 4 x 4 and larger can be furnished with non-removable pin when door is closed, to order suffix "A" to number. No. 180 4 x 4 and larger can be furnished with four ball bearing washers when so ordered at additional charge.

Packed with screws.

Specify number, size and finish. See pages 1 and 2.



Loose Pin Template Butts

Heavy Wrought Brass or Bronze

Polished




90

Stainless steel bushed
Type of 90½
Not bushed

No. 90 and 190 can also be furnished wrought aluminum DL finish, when so ordered. Prefix DL to number.

Cold Rolled for toughness
Non-rising Stainless Steel Pins
All edges square
Leaves beveled at Knuckles for close fit
Button tipped; Five Knuckles
Finished to match other Corbin Hardware



190, 190½

Two non-detachable
stainless steel ball bearings

Polished designates knuckles polished and buffed and each leaf buffed only.

Highly polished designates complete butt polished and buffed.

For wood doors and hollow metal frames specify ½ TMS

Number Polished	Number Highly Polished	Size Open Inches	Gauge of Metal	Machine Screws per butt	Brass or Bronze Weight Pair Lbs.	Aluminum Weight Pair Lbs.	Packed in a Box, Pair
90½	90	3½ x 3½	.123	6-½ x 10-24	1¾	¾	1
For medium weight hollow metal or wood doors and hollow metal frames		4 x 4	.130	8-½ x 12-24	1¾	¾	1
		4½ x 4½	.138	8-½ x 12-24	2¼	1½/16	1
		5 x 4	.146	8-½ x 12-24	2⅝	1¾/16	1
		5 x 4½	.146	8-½ x 12-24	2⅜/16	¾	1
		5 x 5	.146	8-½ x 12-24	3	1⅝/16	1
		6 x 6	.160	10-½ x ¼-20	4⅜/16	1⅞/16	1
190½	190	3½ x 3½	.123	6-½ x 10-24	1¾	¾	1
For medium weight hollow metal or wood doors and closer equipped doors with hollow metal frames		4 x 4	.130	8-½ x 12-24	1⅝	½	1
		4½ x 4½	.138	8-½ x 12-24	2¼	1½/16	1
		5 x 4	.146	8-½ x 12-24	2⅞/16	1¾/16	1
		5 x 4½	.146	8-½ x 12-24	2¾	¾	1
		5 x 5	.146	8-½ x 12-24	2⅝/16	1⅝/16	1
		6 x 6	.160	10-½ x ¼-20	4¾	1½	1

Size 4 x 4 and larger can be furnished with non-removable pin when door is closed, to order suffix "A" to number. No. 190 4 x 4 and larger can be furnished with four ball bearing washers when so ordered at additional charge.

Packed with screws.

Specify number, size and finish. See pages 1 and 2.




Loose Pin Butts

11

CAST IRON

Extra Heavy, Polished and Plated
Five Knuckles
Non-Rising Steel Pins
Button Tips



062, T062, 072

Number Plain	Number Polished	Size Open Inches	Grade	Wood Screws per Butt	Weight Pair Lbs.	Packed in a box, Pair
T062	062	3 x 3	Extra Heavy	6-1 x10	$\frac{3}{4}$	1
For wood doors and frames		4 x 4	Extra Heavy	8-1 $\frac{1}{4}$ x12	2 $\frac{5}{8}$	1
		4 $\frac{1}{2}$ x 4 $\frac{1}{2}$	Extra Heavy	8-1 $\frac{1}{4}$ x12	3	1
		5 x 5	Extra Heavy	8-1 $\frac{1}{2}$ x12	4 $\frac{5}{8}$	1
		5 $\frac{1}{2}$ x 5 $\frac{1}{2}$	Extra Heavy	8-1 $\frac{1}{2}$ x12	6	1

Can be furnished prime coat for painting when so ordered.

Packed with screws.

Loose Pin Template Butts

CAST IRON

For wood doors and hollow metal frames specify $\frac{1}{2}$ TMS

Number	Size Open Inches	Finish	Grade	Machine Screws per Butt	Weight Pair Lbs.	Packed in a box, Pair
072	4 x 4	Polished	Extra Heavy	8- $\frac{1}{2}$ x10-24	2 $\frac{5}{8}$	1
For hollow metal or wood doors and hollow metal frames	4 $\frac{1}{2}$ x 4 $\frac{1}{2}$	Polished	Extra Heavy	8- $\frac{1}{2}$ x12-24	3	1
	5 x 5	Polished	Extra Heavy	8- $\frac{5}{8}$ x12-24	4 $\frac{5}{8}$	1
	5 $\frac{1}{2}$ x 5 $\frac{1}{2}$	Polished	Extra Heavy	8- $\frac{5}{8}$ x12-24	6	1

Packed with screws.

Specify number, size and finish. See pages 1 and 2.



Loose Pin Butts


NON-RISING PIN

With Two Self-retaining Non-Detachable Ball Bearing Washers

Five Knuckles

Furnished with Stainless Steel Pins and Stainless Steel Ball Bearings

Button Tips



HALF MORTISE — To Template. For Hollow Metal Doors with Channel Iron Jamb

No.	Size	Material and Finish	A Width of Jamb Leaf	B Width of Door Leaf	Gauge of Metal	C Offset of Jamb Leaf	Quantity and Size of Machine Screws		Weight Pair with Screws
							Jamb Leaf	Door Leaf	
208	4½ in.	Heavy Wrought Brass or Bronze	1½ in.	2¼ in.	.138	1⅜ in.	3-OH ½ x 12-24	4-FH ½ x 12-24	3 Lbs.
	5 in.	Polished Polished	1½ in.	2½ in.	.146	⅞ in.	4-OH ½ x 12-24	4-FH ½ x 12-24	3½ Lbs.

FULL SURFACE — To Template. For Kalamein Doors with Channel Iron Jamb

No.	Size	Material and Finish	A Width of Jamb Leaf	B Width of Door Leaf	Gauge of Metal	C Offset of Door Leaf	D Offset of Jamb Leaf	Machine Screws for Jamb Leaf	*Machine Screws and Grommet Nuts for Door Leaf	Weight Pair with Screws
210	4½ in.	Heavy Wrought Brass or Bronze	1½ in.	2⅞ in.	.138	1⅝ in.	1⅝ in.	3-OH ½ x 12-24	3-OH 2 x ¼-20	3 Lbs.
	5 in.	Polished Polished	1½ in.	2⅞ in.	.146	1 in.	2¼ in.	4-OH ½ x 12-24	4-OH 2 x ¼-20	3½ Lbs.

HALF SURFACE — To Template. For Kalamein Doors with Pressed Steel Jamb

No.	Size	Material and Finish	A Width of Jamb Leaf	B Width of Door Leaf	Gauge of Metal	C Offset of Door Leaf	Machine Screws for Jamb Leaf	*Machine Screws and Grommet Nuts for Door Leaf	Weight Pair with Screws
212	4 in.	Heavy Wrought Brass or Bronze	2 in.	2¼ in.	.130	1⅜ in.	4-FH ½ x 12-24	3-OH 2 x ¼-20	3 Lbs.
	4½ in.	Polished	2¼ in.	2⅞ in.	.138	¾ in.	4-FH ½ x 12-24	3-OH 2 x ¼-20	3 Lbs.
	5 in.	Polished	2½ in.	2⅞ in.	.146	1 in.	4-FH ½ x 12-24	4-OH 2 x ¼-20	3½ Lbs.

HALF SURFACE — Non-Template. For Kalamein Doors with Kalamein Jamb

No.	Size	Material and Finish	A Width of Jamb Leaf	B Width of Door Leaf	Gauge of Metal	C Offset of Door Leaf	Wood Screws for Jamb Leaf	*Machine Screws and Grommet Nuts for Door Leaf	Weight Pair with Screws
216	4 in.	Heavy Wrought Brass or Bronze	2 in.	2¼ in.	.130	1⅜ in.	4-FH 1¼ x 12	3-OH 2 x ¼-20	3 Lbs.
	4½ in.	Polished	2¼ in.	2⅞ in.	.138	¾ in.	4-FH 1¼ x 12	3-OH 2 x ¼-20	3 Lbs.
	5 in.	Polished	2½ in.	2⅞ in.	.146	1 in.	5-FH 1¼ x 12	4-OH 2 x ¼-20	3½ Lbs.

When so ordered above Butts can be furnished with pins which cannot be removed when door is closed. In ordering affix A to number, thus: 208A.

*If machine screws with grommet nuts are required longer than 2 in. order should so state.

One and one-half pair in a box, with screws.


Specify number, size and finish. See pages 1 and 2.





Wrought Brass Butts

13

STEEL PIN

Type	Size Length Inches	Width Open Inches	Gauge of Metal	Countersunk For Screws	Packed in a Box, Doz. Pairs	Weight per Box	
 2 in.	NARROW	$\frac{1}{2}$	$\frac{1}{2}$.027	0	24	1 $\frac{3}{4}$ Lbs.
		$\frac{3}{4}$	$1\frac{1}{16}$.033	2	6	1 $\frac{1}{8}$ Lbs.
		1	$\frac{3}{4}$.036	2	6	1 $\frac{3}{4}$ Lbs.
		$1\frac{1}{4}$	$2\frac{5}{32}$.040	3	6	2 $\frac{1}{2}$ Lbs.
		$1\frac{1}{2}$	$\frac{7}{8}$.040	4	6	3 $\frac{1}{4}$ Lbs.
		$1\frac{3}{4}$	1	.042	5	6	4 $\frac{3}{4}$ Lbs.
		2	$1\frac{1}{32}$.045	5	6	5 $\frac{1}{16}$ Lbs.
		$2\frac{1}{2}$	$1\frac{1}{2}$.052	6	3	5 $\frac{1}{2}$ Lbs.
		3	$1\frac{5}{8}$.062	8	1	2 $\frac{7}{8}$ Lbs.

Type	Size Length Inches	Width Open Inches	Gauge of Metal	Countersunk For Screws	Packed in a Box, Doz. Pairs	Weight per Box
 2 in.	MIDDLE					
	1/2	9/16	.027	0	24	2 Lbs.
	3/4	3/4	.033	2	6	1 1/16 Lbs.
	1	7/8	.036	3	6	1 7/8 Lbs.
	1 1/4	7/8	.040	4	6	2 3/4 Lbs.
	1 1/2	1 1/32	.040	4	6	3 3/4 Lbs.
	1 3/4	1 1/8	.042	5	6	5 Lbs.
	2	1 1/16	.045	5	6	6 1/16 Lbs.
	2 1/2	1 5/8	.052	6	3	5 7/8 Lbs.
3	1 3/4	.062	8	1	3 1/8 Lbs.	

Type	Size Length Inches	Width Open Inches	Gauge of Metal	Countersunk For Screws	Packed in a Box, Doz. Pairs	Weight per Box
 2 in.	BROAD					
	$\frac{1}{2}$	$\frac{5}{8}$.027	0	24	2 $\frac{1}{4}$ Lbs.
	$\frac{3}{4}$	$\frac{7}{8}$.033	3	6	1 $\frac{1}{16}$ Lbs.
	1	1	.036	3	6	2 $\frac{1}{16}$ Lbs.
	$1\frac{1}{4}$	$1\frac{1}{32}$.040	4	6	3 Lbs.
	$1\frac{1}{2}$	$1\frac{1}{4}$.040	4	6	4 $\frac{3}{8}$ Lbs.
	$1\frac{3}{4}$	$1\frac{1}{16}$.042	5	6	5 $\frac{3}{4}$ Lbs.
	2	$1\frac{3}{8}$.045	5	6	7 $\frac{1}{2}$ Lbs.
	$2\frac{1}{2}$	$1\frac{3}{4}$.052	6	3	6 $\frac{3}{8}$ Lbs.
	3	2	.062	8	1	3 $\frac{3}{8}$ Lbs.


Packed without screws.

Specify Size



Adjustable Ball Bearing Pivot Hinges

PATENTED



The Corbin Ball-Bearing Pivot Hinge is truly anti-friction. Thrust and radial loads are taken care of by separate bearings. The door weight is carried on hardened steel races and precision steel balls, while the radial loads are taken by long roller bearings. Both the ball thrust bearings and the roller radial bearings contain a liberal supply of lubricant and are completely housed. Long, trouble-free life is assured.

The Corbin Ball-Bearing Intermediate and Bottom Pivot Hinges are adjustable to permit raising and lowering the door.

The Bottom Pivot Hinge is provided with a threaded cap and moisture-proof gasket to keep water and dirt from the bearings.

They are made of the finest quality of cast bronze or malleable iron. The pins on which are carried both thrust and radial loads are of high manganese steel with an extra-deep pack hardened case to guard against spalling or brinelling. The balls in the thrust bearings are of the highest quality obtainable, thus ensuring the carrying of the weight of the door on all of the balls instead of on just a few.

The use of the roller bearings to take the radial loads provides load distribution over a large projected area.

The weight of the door automatically locks the adjusting screw of the Bottom Pivot Hinge so that the swinging of the door cannot change the adjustment.

The adjustment of the Intermediate Pivot Hinge cannot change once it is set.

All corners of the mortised portions are square, simplifying mortising operations.

Corbin Pivot Hinges may be used in various combinations to hang the door to suit different requirements.

1. Top and bottom pivot hinges.
2. Top, bottom, and intermediate.
3. Top, with the intermediate type located near the bottom of the door.
4. Bottom, with the intermediate type located near the top of the door.
5. Two or more of the intermediate type.

A Top and a Bottom Pivot Hinge will safely handle the average door.

For doors of extra height or width or of unusual weight the additional use of one or more Intermediate Pivot Hinges is recommended.


Consult us for specifications to take care of unusual conditions.





Wrought Brass Butts

13

STEEL PIN

Type	Size Length Inches	Width Open Inches	Gauge of Metal	Countersunk For Screws	Packed in a Box, Doz. Pairs	Weight per Box	
	NARROW	½	½	.027	0	24	1¾ Lbs.
		¾	1⅛	.033	2	6	1⅛ Lbs.
		1	¾	.036	2	6	1¾ Lbs.
		1¼	23⁄32	.040	3	6	2½ Lbs.
		1½	7⁄8	.040	4	6	3¼ Lbs.
		1¾	1	.042	5	6	4¾ Lbs.
		2	1⅛	.045	5	6	5⅛ Lbs.
		2½	1⅞	.052	6	3	5½ Lbs.
		3	1⅝	.062	8	1	2⅞ Lbs.

Type	Size Length Inches	Width Open Inches	Gauge of Metal	Countersunk For Screws	Packed in a Box, Doz. Pairs	Weight per Box	
 2 in.	MIDDLE	½	⅞	.027	0	24	2 Lbs.
		¾	¾	.033	2	6	1⅜ Lbs.
	1	⅞	.036	3	6	1⅞ Lbs.	
	1¼	⅞	.040	4	6	2¾ Lbs.	
	1½	1⅛	.040	4	6	3¾ Lbs.	
	1¾	1⅞	.042	5	6	5 Lbs.	
	2	1¾	.045	5	6	6⅞ Lbs.	
	2½	1⅝	.052	6	3	5⅞ Lbs.	
	3	1¾	.062	8	1	3½ Lbs.	

Type	Size Length Inches	Width Open Inches	Gauge of Metal	Countersunk For Screws	Packed in a Box, Doz. Pairs	Weight per Box	
 2 in.	BROAD	$\frac{1}{2}$	$\frac{5}{8}$.027	0	24	2¼ Lbs.
		$\frac{3}{4}$	$\frac{7}{8}$.033	3	6	1⅝ Lbs.
		1	1	.036	3	6	2⅛ Lbs.
		1¼	1⅜	.040	4	6	3 Lbs.
		1½	1½	.040	4	6	4⅜ Lbs.
		1¾	1⅞	.042	5	6	5¼ Lbs.
		2	1⅞	.045	5	6	7½ Lbs.
		2½	1¾	.052	6	3	6⅜ Lbs.
		3	2	.062	8	1	3⅝ Lbs.


Packed without screws.

Specify Size

CORBIN

Adjustable Ball Bearing Pivot Hinges

PATENTED



The Corbin Ball-Bearing Pivot Hinge is truly anti-friction. Thrust and radial loads are taken care of by separate bearings. The door weight is carried on hardened steel races and precision steel balls, while the radial loads are taken by long roller bearings. Both the ball thrust bearings and the roller radial bearings contain a liberal supply of lubricant and are completely housed. Long, trouble-free life is assured.

The Corbin Ball-Bearing Intermediate and Bottom Pivot Hinges are adjustable to permit raising and lowering the door.

The Bottom Pivot Hinge is provided with a threaded cap and moisture-proof gasket to keep water and dirt from the bearings.

They are made of the finest quality of cast bronze or malleable iron. The pins on which are carried both thrust and radial loads are of high manganese steel with an extra-deep pack hardened case to guard against spalling or brinelling. The balls in the thrust bearings are of the highest quality obtainable, thus ensuring the carrying of the weight of the door on all of the balls instead of on just a few.

The use of the roller bearings to take the radial loads provides load distribution over a large projected area.

The weight of the door automatically locks the adjusting screw of the Bottom Pivot Hinge so that the swinging of the door cannot change the adjustment.

The adjustment of the Intermediate Pivot Hinge cannot change once it is set.

All corners of the mortised portions are square, simplifying mortising operations.

Corbin Pivot Hinges may be used in various combinations to hang the door to suit different requirements.

1. Top and bottom pivot hinges.
2. Top, bottom, and intermediate.
3. Top, with the intermediate type located near the bottom of the door.
4. Bottom, with the intermediate type located near the top of the door.
5. Two or more of the intermediate type.

A Top and a Bottom Pivot Hinge will safely handle the average door.


For doors of extra height or width or of unusual weight the additional use of one or more Intermediate Pivot Hinges is recommended.

Consult us for specifications to take care of unusual conditions.



Adjustable Ball Bearing Pivot Hinges 15

PATENTED



No.	Type of Pivot	Material and Finish	Type of Bearing	Packed in a Box	Weight Each
321	Top	*Cast Bronze	Roller	1	1 Lb.
322	Intermediate	Polished	Ball & Roller	1	1½ Lbs.
323	Bottom	Polished	Ball & Roller	1	2 Lbs.
0321	Top	†Malleable Iron	Roller	1	1 Lb.
0322	Intermediate	Prime Coat	Ball & Roller	1	1½ Lbs.
0323	Bottom	Prime Coat	Ball & Roller	1	2 Lbs.

All leaves are $\frac{7}{8}$ inch wide making the Corbin Ball Bearing Pivot Hinges applicable to rabbeted doors. All barrels or knuckles are of the same diameter lending to neat, trim appearance. All screw locations are to template. Complete templating details available upon request.


Intermediate pivots can be furnished with set screw to prevent removal of cap screw. In ordering, affix "A" to number, thus 322A.

Packed with screws.

*Cast bronze furnished in any standard finish.

†Malleable iron also furnished in cadmium and dead black finishes.

Details Showing Offset Dimensions




Specify number, hand and finish. See pages 1 and 2.




Surface Floor Spring Hinges

FDR LIGHT DDUBLE-ACTING INSIDE DOORS



400-0400



View With Side Plates Removed

Adjustable as to alignment. For doors 1½" to 1¾" thickness



Top Pivot

Pivot Wrought Steel, Socket Cast Iron
Furnished with Nos. 400-0400

0406

Jamb Plate

No.

D0406 Wrought Steel, Dead Black

0406 Wrought Steel, Plated

For cement or tile floors

Furnished only when so ordered

Frame—Wrought steel 9 in. long.

Top Pivot—Wrought steel with cast iron socket.

Base—Wrought steel 3 x 2¾ in.

Side Plates—Reversible 1⅞ x 9½ in. ⅜ in. Projection.

Will hold door open at 90° angle. Cannot be otherwise furnished.

No.	Side Plates	Base Plate	Weight Each
400	Wrought Brass or Bronze Polished	Wrought Steel Plated	3 lbs.
D0400	Wrought Steel Dead Black	Dead Black	3 lbs.
0400	Plated	Plated	3 lbs.

One in a box with screws.





Specify number and finish. See pages 1 and 2.



Gravity Pivot Hinges

17

FOR SINGLE OR DOUBLE ACTING RIGHT OR LEFT HAND LAVATORY DOORS
CAST BRASS OR BRONZE



500

For Surface Application on Wood or Metal Frontals with Not Less than 1 3/8 in. Hanging Stile.

501

With Clamp Bracket for use on Marble, Slate or Glass Frontals.

Furnished only for Center Hung Doors lower than height of Frontal.

Cannot be furnished for Doors same height as Frontal.

Adjustable Alignment: The Adjustable Cam permits aligning and setting the Door to any desired Close or Hold Open position after Door is hung.

Furnished only for Door and Frontal Thickness as listed.

No.	Material and Finish	*Frontal Thickness	*Door Thickness							Packed in a Box	Weight Each
500	Cast Brass or Bronze	Not less than 1 3/8 in.									
	Polished		3/4 in.	1 in.	1 1/8 in.	1 1/4 in.	1 3/8 in.	1 1/2 in.	1 3/4 in.	1 Set	2 1/4 lbs.
501	Cast Brass or Bronze										
	Polished	1 in.	3/4 in.	1 in.	—	—	—	—	—	1 Set	3 1/4 lbs.
	Polished	1 1/8 in.	3/4 in.	1 in.	1 1/8 in.	—	—	—	—	1 Set	3 1/4 lbs.
	Polished	1 1/4 in.	3/4 in.	1 in.	1 1/8 in.	1 1/4 in.	—	—	—	1 Set	3 1/4 lbs.
	Polished	1 3/8 in.	3/4 in.	1 in.	1 1/8 in.	1 1/4 in.	1 3/8 in.	—	—	1 Set	3 1/4 lbs.
	Polished	1 1/2 in.	3/4 in.	1 in.	1 1/8 in.	1 1/4 in.	1 3/8 in.	1 1/2 in.	—	1 Set	3 1/4 lbs.
	Polished	1 3/4 in.	3/4 in.	1 in.	1 1/8 in.	1 1/4 in.	1 3/8 in.	1 1/2 in.	1 3/4 in.	1 Set	3 1/4 lbs.

No. 500 Frontal Bracket with wood or machine screws; door clip furnished with through bolts.

No. 501 Frontal Flange and Door Clip furnished with through bolts.

* Specify thickness of door and frontal.

Minimum distance top edges of door and frontal—3 in.

Specify number and finish. See pages 1 and 2.





CANADA

DOOR CLOSERS



**SURFACE DOOR
CLOSERS**

**DOOR CLOSERS WITH
HOLD-OPEN DEVICES**

FIRE DOOR CLOSERS

**THE "400"
SEMI-CONCEALED
DOOR CLOSERS**

**SCREEN DOOR
CLOSERS**





 INDEX OF


Door Closers, Brackets and Parts

Item	Page
BRACKETS	27, 31
CLOSERS:	
Corbin "400"	37, 45
Coupon Booth	24
Fusible Link	24
Hold-Open	23
Hospital	25
Parallel Arm	29, 30
Regular	22
Screen Door	34, 36
PARTS:	
Regular	32, 33
Screen Door	35
TABLES:	
Ordering Information "400"	39
Special Arm Brackets "400"	41
Application Details "400"	42, 45

Door Closers

MODEL 150

21



It is very generally recognized that the Corbin door closer meets most perfectly all the conditions of difficult and exacting requirements. It is this recognition which has led to the adoption of the Corbin door closer for the entrances of large terminal stations where throngs pass in and out and strong draughts are encountered; in public and office buildings where the cost of up-keep and trouble of frequent attention are carefully considered, and in many other places where the requirements are severe. It is mechanically correct, well made, generous in its design, and contains features of unusual merit which have warranted the favor it has received.

It is right or left hand without change; can be used upon any door and can be easily applied by following the simple instructions packed in each box. It is not affected by extremes of temperature, and by a turn of a screw can be adjusted to any draught. Special adaptations fit it to unusual installations, and it responds satisfactorily to all demands. The sizes recommended have a greater margin of capacity for the work assigned than others less sturdily built or less efficient in mechanism.

Specialized Speed Control It has one characteristic feature which makes it easily the leader in its field. Through a dual valve control, it is possible to regulate the speed of closing of the door. It can be made to move quickly to a point near the jamb and then close slowly, or it can be made to close at a uniform rate of speed. In each instance, the adjustment is simple, accurate and easy to make, by means of the two valves. No other door closer has this function so easily manipulated that anyone can make the adjustments.

The Spring is light, long, and resilient. The tension is evenly distributed over twenty coils of flat wire which are so made that they do not touch each other, eliminating internal friction and permitting the full power of the spring to be exerted in performing its function.

The Rack and Pinion keep the door under checking control from the moment the motion of closing begins until the door touches the stop noiselessly and is held in close contact with it.

Liquid M is a special mineral oil of the proper viscosity and not affected by extremes of temperature. Under tests, it functions perfectly at -60° F.

For sizes 2, 3 and 4 use type **M** liquid. For sizes 5 and 6 use type **A** liquid. Do not mix the two liquids.

There are but four moving parts.




The Spring

Tension evenly distributed over entire length reduces strain.



Rack and Pinion

The lower end of the spindle engages the rack attached to the piston head, giving direct and constant control.




The Valves

Turning the screw regulates the speed of closing.



Door Closers

MODEL 150




2 to 6

Unpolished iron closers are regularly furnished Maroon Bronze finish. Also furnished Aluminum Bronzed, Dead Black or Prime Coat, when so ordered.

Cast Iron Unpolished No.	Type of Door	Maximum size of Door	Packed		Weight Each
			In a Box	In a Case	
2	For heavy screen doors or light interior doors and closet doors	1 $\frac{3}{8}$ "x3'0"x7'0" 1 $\frac{3}{8}$ "x2'8"x7'0" 1 $\frac{3}{4}$ "x2'8"x7'0"	1	6	10 lbs.
3	For light exterior doors and corridor and office doors of wood or metal	1 $\frac{3}{4}$ "x2'6"x7'0" 1 $\frac{3}{4}$ "x3'4"x7'0"	1	5	14 $\frac{3}{4}$ lbs.
4	For ordinary exterior doors and heavy interior doors of wood or metal	2 $\frac{1}{4}$ "x3'0"x7'6" 2 $\frac{1}{4}$ "x4'0"x7'6"	1	4	19 $\frac{3}{4}$ lbs.
5	For heavy exterior doors and heavy interior doors subject to strong draughts	3" x3'6"x7'6"	1	3	23 $\frac{3}{4}$ lbs.
6	For extra heavy entrance doors or doors of unusual height or width and for refrigerator doors, etc.	1	2	28 $\frac{1}{4}$ lbs.

Packed with screws.



WITH KEY ADJUSTMENT TO VALVE

For use in locations where it is desired to make it impossible for every one who wishes to do so to change the valve adjustment. The ordinary knurled regulating screw is replaced by a stem protected by a tube and operated by a key. There is no change in the valve, the only alteration being in the method of manipulation.


Can be applied to any closer. In ordering, state — with key valve.

Machine screws and grommets recommended for kalamein and mono doors.

Specify number and finish. See pages 1 and 2.

Door Closers

MODEL 150



102 to 106

WITH AUTOMATIC HOLD-BACK ATTACHMENT

The hold-back attachment can be adjusted to hold the door open at any angle.

Unpolished iron closers are regularly furnished Maroon Bronze finish. Also furnished Aluminum Bronzed, Dead Black or Prime Coat, when so ordered.

Cast Iron Unpolished No.	Type of Door	Maximum size of Door	Packed		Weight Each
			In a Box	In a Case	
102	For heavy screen doors or light interior doors and closet doors	1 $\frac{3}{8}$ "x3'0"x7'0" 1 $\frac{3}{8}$ "x2'8"x7'0" 1 $\frac{3}{4}$ "x2'8"x7'0"	1	6	10 $\frac{3}{4}$ lbs.
103	For light exterior doors and corridor and office doors of wood or metal	1 $\frac{3}{4}$ "x2'6"x7'0" 1 $\frac{3}{4}$ "x3'4"x7'0"	1	5	15 $\frac{1}{2}$ lbs.
104	For ordinary exterior doors and heavy interior doors of wood or metal	2 $\frac{1}{4}$ "x3'0"x7'6" 2 $\frac{1}{4}$ "x4'0"x7'6"	1	4	20 lbs.
105	For heavy exterior doors and heavy interior doors subject to strong draughts	3" x3'6"x7'6"	1	3	24 lbs.
106	For extra heavy entrance doors or doors of unusual height or width and for refrigerator doors, etc.	1	2	29 lbs.

Packed with screws.


Machine screws and grommets recommended for kalamein and mono doors.

Specify number and finish. See pages 1 and 2.



Door Closers

MODEL 150



523, 524

HOLD-BACK TYPE WITH FUSIBLE LINK FOR FIRE DOORS


Approved by The National Board of Fire Underwriters.

The fusible link melts in case of fire, releasing the hold-back which causes the closer to close the door.

When used with brackets use No. 86 or 26 $\frac{3}{4}$ corner brackets or No. 85 soffit bracket.

No.	Material and Finish	For Hinged Fire Doors	Packed in a Box	Weight Each
523	Cast Iron *Maroon Bronze Finish	Not over 7 x 3 $\frac{1}{2}$ ft.	1	16 $\frac{1}{2}$ lbs.
524	*Maroon Bronze Finish	Not over 7 $\frac{1}{2}$ x 4 ft.	1	22 $\frac{1}{2}$ lbs.

*Also furnished in other finishes.
Packed with screws.

102 $\frac{3}{4}$ **FOR COUPON BOOTH DOORS**

The door closer holds the door ajar as an indication that the booth is ready for use; or closes it when the occupant leaves, causing the door to lock. It remains locked until the attendant prepares the booth for the next occupant and sets the door ajar.

No.	Material and Finish	For Coupon Booth Doors	Packed in a Box	Weight Each
102 $\frac{3}{4}$	Cast Iron *Maroon Bronze Finish	Heavier than ordinary	1	9 $\frac{1}{2}$ Lbs.

*Also furnished in other finishes.
Packed with screws.


Specify number and finish. See pages 1 and 2.



Door Closers

25

MODEL 150



423, 424


WITH TWO POINT HOLO-BACK ATTACHMENT

Especially adapted to use on hospital doors.

The first hold open point is fixed and will hold door open at 20° angle or about 6 in. from the latching point. The second hold open point is adjustable and will hold the door open at any angle 45° and over which is desired.

No.	Material and Finish	For Interior Doors	Packed in a Box	Weight Each
423	Cast Iron *Maroon Bronze Finish	Not over 7 x 3½ ft.	1	15¾ Lbs.
424	*Maroon Bronze Finish	Not over 7½ x 4 ft.	1	20¼ Lbs.

*Also furnished in other finishes.
Packed with screws.



723, 724

WITH THREE POINT HOLO-BACK ATTACHMENT

Especially adapted to use on hospital doors.

Hold open attachment will hold the door open at 20, 55 or 90 degrees.

No.	Material and Finish	For Interior Doors	Packed in a Box	Weight Each
723	Cast Iron *Maroon Bronze Finish	Not over 7 x 3½ ft.	1	15¾ Lbs.
724	*Maroon Bronze Finish	Not over 7½ x 4 ft.	1	20¼ Lbs.



*Also furnished in other finishes.
Packed with screws.

Specify number and finish. See pages 1 and 2.



Door Closers

DIMENSIONS



Door Closer Size	A Width	B Height	C Projection of Closer Approximate	D Projection of Arm Approximate	Arm Bracket	
					E Width	F Length
2	5 ⁷ / ₈ in.	5 ⁷ / ₈ in.	3 ¹¹ / ₁₆ in.	10 ¹ / ₄ in.	1 ³ / ₁₆ in.	2 ¹ / ₄ in.
3	6 ³ / ₈ in.	7 in.	4 in.	*12 in.	1 ³ / ₁₆ in.	2 ¹ / ₄ in.
4	7 ⁵ / ₈ in.	7 ¹ / ₂ in.	4 ³ / ₈ in.	*12 ⁵ / ₈ in.	7 ⁷ / ₈ in.	2 ¹ / ₄ in.
5	8 ³ / ₈ in.	8 in.	4 ¹¹ / ₁₆ in.	13 ³ / ₄ in.	7 ⁷ / ₈ in.	2 ¹ / ₄ in.
6	8 ³ / ₈ in.	8 ³ / ₄ in.	5 ¹ / ₄ in.	15 in.	7 ⁷ / ₈ in.	2 ¹ / ₄ in.


*Does not apply to fire door closers. The projection of arm for No. 523 is approximately 15¹/₈ in., and for No. 524 is approximately 16 in.

LENGTH OF ARMS

Long Arms Are Used on Doors Which Are Recessed in Casing


			For Closer No.				
			2	3	4	5	6
Regular Arm No. 110	} Length		8 in.	9½ in.	10 in.	11 in.	12 in.
Hold-Back No. 110A							
Long Arm Type No. 110	} Length						
Hold-Back Arm Type No. 110A							
			11 in.	12½ in.	13 in.	14 in.	15 in.

Applications of Door Closers



Right Hand Door with Closer

APPLIED TO EITHER
RIGHT OR LEFT
HAND DOORS WITH-
OUT CHANGE




Left Hand Door with Closer




Applications of Door Closers

27

WITH BRACKETS



25 Bracket
Right hand reverse (left hand) door with
closer. Reversible.



28 Bracket
Right hand reverse (left hand) door with
closer. Reversible.

For use in applying closer to the recessed side (opposite hinge side) of door. Should be used only where it is impossible, or not desirable, to apply closer to hinge side of door.

SOFFIT BRACKET

No.	For Closer Size	Material and Finish	Base		Weight Each
			Width Inches	Length Inches	
25		Malleable Iron			
	2	*Maroon Bronze Finish	1 $\frac{13}{32}$	4	1 $\frac{3}{8}$ Lbs.
	3	*Maroon Bronze Finish	1 $\frac{7}{16}$	4 $\frac{1}{16}$	2 $\frac{1}{16}$ Lbs.
	4	*Maroon Bronze Finish	1 $\frac{5}{8}$	4 $\frac{7}{8}$	2 $\frac{1}{2}$ Lbs.
	5	*Maroon Bronze Finish	1 $\frac{5}{8}$	4 $\frac{7}{8}$	2 $\frac{7}{8}$ Lbs.
85	6	*Maroon Bronze Finish	1 $\frac{3}{4}$	5 $\frac{3}{4}$	3 $\frac{5}{8}$ Lbs.
	523	*Maroon Bronze Finish	1 $\frac{7}{16}$	4 $\frac{1}{4}$	2 $\frac{1}{4}$ Lbs.
	524	*Maroon Bronze Finish	1 $\frac{5}{8}$	4 $\frac{7}{8}$	2 $\frac{7}{8}$ Lbs.

No. 85 has 1 in. greater drop than No. 25 and is for use with fusible link fire door closers Nos. 523 and 524, or for closers sizes 3 and 4 only when they are applied to same side of door with overhead type door holders.

Packed one in a box, with both wood screws and machine screws.

FLUSH BRACKET

No.	For Closer Size	Material and Finish	Attaching Base Inches	Weight Each
28		Malleable Iron		
	2	*Maroon Bronze Finish	2 x 3 $\frac{1}{2}$	1 $\frac{3}{4}$ Lbs.
	3	*Maroon Bronze Finish	2 $\frac{1}{2}$ x 4	2 $\frac{1}{4}$ Lbs.
	4	*Maroon Bronze Finish	2 $\frac{3}{4}$ x 4 $\frac{1}{2}$	3 Lbs.
	5	*Maroon Bronze Finish	3 x 4 $\frac{1}{2}$	3 $\frac{1}{16}$ Lbs.
	6	*Maroon Bronze Finish	3 x 5 $\frac{1}{2}$	5 $\frac{1}{4}$ Lbs.

Packed one in a box, with both wood screws and machine screws.

When closers with regular arms are used on these brackets door will open up to 135°. When doors are required to open over 135° up to 180°, specify closers with long arms.

In ordering, state number of bracket and number of closer with which it is to be used.

*Also furnished other finishes.

Specify Finish, See pages 1 and 2.




Applications of Door Closers

WITH BRACKETS

CORNER BRACKET

For use in mounting closers on recessed side (opposite to hinge side) of door.




26 Bracket

Right hand reverse (left hand) door with closer. Reversible.

When closers with regular arms are used on these brackets door will open up to 135°. When doors are required to open over 135° and up to 180°, specify closer with long arms.

No.	For Closer Size	Material and Finish	Base			Weight Each
			Width Inches	Height Inches	Length Inches	
26		Malleable Iron				
	2	*Maroon Bronze Finish	15 ¹ / ₁₆	4 ³ / ₄	4 ³ / ₄	2 Lbs.
	3	*Maroon Bronze Finish	7 ⁷ / ₈	5 ¹ / ₈	4 ⁷ / ₈	2 ⁵ / ₈ Lbs.
	4	*Maroon Bronze Finish	1 ¹ / ₁₆	5 ⁵ / ₈	5 ⁵ / ₈	3 ³ / ₈ Lbs.
	5	*Maroon Bronze Finish	1 ¹ / ₈	6 ¹ / ₈	6 ¹ / ₈	3 ⁷ / ₈ Lbs.
26 ¹ / ₂		Malleable Iron				
	2	*Maroon Bronze Finish	11 ³ / ₁₆	4 ³ / ₄	4 ⁵ / ₈	2 ³ / ₈ Lbs.
	3	*Maroon Bronze Finish	11 ³ / ₁₆	5 ¹ / ₁₆	5	3 ¹ / ₄ Lbs.
	4	*Maroon Bronze Finish	1 ³ / ₄	5 ⁵ / ₈	5 ⁵ / ₈	4 ¹ / ₂ Lbs.
	5	*Maroon Bronze Finish	1 ³ / ₄	5 ⁵ / ₈	5 ⁵ / ₈	5 ¹ / ₄ Lbs.
26 ³ / ₄		Malleable Iron				
	2	*Maroon Bronze Finish	1 ³ / ₄	5 ³ / ₄	4 ³ / ₄	3 ¹ / ₂ Lbs.
	3	*Maroon Bronze Finish	1 ³ / ₄	5 ¹ / ₄	5	3 ³ / ₈ Lbs.
	4	*Maroon Bronze Finish	1 ³ / ₄	5 ⁵ / ₈	5 ³ / ₄	4 ³ / ₄ Lbs.
	5	*Maroon Bronze Finish	1 ³ / ₄	5 ⁵ / ₈	5 ⁵ / ₈	5 ⁵ / ₈ Lbs.
86		Malleable Iron				
	523	*Maroon Bronze Finish	7 ⁷ / ₈	5 ¹ / ₈	4 ⁷ / ₈	3 Lbs.
	524	*Maroon Bronze Finish	1 ¹ / ₈	5 ⁵ / ₈	5 ³ / ₄	4 ⁵ / ₈ Lbs.

No. 26¹/₂ has a wider base than No. 26 allowing the use of 8 screws in attaching. No. 26³/₄ has base like No. 26¹/₂, but has 1 in. greater drop for use when closer is to be applied to same side of door with overhead door holder. No. 86 same as No. 26 but with 1 in. greater drop for use with fusible link fire door closers Nos. 523 and 524. All packed one in a box with both wood screws and machine screws.



335

SOFFIT PLATE

For Door Closer Arm Bracket

For use where it is not desired to cut expensive ornamental trim in applying arm bracket.

No.	Material and Finish	Soffit Plate Size Inches	Weight Each
335	Malleable Iron *Maroon Bronze Finish	2 ¹ / ₂ x 1 ⁵ / ₈	1/2 Lb.

State number of closer with which it is to be used. Packed with screws.

In ordering, state number of bracket and number of closer with which it is to be used.
*Also furnished in other finishes.

Specify Finish, See pages 1 and 2.




Applications of Door Closers

29


ADJUSTABLE ARM BRACKETS

For use with parallel arm No. 30 on non-hold-back door closers sizes 2, 3, 4, 5, 6 only and parallel arm No. 35A on hold-back door closers sizes 102, 103, 104, 105, 106 only.

Arm post adjustable, so that arm will stand at proper V regardless of width of frame. Used for mounting closers on recessed side (opposite to hinge side) of door.




330 Applied to Soffit



331 Applied to Casing


No.	Material and Finish	Type	Attaching Base Inches	Arm Bracket Inches
330	Malleable Iron *Maroon Bronze Finish	Straight	1 x 2½	4 x 1¼
331	*Maroon Bronze Finish	Angle	1 x 2½	3⅞ x 1¼

Packed with screws. Bracket reversible. State hand of door for parallel arms.



332 Applied to Soffit

FOR CIRCULAR TOP DOORS
Adjustable to Curve of Door



333 Applied to Casing

No.	Material and Finish	Type	Attaching Base Inches	Arm Bracket Inches
332	Malleable Iron *Maroon Bronze Finish	Straight	2½ x 1	3¾ x 1¼
333	*Maroon Bronze Finish	Angle	2½ x 1	3¾ x 1¼

Packed with screws. Bracket reversible. State hand of doors for parallel arms.
*Also furnished in other finishes.


Specify Number of Bracket and Finish, See pages 1 and 2.



Applications of Door Closers

PARALLEL ARMS WITH SPECIAL BRACKETS

For Use when Closers are to be Mounted between Doors.




Special Bracket 30

Right hand reverse (left hand) door with closer. Reversible.

†Parallel Arm No. 30 Used with both Nos. 30 and 31 Brackets for Non-Hold-back Closers

†Parallel Arm No. 35A Used with both Nos. 30 and 31 Brackets for Hold-back Closers



Special Bracket 31

Right hand reverse (left hand) door with closer. Reversible.


No.	For Closer Size	Material and Finish	Base Size Inches
30	2 to 6	Malleable Iron *Maroon Bronze Finish	2 $\frac{5}{16}$ x 1 $\frac{15}{16}$
31	2 to 6	*Maroon Bronze Finish	1 $\frac{7}{16}$ x 2 $\frac{5}{8}$

†Not reversible. State hand.
Packed with screws.

For Closer No.	Minimum Space Required Between Doors	Min. Width of Top Rail Below Stop	
		30 Bracket	31 Bracket
2	4 $\frac{1}{2}$ in.	4 $\frac{1}{4}$ in.	5 in.
3	5 in.	4 $\frac{3}{4}$ in.	5 $\frac{1}{2}$ in.
4	5 $\frac{1}{2}$ in.	5 $\frac{1}{16}$ in.	5 $\frac{15}{16}$ in.
5	6 in.	5 $\frac{7}{16}$ in.	6 $\frac{1}{16}$ in.
6	6 in.	6 $\frac{1}{8}$ in.	6 $\frac{1}{8}$ in.

For use with No. 31 arm bracket when doors have narrow top rail (not less than 2 in.)

No.	For Closer Size	Material and Finish	Attaching Base Inches
43	2	Malleable Iron *Maroon Bronze Finish	1 $\frac{1}{8}$ x 5 $\frac{3}{4}$
	3	*Maroon Bronze Finish	1 $\frac{1}{8}$ x 6 $\frac{1}{4}$
	4	*Maroon Bronze Finish	1 $\frac{1}{8}$ x 7 $\frac{1}{8}$
	5	*Maroon Bronze Finish	1 $\frac{1}{8}$ x 7 $\frac{1}{8}$
	6	*Maroon Bronze Finish	1 $\frac{1}{8}$ x 7 $\frac{1}{8}$

Bracket No. 43 reversible. State hand of door for parallel arms.
Packed one in a box with screws.

Closer Bracket 43

Right hand reverse (left hand) door with closer

In ordering, state number of bracket and number of closer with which it is to be used.

*Also furnished in other finishes.

Specify Finish, See pages 1 and 2.



Applications of Door Closers


31

WITH BRACKETS


For Gothic or Arched Doors

Used on recessed side (opposite to hinge side) of door.


Adjustable to curve of door except for doors with steep curve in arch.



Arched Top Door, Bracket 37 1/2
Right hand reverse (left hand) door with
closer. Reversible.



Circular Top Door, Bracket 37 1/2
Right hand reverse (left hand) door with
closer. Reversible.



Arched Door, Bracket 49
Right hand door with closer. Reversible.

In ordering, state number of bracket and number of closer with which it is to be used.

*Also furnished in other finishes.

Specify Finish, See pages 1 and 2.

No.	For Closer Size	Material and Finish	Base		Weight Each
			Width Inches	Length Inches	
37 1/2	2	Malleable Iron *Maroon Bronze Finish	2	5	3 3/8 Lbs.
	3	*Maroon Bronze Finish	2	5 7/8	3 3/4 Lbs.
	4	*Maroon Bronze Finish	2 1/2	5 5/8	5 3/4 Lbs.
	5	*Maroon Bronze Finish	2 1/2	5 5/8	5 7/8 Lbs.

Packed one in a box with screws.

BRACKET NO. 37 1/2

For Circular Top Doors

Bracket No. 37 1/2 can be furnished for circular top doors or arched doors with steep curve in arch providing doors are of batten type or doors without panel.

Doors should be high enough to afford sufficient head clearance when bracket and closer are mounted on lower portion of arch.

For Gothic Top Doors

Used on hinge side of doors which are recessed in casing.

Adjustable to curve of door except for doors with steep curve in arch.

No.	For Closer Size	Material and Finish	Base Diameter Inches	Regular †Recess Inches	Weight Each
‡49	2	Malleable Iron *Maroon Bronze Finish	3 9/16	1 1/4	3 Lbs.
	3	*Maroon Bronze Finish	3 9/16	1 1/4	3 1/4 Lbs.
	4	*Maroon Bronze Finish	3 9/16	1 1/4	3 1/2 Lbs.
	5	*Maroon Bronze Finish	3 9/16	1 1/4	3 3/8 Lbs.
	6	*Maroon Bronze Finish	3 9/16	1 1/4	4 1/8 Lbs.

†When so ordered, can be furnished with spacer for doors 1 1/2, 1 3/4, 2 or 2 1/4 in. recess.

Packed one in a box with screws.



Door Closer Parts

(Models 131, 127 and 1911)



When ordering state number of closer for which the part is to be used. Model number of closer is marked on arm.

Part No.	Description	Part No.	Description
24	Wrench	134	Middle Dog Screw — 2 required
110	Arm and Pawl (Models 1911-127-131)	135	Top and Bottom Dog — 2 required
110A	Arm and Pawl for Hold-back Closer (Models 127 and 131)	136A	Piston (Model 131)
111A	Arm Loop (Model 131)	137A	Piston Rack (Model 131)
112	Screw for Arm Loop	138	Piston Screw
116B	Case (Model 131)	139	Spring
117	Cap (1911 Model)	140	Packing Gland
117A	Cap (Models 127 and 131)	141	Spring for Packing Gland
118	Packing for Cap (1911 Model)	142	Gland Packing Nut
119	Cover	143	Steel Packing Washer
120	Stop Cover	144	Packing Washer — 4 required
121	Stop Cover Pin (1911 Model)	145	Clamp Screw
122A	Stop Cover Band (Models 127 and 131)	149	Hold-Back Spring
123	Stop Cover Band Screw	150	Hold-Back Spring Guide
124	Stop Cover Spring (1911 Model)	151	Hold-Back Spring Adjusting Screw
125	Stop Cover Spring Screw (1911 Model)	153	Steel Ball for Hold-Back
126	Ratchet	154	Pinning Screw (Models 127 and 131)
127	Upper Valve complete	155B	Arm Bracket and Connecting Rod (Model 131)
*127K	Upper Valve complete with Key	157	Lower Valve complete with Wrench (Model 131)
131	Spindle	157W	Wrench for Lower Valve
132	Spindle Nut	158	Rod Set Screw (Model 131)
133	Middle Dog	159	Packing Washer for Lower Valve—4 required

CHECKING LIQUID A: Liquid for closer furnished in one-pint, one-quart and one-gallon cans.

Parts not listed by model number can be used in models 127, 131 and 1911.

A complete arm for regular closer consists of parts Nos. 110, 111A, 112, 145, 155B and 158. For Models 1911-127 and 131.

A complete arm for hold-back closer consists of parts Nos. 110A, 111A, 112, 145, 155B and 158. For Models 1911-127 and 131.

Parts Nos. 110A, 116B and 122A can also be used to repair old model closers. When case 116B is ordered parts 117A, 127, 136A, 137A, 138, 154 and 157 are also included. Arm parts 111A and 115B (Model 131) can also be used to repair Model 127 and old model closers, provided parts 111A, 112, 155B and 158 are all ordered. Parts 136A and 137A can also be used to repair Model 127 and old model closers, providing both parts are ordered.

Part No. 127K can be used for replacement only on closers originally furnished with key valves.

The metal used in Corbin door-closer springs is made to a special Corbin formula. The size and shape ensure an exact fit without binding. They will give the longest service without breakage, the greatest strength and resiliency of any springs used in door closers. The liquid is a Special Corbin Compound having a high viscosity index, excellent lubricating properties and capable of flowing at -60°F.

Liquid A must be used for closer models 131, 127 and 1911.

We cannot assume responsibility for the performance of Corbin door closers unless the springs and liquid are supplied by us.


*When ordering replacements new type key furnished, see page 33.



Door Closer Parts

FOR MODEL 150

33



When ordering state number of closer for which the part is to be used. Model 150 closers have model number marked on name plate.

Part No.	Description	Part No.	Description
* 24	Wrench	136B	Piston and Ball Assembly for sizes 2-3 and 4
* 110	Arm and Pawl	* 136A	Piston and Ball Assembly for sizes 1-5 and 6
* 110A	Arm and Pawl for Hold-Back Closers	137B	Piston Rack for sizes 2-3 and 4
* 111A	Arm Loop	* 137A	Piston Rack for sizes 1-5 and 6
* 112	Screw for Arm Loop	* 138	Piston Rack Screw
116D	Case	* 139	Spring
117C	Cap	140B	Gland
* 119	Cover	142A	Gland Packing Nut
* 120	Slop Cover	143A	Spindle Packing Washer
* 122A	Slop Cover Band	144A	Spindle Packing
* 123	Slop Cover Band Screw	* 145	Clamp Screw
126A	Ratchet for sizes 2 and 3	* 149	Hold-Back Spring
* 126	Ratchet for sizes 1-4-5 and 6	* 150	Hold-Back Spring Guide
127A	Regulating Valve, complete	* 151	Hold-Back Spring Adjusting Screw
127AK	Key Regulating Valve, complete	* 153	Steel Ball for Hold-Back
131B	Spindle for sizes 2-3 and 4	154B	Case Screw (2 required)
* 131	Spindle for sizes 1-5 and 6	* 155B	Rod, Link, Bracket Assembly
* 132	Spindle Nut	157A	Lower Valve complete
* 133	Center Dog	157W	Wrench for Lower Valve
* 134	Center Dog Screw (2 required)	* 158	Rod Set Screw
135A	Top and bottom Dog for sizes 2 and 3 (2 required)	159A	Lower Valve Packing (2 required)
* 135	Top and bottom Dog for sizes 1-4-5 and 6 (2 required)	163A	Case Screw Packing (2 required)
		167	Piston Rack Pin

CHECKING LIQUID M: Liquid for closers furnished in one-pint, one-quart and one-gallon containers.

A complete arm for regular closer consists of parts Nos. 110, 111A, 112, 145, 155B and 158.

A complete arm for hold-back closer consists of parts Nos. 110A, 111A, 112, 145, 155B and 158.

Part No. 127AK can be used for replacement only on closers originally furnished with key valves.

The metal used in Corbin door closer springs is made to a special Corbin formula. The size and shape ensure an exact fit without binding. They will give the longest service without breakage, the greatest strength and resiliency of any springs used in door closers.

The liquid is compounded by us, and repeated tests show it to be superior to any other used for a like purpose. It has the proper lubricating and checking qualities with least absorption, and is not affected by extremes of temperature.

We cannot assume responsibility for the performance of Corbin 150 Model door closers unless the springs and liquid M are supplied by us.


Liquid M must be used for closer Model 150 Sizes 2, 3 and 4. Liquid A must be used for Sizes 1, 5 and 6.

*Note: These parts same as for Model 131 (see page 32).




Screen Door Closers

LIQUID CONTROL



0

Reversible for Right or Left Hand Doors



No.	Material and Finish	Classification	Packed		Weight Each
			In a Box	In a Carton	
0	Cast Iron Maroon Bronze Finish	For screen doors and light inside residence doors	1	6	5¼ Lbs.

Construction

The Spindle or crankshaft is of one-piece drop forged steel supported at the bottom end giving a four point bearing.

The Gland is packed with composition, cork and leather washers assuring an evenly and tightly packed joint.


The Piston has an extra long bearing supported at both ends, accurately machined and fitted, assuring a perfect compression and checking control.

The Spring is a flat rectangular wire coil spring. This


type of spring allows maximum resiliency thereby guarding against crystallization and breakage.

Speed Control. The speed of the door can be readily controlled by the adjusting screw or valve, a turn to the left increasing and a turn to the right decreasing its speed.

Application. The closer can be reversed for right or left hand doors and for the different applications by removing the arm and replacing it on the closer in the correct position for the desired application as explained in the direction sheets and templates packed with each closer.



Applied to outside of door opening
out or inside of door opening in.
Requires top rail 2½ in. wide.




Applied to inside of door opening
out or outside of door opening in
and between doors. Requires top
rail 3½ in. wide and 3¼ in. space
between doors.

Door Closer Parts

FOR MODEL 150

33



When ordering state number of closer for which the part is to be used. Model 150 closers have model number marked on name plate.

Part No.	Description	Part No.	Description
* 24	Wrench	136B	Piston and Ball Assembly for sizes 2-3 and 4
*110	Arm and Pawl	*136A	Piston and Ball Assembly for sizes 1-5 and 6
*110A	Arm and Pawl for Hold-Back Closers	137B	Piston Rack for sizes 2-3 and 4
*111A	Arm Loop	*137A	Piston Rack for sizes 1-5 and 6
*112	Screw for Arm Loop	138	Piston Rack Screw
*116D	Case	139	Spring
*117C	Cap	140B	Gland
*119	Cover	142A	Gland Packing Nut
*120	Stop Cover	143A	Spindle Packing Washer
*122A	Stop Cover Band	144A	Spindle Packing
*123	Stop Cover Band Screw	*145	Clamp Screw
126A	Ratchet for sizes 2 and 3	*149	Hold-Back Spring
*126	Ratchet for sizes 1-4-5 and 6	*150	Hold-Back Spring Guide
127A	Regulating Valve, complete	*151	Hold-Back Spring Adjusting Screw
127AK	Key Regulating Valve, complete	*153	Steel Ball for Hold-Back
131B	Spindle for sizes 2-3 and 4	154B	Case Screw (2 required)
*131	Spindle for sizes 1-5 and 6	*155B	Rod, Link, Bracket Assembly
*132	Spindle Nut	157A	Lower Valve complete
*133	Center Dog	*157W	Wrench for Lower Valve
*134	Center Dog Screw (2 required)	*158	Rod Set Screw
135A	Top and bottom Dog for sizes 2 and 3 (2 required)	159A	Lower Valve Packing (2 required)
*135	Top and bottom Dog for sizes 1-4-5 and 6 (2 required)	163A	Case Screw Packing (2 required)
		167	Piston Rack Pin

CHECKING LIQUID M: Liquid for closers furnished in one-pint, one-quart and one-gallon containers.

A complete arm for regular closer consists of parts Nos. 110, 111A, 112, 145, 155B and 158.

A complete arm for hold-back closer consists of parts Nos. 110A, 111A, 112, 145, 155B and 158.

Part No. 127AK can be used for replacement only on closers originally furnished with key valves.

The metal used in Corbin door closer springs is made to a special Corbin formula. The size and shape ensure an exact fit without binding. They will give the longest service without breakage, the greatest strength and resiliency of any springs used in door closers.

The liquid is compounded by us, and repeated tests show it to be superior to any other used for a like purpose. It has the proper lubricating and checking qualities with least absorption, and is not affected by extremes of temperature.

We cannot assume responsibility for the performance of Corbin 150 Model door closers unless the springs and liquid M are supplied by us.



Liquid M must be used for closer Model 150 Sizes 2, 3 and 4. Liquid A must be used for Sizes 1, 5 and 6.

*Note: These parts same as for Model 131 (see page 32).



Screen Door Closers

LIQUID CONTROL



Reversible for Right or Left Hand Doors

No.	Material and Finish	Classification	Packed		Weight Each
			In a Box	In a Carton	
O	Cast Iron Maroon Bronze Finish	For screen doors and light inside residence doors	1	6	5¼ Lbs.

Construction

The Spindle or crankshaft is of one-piece drop forged steel supported at the bottom end giving a four point bearing.

The Gland is packed with composition, cork and leather washers assuring an evenly and tightly packed joint.


The Piston has an extra long bearing supported at both ends, accurately machined and fitted, assuring a perfect compression and checking control.

The Spring is a flat rectangular wire coil spring. This


type of spring allows maximum resiliency thereby guarding against crystallization and breakage.

Speed Control. The speed of the door can be readily controlled by the adjusting screw or valve, a turn to the left increasing and a turn to the right decreasing its speed.

Application. The closer can be reversed for right or left hand doors and for the different applications by removing the arm and replacing it on the closer in the correct position for the desired application as explained in the direction sheets and templates packed with each closer.



Applied to outside of door opening out or inside of door opening in.
Requires top rail 2½ in. wide.




Applied to inside of door opening out or outside of door opening in and between doors. Requires top rail 3½ in. wide and 3¼ in. space between doors.



Parts for No. 0 Screen Door Closer

35



Part No.	Description	Part No.	Description
1	Case	16	Composition Gland Washer
2	Cap	17	Valve Nut
3	Cover	18	Arm Bracket
4	Top Dog	19	Coil Spring
5	Middle Dog	20	Valve Stem
6	Lower Dog	21	Spindle Nut
7	Gland	22	Piston Pin
8	Piston	23	Piston Spring
9	Main Arm	24	Cotter Pin
10	Loop	25	Valve Ball
11	Spindle	26	Leather Gland Washer
12	Gland Packing Nut	27	Cork Gland Washer
13	Extension Rod	28	Leather Valve Washer
14	Arm Bracket Rivet	29	Spring Lock Ring
15	Piston Ball Pin		

In ordering state Part Number and for No. 0 Closer.



Screen Door Closers


AIR CONTROL



21


Hand Reversible for right or left hand doors opening in or out.
 Space Requires 2¼ in. space when mounted between doors.
 Spring Encased spring of coiled torsion type. Adjustable tension.
 Adjustment Speed of closing adjustable. Packed with screws.

No.	Length Overall Inches	Finish	Jamb Bracket Inches	Tube Seamless Brass Diameter Inches	Barrel Length Inches	Packed		Weight Each
						In a Box	In a Carton	
MR 21	16¼	Maroon Bronze Finish	3¾ x 1¾	1¼	10½	1	12	3 Lbs.



Applied to outside of door opening
out or inside of door opening in.

Can be easily reversed for right or
left hand doors and for the different
applications by following the direc-
tions packed with each closer.



Applied between doors on inside of
door opening out or outside of door
opening in.



17

For use on recessed (opposite hinged side) of door only.
 2¼ in. space required when mounted between doors.
 Speed of closing adjustable. With hold open device.

No.	Length Overall Inches	Finish	Jamb Bracket Steel Inches	Tube Extruded Aluminum Diameter Inches	Barrel Length Inches	Packed		Weight Each
						In a Box	In a Carton	
17	15½	Maroon Bronze Finish	1¾ x 2	1¼	11	1	12	1½ Lbs.


Packed with screws.



Corbin "400" Door Closer


37

Patented



View of Mortise Type Applied

The only Exposed Parts are the Arm and a Small Part of the Case



View of Surface Type Applied

The Corbin "400" Door Closer is the result of intensive research aimed at developing a Door Closer of pleasing appearance and capable of superlative **performance**. Performance was made the prime consideration since consistently good **performance** remains a requirement long after the desire for total concealment for appearance is forgotten.

The soundness of design and engineering, the selection of the finest materials for each specialized function, the manufacturing precision and the patented valving system have earned for the "400" Closer an enviable record of **performance** during many years of practical service in the field under varied and difficult conditions.

The Corbin "400" Door Closer, made with one size of housing and in five spring sizes, is capable of handling all interior and exterior doors which can be handled by a Door Closer. Its patented control is superior to that of any other Door Closer. Structurally, it has no equal for strength.

Everything that makes for efficiency of operation and trouble free **performance** has been built into this precision made Door Closer and, at the same time, attractiveness and unobtrusive appearance has been obtained. Here, then, is an ideal combination, providing the ultimate in Door Closers.

Outstanding Features:

1. Exposed portion of Mortise Type Closer is smaller than the smallest size of Hydraulic Surface Closer of any known make.
2. One size of Housing with five different sizes of Springs.
3. One standardized mortise or location regardless of the door size and the degree of opening.
4. High pressure, hydraulic iron Housing.
5. Forged steel Closer Arm.
6. Automotive valve type Springs.
7. Long, precision fitted Piston.
8. Strong, heat treated and ground alloy steel Pinion.
9. Heavy, forged alloy steel Rack, heat treated and ground.

10. Two first grade Ball Bearings.
11. Two non-critical Control Valves—plus "Silence Adjustment" for noiseless complete closing at all closing speeds.
12. High lubrication value Checking Fluid which will flow at minus 60° Fahrenheit.
13. Eighteen-point built in Hold-Open Feature.
14. Eighteen through-hardened or deep-hardened wearing parts.
15. Copper Gasketing.

The Corbin "400" Closer is adapted for three different types of installations.

1. **Mortise Application:** Closer is mortised in Top Rail of door; if metal, the minimum thickness is 1½ inch; if wood or kalamain 1¾ inch. When mortised in wood or kalamain doors, two steel reinforcing plates are furnished. Projection from door is only 1¾ inches.
2. **Partial Mortise Application:** Closer is partially mortised in Top Rail of door when the thickness of the metal door is less than 1½ inches. A special cover is furnished to enclose the "400" Closer entirely.
3. **Surface Application:** Closer is mounted on surface of Top Rail of door, and as such there is no minimum limit of thickness of door. A brass cover is furnished which entirely conceals the closer. Projection from door is only 3¼ inches.

In some instances special conditions are encountered in relation to the Closers with the above application. Such instances, as well as any problems relating to the application of the arms to the frames, should be brought to the attention of our Engineering Department. For example, the "400" Closer has been successfully applied to the surface of doors whose top rail measured 2, 2¼, 2½ and 3 inches.

When special conditions are encountered all possible information should be sent to us, including width and thickness of door, width of stile and top rail, method of hanging door, hinge clearance, door frame detail. Careful consideration can then be given by our Engineering Department to your requirements.




Corbin "400" Door Closer

Approved by The National Board of Fire Underwriters

FULL MORTISE, PARTIAL MORTISE AND SURFACE APPLICATION



Hold-Open Mechanism



Patented




Fusible Link Arm

Size	MORTISE APPLICATION				SURFACE APPLICATION	
	Metal Doors		Wood or Kalamein Doors		All Doors	
	Regular No.	Hold-Open No.	Regular No.	Hold-Open No.	Regular No.	Hold-Open No.
2	400 M-2	400 MH-2	400 W-2	400 WH-2	400 S-2	400 SH-2
3	400 M-3	400 MH-3	400 W-3	400 WH-3	400 S-3	400 SH-3
4	400 M-4	400 MH-4	400 W-4	400 WH-4	400 S-4	400 SH-4
5	400 M-5	400 MH-5	400 W-5	400 WH-5	400 S-5	400 SH-5
6	400 M-6	400 MH-6	400 W-6	400 WH-6	400 S-6	400 SH-6

Reinforcing Plates furnished for Kalamein and Wood Doors.

Packed with Wood Screws, Machine Screws, or Through Bolts as required. Specify type required.


One in a Box Complete with Screws, Installation Sheets and Wrench. Weight 13 lbs.



Cover for Mortise Closer



Cover for Partial Mortise and Surface Closers

Size 5 x 15 $\frac{1}{4}$ x $\frac{3}{8}$ in.

Reinforcing Plates For Kalamein or Wood Doors

HOLO OPEN

The Patented hold-open device furnished for the "400" closer is based on the Cam and Pawl principle with all parts having glass hard surfaces. Holding Tension and Degree of hold-open are adjustable; there are eighteen holding points between 0 and 180 degrees. Holding mechanism is totally concealed when closer is applied and can be adjusted only by means of special wrench. Hold-Open device is fully automatic when set to degree of holding required.

PARTIAL MORTISE APPLICATION

It is recommended that full details of Door be submitted for partial mortise application before ordering.

FUSIBLE LINK ARM

This type of arm is designed for use with closers used on Fire Doors to allow door to close automatically in case of fire. The Hold-Open Device is constructed with a fusible link that will melt when subjected to a temperature of 165 degrees Fahrenheit allowing the door to close automatically. Furnished with No. 9 Arm only on closers Size 3, 4, 5 and 6 for doors opening to 120 degrees.

To order suffix "F" to closer number i.e. 400MHF3, 400SHF3, etc.

COVERS

Wrought Brass Covers regularly furnished on all closers.

REINFORCING PLATES

Wrought steel $\frac{3}{8}$ inch thick plates bolted together from one side regularly furnished with closers for mortise application on Wood or Kalamein Doors. We recommend that reinforcing plates be sent to manufacturer of Kalamein doors before doors are fabricated, and that reinforcing plates for use on wood doors be applied at the mill.

Finish: Covers and Arms are furnished Prime Coat for Painting. Plated finishes available—specify Finish required.

Specify Number, Size, Hand and Finish. See Pages 1 and 2. See Page 39 for ordering details.



Corbin "400" Door Closer

39

Patented

INFORMATION NECESSARY FOR ORDERING
FOR ALL INTERIOR AND EXTERIOR DOORS*

List of Sizes

Size 2—For interior doors not exceeding 2'-8" x 7'-0".

Size 3—For interior doors not exceeding 3'-4" x 7'-0", and exterior doors not exceeding 2'-6" x 7'-0".

Size 4—For heavy interior doors 4'-0" x 7'-0", and exterior doors not exceeding 3'-6" x 7'-0".

Size 5—For heavy interior doors subject to strong draughts, and heavy exterior doors not exceeding 3'-6" x 7'-6".

Size 6—For extra heavy interior doors, exterior doors subject to strong draughts, and doors of unusual height, width and weight.

Thickness of Doors

In the listing of door sizes above, thickness of door has been omitted since this dimension varies with the type of door and the method of application. Herewith is listed door thicknesses for the different types of door for:

Full Mortise Application: Metal Doors—1½ inches minimum, Wood or Kalamein Doors—1¾ inches minimum.

Partial Mortise Application: Metal Doors only 1 inch minimum.

Surface Application: All types of doors—any thickness.

To determine the proper size of closer, first consideration should be given to the width and height of the door and also to the draught conditions to which the door may be subjected. The weight of the door is, of course, important and also, therefore, the thickness as being contributory to the weight.

Existing installations of the Corbin "400" Closer cover extreme sizes of door widths, heights, thicknesses and weights beyond dimensions listed above. Careful consideration of unusual requirements of the Corbin "400" Closer will be given by our Engineering Department upon request.

The specifications apply to doors under normal conditions. If the door is unusually heavy or is subject to very strong draughts, use one size larger than is specified.

For metal doors minimum width of top rail is 4" for Mortise application.

For wood or kalamein doors minimum width of stile and top rail is 5" for Mortise application.

Finishes: The Cover and Arms are regularly furnished with Prime Coat. All other finishes are special.

Case and arm of closers on Outswinging doors should be electro-galvanized.

Information Required When Ordering

The information requested below is absolutely necessary if we are to fill your orders correctly and promptly. We cannot do so without it.


1. Hand of Door.
2. Type of Door and Frame: Metal, Wood or Kalamein.
3. Thickness of Door.
4. If Wood or Kalamein Door give width of Stile and Top Rail.
5. Size of Closer.

6. Type of Arm—Closers are regularly furnished with No. 9 Arm for 120° doors. If doors are required to open between 120° and 180° specify No. 11 Arm.


7. Finish—Cover and Arms only, if other than Prime Coat.

8. The regular Bracket is standard for mortise application. The 400-1 Bracket is standard for surface application. Either Bracket is available for either type of application, when so ordered.

9. Surface type Checks can be furnished with Parallel Arm. see Page 42. In ordering, prefix P to number, thus: P400S-2.



LEFT HAND



RIGHT HAND

Suggested Specification

Door Closers for all Interior and Exterior metal doors not less than 1½ inches thick and wood or kalamein doors not less than 1¾ inches thick shall be of the Semi-Concealed type partially mortised into the top rail, such as the Corbin "400" Semi-Concealed Door Closer, manufactured by Corbin Lock Company of Canada Limited.

Closers shall be of Rack and Pinion construction, with dual, independent valve control and "Silence Adjustment," two helical compression springs, forged steel closer

arm, and tubular adjustable frame arm. The operating spindle shall be mounted in two ball bearings.

Closers shall have a totally concealed, adjustable, fully automatic hold-open, with all parts hardened against wear.

Closers shall be of one size with various spring capacities and all capacities shall be interchangeable in the same mortise.


* Outswinging Exterior doors equipped with mortised "400" closer should be protected by reveal or canopy over top of door.



Corbin "400" Door Closer

Patented

MECHANICAL DETAILS



1. **Case:** Alloy cast iron, the same as used in the cylinders of high pressure hydraulic devices. Precision machined.
2. **Arms:** Forged steel and tubular sections. All turning or wearing parts are pack hardened, giving glass hard surfaces.
3. **Springs:** Helical, automobile valve type. Made of high carbon steel, oil tempered after winding.
4. **Piston:** 1 3/4 inch long. This makes for long life, giving a long bearing surface, decreasing the amount of wear and increasing the length of time during which the Piston effectively seals and the Closer effectively checks.
5. **Nickel Steel Rack:** Accurately cut and heat treated. The back bearing surface is ground to a glass smooth finish and slides against a hardened and ground steel block.
6. **Alloy Steel Pinion:** Accurately cut and heat treated. Cut from a single piece of steel making a true one piece Pinion. All shaft surfaces are ground.
7. **Ball Bearings:** Two large Ball Bearings of the same type and manufacture used in fine automobiles. Self lubricating.
8. **Oil Seal:** Same type and manufacture used in fine automotive design. Successfully resists capillary attraction. There are no packing nuts, glands, or tightly seated packings. The Oil Seal used is practically frictionless.
9. **Valves:** Dual control, plus "silence adjustment" (patented). Wide range of valve movement. No fussy or hairline adjustments. Large packing area with 1 leather and 2 buna washers to each valve.

With the system of valve control used in the Corbin "400" Door Closer, any desired manner of closing may be obtained. One valve controls the door up to approximately ten degrees of the Latch, and the second valve controls the latching speed. The door may be closed in less than three seconds from 90° so quietly that there is no audible contact between the door and the stop. This is accomplished with the "silence

adjustment." The Latch Control Valve may be so adjusted that the speed of the door may be hastened sufficiently to pull the stiffest latch beyond the lip of the strike and then the movement of the door may be slowed down as to give noiseless complete closing, by means of the "silence adjustment." If exceptionally strong draughts are encountered or if door or frame is warped, the Latch Control Valve may be so adjusted as to hasten the movement of the door during the last few degrees of closing to bring the door against the stop, ensuring positive and complete latching.

10. **Leak Proof:** We firmly believe that the Corbin "400" Door Closer is as leak proof as it is possible to make any door closer. The Cylinder Plug is provided with an exceptionally long thread and has a copper gasket under the flange. No cement or other compound is used. The packings throughout the Closer are of copper, oil proof fibre, chrome tanned leather and buna.
11. **Checking Fluid:** Mineral Oil, compounded to our own formula. Flows at extremely low temperatures. Has high lubrication value. The use of Mineral Oil is possible because of the alloy iron used in the making of the Case.
12. **Installation:** Exceptionally easy. The re-inforcements are simple and actually strengthen the door where the Closer is applied. The Corbin "400" Door Closer is applicable as standard to Hollow Metal Doors 1 1/2 inches or more in thickness, and to Wood Doors 1 3/4 inches or more in thickness.

In the Corbin "400" Door Closer you will find:

1. Two Alloy steel parts, heat treated.
2. 18 parts pack or case hardened.

These constitute striking examples of the type of construction built into this modern Door Closing Machine.




Corbin "400" Door Closers


41

Rev. 6-1-57


SPECIAL ARM BRACKETS FOR UNUSUAL CONDITIONS




400 (Regular Bracket)
Bracket $\frac{1}{16}$ " thick




*400.3



400.1




*400.2





P400S.21 for
mounting on
soffit


P400S.22 for
mounting
on top stop.




400.5



*400.4



*400.8



*400.9

400.7

*Other dimensions same as on Regular Bracket 400.

These Brackets represent only a few of the special adaptations available. Special Brackets may be obtained to suit practically any special condition; information will be furnished readily by our Engineering Department upon request.




42

Rev. 6-1-57


Application of Corbin "400" Door Closer

SURFACE TYPE WITH PARALLEL ARMS


RIGHT HAND
SHOWN




WITH BRACKET NO. 21



RIGHT HAND
SHOWN



WITH BRACKET NO. 22





Corbin "400" Door Closers


41

Rev. 6-1-57


SPECIAL ARM BRACKETS FOR UNUSUAL CONDITIONS

400 (Regular Bracket)
Bracket $\frac{1}{4}$ " thick




*400-3




400-1




*400-2

P400S-21 for
mounting on
soffitP400S-22 for
mounting
on top stop.

*400-4




400-5



*400-8

*400-9



400-7

*Other dimensions same as on Regular Bracket 400.


These Brackets represent only a few of the special adaptations available. Special Brackets may be obtained to suit practically any special condition; information will be furnished readily by our Engineering Department upon request.




Application of Corbin "400" Door Closer

SURFACE TYPE WITH PARALLEL ARMS


RIGHT HAND
SHOWN




WITH BRACKET NO. 21



RIGHT HAND
SHOWN



WITH BRACKET NO. 22



RIGHT HAND SHOWN



RIGHT HAND SHOWN



RIGHT HAND SHOWN





CANADA

BOLTS

FLUSH BOLTS

EXTENSION FLUSH BOLTS



CREMONE BOLTS

SURFACE BOLTS

CHAIN AND FOOT BOLTS

BARREL BOLTS

MORTISE BOLTS





INDEX OF

Item	Page
BOLTS:	
Barrel	50
Flush	50
Extension Flush	49
Cremone	51
Surface	52
Chain	55
Foot	55
Mortise	54

Extension Flush Bolts

49




2850
Type of 2851




2856



2857
Rabbit $\frac{1}{2}$ in.
Reversible




2858
Requires $1\frac{3}{8}$ in. mortise



2859

No.	Plate Inches	Material and Finish	Length Inches	Backset of Rod Inches	Bolt Head Inches	Throw of Bolt inches	Strike Inches	Packed in a box
		Cast Brass or Bronze						
2850	$6\frac{3}{4} \times 1\frac{1}{4}$	Polished	8 to 24	$\frac{5}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	None	2
2851	$6\frac{3}{4} \times 1\frac{1}{4}$	Polished	8 to 24	$\frac{7}{8}$	$\frac{7}{8}$	$\frac{3}{4}$	None	2
2856	$6\frac{3}{4} \times 1\frac{1}{4}$	Polished	6 to 24	$\frac{5}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	$2\frac{1}{4} \times 1$	2
2857	$6\frac{3}{4} \times 1\frac{1}{4}$	Polished	8 to 24	$\frac{5}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	$2\frac{1}{4} \times 1$	2
2858	$5 \times 1\frac{3}{4}$	Polished	8 to 24	1	$\frac{1}{2}$	$\frac{5}{8}$	$2\frac{7}{8} \times 1\frac{13}{16}$	2
2859	$6\frac{3}{4} \times 1\frac{1}{2}$	Polished	8 to 24	$\frac{7}{8}$	$\frac{7}{8}$	1	$2\frac{1}{4} \times 1\frac{17}{16}$	2

Packed with screws. Nos. 2850 and 2851 used with metal frames.



WEIGHT PER DOZEN

Length Inches	No. 2850 lbs.	No. 2851 lbs.	No. 2856 lbs.	No. 2857 lbs.	No. 2858 lbs.	No. 2859 lbs.
6			$10\frac{1}{8}$			
8	$10\frac{3}{4}$	$13\frac{5}{8}$	$10\frac{1}{2}$	$13\frac{1}{4}$	$14\frac{5}{8}$	18
12	$11\frac{3}{4}$	$16\frac{1}{4}$	11	$13\frac{7}{8}$	$14\frac{3}{4}$	$19\frac{1}{2}$
18	$12\frac{1}{4}$	$18\frac{3}{8}$	12	15	15	$21\frac{3}{4}$
24	13	$20\frac{1}{4}$	$12\frac{3}{4}$	$15\frac{3}{4}$	$15\frac{7}{8}$	$23\frac{5}{8}$


The length of extension flush bolts is measured from the pivot pin of the lever to top of bolt when retracted.

For dust proof strikes and strikes for cement.
See page 53

Specify number, size and finish. See pages 1 and 2.



Barrel Bolts



0223




Flat Strike
Can be furnished with all numbers in place of Surface Strike, when so ordered.



Angle Strike
Can be furnished when ordered with bolts No. 0223 3-4 5 inch.

No. Surface Strike	Length Inches	Material and Finish	Plate Inches	Bolt Dia. Inches	STRIKE		Packed in a box	Weight Dozen
					Flat Inches	Surface Inches		
Wrought Steel								
J0223½	2½	Japanned without screws	1 x2½	¼	1 x1½	1 x 1⅝	12	1¼ lbs.
J0223½	3	Japanned without screws	1⅝x3	⅜	1⅝x1⅜	1⅝x1⅝	12	2½ lbs.
J0223½	4	Japanned without screws	1⅝x4	⅜	1⅝x1⅜	1⅝x1⅝	12	3¼ lbs.
J0223½	5	Japanned without screws	1⅝x5	⅜	1⅝x1⅜	1⅝x1⅝	12	4 lbs.
J0223	2½	Japanned with screws	1 x2½	¼	1 x1½	1 x 1⅝	12	1¼ lbs.
J0223	3	Japanned with screws	1⅝x3	⅜	1⅝x1⅜	1⅝x1⅝	12	2½ lbs.
J0223	4	Japanned with screws	1⅝x4	⅜	1⅝x1⅜	1⅝x1⅝	12	3¼ lbs.
J0223	5	Japanned with screws	1⅝x5	⅜	1⅝x1⅜	1⅝x1⅝	12	4 lbs.
T0223	2½	Plated with screws	1 x2½	¼	1 x1½	1 x 1⅝	12	1¼ lbs.
T0223	3	Plated with screws	1⅝x3	⅜	1⅝x1⅜	1⅝x1⅝	12	2½ lbs.
T0223	4	Plated with screws	1⅝x4	⅜	1⅝x1⅜	1⅝x1⅝	12	3¼ lbs.
T0223	5	Plated with screws	1⅝x5	⅜	1⅝x1⅜	1⅝x1⅝	12	4 lbs.


Japanned Bolts have Japanned Plate with steel bolt and Brass Plated Knob.



2813



2823, 02823



2834

Flush Bolts

WEIGHT PER DOZEN

Length Inches	No. 2813	No. 2823 No. 02823	No. 2834
2 7/8 x 3/4	1 1/2 lbs.		
2 7/8 x 1	2 1/2 lbs.		
6		5 1/4 lbs.	6 lbs.
8		6 lbs.	7 lbs.
12		10 lbs.	11 lbs.

No.	Length Inches	Material and Finish	Width of Plate	Width of Lip	Diameter of Bolt	Throw of Bolt	Strike	Packed in a Box
Cast Brass or Bronze								
2823	6-8-12	Polished	1 in.	1 5/16 in.	7/16 in.	1 1/8 in.	1 3/4 x 1 in.	6
2834	6-8-12	Polished	1 in.	1 in.	7/16 in.	1 1/16 in.	1 3/4 x 1 in.	6
Wrought Brass or Bronze								
2813	2 7/8	Polished	3/4 in.	5/8 in.	1/4 in.	1/2 in.	1 1/8 x 5/8 in.	12
2813	2 7/8	Polished	1 in.	1 1/16 in.	3/8 in.	5/8 in.	1 3/8 x 5/8 in.	12
Cast Iron								
02823	6-8-12	Plated	1 in.	1 5/16 in.	7/16 in.	1 1/8 in.	1 3/4 x 1 in.	6

Packed with screws.

Specify number, size and finish. See pages 1 and 2.

Cremone Bolts

51

FOR SASH OR DOORS OPENING IN OR OUT



1990



Strikes

See page 53



For Sash or Doors Opening In. For Sash or Doors Opening Out.
Both types furnished regularly with all bolts.

Strikes Type "D"



Furnished with cremone bolts, when so ordered.

Supplied stock size for doors 7 ft. 6 in. in height. Knob or handle 3 ft. 6 in. from bottom. Furnished any size required, when so ordered. Specify height of sash or door and distance from bottom to handle; otherwise stock size will be furnished.



1992

*Not Reversible

No.	Size of Case Inches	Material and Finish	Knob or Lever Size Inches	Projection Inches	Width of Guides Inches	½ Oval Rod Width Inches	Throw of Bolt Inches	Weight Each Stock Size
1990	4 $\frac{7}{16}$ x1 $\frac{1}{4}$	Cast Brass or Bronze with Wrought Rods Polished	2x1	1 $\frac{13}{16}$	1 $\frac{1}{4}$	$\frac{1}{2}$	$\frac{1}{2}$	3 $\frac{1}{2}$ lbs.
1992	4 $\frac{7}{16}$ x1 $\frac{1}{4}$	Polished	2	2 $\frac{7}{16}$	1 $\frac{1}{4}$	$\frac{1}{2}$	$\frac{1}{2}$	3 $\frac{1}{2}$ lbs.

Packed one in a box with screws, rod in separate package.

*Specify hand of bolt No. 1992.

Specify number, size and finish. See pages 1 and 2.



Surface Door Bolts



1970, 01970



1971, 01971

No.	Length Inches	Material and Finish	Knob Dia. Inches	Projection Inches	Guides Width Inches	Half Oval Rod Width Inches	Throw of Bolt Inches	Strikes	
								Angle Inches	Flat Lip Inches
1970	4, 6	Wrought Brass or Bronze							
1971	6, 9, 12, 18	Polished	$\frac{7}{16}$	$\frac{3}{4}$	$1\frac{3}{8}$	$\frac{3}{8}$	$\frac{5}{8}$	$\frac{5}{8} \times 1\frac{1}{2} \times \frac{1}{2}$	$1\frac{1}{4} \times 1$
		Polished	$\frac{3}{4}$	1	$1\frac{1}{2}$	$\frac{1}{2}$	$\frac{3}{4}$	$\frac{3}{4} \times 2 \times \frac{1}{2}$	$1\frac{1}{4} \times 1$
01970	4, 6	Wrought Steel							
01971	6, 9, 12, 18	Plated	$\frac{7}{16}$	$\frac{3}{4}$	$1\frac{3}{8}$	$\frac{3}{8}$	$\frac{5}{8}$	$\frac{5}{8} \times 1\frac{1}{2} \times \frac{1}{2}$	$1\frac{1}{4} \times 1$
		Plated	$\frac{3}{4}$	1	$1\frac{1}{2}$	$\frac{1}{2}$	$\frac{3}{4}$	$\frac{3}{4} \times 2 \times \frac{1}{2}$	$1\frac{1}{4} \times 1$

PACKING AND WEIGHT

Length Inches	01970		01971		1970		1971	
	In a Box	Weight Dozen	In a Box	Weight Dozen	In a Box	Weight Dozen	In a Box	Weight Dozen
4	6	2 $\frac{1}{4}$ lbs.			6	2 $\frac{1}{4}$ lbs.		
6	6	2 $\frac{5}{8}$ lbs.	6	4 $\frac{1}{2}$ lbs.	6	2 $\frac{5}{8}$ lbs.	6	5 lbs.
9			6	5 $\frac{3}{4}$ lbs.			6	6 $\frac{1}{2}$ lbs.
12			6	6 $\frac{3}{4}$ lbs.			6	7 $\frac{1}{4}$ lbs.
18			6	9 $\frac{1}{2}$ lbs.			6	9 lbs.

Packed with screws.

Specify number, size and finish. See pages 1 and 2.




Strikes

53

FOR CREMONE AND SURFACE BOLTS

ANGLE STRIKES



Type A

Size, In.	Return, In.	Material	For Bolts
$\frac{5}{8} \times \frac{1}{2}$	$\frac{1}{2}$	Wrought Brass or Bronze	1970
$\frac{3}{4} \times 2$	$\frac{1}{2}$		1971, 1990, 1992

This type of strike furnished regularly with all surface and cremone bolts.

FLAT STRIKES




Type C

Size, In.	Material	For Bolts
$\frac{7}{8} \times 2$	Wrought Brass or Bronze	1971, 1990, 1992

This type of strike furnished with surface and cremone bolts only when so ordered.

BOXED LIP STRIKES




Type E

Size, In.	Material	For Bolts
$1\frac{3}{4} \times \frac{7}{8}$	Cast Brass or Bronze	1971, 1990, 1992.

This type of strike furnished with surface and cremone bolts only when so ordered.

In ordering state type of strike required and number of bolt with which it is to be used.

FLAT LIP STRIKES



Type B

Size, In.	Material	For Bolts
$1\frac{1}{4} \times 1$	Wrought Brass or Bronze	1970, 1971, 1990, 1992

This type of strike furnished regularly with all surface and cremone bolts.

RIM STRIKES




Type D

Size, In.	Material	For Bolts
$\frac{5}{8} \times 1\frac{1}{8}$ $\frac{5}{8} \times 1\frac{3}{16}$	Cast Brass or Bronze	1970 1971, 1990, 1992

This type of strike furnished with surface and cremone bolts only when so ordered.

BOXED LIP STRIKES




Type AA

Size In.	Proj. In.	Height In.	Material	For Bolts
$\frac{5}{8} \times 1\frac{3}{4}$	$\frac{1}{2}$	$\frac{1}{2}$	Cast Brass or Bronze	1971, 1990, 1992

This type of strike furnished with surface and cremone bolts only when so ordered.

Dust Proof Strikes



76

For cement



74, 75


No.	For Bolt	Material and Finish	Face Inches	Depth of Mortise	For bolt Size In.
74	2850	Cast Brass or Bronze Polished	$2\frac{3}{4} \times 1\frac{3}{8}$	1 $\frac{1}{4}$ in.	$\frac{1}{2}$
75	2851		$3\frac{1}{4} \times 1\frac{7}{8}$	1 $\frac{3}{8}$ in.	$\frac{7}{8}$
76	2850, 2856, 2858		1 $\frac{1}{8}$ Dia.	$\frac{3}{4}$ in.	$\frac{1}{2}$

Specify number and finish. See pages 1 and 2.



54

Mortise Bolts



263

CaseJapanned Iron Case $1\frac{1}{4} \times 2\frac{1}{2} \times \frac{9}{16}$ inches.
 Front $2\frac{1}{2} \times 1\frac{1}{16}$ inches.
 HubBronze $\frac{3}{16}$ inches.
 Strike $2\frac{3}{8} \times \frac{3}{4}$ inches.
 OperationBy thumb knob one side only.

No.	Front	Bolt	Backset Inches	Thumb Knob		Packed in a Box	Weight Dozen
				No.	Size		
263	Cast Brass or Bronze Polished	Cast Bronze	1 $\frac{3}{4}$	2148	2 $\frac{3}{4}$ x 1 in.	6	6 $\frac{3}{4}$ lbs.

Packed with screws.




264

CaseJapanned Iron Case $1\frac{1}{4} \times 3\frac{3}{8} \times \frac{1}{2}$ inches.
 Front $2\frac{1}{2} \times 1\frac{1}{16}$ inches.
 HubBronze $\frac{3}{16}$ inches.
 Strike $2\frac{3}{8} \times \frac{3}{4}$ inches.
 OperationBy thumb knob one side only.

No.	Front	Bolt	Backset Inches	Thumb Knob		Packed in a Box	Weight Dozen
				No.	Size		
264	Cast Brass or Bronze Polished	Cast Bronze	2 $\frac{1}{2}$	2148	2 $\frac{3}{4}$ x 1 in.	6	7 $\frac{1}{2}$ lbs.

Packed with screws.



266, 0266

No.	Backset Inches	Material and Finish	Plate Inches	Knob Inches	Strike Inches	Packed in a Box	Weight Dozen
266	1 $\frac{3}{4}$	Wrought Brass or Bronze Cast Brass or Bronze Knob Iron Bolt Polished	1 $\frac{3}{4} \times \frac{7}{8}$	1 $\frac{1}{8} \times 1\frac{1}{16}$	1 $\frac{3}{4}$ x 1	12	3 lbs.
0266	1 $\frac{3}{4}$	Wrought Steel Cast iron bolt and Knob Plated	1 $\frac{3}{4} \times \frac{7}{8}$	1 $\frac{1}{8} \times 1\frac{1}{16}$	1 $\frac{3}{4}$ x 1	12	2 $\frac{3}{4}$ lbs.

Packed with screws.


Diameter of Bolt $\frac{1}{2}$ in.Diameter of bolt housing $\frac{9}{16}$ in.

Specify number and finish. See pages 1 and 2.



Chain and Foot Bolts

55



252, 0252



250, 0250

No.	Length Inches	Material and Finish	Width Inches	Chain Length Inches	Strikes		Packed in a Box	Weight Dozen
					Rim Ins.	Angle Ins.		
252	4	Cast Brass or Bronze	1 13/16	24	1 13/16 x 1	1 3/4 x 7/8	6	10 1/2 lbs.
252	6	Polished	2 1/8	24	2 1/8 x 1 13/16	1 3/4 x 7/8	6	15 1/4 lbs.
J0252	4	Cast Iron	1 13/16	24	1 13/16 x 1	1 3/4 x 7/8	6	10 lbs.
J0252	6	Japanned without screws	2 1/8	24	2 1/8 x 1 13/16	1 3/4 x 7/8	6	14 1/4 lbs.
0252	4	Polished and plated	1 13/16	24	1 13/16 x 1	1 3/4 x 7/8	6	10 lbs.
0252	6	Polished and plated	2 1/8	24	2 1/8 x 1 13/16	1 3/4 x 7/8	6	14 1/4 lbs.

Packed with screws excepting No. J0252.

Regularly furnished with regular and reverse bevel strike.

No.	Length Inches	Material and Finish	Width Inches	Strike Inches	Packed in a Box	Weight Dozen
250	4	Cast Brass or Bronze	1 3/4	2 1/8 x 1	6	10 3/8 lbs.
250	6	Polished	2 1/8	2 1/8 x 1 13/16	6	13 1/2 lbs.
J0250	4	Cast Iron	1 3/4	2 1/8 x 1	6	7 7/8 lbs.
J0250	6	Japanned without screws	2 1/8	2 1/8 x 1 13/16	6	12 3/4 lbs.
0250	4	Polished and plated	1 3/4	2 1/8 x 1	6	7 7/8 lbs.
0250	6	Polished and plated	2 1/8	2 1/8 x 1 13/16	6	12 3/4 lbs.

Packed with screws excepting No. J0250.

Specify number, size and finish. See pages 1 and 2.





CANADA

MISCELLANEOUS HARDWARE

DOOR FASTENER

DOOR STOPS

DOOR HOLDERS

SASH HARDWARE

CASEMENT HARDWARE

TRANSOM HARDWARE

DRAWER HARDWARE


CATCHES

HOOKS

HAND RAIL BRACKETS

DOOR BELLS

SASH PULLEYS






— INDEX OF —


Item	Page
CHAIN DOOR FASTENERS	59
DOOR STOPS	60, 65
DOOR HOLDERS	63, 70
SASH HARDWARE:	
Bar Lifts	73
Fasteners	74
Flush Lifts	73
Pulleys	94
Stop Bead Washers	72
Turn Buttons	91
CASEMENT HARDWARE:	
Adjusters	76, 77
Fasteners	75
TRANSOM HARDWARE:	
Catches	86
Chains	83
Lifters	78, 81
Stays	82, 83
CATCHES:	
Bullet	84
Cupboard	85
Friction	84
Screen Door	87
HOOKS:	
Ceiling	88
Coat and Hat	88
Lavatory	92
Wardrobe	88
CLOSET BARS	39
PULLS:	
Drawer	90
Knob	91
SHELF RESTS	91
DOOR BELLS	92
NUMBERS	93
HAND RAIL BRACKETS	93

Chain Door Fasteners

59



2266, T02266



2265, T02265

No.	Size Inches	Material and Finish	Plate Inches	Anchor Plate Inches	Chain	Packed in a Box	Weight Dozen
T2266	4	Cast Brass or Bronze Roll Polish	1 $\frac{7}{8}$ x4	1 $\frac{7}{8}$ x1 $\frac{7}{8}$	No. 8 Jack	6	7 lbs.
*Z02266	4	Cast Iron Sprayed Brass Finish	1 $\frac{7}{8}$ x4	1 $\frac{7}{8}$ x1 $\frac{7}{8}$	No. 8 Jack	6	7 lbs.
T02266	4	Plated	1 $\frac{7}{8}$ x4	1 $\frac{7}{8}$ x1 $\frac{7}{8}$	No. 8 Jack	6	7 lbs.
2265	4	Cast Brass or Bronze Polished	4 x1 $\frac{5}{16}$	2 $\frac{7}{16}$ x1 $\frac{5}{16}$	$\frac{3}{8}$ in. Link	6	5 $\frac{5}{8}$ lbs.
2265	6	Polished	6 x1 $\frac{5}{16}$	2 $\frac{7}{16}$ x1 $\frac{5}{16}$	$\frac{3}{8}$ in. Link	6	6 $\frac{1}{4}$ lbs.
T02265	4	Cast Iron Plated	4 x1 $\frac{5}{16}$	2 $\frac{7}{16}$ x1 $\frac{5}{16}$	$\frac{3}{8}$ in. Link	6	5 $\frac{5}{8}$ lbs.
T02265	6	Plated	6 x1 $\frac{5}{16}$	2 $\frac{7}{16}$ x1 $\frac{5}{16}$	$\frac{3}{8}$ in. Link	6	6 $\frac{1}{4}$ lbs.

Packed with screws.

*Packed without screws.

Specify number, size and finish. See pages 1 and 2.

Door Stops

WITH RUBBER BUMPERS



3763, T3763, T03763



3765 to T03766




6387


No.	Projection Inches	Material and Finish	Base Diameter Inches	Method of Attaching	Packed in a Box	Weight Dozen
3763	2½	Cast Brass or Bronze	1	Wood Screw	12	1¼ lbs.
T3763	2½	Polished	1	Wood Screw	12	1¼ lbs.
3765	3¼	Roll Polish	1½	Wood Screw	12	2 lbs.
T3765	3¼	Polished	1½	Wood Screw	12	2 lbs.
3766	3¼	Roll Polish	1½	Expansion Bolt	12	2¾ lbs.
T3766	3¼	Polished	1½	Expansion Bolt	12	2¾ lbs.
T03763	2½	Cast Iron	1	Wood Screw	12	1¼ lbs.
T03765	3¼	Plated	1½	Wood Screw	12	1¾ lbs.
T03766	3¼	Plated	1½	Expansion Bolt	12	2½ lbs.
*6387	3	Aluminum	¾	Wood Screw	12	15 oz.
		Roll Polish				

Packed with screws or bolts. *Furnished only EA, DB, E and AL finishes.

Specify number and finish. See pages 1 and 2.



3750 to T03751



3768, 3769



3790, 3791

No.	Projection Inches	Material and Finish	Base Diameter Inches	Method of Attaching	Packed in a Box	Weight Dozen
3750	2, also 2½, 3	Cast Brass or Bronze	2	Wood Screws	6	3½ lbs.
3751	2, also 2½, 3	Polished	2	Wood Screws	6	3¾ to 4 lbs.
3768	3, also 3½, 4½, 6	Polished	2	Expansion Bolt	6	7 lbs.
3769	3, also 3½, 4½, 6	Polished	2	Expansion Bolt	6	8 to 9¾ lbs.
3790	2¾, also 3½, 4¼, 5¼	Polished	1½	Wood Screws	6	4¾ lbs.
3791	2¾, also 3½, 4¼, 5¼	Polished	1½	Wood Screws	6	6½ to 9¾ lbs.
T03750	2, also 2½, 3	Polished	1½	Expansion Bolt	6	5¾ lbs.
T03751	2, also 2½, 3	Polished	1½	Expansion Bolt	6	7 to 10¼ lbs.
		Cast Iron	2¼x1¼	Wood Screws	6	4¼ lbs.
		Plated	2¼x1¼	Wood Screws	6	5 to 6½ lbs.
		Plated	2¼x1¼	Expansion Shields	6	5¾ lbs.
		Plated	2¼x1¼	Expansion Shields	6	6½ to 7¾ lbs.
T03750	2, also 2½, 3	Plated	2	Wood Screws	6	2¾ lbs.
T03751	2, also 2½, 3	Plated	2	Wood Screws	6	3¾ to 4 lbs.
		Plated	2	Expansion Bolt	6	5¾ lbs.
		Plated	2	Expansion Bolt	6	7¼ to 9 lbs.

Packed with screws or bolts.

Specify number, size and finish. See pages 1 and 2.



Door Stops


WITH RUBBER BUMPERS

61

Rev. 6-1-57



3770, 3771

3756, 3757
Type of 6756, 6757


3762, T03762



3752 to T03753



6373

3758, 3759
Type of 6758, 6759


No.	Height Inches	Material and Finish	Base Diameter Inches	Method of Attaching	Packed in a Box	Weight Dozen
Cast Brass or Bronze						
3752	2¼	Polished	2	Wood Screws	6	4¼ lbs.
3753	2¼	Polished	2	Expansion Bolt	6	8¼ lbs.
3762	1⅝	Polished	1¼	Wood Screw	12	1⅞ lbs.
T3762	1⅝	Roll Polish	1¼	Wood Screw	12	1⅞ lbs.
3756	1⅝	Polished	1⅞	Wood Screw	6	3¾ lbs.
3757	1⅝	Polished	1⅞	Expansion Shield	6	4⅞ lbs.
3758	1	Polished	1⅞	Wood Screw	6	2⅝ lbs.
3759	1	Polished	1⅞	Expansion Shield	6	3 lbs.
3770	3	Polished	2½	Wood Screws	3	9 lbs.
3771	3	Polished	2½	Expansion Bolt	3	10⅞ lbs.
Cast Iron						
T03752	2¼	Plated	2	Wood Screws	6	4 lbs.
T03753	2¼	Plated	2	Expansion Bolt	6	7½ lbs.
T03762	1⅝	Plated	1¼	Wood Screw	12	1¾ lbs.
Aluminum						
6756	1⅝	Alumilited	1⅞	Wood Screw	6	1¼ lbs.
6757	1⅝	Alumilited	1⅞	Expansion Shield	6	1⅜ lbs.
6758	1	Alumilited	1⅞	Wood Screw	6	⅞ lbs.
6759	1	Alumilited	1⅞	Expansion Shield	6	1 lb.
6373	1½	Roll Polish	1¼	Wood Screw	12	1 lb.

Packed with screws or bolt.


Specify number and finish. See pages 1 and 2.

Door Stops and Holders

WITH RUBBER BUMPERS



3740 to T03741




*3778, 3779, Right Hand

No.	Projection Inches	Material and Finish	Base Diameter Inches	Staple Inches	Method of Attaching	Packed in a Box	Weight Dozen
Cast Brass or Bronze							
3740	2, also	Polished	2	1 $\frac{1}{16}$ x $\frac{9}{16}$	Wood screws	1	5 $\frac{1}{2}$ lbs.
	2 $\frac{1}{2}$, 3	Polished	2	1 $\frac{1}{16}$ x $\frac{9}{16}$	Wood screws	1	6 to 7 $\frac{1}{2}$ lbs.
3741	2, also	Polished	2	1 $\frac{1}{16}$ x $\frac{9}{16}$	Expansion Bolt	1	9 lbs.
	2 $\frac{1}{2}$, 3	Polished	2	1 $\frac{1}{16}$ x $\frac{9}{16}$	Expansion Bolt	1	10 to 11 $\frac{1}{4}$ lbs.
3778	3, also	Polished	1 $\frac{7}{8}$	1 $\frac{5}{16}$ x 1 $\frac{3}{16}$	Wood screws	1	8 $\frac{3}{4}$ lbs.
	3 $\frac{1}{2}$, 4 $\frac{1}{2}$, 6	Polished	1 $\frac{7}{8}$	1 $\frac{5}{16}$ x 1 $\frac{3}{16}$	Wood screws	1	9 to 14 $\frac{1}{4}$ lbs.
3779	3, also	Polished	1 $\frac{7}{8}$	1 $\frac{5}{16}$ x 1 $\frac{3}{16}$	Expansion Bolt	1	10 $\frac{1}{8}$ lbs.
	3 $\frac{1}{2}$, 4 $\frac{1}{2}$, 6	Polished	1 $\frac{7}{8}$	1 $\frac{5}{16}$ x 1 $\frac{3}{16}$	Expansion Bolt	1	10 $\frac{1}{4}$ to 15 lbs.
Cast Iron							
T03740	2, also	Plated	2	1 $\frac{1}{16}$ x $\frac{9}{16}$	Wood screws	1	4 $\frac{1}{4}$ lbs.
	2 $\frac{1}{2}$, 3	Plated	2	1 $\frac{1}{16}$ x $\frac{9}{16}$	Wood screws	1	5 to 5 $\frac{5}{8}$ lbs.
T03741	2, also	Plated	2	1 $\frac{1}{16}$ x $\frac{9}{16}$	Expansion Bolt	1	6 lbs.
	2 $\frac{1}{2}$, 3	Plated	2	1 $\frac{1}{16}$ x $\frac{9}{16}$	Expansion Bolt	1	7 to 8 $\frac{1}{2}$ lbs.


Packed with screws or bolts.

Specify number, size required and finish. See pages 1 and 2.

*Door stops and holders are regularly furnished right hand. Left hand furnished only when hand is specified on order.



3742 to T03743



*3780, 3781, Right Hand

No.	Height Inches	Material and Finish	Base Diameter Inches	Staple Inches	Method of Attaching	Packed in a Box	Weight Dozen
Cast Brass or Bronze							
3742	2 $\frac{1}{4}$	Polished	2	1 $\frac{1}{16}$ x $\frac{9}{16}$	Wood screws	1	6 $\frac{3}{8}$ lbs.
3743	2 $\frac{1}{4}$	Polished	2	1 $\frac{1}{16}$ x $\frac{9}{16}$	Expansion Bolt	1	10 lbs.
3780	3	Polished	2 $\frac{1}{2}$	1 $\frac{5}{16}$ x 1 $\frac{3}{16}$	Wood screws	1	14 $\frac{3}{4}$ lbs.
3781	3	Polished	2 $\frac{1}{2}$	1 $\frac{5}{16}$ x 1 $\frac{3}{16}$	Expansion Bolt	1	15 $\frac{1}{2}$ lbs.
Cast Iron							
T03742	2 $\frac{1}{4}$	Plated	2	1 $\frac{1}{16}$ x $\frac{9}{16}$	Wood screws	1	5 $\frac{5}{8}$ lbs.
T03743	2 $\frac{1}{4}$	Plated	2	1 $\frac{1}{16}$ x $\frac{9}{16}$	Expansion Bolt	1	9 $\frac{5}{8}$ lbs.

Packed with screws or bolts.

*Door stops and holders are regularly furnished right hand. Left hand furnished only when hand is specified on order.

Specify number and finish. See pages 1 and 2.



Door Stops


WITH RUBBER BUMPERS

61

Rev. 6-1-57



3770, 3771

3756, 3757
Type of 6756, 6757


3762, T03762



3752 to T03753



6373

3758, 3759
Type of 6758, 6759


No.	Height Inches	Material and Finish	Base Diameter Inches	Method of Attaching	Packed in a Box	Weight Dozen
Cast Brass or Bronze						
3752	2¼	Polished	2	Wood Screws	6	4½ lbs.
3753	2¼	Polished	2	Expansion Bolt	6	8¼ lbs.
3762	1½	Polished	1¼	Wood Screw	12	1½ lbs.
T3762	1½	Roll Polish	1¼	Wood Screw	12	1½ lbs.
3756	1½	Polished	1½	Wood Screw	6	3¾ lbs.
3757	1¾	Polished	1¾	Expansion Shield	6	4½ lbs.
3758	1	Polished	1¾	Wood Screw	6	2½ lbs.
3759	1	Polished	1¾	Expansion Shield	6	3 lbs.
3770	3	Polished	2½	Wood Screws	3	9 lbs.
3771	3	Polished	2½	Expansion Bolt	3	10½ lbs.
Cast Iron						
T03752	2¼	Plated	2	Wood Screws	6	4 lbs.
T03753	2¼	Plated	2	Expansion Bolt	6	7½ lbs.
T03762	1½	Plated	1¼	Wood Screw	12	1¾ lbs.
Aluminum						
6756	1¾	Alumilited	1¾	Wood Screw	6	1¼ lbs.
6757	1¾	Alumilited	1¾	Expansion Shield	6	1¾ lbs.
6758	1	Alumilited	1¾	Wood Screw	6	¾ lbs.
6759	1	Alumilited	1¾	Expansion Shield	6	1 lb.
6373	1½	Roll Polish	1¼	Wood Screw	12	1 lb.

Packed with screws or bolt.


Specify number and finish. See pages 1 and 2.

Door Stops and Holders

WITH RUBBER BUMPERS



3740 to T03741




*3778, 3779, Right Hand

No.	Projection Inches	Material and Finish	Base Diameter Inches	Staple Inches	Method of Attaching	Packed in a Box	Weight Dozen
Cast Brass or Bronze							
3740	2, also 2½, 3	Polished	2	1½x ¾	Wood screws	1	5½ lbs.
3741	2, also 2½, 3	Polished	2	1½x ¾	Wood screws	1	6 to 7½ lbs.
		Polished	2	1½x ¾	Expansion Bolt	1	9 lbs.
3778	3, also 3½, 4½, 6	Polished	2	1½x ¾	Expansion Bolt	1	10 to 11¼ lbs.
		Polished	1⅞	1½x1¾	Wood screws	1	8¾ lbs.
3779	3, also 3½, 4½, 6	Polished	1⅞	1½x1¾	Wood screws	1	9 to 14¼ lbs.
		Polished	1⅞	1½x1¾	Expansion Bolt	1	10½ lbs.
Cast Iron							
T03740	2, also 2½, 3	Plated	2	1½x ¾	Wood screws	1	4¼ lbs.
T03741	2, also 2½, 3	Plated	2	1½x ¾	Wood screws	1	5 to 5½ lbs.
		Plated	2	1½x ¾	Expansion Bolt	1	6 lbs.
		Plated	2	1½x ¾	Expansion Bolt	1	7 to 8½ lbs.


Packed with screws or bolts.

Specify number, size required and finish. See pages 1 and 2.

*Door stops and holders are regularly furnished right hand. Left hand furnished only when hand is specified on order.



3742 to T03743



*3780, 3781, Right Hand

No.	Height Inches	Material and Finish	Base Diameter Inches	Staple Inches	Method of Attaching	Packed in a Box	Weight Dozen
Cast Brass or Bronze							
3742	2¼	Polished	2	1½x ¾	Wood screws	1	6¾ lbs.
3743	2¼	Polished	2	1½x ¾	Expansion Bolt	1	10 lbs.
3780	3	Polished	2½	1½x1¾	Wood screws	1	14¼ lbs.
3781	3	Polished	2½	1½x1¾	Expansion Bolt	1	15½ lbs.
Cast Iron							
T03742	2¼	Plated	2	1½x ¾	Wood screws	1	5½ lbs.
T03743	2¼	Plated	2	1½x ¾	Expansion Bolt	1	9½ lbs.


Packed with screws or bolts.

*Door stops and holders are regularly furnished right hand. Left hand furnished only when hand is specified on order.


Specify number and finish. See pages 1 and 2.

Door Stops and Holders

63



3760, T03760




3761, T03761

No.	Projection or Height Inches	Material and Finish	Base Inches	Spring Base Inches	Packed in a Box	Weight Dozen
3760	1 $\frac{7}{8}$	Cast Brass or Bronze	1 $\frac{3}{4}$ x2 $\frac{3}{4}$	$\frac{3}{4}$ x2 $\frac{3}{16}$	12	4 $\frac{3}{4}$ lbs.
3761	2 $\frac{5}{8}$	Spring Wrought Brass or Bronze Polished	1 $\frac{7}{8}$ x1	$\frac{3}{4}$ x2 $\frac{3}{16}$	12	3 $\frac{7}{8}$ lbs.
T03760	1 $\frac{7}{8}$	Cast Iron	1 $\frac{3}{4}$ x2 $\frac{3}{4}$	$\frac{3}{4}$ x2 $\frac{3}{16}$	12	4 $\frac{1}{2}$ lbs.
T03761	2 $\frac{5}{8}$	Wrought steel Spring Plated	1 $\frac{7}{8}$ x1	$\frac{3}{4}$ x2 $\frac{3}{16}$	12	3 $\frac{1}{2}$ lbs.

Packed with screws.

Door Holder



D03875

For Doors opening
Outward over steps
with 6 to 7 inch riser.

No.	Height Inches	Material and Finish	Base Inches	Strike Inches	Screws	Weight Each
D03875	10 $\frac{1}{4}$	Cast Iron Dead Black	6 $\frac{1}{4}$ x7	4 $\frac{3}{8}$ x3	Wood screws	18 lbs.

No. D03875 has cast bronze trip and strike. Packed with screws.

Specify number and finish. See pages 1 and 2.



Door Holders



3861, 03861

Rubber tip on bolt head



5

The rubber tip No. 5 furnished regularly with these holders is moulded integrally with brass ferrule which threads into tapped hole in holder. Will not loosen in service.

To remove, pull tip to stretch rubber and turn. Insert replacement tip in same manner; releasing tension allows rubber to grip stop firmly.

End of tip formed in concentric rings to provide floor gripping surface.

No. 1 rubber tip can be furnished for replacement on old model holders.



1

No.	Size Inches	Material and Finish	Throw Inches	Packed in a Box	Weight Dozen
3861	7¼ x 2½	Wrought Brass or Bronze Polished	1⅞	6	9¼ lbs
03861	7¼ x 2½	Wrought Steel Plated	1⅞	6	11½ lbs.

Packed with screws.

3864 to T03865
Lever type

The rubber tip grips the floor and will hold door open at any angle desired. Can be operated by the foot. Spring catch holds lever up out of the way when not in use.

Rubber tip No. 5 furnished regularly with these holders is moulded integrally with brass ferrule which threads into tapped hole in holder. Will not loosen in service. To remove, pull tip to stretch rubber and turn. Insert replacement tip in same manner; releasing tension allows rubber to grip stop firmly. End of tip formed in concentric rings to provide floor gripping surface.

No. 1 rubber tip can be furnished for replacement on old model holders.



5



1

No.	Length Inches	Material and Finish	Plate Inches	For doors with floor clearance	Packed in a Box	Weight Dozen
3864	4	Cast Brass or Bronze Polished	1⅞ x 1¼	2 in. or less	6	7⅞ lbs.
T3864	4	Roll polish	1⅞ x 1¼	2 in. or less	6	7⅞ lbs.
3865	5	Polished	1⅞ x 1¼	3½ in. or less	6	7⅞ lbs.
T3865	5	Roll polish	1⅞ x 1¼	3½ in. or less	6	7⅞ lbs.
		Cast Iron				
T03864	4	Plated	1⅞ x 1¼	2 in. or less	6	6¼ lbs.
T03865	5	Plated	1⅞ x 1¼	3½ in. or less	6	6¾ lbs.

Packed with screws.


Specify number and finish. See pages 1 and 2.




Door Bumpers

WITH RUBBER CENTER


65



334 1/2, 0334 1/2
Convex Rubber
Center



Showing method of at-
taching Nos. 334 1/2




Showing method of at-
taching Nos. 0334 1/2,
0343, 0343 1/2




*343 1/2, *0343 1/2
Convex Rubber Center




*336, *337, *0337




Showing method of at-
taching No. 343 1/2



*338, *339, *340



0337 337 336
Methods of Attaching



339 340
Methods of Attaching

ATTACHED TO WALL SO THAT DOOR KNOB WILL STRIKE AGAINST RUBBER CENTER

No.	Diameter Inches	Material and Finish	Rubber Center	Projection Inches	Method of Attaching	Packed in a Box	Weight Dozen
Cast Brass or Bronze							
*†336	2 1/4	Polished	Round	1 1/4	Wood Screw	6	6 7/8 Lbs.
*†337	2 1/4	Polished	Round	1 1/4	Mach. Screw x Exp. Bolt	6	8 3/8 Lbs.
*†0337	2 1/4	Polished	Round	1 1/4	Mach. Screw x Toggle Head	6	7 5/8 Lbs.
334 1/2	3	Polished	Convex	1 3/16	2 Wood Screws x Exp. Shields	2	7 1/8 Lbs.
0334 1/2	3	Polished	Convex	1 3/16	3 in. Mach. Screw x Toggle Head	2	7 3/4 Lbs.
*343 1/2	4	Polished	Convex	1 3/16	2 1/4 in. Expansion Bolt	2	12 7/8 Lbs.
*0343 1/2	4	Polished	Convex	1 3/16	2 1/4 in. Mach. Screw x Toggle Head	2	14 3/8 Lbs.
*338	2 3/8	Polished	Convex	1 5/16	3 in. Wood Screws	2	3 1/4 Lbs.
*339	2 3/8	Polished	Convex	1	3 in. Mach. Screw & Toggle Head	2	4 1/4 Lbs.
*340	2 3/8	Polished	Convex	1	3 in. Expansion Bolt	2	5 Lbs.

†Nos. 336, 337 and 0337. The flange is fastened to base with hollow head set screw which cannot be removed without the proper tool. Key for operating hollow head set screw furnished with these bumpers.

*Also furnished in aluminum.

Specify number and finish. See pages 1 and 2.




Overhead Door Holders

67

POSITIVE GRIP

CONCEALED TYPE

FOR SINGLE AND DOUBLE ACTING DOORS



A heavy duty holder that is mortised in the top edge of door and is completely concealed when door is closed, (when door is open only knurled knob and arm are exposed.)

The Corbin No. 870 is a strong, sturdy, free-acting door holder with an automatically engaging and releasing hold open, shock absorber and manual holder-disengaging feature.

The track is of extruded brass, the arm is of hard drawn brass or bronze. The slide is of extruded brass. All holding parts are pack hardened against wear.

The enclosed shock absorber consists of a leather faced block working against a large spring. The disengaging mechanism, which makes the device non-holding, if desired, is operated by means of a neat knob extending slightly beyond the face of the door. The holding tension is adjustable.

The entire device requires a minimum amount of mortising.

Contact holding parts hardened steel.

EXTRUDED BRASS

Number for Use with				Width of Door	Dimensions	
Butts	Offset Pivots	Single Acting Center Hung Pivots	Double Acting Center Hung Pivots		Extruded Brass Track	Jamb Bracket
870A	871A	872A	873A	24 to 25½ in. Inclusive	1½ in. wide ¾ in. deep ½ in. thick	4 x 1½ in.
870B	871B	872B	873B	26 to 28½ in. Inclusive		
870C	871C	872C	873C	29 to 33½ in. Inclusive		
870D	871D	872D	873D	34 to 37½ in. Inclusive		
870E	871E	872E	873E	38 to 42½ in. Inclusive		
870F	871F	872F	873F	43 to 48 in. Inclusive		

One in a box, with screws.

*Arm 1½ in. wide, ¾ in. thick. Maximum opening approximately 110 degrees.

*For 873 Series arm width same as door thickness.

When ordering, specify type and size of butt or pivot; degree of opening; width and thickness of door; hand of door; wood or metal doors and frames; make and number of fire exit bolts, flush bolts and door closer.

Specify number and finish. See pages 1 and 2.




Overhead Door Holders

POSITIVE GRIP

HEAVY DUTY SURFACE TYPE

FOR SINGLE ACTING DOORS
WITH ENCASED SHOCK ABSORBER



A heavy duty door holder for exterior or interior doors that is applied to top rail of door.

This is a neat, inconspicuous device mounted directly on the surface of the door slightly below the header. The track is of extruded brass, I beam in section for maximum strength. The slide is of extruded brass and carries the holding mechanism which engages and disengages automatically. The arm is of hard drawn brass or bronze. Contact holding parts hardened steel.

The disengaging mechanism, which makes the device non-holding, if desired, is carried by the slide and a quarter turn of the control lever in either direction renders the holding mechanism inoperative. The holding tension is adjustable.

EXTRUDED BRASS

Number for Use with			Width of Door	Dimensions		
Butts	Offset Pivots	Single Acting Center Hung Pivots		Extruded Brass Track	Projection	Jamb Bracket
890A	891A	892A	28 to 29½ in. Inclusive	1¾ in. wide 1¼ in. deep	1¾ in.	3¾ x 1 in.
890B	891B	892B	30 to 31½ in. Inclusive			
890C	891C	892C	32 to 35½ in. Inclusive			
890D	891D	892D	36 to 39½ in. Inclusive			
890E	891E	892E	40 to 43½ in. Inclusive			
890F	891F	892F	44 to 48 in. Inclusive			

One in a box, with screws. Furnished regularly with through bolts and sex nuts on wood doors.

Arm 1 in. wide x ¼ in. thick. Maximum opening approximately 110 degrees.

When ordering, specify type and size of butt or pivot; degree of opening; width and thickness of door; hand of door; wood or metal doors and frames; make and number of fire exit bolts, flush bolts and door closer.

Door closers when used on same side of door with these overhead door holders require bent arm.

Specify number and finish. See pages 1 and 2.





Overhead Friction Door Holders

69

POSITIVE GRIP

CONCEALED TYPE, REVERSIBLE

FOR SINGLE AND DOUBLE ACTING DOORS



Designed for use on light and medium weight interior doors. Operation by a slight pull or push.



Triple Grip Friction Slide
Nos. 820 to 823



Hold Open Feature
Nos. 840 to 843

CORBIN No. 820 CONCEALED FRICTION DOOR HOLDER

By means of an original and entirely new friction-applying method all three available inner surfaces of the track are utilized, providing more than twice the frictional area found in similar devices, ensuring increased life of all frictional parts and eliminating the necessity of frequent adjustments. The accessible adjusting screw works against a metal plate which compresses a synthetic rubber pad. The pad tends to "flow" evenly in all directions, transmitting the pressure to compressed asbestos friction linings which bear against the bottom and both side surfaces of the track.

CORBIN No. 840 CONCEALED FREE ACTING DOOR HOLDERS

This device uses the same track, arm and shock absorber as the No. 820 but has an extruded brass slide and a fixed holding mechanism which engages and releases automatically. Large holding surfaces make for long life and the holding parts are hardened against wear.

CORBIN No. 850 CONCEALED DOOR STAY

The concealed door stay uses the same track, arm and shock absorber as the No. 820 but has no friction control or fixed holding mechanism.

Dimensions: Track $\frac{7}{8}$ in. wide, $\frac{3}{4}$ in. deep, $\frac{1}{16}$ in. thick. Arm $\frac{7}{8}$ in. wide x $\frac{3}{16}$ in. thick. Jamb Bracket $3\frac{1}{2}$ in. x 1 in. Maximum opening approximately 110 degrees.

EXTRUDED BRASS**Concealed Three Way Friction Holder**

Number for Use with				Width of Doors	Number for Use with				Width of Doors
Butts	Offset Pivots	Single Acting Center Hung Pivots	Double Acting Center Hung Pivots		Butts	Offset Pivots	Single Acting Center Hung Pivots	Double Acting Center Hung Pivots	
820A	821A	822A	823A	15 to 17½ in. Incl.	820D	821D	822D	823D	30 to 35½ in. Incl.
820B	821B	822B	823B	18 to 23½ in. Incl.	820E	821E	822E	823E	36 to 41½ in. Incl.
820C	821C	822C	823C	24 to 29½ in. Incl.	820F	821F	822F	823F	42 to 48 in. Incl.

Concealed Free Acting Holder

840A	841A	842A	843A	15 to 17½ in. Incl.	840D	841D	842D	843D	30 to 35½ in. Incl.
840B	841B	842B	843B	18 to 23½ in. Incl.	840E	841E	842E	843E	36 to 41½ in. Incl.
840C	841C	842C	843C	24 to 29½ in. Incl.	840F	841F	842F	843F	42 to 48 in. Incl.

Concealed Door Stay

850A	851A	852A	853A	15 to 17½ in. Incl.	850D	851D	852D	853D	30 to 35½ in. Incl.
850B	851B	852B	853B	18 to 23½ in. Incl.	850E	851E	852E	853E	36 to 41½ in. Incl.
850C	851C	852C	853C	24 to 29½ in. Incl.	850F	851F	852F	853F	42 to 48 in. Incl.

One in a box, with screws.

When ordering, specify type and size of butt or pivot; degree of opening; width and thickness of door; wood or metal doors and frames.

Specify number and finish. See pages 1 and 2.



Overhead Friction Door Holders

LIGHT WEIGHT SURFACE TYPE

FOR SINGLE ACTING DOORS AND WINDOWS

Triple Grip Friction Slide
Nos. 860 to 862Hold Open Feature
Nos. 760 to 762**CORBIN No. 860 SURFACE FRICTION DOOR HOLDER**

By means of an original and entirely new friction-applying method all three available inner surfaces of the track are utilized, providing more than twice the frictional area found in similar devices, ensuring increased life of all frictional parts and eliminating the necessity of frequent adjustments. The accessible adjusting screw works against a metal plate which compresses a synthetic rubber pad. The pad tends to "flow" evenly in all directions, transmitting the pressure to compressed asbestos friction linings which bear against the bottom and both side surfaces of the track.

CORBIN No. 760 SURFACE FREE ACTING DOOR HOLDERS

This device uses the same track, arm and shock absorber as the No. 820 but has an extruded brass slide and a fixed holding mechanism which engages and releases automatically. Large holding surfaces make for long life and the holding parts are hardened against wear.

CORBIN No. 770 SURFACE DOOR STAY

The concealed door stay uses the same track, arm and shock absorber as the No. 820 but has no friction control or fixed holding mechanism.

Dimensions: Track $\frac{7}{8}$ in. wide, $\frac{3}{4}$ in. deep, $\frac{1}{16}$ in. thick. Arm $\frac{3}{16}$ in. thick. Projection $\frac{7}{8}$ in. Jamb Bracket $3\frac{1}{2}$ in. x 1 in. x $\frac{3}{16}$ in. Maximum Opening: Approximately 110 degrees.

EXTRUDED BRASS**Surface Three Way Friction Holder**

Number for Use with			Width of Doors	Number for Use with			Width of Doors
Butts	Offset Pivots	Single Acting Center Hung Pivots		Butts	Offset Pivots	Single Acting Center Hung Pivots	
860A	861A	862A	15 to 17½ in. Incl.	860D	861D	862D	30 to 35½ in. Incl.
860B	861B	862B	18 to 23½ in. Incl.	860E	861E	862E	36 to 41½ in. Incl.
860C	861C	862C	24 to 29½ in. Incl.	860F	861F	862F	42 to 48 in. Incl.

Surface Free Acting Holder

760A	761A	762A	15 to 17½ in. Incl.	760D	761D	762D	30 to 35½ in. Incl.
760B	761B	762B	18 to 23½ in. Incl.	760E	761E	762E	36 to 41½ in. Incl.
760C	761C	762C	24 to 29½ in. Incl.	760F	761F	762F	42 to 48 in. Incl.

Surface Door Stay

770A	771A	772A	15 to 17½ in. Incl.	770D	771D	772D	30 to 35½ in. Incl.
770B	771B	772B	18 to 23½ in. Incl.	770E	771E	772E	36 to 41½ in. Incl.
770C	771C	772C	24 to 29½ in. Incl.	770F	771F	772F	42 to 48 in. Incl.

One in a box, with screws.


When ordering, specify type and size of butt or pivot; degree of opening; width and thickness of door; wood or metal doors and frames.

Specify number and finish. See pages 1 and 2.



Sash Pulls

71



3196, T03196

No.	Length, inches	Material and Finish	Diameter inches	Socket Dia. Open End	Packed in a Box	Weight Dozen
3196	2½	Cast Brass or Bronze Polished	1	⅝	6	1⅞ lbs.
T03196	2½	Cast Iron Plated	1	⅝	6	1¾ lbs.

Packed with screws.

STEEL WINDOW POLES WITH PULL DOWN HOOKS




2280

Pole 035 Ga. butt jointed wrought steel tubing. Hook with removable rubber tip to prevent marring of sash. The lower end of pole is fitted with a removable rubber tip with steel insert to prevent pole from cutting through the rubber.


No.	Length Feet	Material and Finish		Outside Diameter of Pole
		Pole	Hook	
2280	4, 6, 8, 10, or 12	Wrought Steel Black Finish	Cast Brass or Bronze Black Finish	¾ in.

State length required. Can be furnished in other lengths when so ordered at additional price. One in a package.

Sash Sockets



3186, T03186



3187, T03187

No.	Size inches	Article	Material and Finish	Packed in a Box	Weight Dozen
3186	1¼ Dia.	Socket	Cast Brass or Bronze Polished	12	1½ lbs.
3187	1¼ x 2¼	Socket	Polished	12	1⅞ lbs.
3190	2⅜ x 1⅞	Hanger	Polished	12	1½ lbs.
T03186	1¼ Dia.	Socket	Cast Iron Plated	12	1⅞ lbs.
T03187	1¼ x 2¼	Socket	Plated	12	1 lb.
T03190	2⅜ x 1⅞	Hanger	Plated	12	1⅞ lbs.

Packed with screws.

Specify number and finish. See pages 1 and 2.

Pole Hangers




3190, T03190

Stop Bead Screws and Washers



180, T0180



183, T0183

No.	Diameter Washer Inches	Material and Finish	Screw	Packed in a Box	Weight Gross
180	$\frac{5}{8}$	Wrought Brass or Bronze	$1\frac{1}{4}$ in. No. 8	1 Gross	$1\frac{1}{4}$ Lbs.
183	$1\frac{1}{16}$	Polished	1 in. No. 8	1 Gross	2 Lbs.
		Polished			
T0180	$\frac{5}{8}$	Wrought Steel	$1\frac{1}{4}$ in. No. 8	1 Gross	$1\frac{1}{2}$ Lbs.
T0183	$1\frac{1}{16}$	Plated	1 in. No. 8	1 Gross	$1\frac{3}{4}$ Lbs.
		Plated			

Hook Sash Lifts



3302



3308, 03308

No.	Size Inches	Material and Finish	Projection Inches	Packed in a Box	Weight Dozen
3302	$\frac{3}{4}$ x $1\frac{1}{2}$	Cast Brass or Bronze			
		Polished	$\frac{7}{8}$	3 Dozen	$1\frac{1}{8}$ Lbs
3308	1 x $1\frac{5}{8}$	Wrought Brass or Bronze			
		Polished	$\frac{5}{8}$	3 Dozen	9 oz.
03308	1 x $1\frac{5}{8}$	Wrought Steel			
		Plated	$\frac{5}{8}$	6 Dozen	9 oz.

Packed with screws.

Specify number and finish. See pages 1 and 2.

Flush Sash Lifts


73



3319



3316, 03316



3315, 03315

No.	Size, Inches	Material and Finish	Size of Cup Inches	Packed in a Box	Weight Dozen
3319	1 $\frac{1}{16}$ x 3 $\frac{1}{16}$	Cast Brass or Bronze Polished	1 $\frac{1}{16}$ x 2 $\frac{3}{16}$ x $\frac{5}{16}$	1 Dozen	1 $\frac{7}{8}$ lbs.
3315	1 $\frac{1}{2}$ x 3	Wrought Brass or Bronze Polished	$\frac{7}{8}$ x 2 $\frac{3}{8}$ x $\frac{7}{16}$	3 Dozen	9 oz.
03316	1 $\frac{1}{2}$ x 3	Polished	$\frac{7}{8}$ x 2 $\frac{3}{8}$ x $\frac{7}{16}$	3 Dozen	10 oz.
03315	1 $\frac{1}{2}$ x 3	Wrought Steel Plated	$\frac{7}{8}$ x 2 $\frac{3}{8}$ x $\frac{5}{16}$	3 Dozen	9 oz.
03316	1 $\frac{1}{2}$ x 3	Plated	$\frac{7}{8}$ x 2 $\frac{3}{8}$ x $\frac{5}{16}$	3 Dozen	9 oz.

Packed with screws.

Bar Sash Lifts

3394 to T03396
Type of 6396*Offset
3396 to T03396
Type of 3394, T03394

No.	Size Inches	Material and Finish	Projection Inches	Clearance Inches	Type	Packed in a Box	Weight Dozen
3394	1 $\frac{1}{4}$ x 4 $\frac{1}{2}$	Cast Brass or Bronze Polished	1 $\frac{3}{16}$	$\frac{3}{4}$	Straight	12	2 $\frac{5}{8}$ lbs.
T3394	1 $\frac{1}{4}$ x 4 $\frac{1}{2}$	Roll Polish	1 $\frac{3}{16}$	$\frac{3}{4}$	Straight	12	2 $\frac{5}{8}$ lbs.
3395	1 $\frac{1}{4}$ x 4 $\frac{7}{8}$	Polished	1 $\frac{3}{16}$	1 $\frac{3}{16}$	Straight	12	2 $\frac{7}{8}$ lbs.
T3395	1 $\frac{1}{4}$ x 4 $\frac{7}{8}$	Roll Polish	1 $\frac{3}{16}$	1 $\frac{3}{16}$	Straight	12	2 $\frac{7}{8}$ lbs.
3396	1 x 4	Polished	1 $\frac{1}{16}$	$\frac{3}{4}$	Straight	12	1 $\frac{7}{8}$ lbs.
T3396	1 x 4	Roll Polish	1 $\frac{1}{16}$	$\frac{3}{4}$	Straight	12	1 $\frac{7}{8}$ lbs.
T03394	1 $\frac{1}{4}$ x 4 $\frac{1}{2}$	Cast Iron Plated	1 $\frac{3}{16}$	$\frac{3}{4}$	Straight	12	2 $\frac{1}{2}$ lbs.
T03395	1 $\frac{1}{4}$ x 4 $\frac{7}{8}$	Plated	1 $\frac{3}{16}$	1 $\frac{3}{16}$	Straight	12	2 $\frac{3}{4}$ lbs.
T03396	1 x 4	Plated	1 $\frac{1}{16}$	$\frac{3}{4}$	Straight	12	1 $\frac{1}{2}$ lbs.
†6396	1 x 4	Aluminum Roll Polish	1 $\frac{1}{16}$	$\frac{5}{8}$	Straight	12	11 $\frac{1}{2}$ oz.


Packed with screws.

†Furnished in EA, DB, E and AL finishes only. *When required offset suffix offset to number I.E. 3396 offset.



Specify number and finish. See pages 1 and 2.



Sash Fasteners



1829, T01829


1831, T01831
Type of 6829

1840


No.	Size of Case Inches	Material and Finish	Strike Inches	Height Inches	Packed in a Box	Weight Dozen
1829	$\frac{7}{8} \times 2\frac{1}{2}$	Cast Brass or Bronze				
T1829	$\frac{7}{8} \times 2\frac{1}{2}$	Polished	$\frac{9}{16} \times 2\frac{9}{16}$	1	12	$2\frac{3}{4}$ lbs.
1831	$1 \times 2\frac{7}{8}$	Roll Polish	$\frac{9}{16} \times 2\frac{9}{16}$	1	12	$2\frac{3}{4}$ lbs.
T1831	$1 \times 2\frac{7}{8}$	Polished	$\frac{11}{16} \times 2\frac{3}{4}$	$1\frac{1}{4}$	12	$5\frac{3}{16}$ lbs.
1840	$\frac{7}{8} \times 2\frac{3}{8}$	Roll Polish	$\frac{11}{16} \times 2\frac{3}{4}$	$1\frac{1}{4}$	12	$5\frac{3}{16}$ lbs.
		Polished	$\frac{7}{8} \times 2\frac{3}{8}$	$1\frac{1}{2}$	6	$6\frac{1}{16}$ lbs.
		Cast Iron				
T01829	$\frac{7}{8} \times 2\frac{1}{2}$	Plated	$\frac{9}{16} \times 2\frac{9}{16}$	1	12	$2\frac{1}{2}$ lbs.
T01831	$1 \times 2\frac{7}{8}$	Plated	$\frac{11}{16} \times 2\frac{3}{4}$	$1\frac{1}{4}$	12	$3\frac{3}{8}$ lbs.
		Aluminum				
*6829	$\frac{7}{8} \times 2\frac{1}{2}$	Roll Polish	$\frac{9}{16} \times 2\frac{9}{16}$	1	12	$1\frac{1}{4}$ lbs.

Packed with screws. *Furnished only in EA, DB, E and AL finishes.


Special Mortise and Sull Sash Strikes




18A



18B



18C



18D

No.	Size Inches	For Fastener	Material and Finish	Weight Dozen
18A	$2\frac{1}{2} \times 1$	1829	Cast Brass or Bronze	
18B	$2\frac{1}{4} \times 2$	1829	Polished	$13\frac{1}{2}$ oz.
18C	$3\frac{9}{32} \times 1\frac{1}{4}$	1831	Polished	$2\frac{1}{4}$ lbs.
18D	$2\frac{5}{8} \times 2$	1831	Polished	$1\frac{1}{2}$ lbs.
			Polished	$1\frac{1}{2}$ lbs.
			Cast Iron	
T018A	$2\frac{1}{2} \times 1$	T01829	Plated	$13\frac{1}{2}$ lbs.
T018B	$2\frac{1}{4} \times 2$	T01829	Plated	$2\frac{3}{16}$ lbs.
T018C	$3\frac{9}{32} \times 1\frac{1}{4}$	T01831	Plated	$1\frac{1}{2}$ lbs.
T018D	$2\frac{5}{8} \times 2$	T01831	Plated	$1\frac{1}{2}$ lbs.

Specify number and finish. See pages 1 and 2.

Casement Fasteners

REVERSIBLE

75

Rev. 6-1-57




3156

Canada
Turn

8292




T03162


Mortise (M)
For single
casement
opening outRim (R)
For single
casement
opening in3168, T03168
Type of 6168Surface (S)
For double
casements
opening in or out

3174

Quebec Turns



8211, T8211



3175

Offset 1/2 in.
Not reversible

No.	Type Strike	Material and Finish	Plate Inches	Projection Inches	Strike Inches	Packed in a Box	Weight Dozen
Cast Brass or Bronze							
3156M	Mortise	Polished	2 1/4 x 3/4	1 3/16	9/16 x 2 7/16	6	3 3/4 lbs.
3156R	Rim	Polished	2 1/4 x 3/4	1 3/16	1 3/8 x 1 3/8	6	4 1/8 lbs.
3156S	Surface	Polished	2 1/4 x 3/4	1 3/16	9/16 x 2 1/4	6	4 3/8 lbs.
3168M	Mortise	Polished	2 1/8 x 1 1/8	1 3/4	9/16 x 2 7/16	12	3 3/8 lbs.
3168R	Rim	Polished	2 1/8 x 1 1/8	1 3/4	1 3/8 x 1 3/8	12	3 3/4 lbs.
3168S	Surface	Polished	2 1/8 x 1 1/8	1 3/4	9/16 x 2 1/4	12	4 1/8 lbs.
3174M	Mortise	Polished	6 x 3/4	1 1/4	9/16 x 2 7/16	6	3 5/8 lbs.
3174R	Rim	Polished	6 x 3/4	1 1/4	1 3/8 x 1 3/8	6	4 3/4 lbs.
*3175M	Mortise	Polished	6 1/4 x 3/4	1 1/4	9/16 x 2 7/16	6	4 1/8 lbs.
*3175R	Rim	Polished	6 1/4 x 3/4	1 1/4	1 3/8 x 1 3/8	6	4 3/4 lbs.
Cast Iron							
Plate Wrought Steel							
T03162M	Mortise	Plated	1 3/4 x 1 1/8	1 1/4	9/16 x 2 7/16	12	1 1/2 lbs.
T03162R	Rim	Plated	1 3/4 x 1 1/8	1 1/4	1 3/8 x 1 3/8	12	1 5/8 lbs.
T03162S	Surface	Plated	1 3/4 x 1 1/8	1 1/4	9/16 x 2 1/4	12	2 1/4 lbs.
Cast Iron							
T03168M	Mortise	Plated	2 1/8 x 1 1/8	1 3/4	9/16 x 2 7/16	12	3 3/4 lbs.
T03168R	Rim	Plated	2 1/8 x 1 1/8	1 3/4	1 3/8 x 1 3/8	12	3 3/4 lbs.
T03168S	Surface	Plated	2 1/8 x 1 1/8	1 3/4	9/16 x 2 1/4	12	4 lbs.
Aluminum							
†6168M	Mortise	Roll Polish	1 3/4 x 1 1/8	1 3/4	9/16 x 2 7/16	12	1 1/4 lbs.
†6168R	Rim	Roll Polish	1 3/4 x 1 1/8	1 3/4	1 3/8 x 1 3/8	12	1 1/4 lbs.
†6168S	Surface	Roll Polish	1 3/4 x 1 1/8	1 3/4	9/16 x 2 1/4	12	1 1/8 lbs.

Packed with screws.

*No. 3175 not reversible. Specify Hand. †Rim and mortise Keepers Steel Zinc Plated.

No. 6168 furnished only in EA, DB, E and AL finishes.

No.	Size Inches	Projection Inches	Material and Finish	Packed in a Box	Weight Dozen	Type
T8211	1 13/16 x 2	1 3/32	Cast Brass or Bronze	3 Dozen	1 3/8 lbs.	Quebec Turn
8211	1 13/16 x 2	1 3/32	Roll Polish	3 Dozen	1 3/8 lbs.	Quebec Turn
8292	1 x 7/8	7/8	Polished	12 Dozen	7 oz.	Canada Turn
			Roll Polish			
			Plated Steel Keeper			

Nos. T8211, 8211 packed with screws. No. 8292 packed without screws.


Specify number and finish. See pages 1 and 2.



Casement Adjusters

77

FOR CASEMENTS OPENING IN



1046

No.	Length Inches	Material and Finish	Sash Plate Inches	Sill Plate Inches	Bar	Packed in a Box	Weight Dozen
1046	10	Cast Brass or Bronze	$\frac{7}{8} \times 2\frac{1}{2}$	1 x 2	$\frac{1}{4} \times \frac{1}{2}$	6	6 $\frac{3}{4}$ lbs.
1046	12	Polished Polished	$\frac{7}{8} \times 2\frac{1}{2}$	1 x 2	$\frac{1}{4} \times \frac{1}{2}$	6	7 $\frac{1}{2}$ lbs.

Packed with screws.


FOR TOP OR BOTTOM OF CASEMENTS OPENING IN OR OUT

(Mounted on outside of casements opening in)

Friction Type—Friction adjustable by means of knurled ring at end of tube



1055



View Applied

No.	Length Closed Inches	Material and Finish	Length Overall Extended	Sash Plate Inches	Sill Plate Inches	Bar Diameter Inches	Tube Diameter Inches	Packed in a Box	Weight Dozen
1055	10 12	Wrought Brass or Bronze Polished Polished	16 $\frac{1}{4}$ in. 20 $\frac{1}{8}$ in.	$\frac{5}{8} \times 1\frac{7}{8}$ $\frac{5}{8} \times 1\frac{7}{8}$	$\frac{3}{4} \times 2\frac{1}{4}$ $\frac{3}{4} \times 2\frac{1}{4}$	$\frac{3}{8}$ $\frac{3}{8}$	$\frac{5}{8}$ $\frac{5}{8}$	6 6	9 lbs. 10 $\frac{3}{4}$ lbs.

Height, distance from sill to top of sash plate $\frac{7}{8}$ in. Packed with screws.

Specify number, size and finish. See pages 1 and 2.




Transom Lifters

WITH AUTOMATIC GRIP


FOR TRANSOMS CENTER HUNG OPENING IN OR OUT; TOP HUNG OPENING IN




Center Hung, Opening In



Automatic Grip



Top Hung, Opening In



Center Hung, Opening Out

No.	Rod Dia. Inches	Material and Finish	Grip Plate Width Inches	Length (Weight Each)			
				3 ft.	4 ft.	5 ft.	6 ft.
083	1/4	Wrought Steel	1	1 lb.	1 1/8 lbs.	1 3/8 lbs.	3 1/4 lbs.
084	5/16	Plated	1	1 3/8 lbs.	1 5/8 lbs.	2 1/8 lbs.	
085	3/8	Plated	1 3/2		2 1/2 lbs.	2 3/4 lbs.	

For size of transom, detail of brackets etc. see following page.


Packed with screws.

Specify number, size and finish. See pages 1 and 2.


Transom Lifters

DETAILS OF NO. 083, 084 AND 085 SERIES


79



083 TO 085
HINGED AT TOP
BOTTOM OPENS IN
APPROX. 45°
PUSH UP




083 TO 085
HUNG ON CENTERS
TOP OPENS IN
APPROX. 60°
PULL DOWN



083 TO 085
HUNG ON CENTERS
BOTTOM OPENS IN
APPROX. 60°
PUSH UP

MEASUREMENTS OF REGULAR TRANSOM LIFTERS														SIZE OF TRANSOM	
NO.	WIDTH OF GRIP	ROD DIA.	A	B	C	D	E	F	G	H	J	K			
083	15/16	1/4	3 3/4	1/8	3	13 3/8	5 1/8	5 1/4	6 1/4	6 5/8	9 1/8	3 3/8		10	LIGHT TRANSOMS
								4 5/8	7	7 1/8	10 1/8	4 1/8		12	
								3 3/4	7 7/8	8 1/8	11 1/8	5 1/8		14	
								2 3/4	8 3/4	9 1/8	12 1/8	6 1/8		16	
								1 3/4	9 3/4	10 1/8	13 1/8	7 1/8		18	
084	15/16	5/16	3 3/4	1/8	6	13 3/8	5 3/8	5 1/8	7 3/4	8 1/8	14 1/8	2 1/8		16	MEDIUM TRANSOMS
								5	8 5/8	9 1/8	15 1/8	3 1/8		18	
								4 1/8	9 1/2	10 1/8	16 1/8	4 1/8		20	
								3 1/4	10 3/8	11 1/8	17 1/8	5 1/8		22	
								1 3/4	11 7/8	12 7/8	18 7/8	6 7/8		24	
085	1	3/8	5 1/8	1/8	8	18 1/8	7 3/4	8	10 1/2	12 1/8	20 1/8	4 1/8		22	HEAVY TRANSOMS
								6 3/4	11 1/8	13 1/8	21 1/8	5 1/8		24	
								6	12 5/8	14 1/8	22 1/8	6 1/8		26	
								5 1/8	13 1/2	15 1/8	23 1/8	7 1/8		28	
								4 1/8	14 1/2	16 1/8	24 1/8	8 1/8		30	
								3 1/8	15 1/2	17 1/8	25 1/8	9 1/8		32	
								2 1/8	16 1/2	18 1/8	26 1/8	10 1/8		34	
								1/2	18 1/8	19 1/8	27 1/8	11 1/8		36	



REGULAR TRANSOM BRACKETS

For intermediate size transoms use dimensions of nearest size transom.

Special brackets furnished to order except on 083 series—state recess and offset.


All dimensions except length of rod are given in inches.




Transom Lifters

WITH AUTOMATIC GRIP


FOR TRANSOMS CENTER HUNG OPENING IN OR OUT; TOP AND BOTTOM OPENING IN




Bottom Hung, Opening In




Top Hung, Opening In



Center Hung, Opening In



Automatic Grip



Center Hung, Opening Out

No.	Rod Dia. Inches	Material and Finish	Grip Plate Width Inches	Length (Weight Each)			
				3 ft.	4 ft.	5 ft.	6 ft.
093	3/4	Wrought Steel	1	1 1/8 lbs.	1 1/4 lbs.	2 1/8 lbs.	
094	5/16	Plated	1	1 1/2 lbs.	1 3/4 lbs.	2 1/8 lbs.	
095	3/8	Plated	1 3/32		2 3/4 lbs.	3 1/8 lbs.	3 5/8 lbs.


For size of transom, detail of brackets, etc. see following page.

Packed with screws.


Specify number, size and finish. See pages 1 and 2.

Transom Lifters

DETAILS OF NO. 093, 094 AND 095 SERIES



REGULAR TRANSOM BRACKETS



093 TO 095

HINGED AT BOTTOM
TOP OPENS IN
APPROX. 45°
PULL DOWN

MEASUREMENTS OF REGULAR TRANSOM LIFTERS									
NO.	WIDTH OF GRIP	ROD DIA.	SIZE OF TRANSOM	A	B	S	T	U	
093	15/16	1/4	10 TO 18	3 3/4	1/8	6	13 1/4	12 1/4	LIGHT TRANSOMS
094	15/16	5/16	16 TO 24	3 3/4	1/8	9	18 5/8	17 3/4	MEDIUM TRANSOMS
095	1	3/8	22 TO 30	5 1/8	1/8	12	24 1/2	23 5/8	HEAVY TRANSOMS

Special brackets furnished to order except on 093 series. State recess and offset.
All dimensions except length of rod are given in inches.

Length—To determine the proper length of a Transom Lifter, deduct 5 feet from the distance between the floor and the center of Transom.

Offset—The distance from center of Transom Rod in position to edge of Transom Bracket.

Recess—The distance from face of door casing to face of Transom.

Clearance—The distance from back of rod in position to face of door casing.

Width of sash bracket base is the measurement required on face of Transom Rail for attaching bracket.

Width of rod base is the measurement required on face of door casing for attaching rod guides and grip boxes.

TABLE GIVING MEASUREMENTS OF REGULAR TRANSOM LIFTERS

Number	Offset Inches	Recess Inches	Width of Sash Bracket Base Ins.	Max. Width of Grip Base Ins.	Clearance Inches
083	1 1/4	Flush to 1 in.	3/4	15/16	1/8
084	1 1/4	Flush to 1 in.	3/4	15/16	1/8
085	1 1/8	Flush to 1 1/2 in.	1 1/2	1	1/8
093	1 1/4	Flush to 1 in.	3/4	15/16	1/8
094	1 1/4	Flush to 1 in.	3/4	15/16	1/8
095	1 1/8	Flush to 1 1/2 in.	1 1/2	1	1/8

Orders for Transom Lifters requiring "Offset," "Recess," "Clearance," Width of Sash Bracket Base and Width of Grip Base, other than the regular distance, should give these measurements.

If any mouldings or projections stand in the path of the Transom Lifter, a sketch showing position and projection of such obstructions will be necessary for making special guides, or risers and grip boxes.

Limitations—When furnished with brackets to give special offset and recess, either one or both, the total to offset and recess combined, must be on:

Nos. 084 and 094 series, 10 inches or less.

Nos. 085 and 095 series, 13 inches or less.

Nos. 083 and 093 series, cannot be furnished with special reach and recess.



Concealed Transom Adjuster

POSITIVE GRIP

Reversible

45° OPENING



By means of the exclusive CORBIN Friction-applying method, friction is obtained against all three inner surfaces of the track. An accessible adjusting screw regulates the amount of holding friction. An encased shock absorber, comprising a resilient rubber bumper in connection with a spring, limits the degree of transom opening.

The No. 915 Transom Adjuster is designed for heavy duty, two Adjusters being used with each transom. It is identical in construction with the No. 820 Concealed Friction Door Holder, the extruded brass track being $\frac{7}{8}$ in. x $\frac{3}{4}$ in. with $\frac{1}{16}$ in. walls.



Triple Grip Friction Slide
Nos. 910, 915

LIGHT WEIGHT TYPE

No.	Height of Transom	Material	Dimensions	
			Extruded Brass Track	Jamb Bracket
910A	8 to 9½ in. Inclusive	Extruded Brass	¾ in. wide ½ in. deep walls ⅛ in. thick	2¼ x ¾ in.
910B	10 to 11½ in. Inclusive	Extruded Brass		
910C	12 to 13½ in. Inclusive	Extruded Brass		
910D	14 to 17½ in. Inclusive	Extruded Brass		
910E	18 to 23½ in. Inclusive	Extruded Brass		
910F	24 to 29½ in. Inclusive	Extruded Brass		
910G	30 to 35½ in. Inclusive	Extruded Brass		
910H	36 to 42 in. Inclusive	Extruded Brass		

HEAVY DUTY TYPE

No.	Height of Transom	Material	Dimensions	
			Extruded Brass Track	Jamb Bracket
915C	12 to 13½ in. Inclusive	Extruded Brass	⅞ in. wide ¾ in. deep walls ⅛ in. thick	3½ x 1 in.
915D	14 to 17½ in. Inclusive	Extruded Brass		
915E	18 to 23½ in. Inclusive	Extruded Brass		
915F	24 to 29½ in. Inclusive	Extruded Brass		
915G	30 to 35½ in. Inclusive	Extruded Brass		
915H	36 to 42 in. Inclusive	Extruded Brass		

One in a box, with screws.

When ordering, specify height and thickness of transom; hinge clearance.

Specify number and finish. See pages 1 and 2.



Transom Stay



REVERSIBLE

FOR TRANSOMS OPENING OUT

Can also be applied to transoms opening in if there is no objection to applying the stay on the outside.

Friction adjustable by means of a hexagon headed bolt with a spring washer under head to take up wear.


Short arm $4\frac{1}{4}$ in. center to center. Long arm 7 in. center to center. Sash to center of bearing $1\frac{3}{16}$ in.



No.	Allows Transom to Open	Material and Finish	Sash Plate Inches	Jamb Plate Inches	Packed in a Box	Weight Dozen
01059	45°	Wrought Steel *Zinc Plated	$\frac{7}{8}$ x $2\frac{1}{2}$	1 x 2	6	8 lbs.

Packed with screws. *Also furnished in plated finishes.

Transom Eyes




197




198

No.	Size Inches	Material and Finish	Projection Inches	Packed in a Box	Weight Dozen
197	1 x $1\frac{3}{8}$	Cast Brass or Bronze Polished	$1\frac{1}{2}$	3 Dozen	$1\frac{1}{4}$ lbs.
198	$\frac{5}{8}$ x $1\frac{1}{2}$	Polished	$1\frac{1}{16}$	3 Dozen	$\frac{7}{8}$ lbs.

Packed with screws.



203



201, 0201

Transom Chains

No.	Length Inches	Material and Finish	Plates Inches	Sash Chain No.	Packed in a Box	Weight Dozen
203	10	Cast Brass or Bronze Polished	$1\frac{3}{4}$ x 1	40	12	$2\frac{1}{8}$ lbs.
203	12	Polished	$1\frac{3}{4}$ x 1	40	12	$2\frac{3}{8}$ lbs.
203	15	Polished	$1\frac{3}{4}$ x 1	40	12	$2\frac{3}{4}$ lbs.
201	10	Wrought Brass or Bronze Polished	$1\frac{3}{8}$ x $\frac{5}{8}$	40	12	$1\frac{5}{8}$ lbs.
201	12	Polished	$1\frac{3}{8}$ x $\frac{5}{8}$	40	12	$1\frac{7}{8}$ lbs.
0201	10	Wrought Steel Plated	$1\frac{3}{8}$ x $\frac{5}{8}$	80	12	$1\frac{1}{2}$ lbs.
0201	12	Plated	$1\frac{3}{8}$ x $\frac{5}{8}$	80	12	$1\frac{7}{8}$ lbs.

Packed with screws.
Can be furnished with spring snap when so ordered at additional charge.

Specify number, size and finish. See pages 1 and 2.

Friction Catches




E03234

No.	Catch Inches	Material and Finish Wrought Steel		Strike Inches	Packed in a Box	Weight Dozen
		Catch	Strike			
E03234	1 1/4 x 3/8	Nickel Plated	Nickel Plated	3/4 x 1 1/8	3 Dozen	8 oz.

Packed with screws.


Projection Adjustable



3236 to 3239

No.	Length Inches	Material and Finish	Diam- eter Inches	Adjust- ment Inches	Strike Inches	Packed in a Box	Weight Dozen
		All Brass					
3236	3/8	Steel Ball Center	1/4	1/8	5/16 x 1 3/16	3 Doz.	1 1/2 oz.
3237	1/2	Steel Ball Center	3/8	1/4	5/8 x 1 1/8	3 Doz.	4 3/4 oz.
3238	3/4	Steel Ball Center	3/8	1/4	5/8 x 1 1/8	3 Doz.	5 oz.
3239	1	Steel Ball Center	5/8	3/8	3/4 x 1 11/16	1 Doz.	1 lb.

Packed with screws.



3232

No.	Size Inches	Material and Finish	Strike Inches	Packed in a Box	Weight Dozen
3232	2 3/8 x 3/4	Wrought Brass Polished	2 3/8 x 5/8	3 Dozen	14 oz.

Packed with screws.

Elbow Catch

ELBOW CATCH




3222-T03222

No.	Plate, Inches	Material and Finish	Packed in a Box	Weight Dozen
3222 T3222	5/8 x 1 1/4 5/8 x 1 1/4	Cast Brass or Bronze Polished Unpolished	3 Dozen 3 Dozen	1 lb. 1 lb.
T03222 O3222	5/8 x 1 1/4 5/8 x 1 1/4	Cast Iron Japanned Plated	3 Dozen 3 Dozen	1 lb. 1 lb.

Packed with screws, excepting J03222.

Show Case Catch



3220

No.	Size Inches	Material and Finish	Strike Inches	Packed in a Box	Weight Dozen
3220	1 1/4 x 2	Cast Brass or Bronze Polished	1 1/4 x 1/2	1 Dozen	1 1/2 lbs.

Packed with screws.

Specify number, size and finish. See pages 1 and 2.



Secret Gate Catch


85

Rev. 6-1-57

REVERSIBLE

FOR SINGLE ACTING GATES


Operated by finger operating lever in bottom of case



3213, 03213


No.	Case Size Inches	Material and Finish	Strike Inches	Packed in a Box	Weight Dozen
3213	2 x 2½	Cast Brass or Bronze Polished	2 x ¾	6	7⅞ lbs.
03213	2 x 2½	Cast Iron Polished, Plated	2 x ¾	6	8⅞ lbs.

Packed with screws.



3038


Cupboard Turns



03045


No.	Case Size Inches	Material and Finish	Strike Inches	Packed in a Box	Weight Dozen
3038	2⅜ x 1½	Cast Brass or Bronze Polished	2⅜ x ⅝	12	4½ lbs.
03045	1⅝ x 2⅜	Wrought Steel Plated	1⅝ x ½	12	1¾ lbs.

Packed with screws.



03253

Cupboard Catches



03259

No.	Case Size Inches	Material and Finish	Strike Inches	Packed in a Box	Weight Dozen
03253	1⅝ x 1½	Wrought Steel Plated	1⅝ x ⅞	12	¾ lb.
03259	1⅝ x 1¾	Plated	1⅝ x ⅞	12	15 oz.

Packed with screws.


Specify number and finish. See pages 1 and 2.




86

Rev. 6-1-57


Transom Catches



3273, T3273



3275, T03275



3277, 03277

No.	Case Size Inches	Material and Finish	Strike Size Inches	Packed in a Box	Weight Dozen
3273	$1\frac{1}{8} \times 2\frac{7}{16}$	Cast Brass or Bronze			
T3273	$1\frac{1}{8} \times 2\frac{7}{16}$	Polished	$2\frac{1}{8} \times 1\frac{13}{16}$	12	3 $\frac{3}{4}$ lbs.
3275	$1\frac{3}{8} \times 2\frac{1}{4}$	Roll Polish	$2\frac{1}{8} \times 1\frac{13}{16}$	12	3 $\frac{3}{4}$ lbs.
		Polished	$1\frac{13}{16} \times 1\frac{3}{4}$	12	3 $\frac{3}{16}$ lbs.
*3277	$1\frac{1}{8} \times 2\frac{1}{8}$	Wrought Brass or Bronze			
		Polished	$1\frac{13}{16} \times 1\frac{3}{4}$	12	2 $\frac{1}{4}$ lbs.
T03275	$1\frac{3}{8} \times 2\frac{1}{4}$	Cast Iron			
		Plated	$1\frac{13}{16} \times 1\frac{3}{4}$	12	3 $\frac{3}{16}$ lbs.
*03277	$1\frac{1}{8} \times 2\frac{1}{8}$	Wrought Steel			
		Plated	$1\frac{13}{16} \times 1\frac{3}{4}$	12	2 $\frac{1}{4}$ lbs.



Packed with screws.

*No. 3277 and 03277 can be furnished with reverse bevel latch when so ordered.

Box strike of type as shown, furnished with any of the above transom catches, when so ordered.



Box Strike



1144

Combination Door Fastener

FOR DOORS $1\frac{1}{8}$ " TO $1\frac{3}{4}$ " THICK

No.	Size of Plate	Description	Packed in a Box	Weight Dozen
1145	$1\frac{1}{4} \times \frac{5}{8}$	Wrought Brass Plate Brass Knurled Nut	$\frac{1}{2}$ gross	5 $\frac{1}{2}$ oz.


A quarter turn of screw allows plate to drop in line with stile allowing panel to be removed or replaced without removing screw.

Specify number and finish. See pages 1 and 2.




Screen Door Catches

87



3463-T03463

FOR DOORS
7/8 TO 1 1/8 IN.
THICK




3457-03457

Catch2 1/4 x 1 7/8 x 5/8 in.
Backset1 3/8 in.
Strike 1 3/4 x 1 3/16 in.
Projection, lever 1 5/16 in., knob 2 1/8 in.

CaseJapanned iron 2 x 2 1/8 x 2 1/2 in.
Front3 7/16 x 1 1/16 in.
Backset1 3/8 in.
Hub5/16 in.
Strike1 3/4 x 1 3/16 in.
ProjectionLever 1 5/16 in., knob 2 in.
OperationLatch bolt by knob from outside and by lever from inside. Knob and lever locked by slide stop inside

No.	For Doors Opening	Material and Finish	Escutcheon Size, Inches	Lever Inches	Knob, Dia. Inches	Packed in a Box	Weight Dozen
3463	Out	Cast Brass or Bronze Polished, with Wrought Brass or Bronze Knob and Escutcheon	3 3/4 x 1 1/2	1 5/8	1 3/4	1 set	7 1/2 lbs.
T03463	Out	Cast Iron Plated, with Wrought Steel Knob and Escutcheon	3 3/4 x 1 1/2	1 5/8	1 3/4	1 set	7 1/2 lbs.
3457	In or Out	Wrought Brass or Bronze With Cast Brass or Bronze Bolt and Lever. Polished	4 1/2 x 1 1/2	1 5/8	1 3/4	1 set	10 1/2 lbs.
03457	In or Out	Wrought Steel With Cast Iron Bolt and Lever. Plated	4 1/2 x 1 1/2	1 5/8	1 3/4	1 set	10 1/2 lbs.

Packed with screws.



2465

For Doors 7/8 to 1 1/8 in. Opening Out

Backset....1 1/4 in. for 3/8 in. stop or 7/8 in. from stop.
Projection. Knob 1 13/16 in. Lever 1 1/16 in.
Operation. .By turn of knob outside or lever inside except when knob and lever are locked by slide on inside rose. Slide can be used to lock latch in open position. Bore 13/16 in. hole through door to apply.



No.	Knob Wrought Brass or Bronze	Lever Cast Brass or Bronze	Roses Wrought Brass or Bronze	Packed in a Box	Weight Dozen
2465	1 3/4 in.	1 7/8 in.	1 3/4 x 1 3/8 in.	1	5 1/4 lbs.

Packed with screws.


Specify number and finish. See pages 1 and 2.



Coat and Hat Hooks

1232, T01232
Type of 62321210, T01210
Type of 1211, to T01212

T01239



T01217

No.	Projection Inches	Material and Finish	Base Inches	Packed in a Box	Weight Dozen
Cast Brass or Bronze					
1210	2 ⁵ / ₈	Polished	1 ⁵ / ₁₆ x 1 ¹¹ / ₁₆	2 Dozen	2 lbs.
1211	3 ⁵ / ₈	Polished	1 ⁷ / ₁₆ x 1 ¹¹ / ₁₆	2 Dozen	3 ³ / ₄ lbs.
1212	4	Polished	1 ⁷ / ₈ x 1 ⁷ / ₈	2 Dozen	5 ⁷ / ₈ lbs.
1232	3 ³ / ₈	Polished	1 ⁷ / ₈ x 1 ¹ / ₂	2 Dozen	1 ¹¹ / ₁₆ lbs.
T1232	3 ¹ / ₈	Roll Polish	1 ⁷ / ₈ x 1 ¹ / ₂	2 Dozen	1 ¹¹ / ₁₆ lbs.
Cast Iron					
T01210	2 ⁵ / ₈	Plated	1 ⁵ / ₁₆ x 1 ¹¹ / ₁₆	2 Dozen	1 ¹ / ₂ lbs.
T01211	3 ⁵ / ₈	Plated	1 ⁷ / ₁₆ x 1 ¹¹ / ₁₆	2 Dozen	3 ³ / ₄ lbs.
T01212	4	Plated	1 ⁷ / ₈ x 1 ⁷ / ₈	2 Dozen	4 ¹ / ₂ lbs.
T01217	3 ³ / ₈	Plated	1 ³ / ₄ x 2	2 Dozen	4 ¹ / ₂ lbs.
J01217	3 ³ / ₈	Japanned	1 ³ / ₄ x 2	2 Dozen	4 ¹ / ₂ lbs.
J01217 ¹ / ₂	3 ³ / ₈	Japanned	1 ³ / ₄ x 2	2 Dozen	4 ¹ / ₂ lbs.
T01232	3 ¹ / ₈	Plated	1 ⁷ / ₈ x 1 ¹ / ₂	2 Dozen	1 ¹¹ / ₁₆ lbs.
C01232	3 ¹ / ₈	Coppered	1 ⁷ / ₈ x 1 ¹ / ₂	2 Dozen	1 ¹¹ / ₁₆ lbs.
C01232 ¹ / ₂	3 ¹ / ₈	Coppered	1 ⁷ / ₈ x 1 ¹ / ₂	2 Dozen	1 ¹¹ / ₁₆ lbs.
T01239	3	Plated	1 ⁷ / ₈ x 1 ¹ / ₂	2 Dozen	1 ¹¹ / ₁₆ lbs.
Aluminum					
*6232	3 ¹ / ₈	Roll Polish	1 ⁷ / ₈ x 1 ¹ / ₂	2 Dozen	5 ⁵ / ₈ lbs.

J01217¹/₂ and C01232¹/₂ less screws, all others packed with screws. *Furnished only in EA, DB, E and AL finishes.

Wordrobe Hooks




T01206



T01203

Ceiling Hooks



T01240

Pew Hooks



T01204

No.	Projection Inches	Material and Finish	Base Inches	Packed in a Box	Weight Dozen
Cast Iron					
T01203	1 ³ / ₄	Plated	1 ¹ / ₄ x 1 ³ / ₈	2 Dozen	1 ¹ / ₈ lbs.
T01204	2 ¹ / ₄	Plated	1 ¹ / ₈ x 2 ⁵ / ₈	2 Dozen	3 ³ / ₁₆ lbs.
T01206	1 ³ / ₄	Plated	1 ³ / ₈ x 1 ¹ / ₄	2 Dozen	1 ¹¹ / ₁₆ lbs.
T01240	2 ¹ / ₄	Plated	3 ³ / ₄ x 1 ³ / ₁₆	1 Dozen	1 ⁹ / ₁₆ lbs.

Packed with screws.

Specify number and finish. See pages 1 and 2.

Closet Bars

89




1235 01235
Wall to Wall Type

No. **E1235 Wrought Brass, Nickel Plated**
No. **E01235 Wrought Steel, Nickel Plated**

Length Inches	Extends To	Wall Base	Bars Diameter	Packed in a Box	Weight Dozen
18	30 in.	2 1/8 in. Dia.	1 in. & 1 1/16 in.	6	16 1/2 lbs.
30	48 in.	2 1/8 in. Dia.	1 in. & 1 1/16 in.	6	28 1/4 lbs.
48	72 in.	2 1/8 in. Dia.	1 in. & 1 1/16 in.	6	40 lbs.
72	120 in.	2 1/8 in. Dia.	1 in. & 1 1/16 in.	6	60 lbs.

Packed with screws.



1235, 01235
View applied




1236, 01236
Wall to shelf type. Shelf to center of bar 2 1/16 in.

No. **E1236 Wrought Brass, Nickel Plated**
No. **E01236 Wrought Steel, Nickel Plated**

Length Inches	Extends To	Wall Base	Shelf Bracket Inches	Bars Diameter	Packed in a Box	Weight Dozen
8	12 in.	2 1/8 in. Dia.	3 1/2 x 1 7/8 x 1	1 in. & 1 1/16 in.	6	11 1/2 lbs.
12	18 in.	2 1/8 in. Dia.	3 1/2 x 1 7/8 x 1	1 in. & 1 1/16 in.	6	14 lbs.
18	30 in.	2 1/8 in. Dia.	3 1/2 x 1 7/8 x 1	1 in. & 1 1/16 in.	6	18 lbs.

Packed with screws.



1236, 01236
View applied



**1235C,
01235C**


CENTER SUPPORTING BRACKET

For use as a center support for long bars mounted under a shelf, when so desired.

Size 3 1/2 x 1 7/8 x 1 in.

Shelf to center of bar 2 1/16 in.

No. **E1235C Wrought Brass, Nickel Plated**
No. **E01235C Wrought Steel, Nickel Plated**



1235C, 01235C

View applied to center of 1235 type bar

Steel bars made from butt jointed steel tubing. Brass bars made from seamless brass tubing.

Closet Bars are furnished nickel plated finish only.

Specify number and size.



Drawer Pulls



1344



1355




1345



1357



1346



01366



1358



4382



4383

No.	Overall Size Inches	Material and Finish	Cent. to Cent. of Screws Inches	Projection Inches	Clearance Inches	Packed in a Box	Weight Dozen
*1344	1 ¹¹ / ₁₆ x 4 ¹ / ₄	Cast Brass or Bronze					
*1345	1 ¹¹ / ₁₆ x 4 ¹ / ₄	Polished	3 ¹ / ₂	1	3 ³ / ₄	12	2 ¹ / ₁₆ lbs.
*1346	1 ¹¹ / ₁₆ x 3 ⁵ / ₈	Polished	3 ⁷ / ₁₆	1	3 ³ / ₄	12	1 ¹¹ / ₁₆ lbs.
1355	1 ¹ / ₁₆ x 4 ¹ / ₄	Polished	3 ¹ / ₄	1 ¹¹ / ₁₆	5 ³ / ₈	12	1 ¹¹ / ₁₆ lbs.
*1357	7 ⁷ / ₈ x 4 ¹ / ₈	Polished	1 ³ / ₁₆	7 ⁷ / ₈	12	2 ¹ / ₁₆ lbs.
*1358	1 ¹¹ / ₁₆ x 4 ¹¹ / ₁₆	Polished	3 ¹ / ₄	1 ⁵ / ₁₆	7 ⁷ / ₈	12	3 lbs.
			3 ¹ / ₂	1	12	2 ¹¹ / ₁₆ lbs.
01366	1 ¹ / ₂ x 3 ¹ / ₂	Wrought Steel Plated	6 Dozen	5 ³ / ₈ lb.
		Die Cast					
†4382	4	Roll Polish	3	1 ⁵ / ₁₆	1 ¹ / ₁₆	12	2 ⁵ / ₈ lbs.
†4383	5	Roll Polish	3 ¹ / ₂	1 ¹¹ / ₁₆	3 ³ / ₄	12	3 ³ / ₈ lbs.

{Nos. 4382 and 4383 furnished only in EA, DB, E and CR finishes.

*FASTEN WITH MACHINE SCREWS FROM THE INSIDE

Packed with screws.


Specify number and finish. See pages 1 and 2.

Drawer Knobs


FASTEN WITH MACHINE SCREW FROM THE INSIDE




2531



2537



2538



4544

No.	Diameter Inches	Material and Finish	Projection Inches	Packed in a Box	Weight Dozen
2531	1	Cast Brass or Bronze Polished	1	12	2 lbs.
2531	1 1/4	Polished	1	12	2 3/4 lbs.
2537	1	Polished	7/8	12	3/4 lb.
2538	1	Polished	1 3/16	12	2 lbs.
2538	1 1/4	Polished	1 3/8	12	3 1/4 lbs.
*4544	7/8	Die Cast Roll Polish	7/8	12	5/8 lb.
*4544	1 1/8	Roll Polish	1 5/16	12	1 lb.


Packed with screws and washers for wood up to 1 1/8 in. thick.

*No. 4544 furnished only in EA, DB, E and CR finishes.

Cupboard Turn Buttons



3028



03024, 03025

03025 including strike



03023

No.	Size Inches	Material and Finish	Packed in a Box	Weight Gross
*3028	1	Cast Brass Polished	1 Gross	2 5/8 lbs.
*3028	1 1/2	Polished	1 Gross	4 1/8 lbs.
G03023	1 3/4	Cast Iron Zinc Plated	1 Gross	4 lbs.
G03023	2	Zinc Plated	1 Gross	6 lbs.
G03024	1 1/2	Zinc Plated	1 Gross	4 11/16 lbs.
*G03025	1 1/2	Zinc Plated	1 Gross	6 1/4 lbs.

*Packed with screws.

Shelf Supports

No.	Diameter of Pin, Inches	Material and Finish	Rest	Packed in a Box	Weight Gross
A712	1/4	Wrought Steel	1/2 x 3/4	12 Dozen	2 1/4 lbs.
E712	1/4	Brass Plated Nickel Plated	1/2 x 3/4	12 Dozen	2 1/4 lbs.



712


Specify number, size and finish. See pages 1 and 2.



92

Lavatory Coat Hook and Door Stop

WITH RUBBER BUMPER



1220

No.	Projection Inches	Material and Finish	Base Inches	Packed in a Box	Weight Dozen
1220	3¾	Cast Brass or Bronze Polished	1¾ in. Dia.	12	4⅞ lbs.

Packed with screws. Can be supplied with through bolts for marble.

Flush Rings




520

No.	Size Inches	Material and Finish	Plate Inches	Ring, Dia. Inches	Packed in a Box	Weight Dozen
520	1¾	Cast Brass or Bronze Polished	1⅝ x 1¼	1	3 Dozen	14 oz.


Packed with screws.

Door Bell Sets

ROTARY STROKE, TO OPERATE BY TURN



01897



70264

Bell Wrought Steel, Turns Wrought, Brass or Bronze

Set No.	Bell		Turn			Packed in a Box	Weight Set
With Wrought Brass or Bronze Turn	No.	Diameter Inches	No. Wrought Brass or Bronze	Size Inches	Design		
70211	01897	3	70264	3¼ x 1½	Portland	1 Set	7½ oz.

Packed with screws and 4 in. connecting rod. *Longer connecting rods furnished when so ordered.


Specify number and finish. See pages 1 and 2.



House Numbers



130



L118


1234567890

1234567890


No.	Height	Material and Finish
130	2 in.	Cast Brass or Bronze
130	3 in.	Polished
130	4 in.	Polished
530	4 in.	Polished
	4 in.	Hammered, HPE finish only.
L118	3 in.	Cast Aluminum, Roll Polish

Nos. 130 and 530 packed with screws. No. L118 packed with escutcheon pins.

Hand Rail Brackets



T0170
Type of 6170



T0176, T0177

No.	Base Inches	Material and Finish	Projection Base to Center of Rail	Staple Inches	Packed in a Box	Weight Dozen
T0170	3x1 $\frac{1}{4}$	Cast Iron				
T0176	2 $\frac{1}{8}$	Plated	2 $\frac{1}{2}$ in.	2 $\frac{3}{8}$ x1 $\frac{3}{16}$	12	5 $\frac{1}{4}$ lbs.
T0177	2 $\frac{1}{8}$	Plated	2 $\frac{1}{2}$ in.	12	5 lbs.
		Plated	3 $\frac{1}{2}$ in.	12	7 $\frac{1}{2}$ lbs.
*6170	3x1 $\frac{1}{16}$	Aluminum Roll Polish	2 $\frac{3}{4}$ in.	2 $\frac{3}{8}$ x1 $\frac{3}{16}$	12	3 $\frac{3}{4}$ lbs.

Packed with screws.

*Furnished only in EA, DB, E and AL finishes.

Specify number, size and finish. See pages 1 and 2.



Sash Pulleys

WITH ROUND ENDS, CAST IRON CASE



0909 To 0949

Type of Groove



Universal Groove
For cord or chain,
furnished regularly

Cut-Open View Showing Bearings



Turned Wheel
Noiseless bearing



Turned Wheel
Roller bearing

*Diameter of Wheel	Front Size, Inches
2¼ in.	5⅝ x 1⅝
2½ in.	5¾ x 1¾

No.	Material and Finish		Type	Packed in a Box
	Front	Wheel		
0909	Cast Iron	Cast Iron, Turned	Noiseless Bearing	6
0929	Plain	Cast Iron, Turned	Noiseless Bearing	6
0949	Polished, Plated	Cast Iron, Turned	Roller Bearing	6

Weight Dozen

Wheel	0909	0929	0949
2¼ in.	8⅝ lbs.	8⅝ lbs.	9¾ lbs.
2½ in.	10⅞ lbs.	10⅞ lbs.	12 lbs.

No. 0909 packed without screws, all others with screws.

*State size of wheel.

Specify number and finish. See pages 1 and 2.








CANADA

EXIT FIXTURES

RIM TYPE EXIT
FIXTURES

MULLION

EXIT FIXTURES
FOR USE WITH
MORTISE LOCKS






INDEX OF

Automatic Exit Fixtures


Item	Page
GENERAL DESCRIPTION	97
DETAILED INFORMATION AND INSTRUCTIONS FOR ORDERING..	97
HAND OF DOORS	97
TYPES OF STRIKES	115, 117
HEAVY DUTY TYPE	98, 109
PUSH LEVER TYPE	108, 109
MEDIUM WEIGHT	110, 113
RIM TYPE	98, 100
STEEL MULLION	101
CO-ORDINATING DEVICE	116
THRESHOLDS	118

Automatic Exit Fixtures


INSTRUCTIONS FOR ORDERING



Inside view of single entrance door with exit push bar



Inside view of pair of entrance doors with exit bolt and push bar



Inside view of single exit door with exit bolt

Measurements to be taken from inside of door.

SINGLE DOORS
When ordering specify

- "A" Width of door.
 "B" Width of stile. Minimum width for mortise locks $4\frac{1}{2}$ in. For vertical bolts $3\frac{1}{2}$ in. For rim fixtures $4\frac{1}{2}$ or 5 in. with mullion.
 "C" Height of door for vertical bolts.
 "D" Height of horizontal bar from floor to center of bar (38 in. unless otherwise ordered.)
 "E" Thickness of stops. (Furnished for $\frac{1}{2}$ in. stop unless otherwise ordered.)
 "F" Length of lip for rim fixtures measured from stop to end of lip. Furnished $\frac{1}{4}$ in. more than thickness of door unless otherwise specified.
 "L" Width of stop. Minimum $1\frac{1}{2}$ in. for rim fixtures.

Hand of Door—Must be right hand reverse bevel or left hand reverse bevel.

Thickness of Door.


PAIRS OF DOORS
When ordering specify

- "A" Width of each door.
 "B" Width of stile. Minimum width for mortise locks $4\frac{1}{2}$ in. For vertical bolt $3\frac{1}{2}$ in. For rim fixtures with mullion 5 in.
 "C" Height of door.
 "D" Height of door bar (38 in. unless otherwise ordered.)
 "E" Thickness of stops. (Furnished for $\frac{1}{2}$ in. stop unless otherwise ordered.)
 "F" Length of lip for rim fixtures measured from stop to end of lip. Furnished $\frac{1}{4}$ in. more than thickness of door unless otherwise specified.
 "L" Width of stop.


Hand of Door—Specify hand of active leaf (door with lock). Must be right hand reverse bevel or left hand reverse bevel.

Thickness of Door.

Is bottom strike for wood, stone, cement or metal threshold?


STRIKE FOR SINGLE DOOR
For rim fixtures

Hand of Doors



†Left Hand, Reverse Bevel.

†Hand of door with lock.



†Right Hand, Reverse Bevel.

Automatic Exit Fixtures

HEAVY DUTY RIM TYPE


FOR SINGLE DOORS

Can be used in double openings in conjunction with removable steel mullion.


CAST BRASS, BRONZE OR ALUMINUM

Lock and Exit Mechanism Factory Assembled—Applied as a Unit—No Lock to Mortise
Easy Closing—Only Six Working Parts in Case—Especially Adapted to Doors too thin for Mortise Lock
Drop Forged Arm Lever with Oilite Bearings. Drop Forged Latch Lever

*NOT REVERSIBLE



2926, 2926NT, 2927 and 2929
Left Hand Reverse Bevel shown
2926½ and 2927½ same but
with inside cylinder in case.



674
Universal
Adjustable
Strike

Cases: Heavy castings.

Active case 9¼ x 3 in.

Supporting case 5¼ x 1½ in.

Latch Bolt: Swinging type, ¾ in. throw.

Horizontal Bar: Seamless Tubing 1 in. diameter.

Horizontal bar can be furnished stainless steel or white bronze to order.

Horizontal bar can be furnished reinforced with steel tubing. To order affix **RC** to number, thus: **2926RC**.

Backset: 2½ in. for stops ½ in. thick.

2¾ in. for stops ¾ in. thick.

Strike: Universal type suits most types of installation. Adjustable to overcome shrinkage of doors.


Master Keying: Can be master keyed in sets as desired with other Corbin Cylinder Locks.

Minimum width of stile 4½ in. for door with ¾ in. stops or 5 in. when used with mullion.

Inside Operation

Latch bolt can be retracted from the inside at all times by slight pressure against horizontal bar, affording immediate exit.

Dogging Devices in both cases to lock horizontal bar in depressed position by means of dogging key, holding latch bolt in retracted position. With stainless steel helicoil inserts in cases to prevent wear and corrosion and to overcome loosening of locking screw.



Applied to Double Doors
with Mullion.
See Mullions, page 101



75385¼NT
Outside trim for
No. 2926NT



1519½ x 74130
Outside trim for
Nos. 2927 and 2927½




75385¼
Outside Trim for
Nos. 2926 and 2926½


For optional outside trim see page 114.




FOR DOORS USED FOR ENTRANCE AND EXIT




2926NT




2926




2926 1/2



2927



2927 1/2



2929 1/4

*NOT REVERSIBLE

OPERATION OF OUTSIDE TRIM AND LOCKING MECHANISM

No. **2926NT** Latch bolt operated by key only from outside. Pull can be used to open door when latch bolt is held retracted.

No. **2926** Latch bolt operated by key or thumb piece from outside, except when thumb piece is deadlocked by key.


No. **2926 1/2** Latch bolt operated by key or thumb piece from outside except when thumb piece has been deadlocked from the inside by master key only unless otherwise ordered.

No. **2927** Latch bolt operated by key or knob from the outside except when knob has been deadlocked by key.

No. **2927 1/2** Latch bolt operated by key or knob from the outside except when knob is deadlocked from the inside by master key only unless otherwise ordered.

No. **2929** For exit only, no outside trim or operation.

No. **2929 1/4** Latch bolt operated by key only from outside. No other outside trim.

For Doors
Used For
Exit Only

2929

No.	Material and Finish	Cylinders	2 Keys Class	Key Changes	Outside Trim Cast Brass, Bronze or Aluminum	Approximate Weight, Each
2926NT	Cast Brass or Bronze Polished	One No. 251	77	Unlimited	Door Pull 75385 1/4 NT (8 3/4 x 2 1/4 in.) Cylinder Collar 75314 (2 1/4 x 2 1/4 in.)	14 lbs.
2926	Polished	One No. 251	77	Unlimited	Door Handle 75385 1/4 (8 3/4 x 2 1/4 in.)	14 1/2 lbs.
2926 1/2	Polished	{ One No. 251 One Spec.	77	Unlimited	75385 1/4 (8 3/4 x 2 1/4 in.) 75314 (2 1/4 x 2 1/4 in.)	15 lbs.
2927	Polished	One No. 251	77	Unlimited	Knob 1519 1/2 (2 1/4 in. Dia.)	13 1/2 lbs.
2927 1/2	Polished	{ One No. 251 One Spec.	77	Unlimited	1519 1/2 (2 1/4 in. Dia.)	14 lbs.
2929	Polished	None			Escutcheon 74130 (8 x 2 1/2 in.)	12 1/2 lbs.
2929 1/4	Polished	One No. 251	77	Unlimited	None	12 3/4 lbs.

Stock Size: Can be furnished stock size for doors 3 ft. 6 in. wide with cross bar loose so the bar can be cut down on the job for doors under 3 ft. 6 in. in width. In ordering suffix **S** to number, thus **2926NT-S**.

Unpolished: Brass exit fixtures can be supplied unpolished in **TL** (Sprayed Brass Lacquer). **AL** (Aluminum Bronze) or **TKF** (Dead Black Lacquer). Specify finish for outside trim, example: **EAxTL2926NT**.

Packed with screws. Can be furnished with sex bolts to fasten through door, when so ordered.

*In ordering specify hand and thickness of door, width of door, thickness of stops, etc. For instructions for ordering, see page 97.

Specify number and finish. See pages 1 and 2.



100

Rev. 6-1-57

Automatic Exit Fixtures

HEAVY DUTY RIM TYPE

Can be used in double openings in conjunction with removable steel mullion.


FOR SINGLE DOORS

CAST BRASS, BRONZE OR ALUMINUM

Lock and Exit Mechanism Factory Assembled—Applied as a Unit—No Lock to Mortise
Easy Closing—Only Three Working Parts in Case—Especially Adapted to Doors too thin for Mortise Lock
Drop Forged Arm Lever with Oilite Bearings. Drop Forged Latch Lever




75385 1/4 NT
Outside Trim for
No. 2826 NT



Applied to Double Doors
with Mullion
See Mullions, page 101



674
Universal
Adjustable
Strike




2826 NT, 2829
Left Hand Reverse Bevel
shown.


*NOT REVERSIBLE

FOR ENTRANCE AND EXIT


For Doors
Used For
Exit Only



2826 NT



2829 1/4



2829

Outside Operation

No. 2826 NT: Latch Bolt operated by key only from outside. The pull can be used to open door when latch bolt is secured in retracted position by pushing in latch bolt with finger or retracting by horizontal bar and turning key towards back of lock while in this position.

No. 2829: No operation from outside.

No. 2829 1/4: Latch bolt operated by key only from outside.

Cases: Heavy castings

Active case 7 1/16 x 2 3/4 in.

Supporting case 5 1/16 x 1 13/16 in.

Latch Bolt: Swinging type, 3/4 in. throw.

†Horizontal Bar: 1 in. diameter seamless tubing.

Backset: 2 1/2 in. for 1/2 in. stops.

2 5/8 in. for 5/8 in. stops.

Strike: Universal type to suit most types of installations. Adjustable to overcome shrinkage of doors.

Master Keying: Can be master keyed in sets as desired with other Corbin Cylinder Locks.

Inside Operations: Operated from inside at all times by a slight push on cross bar affording immediate exit.

Dogging Device in both cases to lock cross bar in depressed position by means of dogging key, holding latch bolt in retracted position. With stainless steel helicoil inserts in cases to prevent wear and corrosion and to overcome loosening of locking screw.

Minimum width of style 4 1/2 in. for doors with 5/8 in. stops, 5 in. with removable mullion No. 2565.

No.	Material and Finish	Cylinders	2 Keys Class	Key Changes	Outside Trim Cast Brass, Bronze or Aluminum	Approximate Weight, Each
2826 NT	Cast Brass or Bronze	One No. 251	77	Unlimited	Door Pull 75385 1/4 NT (8 3/4 x 2 1/4 in.)	12 lbs.
2829	Polished	None	77	Unlimited	Cylinder Collar 75314 (2 1/4 x 2 1/4 in.)	10 1/2 lbs.
2829 1/4	Polished	One No. 251	77	Unlimited	None	10 3/4 lbs.

†Horizontal bar can be furnished stainless steel or white bronze to order.

Horizontal bars can be furnished with steel reinforcing tubing. To order affix RC to number thus 2826 NT-RC.

Stock Size: Can be furnished stock size for doors 3 ft. 6 in. wide with cross bar loose so the bar can be cut down on the job for doors under 3 ft. 6 in. In ordering, suffix S to number, thus: 2826 NT-S.

Unpolished: Brass Exit fixtures can be supplied unpolished in TL (Sprayed Brass Lacquer) AL (Aluminum Bronze) or TKF (Dead Black Lacquer). Specify finish for outside trim, example: EAXTL 2826 NT.

Packed with screws. Can be furnished with sex bolts to fasten through door, when so ordered.

*In ordering specify hand and thickness of door, width of door, thickness of stop, etc. For instructions for ordering, see page 97.

Specify number and finish. See pages 1 and 2.




Removable Steel Mullion

101

Rev. 6-1-57

Used to Adapt a Double Door Opening to Two Single Door Rim Exit Fixtures.
Easily and Quickly Removed when a Full Double Door Opening is Desired.



For use only with rim type exit fixtures, all numbers.

No.	Mullion, Size Inches	Material and Finish Mullion, Top and Bottom Plates	Strikes	Top Plate, Size Inches	Bottom Plate, Size Inches
2565	2 3/8 x 2 3/8	Wrought Steel Prime Coat	Cast Brass or Bronze	2 3/8 x 3 3/4	2 3/4 x 4

Mullions are regularly furnished cut and reinforced to receive the No. 674 Universal Adjustable Strike which is packed with the rim exit fixtures.

Regularly furnished stock size for doors 7 ft. 6 in. high which can be cut down at top, on the job, for door under 7 ft. 6 in. in height. Can be furnished 10 ft. high, to order.




Automatic Exit Fixtures

HEAVY DUTY EXIT PUSH BARS WITH ROTARY ACTION AND MORTISE LOCKS

CAST BRASS, BRONZE OR ALUMINUM

*NOT REVERSIBLE



126, 126NT, 127, 129

Left Hand Reverse Bevel shown
126½ and 127½ same except
that case is cut for inside
cylinder

Cases Heavy castings
Active case 8¾ x 2¼ in.
Supporting case 5¼ x 2¼ in.

Arm Levers Drop forged with oilite bearings.

Horizontal Bar 1 in. seamless tubing.

Bars are secured to lever arms with socket type set screws covered by collar. See page 117.

Horizontal bars can also be furnished stainless steel or white bronze, to order. Bars can be furnished with steel reinforcing, to order. Affix RC to Number, thus: 126RC.

Minimum width of stile 4½ in.

Inside Operation

The lock is operated from the inside at all times by a slight push or pull on the double acting horizontal bar affording immediate exit.

Dogging Devices

In both cases to lock horizontal bar in depressed position by means of dogging key holding latch bolt of lock in retracted position.

OUTSIDE TRIM



75385
Outside Trim
For Sets
126, 126½




1519½ x 74130
Outside Trim
For Sets
127, 127½




75385NT
Outside Trim
For Set
126NT

For optional outside trim see page 114.


FOR DODRS USED FOR ENTRANCE AND EXIT




126




126½



126NT



127



127½

FOR SINGLE DOORS

Also used on active leaf of pair of doors
See pages 106, 107

OPERATION OF OUTSIDE TRIM AND LOCKING MECHANISM

No. 126 latch bolt operated by key or thumb piece outside except when thumb piece is locked by key. Latch bolt held retracted by pushing in by finger or retracting by horizontal bar and turning key towards back of lock while in this position.

No. 126½ latch bolt operated by key or thumb piece from outside except when thumb piece is locked by master key from inside.


No. 126NT latch bolt operated by key only from outside. Latch bolt held retracted by pushing in by finger or retracting by horizontal bar and turning key towards back of lock while in this position.

No. 127 latch bolt operated by key or knob outside, except when knob is locked by key. Latch bolt held retracted by pushing in by finger or retracting by horizontal bar and turning key towards back of lock while in this position.

No. 127½ latch bolt operated by key or knob outside except when knob is locked by master key from inside.

No. 129 No outside trim or operation.

For Doors
Used For
Exit Only



129

*Not reversible

No.	LOCK			OUTSIDE TRIM		Approx. Weight Each
	No.	Cyls.	See Page	Cast Brass, Bronze or Aluminum		
126 126½	5785	1	170	Handle 75385 (8¾ x 2¼ in.)	Cyl. Collar 75314 (2¼ x 2¼ in.)	12 lbs.
	5784	2	170	75385 (8¾ x 2¼ in.)	75314 (2¼ x 2¼ in.)	12 lbs.
126NT	5785	1	170	Pull 75385NT (8¾ x 2¼ in.)	75314 (2¼ x 2¼ in.)	12 lbs.
				Knob 1519½ (2¼ in. dia.)	Escutcheon 74130 (8 x 2½ in.)	11 lbs.
127 127½	5585	1	170	1519½ (2¼ in. dia.)	74130 (8 x 2½ in.)	11 lbs.
	5584	2	170	1519½ (2¼ in. dia.)	74130 (8 x 2½ in.)	11 lbs.
129	180	None	168	No Outside Trim		10 lbs.

Stock Size: Can be furnished stock size for doors 3 feet 6 inches wide. Can be fitted to doors under 3 feet 6 inches wide by cutting down horizontal bar to correct size before applying. In ordering affix **S** to number, thus: **126S**.

Unpolished: Brass Exit Fixtures can be furnished unpolished in **TL** (Sprayed Brass Lacquer) **AL** (Aluminum Bronze) or **TKF** (Dead Black Lacquer) only. In ordering specify finish for outside trim; example **EAxTL126**.

Packed with screws. Can be furnished with sex bolts to fasten through door, when so ordered.

*In ordering specify hand and thickness of door, width of door, etc. For instructions for ordering, see page 97.

Specify number and finish. See pages 1 and 2.



104

Rev. 6-1-57

Automatic Exit Fixtures

HEAVY DUTY EXIT BOLTS WITH ROTARY ACTION
CAST BRASS, BRONZE OR ALUMINUM

*Not Reversible

Case: Heavy castings.

Active case 8 $\frac{3}{8}$ x 2 $\frac{1}{4}$ in.

Supporting case 5 $\frac{1}{4}$ x 2 $\frac{1}{4}$ in.

Top and bottom cases 4 x 2 $\frac{1}{2}$ in.

Arm Levers: Drop forged with oilite bearings.


Horizontal Bar: 1 in. seamless tubing.

Vertical Bar: $\frac{1}{2}$ in. seamless tubing.

Latches: Top and bottom latches heavy cast swinging type. Bottom latch has independent action allowing top latch to remain engaged in strike even when bottom latch is forced out of strike or when bottom strike is obstructed.

Minimum width of stile 3 $\frac{1}{2}$ in.

OUTSIDE TRIM



124, 125

134, 135

For Doors Used for Entrance and Exit



134, 135 124, 125

For Doors Used For Exit Only



120


Also used on inactive leaf of pair of doors
See pages 106, 107

Inside Operation

Bolts operated from the inside at all times by a slight push or pull on double acting horizontal bar affording immediate exit.

Top and bottom bolts are held retracted while door remains open. Closing door automatically releases bolts to lock door.

Dogging device in both cases lock horizontal bar in depressed position by means of dogging key holding both top and bottom bolts in retracted position.



120

Type of
124, 125
134, 135

Outside Operation

No. 125 operated by knob from outside except when knob is locked by key.

No. 124 same as No. 125 except that knob is automatically locked when key is removed.

No. 135 operated by T Handle from outside except when T Handle is locked by key.

No. 134 same as No. 135 except that T Handle is automatically locked when key is removed.

FOR SINGLE DOORS

No.	OUTSIDE TRIM Cast Brass, Bronze or Aluminum	Approx. Weight Each
120	For exit only. No outside trim.	22 lbs.
124	Knob 1519 $\frac{1}{2}$ (2 $\frac{3}{4}$ in. dia.). Escutcheon 74130 (8 x 2 $\frac{1}{2}$ in.)	23 lbs.
125	Knob 1519 $\frac{1}{2}$ (2 $\frac{3}{4}$ in. dia.). Escutcheon 74130 (8 x 2 $\frac{1}{2}$ in.)	23 lbs.
134	Pull with T Handle 40288 (13 x 1 $\frac{1}{2}$ in.). Collar 40213 (2 $\frac{1}{4}$ x 1 $\frac{1}{2}$ in.)	24 lbs.
135	Pull with T Handle 40288 (13 x 1 $\frac{1}{2}$ in.). Collar 40213 (2 $\frac{1}{4}$ x 1 $\frac{1}{2}$ in.)	24 lbs.

FOR PAIRS OF DOORS

No.	OUTSIDE TRIM FOR ACTIVE DOOR Cast Brass, Bronze or Aluminum	Approx. Weight Per Set
120x120	For exit only. No outside trim.	40 lbs.
120x124	Knob 1519 $\frac{1}{2}$ (2 $\frac{3}{4}$ in. dia.). Escutcheon 74130 (8 x 2 $\frac{1}{2}$ in.)	41 lbs.
120x125	Knob 1519 $\frac{1}{2}$ (2 $\frac{3}{4}$ in. dia.). Escutcheon 74130 (8 x 2 $\frac{1}{2}$ in.)	41 lbs.
120x134	Pull with T Handle 40288 (13 x 1 $\frac{1}{2}$ in.). Collar 40213 (2 $\frac{1}{4}$ x 1 $\frac{1}{2}$ in.)	42 lbs.
120x135	Pull with T Handle 40288 (13 x 1 $\frac{1}{2}$ in.). Collar 40213 (2 $\frac{1}{4}$ x 1 $\frac{1}{2}$ in.)	42 lbs.

Stock Size: Can be furnished stock size for doors 7 feet 6 inches high x 3 feet 6 inches wide. Can be fitted to doors under 7 feet 6 inches high x 3 feet 6 inches wide by cutting down vertical rod and horizontal bar to the required size before applying. In ordering affix S to number, thus: 120x125S.

Unpolished: Brass Exit Fixtures can be furnished unpolished in TL (Sprayed Brass Lacquer) AL (Aluminum Bronze) or TKF (Dead Black Lacquer) only. In ordering specify finish for outside trim; example EAxTL120x125.

Packed with screws. Can be furnished with sex bolts to fasten through door, when so ordered.

*State hand and thickness of door, height of door, width of door, etc. For instructions for ordering, see page 97.

†Horizontal bar can be furnished stainless steel or white bronze, to order.

Horizontal bar can be furnished reinforced with steel tubing. To order affix RC to number, thus 120RC.

Specify number and finish. See pages 1 and 2.



Automatic Exit Fixtures

105

Rev. 6-1-57

HEAVY DUTY EXIT BOLTS WITH ROTARY ACTION AND FREE LATCHING TOP AND BOTTOM BOLTS

CAST BRASS, BRONZE OR ALUMINUM

*Not Reversible

The use of threshold is required with these bolts so that bottom latch will not drag on floor when door is open.

Cases: Heavy castings.

Active case $8\frac{3}{8}$ x $2\frac{1}{4}$ in.

Supporting case $5\frac{1}{4}$ x $2\frac{1}{4}$ in.

Top and bottom cases 4 x $2\frac{1}{8}$ in.

†Horizontal Bar: 1 in. seamless tubing.

Arm Levers: Drop forged with oilite bearings.

Vertical Rod: $\frac{1}{2}$ in. seamless tubing.

Latches: Top and bottom latches heavy cast swinging type, free acting.


Bottom latch has independent action allowing top latch to remain engaged in strike even when bottom latch is forced out of strike or when bottom strike is obstructed.



OUTSIDE TRIM



138



128

For Ooors Used for
Entrance and Exit

For Ooors
Used For
Exit Only



131, 138



121, 128



122

Minimum width of stile $3\frac{1}{2}$ in.

Inside Operation

Bolts operated from the inside at all times by a slight push or pull on double acting horizontal bar affording immediate exit.

Latch bolts remain projected when door is open unless they are secured in retracted position by locking horizontal bar in depressed position by means of dogging key operating devices in both end cases.

Dogging device in both cases lock horizontal bar in depressed position by means of dogging key holding both top and bottom bolts in retracted position.

Outside Operation

No. 128 operated by knob from outside except when knob is locked by key.

No. 121 same as 128 except that knob is automatically locked when key is removed.

No. 138 operated by T Handle from outside except when T Handle is locked by key.

No. 131 same as 138 except that T Handle is automatically locked when key is removed.

FOR SINGLE OOOORS

No.	Cyl.	OUTSIDE TRIM Cast Brass, Bronze or Aluminum	Approximate Weight Each
121		For exit only. No outside trim.	22 lbs.
122	251	Knob 1519½ (2¼ in. dia.). Escutcheon 74130 (8 x 2½ in.)	23 lbs.
128	251	Knob 1519½ (2¼ in. diam.) Escutcheon 74130 (8 x 2½ in.)	23 lbs.
131	251	Pull x T Handle 40288 (13 x 1½ in.) Collar 40213 (2¼ x 1½ in.)	24 lbs.
138	251	Pull x T Handle 40288 (13 x 1½ in.) Collar 40213 (2¼ x 1½ in.)	24 lbs.

FOR PAIRS OF OOOORS

No.	Cyl.	OUTSIDE TRIM FOR ACTIVE DOOR Cast Brass, Bronze or Aluminum	Approx. Weight Per Set
122 x 122		For exit only. No outside trim.	40 lbs.
122 x 128	251	Knob 1519½ (2¼ in. dia.). Escutcheon 74130 (8 x 2½ in.)	41 lbs.
122 x 138	251	Pull x T Handle 40288 (13 x 1½ in.) Collar 40213 (2¼ x 1½ in.)	42 lbs.

Stock Size: Can be furnished stock size for doors 7 feet 6 inches high x 3 feet 6 inches wide. Can be fitted to doors under 7 feet 6 inches high x 3 feet 6 inches wide by cutting down vertical rod and horizontal bar to the required size before applying. In ordering affix S to number, thus: 122x128S.

Unpolished: Brass Exit Fixtures can be furnished unpolished in TL (Sprayed Brass Lacquer) AL (Aluminum Bronze) or TKF (Dead Black Lacquer) only. In ordering specify finish for outside trim; example EAxTL 122x128.


Packed with screws. Can be furnished with sex bolts to fasten through door, when so ordered.

*State hand and thickness of door, height of door, width of door, etc. For instructions for ordering, see page 97.

†Horizontal bar can be furnished stainless steel or white bronze to order.

Horizontal bar can be furnished reinforced with steel tubing. To order affix RC to number, thus 122RC.

Specify number and finish. See pages 1 and 2.



122

Type of 128
and 138




106

Rev. 6-1-57

Automatic Exit Fixtures


HEAVY DUTY EXIT BOLTS WITH ROTARY ACTION — SETS FOR PAIRS OF DOORS WITH THRESHOLD
CAST BRASS, BRONZE OR ALUMINUM

*Not Reversible

Inactive
Door

122

See page 105.



Active Door

126, 126NT, 127, 129
126½, 127½ same but
with active case cut
for inside cylinder

See page 102.



Open back strikes furnished
with all locks for pairs
of doors, allowing doors to
open or close independently
of each other.

Inactive
DoorBolt
No. 120

Inside Operation

Either door operated from the inside at all times by a slight push or pull on double acting horizontal bar affording immediate exit.

Top and bottom bolts are free latching. The use of our threshold No. 2584 (see page 118) will eliminate the need for bottom strike.

Bolt No. 120 can be substituted in place of No. 122 for doors without threshold, so that top and bottom bolts will be held back when door is open and bottom bolt will not drag on floor.

Dogging device in both cases lock horizontal bar in depressed position by means of dogging key holding bolts in retracted position.

Minimum width of style 4½ in.

OUTSIDE TRIM FOR ACTIVE DOORS



75385
Outside Trim
For Sets
126, 126½



1519½ x 74130
Outside Trim
For Sets
127, 127½



75385NT
Outside Trim
For Set
126NT

For optional outside trim. See page 114.




Automatic Exit Fixtures


107

Rev. 6-1-57


ACTIVE DDDRS USED FOR ENTRANCE OR EXIT




126




126 1/2



126NT



127



127 1/2

OPERATION OF OUTSIDE TRIM AND LOCKING MECHANISM FOR ACTIVE DDORS

No. **126** latch bolt operated by key or thumb piece outside except when thumb piece is locked by key. Latch bolt held retracted by pushing in by finger or retracting by horizontal bar and turning key towards back of lock while in this position.


No. **126 1/2** latch bolt operated by key or thumb piece from outside except when thumb piece is locked by master key from inside.

No. **126NT** latch bolt operated by key only from outside. Latch bolt held retracted by pushing in by finger or retracting by horizontal bar and turning key towards back of lock while in this position.

No. **127** latch bolt operated by key or knob outside, except when knob is locked by key. Latch bolt held retracted by pushing in by finger or retracting by horizontal bar and turning key towards back of lock while in this position.

No. **127 1/2** latch bolt operated by key or knob outside, except when knob is locked by master key from inside.

No. **129** No outside trim or operation.

Active Door
Used For
Exit Only

129

SETS FOR PAIRS OF DOORS WITH THRESHOLD

No.	LOCK			OUTSIDE TRIM FOR ACTIVE DOOR Cast Brass, Bronze or Aluminum		Approx. Weight Per Set
	No.	Cyls.	See Page			
122 x 126	5785 x 606	1	170	Handle	Collar	34 lbs.
122 x 126 1/2	5784 x 606	2	170	75385 (8 3/4 x 2 1/4 in.)	75314 (2 1/4 x 2 1/4 in.)	34 lbs.
				75385 (8 3/4 x 2 1/4 in.)	75314 (2 1/4 x 2 1/4 in.)	
122 x 126NT	5785 x 606	1	170	Pull		34 lbs.
				75385NT (8 3/4 x 2 1/4 in.)	75314 (2 1/4 x 2 1/4 in.)	
122 x 127	5585 x 606	1	170	Knobs	Escutcheon	33 lbs.
122 x 127 1/2	5584 x 606	2	170	1519 1/2 (2 1/4 in. dia.)	74130 (8 x 2 1/2 in.)	33 lbs.
122 x 129	180 x 607	None	168	1519 1/2 (2 1/4 in. dia.)	74130 (8 x 2 1/2 in.)	30 lbs.
				For Exit Only	No Outside Trim	

Stock Size: Can be furnished stock size for doors 7 feet 6 inches high by 3 feet 6 inches wide. Can be fitted to doors under 7 feet 6 inches by 3 feet 6 inches by cutting down vertical rod and horizontal bars to required size before applying. In ordering affix **S** to number, thus: **122 x 126S**.

Unpolished: Brass Exit Fixtures can be furnished unpolished in **TL** (Sprayed Brass Lacquer) **AL** (Aluminum Bronze) or **TKF** (Dead Black Lacquer) only. Specify finish for outside trim: example **EAxTL122 x 126**.

Packed with screws. Can be furnished with sex bolts to fasten through door when so ordered.

*State hand and thickness of door, height of door, width of door, etc. For instructions for ordering, see page 97.

Specify number and finish. See pages 1 and 2.



108

Rev. 6-1-57

Automatic Exit Fixtures

HEAVY DUTY PUSH LEVER TYPE WITH ROTARY ACTION

CAST BRASS, BRONZE OR ALUMINUM

*Not Reversible



Cases: Heavy castings 8 3/4 x 2 1/4 in.

Push Lever: Heavy casting with oilite bearing.

Operation: The lock is operated from the inside at all times by a slight push or pull on the double acting push lever affording immediate exit.

Dogging Devices: In case to lock push lever in depressed position by means of dogging key holding latch bolt of lock in retracted position.

Minimum width of stile 4 1/2 in.

For Doors Used for Entrance and Exit



75385


For sets 146 and 146 1/2

OUTSIDE TRIM




1519 1/2 x 74130
For sets 147 and 147 1/2


146, 147, 149
146 1/2 and 147 1/2 same except that case is cut for inside cylinder.




146



146 1/2



147



147 1/2

No. 146 latch bolt operated by key or thumb piece outside except when thumb piece is locked by key. Latch bolt held retracted by pushing in by finger or retracting by horizontal bar and turning key towards back of lock while in this position.


No. 146 1/2 latch bolt operated by key or thumb piece from outside except when thumb piece is locked by master key from inside.

No. 147 latch bolt operated by key or knob outside, except when knob is locked by key. Latch bolt held retracted by pushing in by finger or retracting by horizontal bar and turning key towards back of lock while in this position.

No. 147 1/2 latch bolt operated by key or knob outside, except when knob is locked by master key from inside.

No. 149 No outside trim or operation.

For Doors
Used For
Exit Only



149

Sets for single doors used for entrance or exit and for active leaf of pair of doors.

No.	LOCK			OUTSIDE TRIM		Approx. Weight Each
	No.	Cyls.	See Page	Cast Brass, Bronze or Aluminum		
				Handle	Cyl. Collar	
146	5785	1	170	75385 (8¾ x 2¼ in.)	75314 (2¼ x 2¼ in.)	9 lbs.
146½	5784	2	170	75385 (8¾ x 2¼ in.)	75314 (2¼ x 2¼ in.)	9 lbs.
				Knob	Escutcheon	
147	5585	1	170	1519½ (2¼ in. dia.)	74130 (8 x 2½ in.)	8 lbs.
147½	5584	2	170	1519½ (2¼ in. dia.)	74130 (8 x 2½ in.)	8 lbs.
149	180	None	168	For exit only. No outside Trim.		7 lbs.

Unpolished: Brass Exit Fixtures can be furnished unpolished in TL (Sprayed Brass Lacquer) AL (Aluminum Bronze) or TKF (Dead Black Lacquer) only. Specify finish for outside trim, example: EAxTL146.

When ordered in sets for pairs of doors (as 140x146), lock for active door will be furnished with open back strike allowing doors to open or close independently of each other.

Packed with screws. Can be furnished with sex bolts to fasten through door, when so ordered.

*State hand and thickness of door. For instructions for ordering, see page 97.

Specify number and finish. See pages 1 and 2.



Automatic Exit Fixtures

HEAVY DUTY PUSH LEVER TYPE BOLTS WITH ROTARY ACTION

CAST BRASS, BRONZE OR ALUMINUM

109

Rev. 6-1-57



140



142

No. 140

Inside Operation

Bolts operated from the inside at all times by a slight push or pull on double acting push lever affording immediate exit.

Top and bottom bolts are held retracted while door remains open. Closing door automatically releases bolts to lock door.

Dogging device in both cases lock push lever in depressed position by means of dogging key holding both top and bottom bolts in retracted position.

Case: Heavy castings.

Active case $8\frac{5}{8}$ x $2\frac{1}{4}$ in.

Top and bottom cases 4 x $2\frac{1}{8}$ in.

Push Lever: Heavy casting with oilite bearing.

Vertical Bar: $\frac{1}{2}$ in. seamless tubing.

Latches: Top and bottom latches heavy swinging type.

Bottom latch has independent action allowing top latch to remain engaged in strike even when bottom latch is forced out of strike or when bottom strike is obstructed.


Minimum width of stile $3\frac{1}{2}$ in.

No. 142

Inside Operation

Bolts operated from the inside at all times by a slight push or pull on double acting push lever affording immediate exit.

Latch bolts remain projected when door is open unless they are secured in retracted position by locking push lever in depressed position by means of dogging key operating devices in both end cases.



140

142 same but with free-acting top and bottom bolts and top and bottom strikes like No. 122, page 105

Vertical bolts for doors used for exit only and for inactive leaf of pair of doors.

No.	Description	Approx. Weight Each
140	For exit only.	18 lbs.
142	For exit only. No outside trim. No outside trim—Free acting latches.	18 lbs.

Stock Size: Can be furnished stock size for doors 7 feet 6 inches high. Can be fitted to doors under 7 feet 6 inches by cutting down vertical rod to required size before applying. In ordering affix **S** to number, thus: **140S**.

Unpolished: Brass Exit Fixtures can be furnished unpolished in **TL** (Sprayed Brass Lacquer) **AL** (Aluminum Bronze) or **TKF** (Dead Black Lacquer) only. Specify finish for outside trim, example: **EAXTL 140**.

Packed with screws. Can be furnished with sex bolts to fasten through door, when so ordered.

State height of door, etc. For instructions for ordering, see page 97.

Specify number and finish. See pages 1 and 2.



110


Rev. 6-1-57

Automatic Exit Fixtures

EXIT PUSH BARS WITH MORTISE LOCKS

CAST BRASS OR BRONZE, POLISHED

OUTSIDE TRIM



76, 77, 76½, 77½, 78, 79
Left Hand Reverse Bevel Shown
76½, 77½ same except that case
is cut for inside cylinder.

FOR SINGLE DOORS

Also used on Active Leaf
of Pair of Doors
See page 112

Cases..... Active case
8½x2½ in.
Supporting case
8½x2½ in.

†Horizontal Bar... 1 in. dia. seamless
tubing.

*Dogging Devices. In cases to lock
cross bar in de-
pressed position.

Minimum Width of Stile 4½ in.




75385 Outside Trim
For Sets
76, 77, 76½, 77½
75385NT Outside Trim
For Sets
76½, 77½

OPERATION

A slight pressure on horizontal bar releases door instantly


FOR ENTRANCE AND EXIT

EXIT ONLY




76, 77

By thumb piece of handle
from outside except when it
is locked by key in outside
cylinder. Key will also set
mechanism so that first time
latch bolt is operated from
either inside or outside it
will remain locked in re-
tracted position allowing
door to be operated on a
push and pull basis.



76½, 77½

Latch bolt retracted by key or
thumb piece from outside at all
times except when thumb piece
locked by key from inside then by
key only from outside. Inside cyl-
inder can also set mechanism so
that first time latch bolt is operated
from either inside or outside it
will remain locked in retracted
position allowing door to be oper-
ated on a push and pull basis.



76¾, 77¾

Latch bolt by key only
from outside. Latch bolt
of 76¾ can be held re-
tracted by means of dog-
ging key with handle act-
ing as pull only.



78, 79

No trim or operation
from outside. Latch
bolt of 78 can be held
retracted by means of
dogging key.

†Not Reversible

No.	LOCK			OUTSIDE TRIM		Approx. Weight Each
	No.	Cyls.	See Page	Cast Brass or Bronze		
*76	5683	1	169	Handle 75385 (8¼x2¼ in.)	Cyl. Collar 75314 (2¼x2¼ in.)	12 lbs.
77	5683	1	169	Handle 75385 (8¼x2¼ in.)	Cyl. Collar 75314 (2¼x2¼ in.)	12 lbs.
*76½	5683½	2	169	Handle 75385 (8¼x2¼ in.)	Cyl. Collar 75314 (2¼x2¼ in.)	12 lbs.
77½	5683½	2	169	Handle 75385 (8¼x2¼ in.)	Cyl. Collar 75314 (2¼x2¼ in.)	12 lbs.
*76¾	5683¾	1	169	Handle 75385NT (8¼x2¼ in.)	Cyl. Collar 75314 (2¼x2¼ in.)	12 lbs.
77¾	5683¾	1	169	Handle 75385NT (8¼x2¼ in.)	Cyl. Collar 75314 (2¼x2¼ in.)	12 lbs.
*78	185	None	168		None	9 lbs.
79	185	None	168		None	9 lbs.

Stock Size: Can be furnished stock size for doors 3 feet 6 inches wide. Can be fitted to doors under 3 feet 6 inches wide by cutting down horizontal bar to correct size before applying. In ordering affix "S" to number, thus: **76S**.

Packed with screws. Can be furnished with sex bolts to fasten through door, when so ordered.

†In ordering specify hand and thickness of door, width of door etc. For instructions for ordering, see page 97.

‡Horizontal bar can be furnished stainless steel. To order affix **BSS** to number, thus: **76BSS**.

Specify number and finish. See pages 1 and 2.



Automatic Exit Fixtures


111

Rev. 6-1-57

FOR SINGLE EXIT DOORS OR STANDING LEAF OF DOUBLE DOORS

CAST BRASS OR BRONZE, POLISHED


FOR DOORS USED FOR EXIT ONLY



70, 71



Can be furnished with top case which holds both top and bottom bolts retracted while door remains open and automatically releases them when door closes. To order, affix **H** to number; i.e. **71H**.



- Cases**..... Active case $8\frac{1}{2} \times 2\frac{1}{8}$ in.
 Supporting case $8\frac{1}{2} \times 2\frac{1}{8}$ in.
 Top case $4\frac{1}{4} \times 2\frac{3}{16}$ in.
- Bars**..... Horizontal bar 1 in. dia.
 Horizontal bar can be furnished stainless steel, to order.
 Vertical bars $\frac{1}{2}$ in. dia.
 Seamless tubing.
- *Dogging Devices**..... In cases to lock cross bar in depressed position.

Minimum width of stile $3\frac{1}{2}$ in.

Operation—A slight pressure on horizontal bar automatically retracts top and bottom bolts instantly releasing the door from inside.

†Not Reversible

No.	Description		Approx. Weight Each
*70	For Exit Only	No Outside Trim	11 lbs.
71	For Exit Only	No Outside Trim	11 lbs.

Stock Size: Can be furnished stock size for doors 7 feet 6 inches high x 3 feet 6 inches wide. Can be fitted to doors under 7 feet 6 inches x 3 feet 6 inches wide by cutting down vertical rod and horizontal bar to required size before applying. In ordering affix "**S**" to number, thus: **70S**.

Packed with screws. Can be furnished with sex bolts to fasten through door, when so ordered.

†State hand, height and width of door, etc. For instructions for ordering, see page 97.


Specify number and finish. See pages 1 and 2.



112

Rev. 6-1-57

Automatic Exit Fixtures

FOR PAIRS OF DOORS
CAST BRASS OR BRONZE, POLISHEDInactive
Door70, 71
See page 111Active
Door76, 77, 76½, 77½
76¾, 77¾, 78, 79
See page 110Inactive
Door

Open back strike furnished with all locks for pairs of doors, allows doors to open or close independently of each other.

Minimum width of stile 4½ in.

OUTSIDE TRIM FOR ACTIVE DOOR



75385



75385NT

Operation

70, 71	See page 111
76, 77	See page 110
76½, 77½	See page 110
76¾, 77¾	See page 110
78, 79	See page 110

A slight pressure on horizontal bar releases door instantly.

SETS FOR PAIRS OF DOORS
†Not reversible

No.	LOCK			OUTSIDE TRIM FOR ACTIVE DOOR Cast Brass or Bronze		Approx. Weight Per Set
	No.	Cyls.	See page			
70 x 76	5683	1	169	Handle 75385 (8¾x2¼ in.)	Cyl. Collar 75314 (2¼x2¼ in.)	23 lbs.
71 x 77	5683	1	169	Handle 75385 (8¾x2¼ in.)	Cyl. Collar 75314 (2¼x2¼ in.)	23 lbs.
70 x 76½	5683½	2	169	Handle 75385 (8¾x2¼ in.)	Cyl. Collar 75314 (2¼x2¼ in.)	23 lbs.
71 x 77½	5683½	2	169	Handle 75385 (8¾x2¼ in.)	Cyl. Collar 75314 (2¼x2¼ in.)	23 lbs.
70 x 76¾	5683¾	1	169	Handle 75385NT (8¾x2¼ in.)	Cyl. Collar 75314 (2¼x2¼ in.)	23 lbs.
71 x 77¾	5683¾	1	169	Handle 75385NT (8¾x2¼ in.)	Cyl. Collar 75314 (2¼x2¼ in.)	23 lbs.
70 x 78	185	None	168		None	20 lbs.
71 x 79	185	None	168		None	20 lbs.

Stock Size: Can be furnished stock size for doors 7 feet 6 inches high x 3 feet 6 inches wide. Can be fitted to doors under 7 feet 6 inches high x 3 feet 6 inches wide by cutting down vertical rod and horizontal bar to required size before applying. In ordering affix "S" to number, thus: 70 x 76S.

Packed with screws. Can be furnished with sex bolts to fasten through door, when so ordered.

†State hand, height, width and thickness of doors, etc. For instructions for ordering, see page 97.

Specify number and finish. See pages 1 and 2.



Automatic Exit Fixtures

112A

FOR SINGLE DOORS USED FOR EXIT ONLY
GRAVITY LOCKING FOR DOORS OPENING OUT.

REVERSIBLE FOR RIGHT HAND REVERSE BEVEL
OR LEFT HAND REVERSE BEVEL DOORS.

MINIMUM WIDTH OF STILE 3 IN.

OPERATION

Both top and bottom bolts operated from inside at all times by slight pressure on cross bar at any point.

Top case is fitted with a device which holds both bolts retracted while the door remains open, preventing bottom bolt from dragging on floor.

Auxiliary latch in top case makes contact with top strike releasing bolts which are projected into strikes by gravity when door closes, locking door against operation from outside.

Doors cannot be operated from outside. No outside trim.

DIMENSIONS

Brackets }	Rod End2"	x 2¼"
	Outer End2"	x 1⅞"
Top Guide	1⅞"	x 1⅞"
Bottom Guide	1½"	x 1⅞"
Top Case	2½"	x 2⅞"
Top Strike	2¼"	x 1⅞"
Bottom Strike	2¾"	x 1¼"
Upper Rod	5/8"	
Lower Rod	½"	
Cross Bar	¾"	

CAST IRON WITH STEEL TUBING AND RODS

Lever Arms Bronze. Guides, Strikes and Working Parts in Top Case are Brass or Bronze.


No.	Finish	Weight Each
J5087	Dead Black Japanned	10½ lbs.
5087	Plated Finishes	10½ lbs.

One in a box, with screws and template for installing.

Angle Strike for
Standard ½" Stop



Side View
of
Top Case
Showing
Auxiliary
Latch



5087

Regularly furnished for doors 7'6" high and 3 ft. wide—Distance from floor to cross bar 38". Can be fitted on the job to doors under this size by cutting down top rod and cross bar to suit door before applying.

Can be furnished to order for doors larger than 7'6" x 3'.


Specify number and finish. See pages 1 and 2.



112B

Automatic Exit Fixtures

FOR PAIRS OF DOORS USED FOR EXIT ONLY
GRAVITY LOCKING FOR DOORS OPENING OUT.



DIMENSIONS

Brackets	Rod End2"	x 2 1/4"
	Outer End2"	x 1 7/8"
Top Guide	1 1/8"	x 1 7/8"
Bottom Guide	1 1/2"	x 1 7/8"
Top Case	2 1/2"	x 2 1/8"
Top Strike	2 1/4"	x 1 7/8"
Bottom Strike	2 3/4"	x 1 1/4"
Upper Rod		5/8"
Lower Rod		1/2"
Cross Bar		3/4"

Regularly furnished for doors 7'6" high and 3 ft. wide—Distance floor to cross bar 38". Can be fitted on the job to doors under this size by cutting down top rod and cross bar to suit door before applying.

Can be furnished to order for doors larger than 7'6" x 3'.

FURNISHED ONLY FOR HAND OF DOORS AS ILLUSTRATED.

MINIMUM WIDTH OF STILE 3 IN.


OPERATION

Both top and bottom bolts operated from inside at all times by slight pressure on cross bar at any point on either door.

Top case is fitted with a device which holds both top and bottom bolts retracted while the door remains open, preventing bottom bolt from dragging on the floor.

Auxiliary latch in top case makes contact with top strike releasing bolts which are projected into strike by gravity when door closes, locking door against operation from outside.

Doors cannot be operated from outside. No outside trim.



The vertical bolt is always applied to the left hand reverse bevel door which must be fitted with an overlapping "T" astragal. Coupling connects cross bars so that bar on either door will operate bolts. See above illustrations.

CAST IRON WITH STEEL TUBING AND RODS

Lever Arms Bronze. Guides, Strikes and Working Parts in Top Case are Brass or Bronze.

No.	Finish	Weight Set
J25087	Dead Black Japanned	12 1/2 lbs.
25087	Plated Finishes	12 1/2 lbs.

Specify number and finish. See pages 1 and 2.




Automatic Exit Fixtures

FOR SINGLE AND DOUBLE DOORS

CAST IRON


113

Rev. 6-1-57

Angle Strike for
Standard $\frac{1}{2}$ " StopSide View
of
Top Case
Showing
Auxiliary
Latch

5087

OUTSIDE TRIM



†326, *329

75385

Cases..... 8 x 2 $\frac{1}{4}$ in.Bar..... $\frac{3}{4}$ in. steel tubing.

Operation.... A slight pressure on bar releases door instantly. Thumb piece locked and unlocked by

†326..... outside cylinder. Latch bolt held retracted by pressing in latch bolt and turning key towards back of lock.

*329..... Bar from inside only.

*Reversible... Standard stock size 3 ft.

Minimum width of stile 4 $\frac{1}{2}$ in.

SETS FOR SINGLE DOORS

No.	LOCK			OUTSIDE TRIM Cast Brass or Bronze	Approx. Weight Each
	No.	Cyls.	See page		
†326 329	5785 180	1 None	170 168	Handle 75385 (8 $\frac{3}{4}$ x2 $\frac{1}{4}$ in.) Cyl. Collar 75314 (2 $\frac{1}{4}$ x2 $\frac{1}{4}$ in.) None	11 lbs. 8 lbs.

Packed with screws. †Not reversible. Specify hand, width and thickness of door, width of stile. For instructions for ordering, see page 97.
Furnished for stops $\frac{1}{2}$ in. unless otherwise ordered.

SETS FOR PAIRS OF DDORS

No.	LOCK			OUTSIDE TRIM Cast Brass or Bronze	Approx. Weight Per Set
	No.	Cyls.	See page		
†326 x 5087 329 x 5087	5785 180	1 None	170 168	Handle 75385 (8 $\frac{3}{4}$ x2 $\frac{1}{4}$ in.) Cyl. Collar 75314 (2 $\frac{1}{4}$ x2 $\frac{1}{4}$ in.) None	27 lbs. 24 lbs.

Packed with screws. †Not reversible. Specify hand, height, width and thickness of doors, width of stile. For instructions for ordering, see page 97.

Furnished for stops $\frac{1}{2}$ in. unless otherwise ordered. Open back strike regularly supplied.

Specify number and finish. See pages 1 and 2.



Optional Outside Trim

FOR EXIT FIXTURES
BRASS, BRONZE OR ALUMINUM

1519 1/2 x 74027

Knob 2 1/4 in. dia.
Escutcheon 8 5/8 x 2 1/2 in.
Cast Metal


1519 1/2 x 74127

Knob 2 1/4 in. dia.
Escutcheon 8 5/8 x 2 1/2 in.
Cast Metal

1519 1/2 x 74028

Knob 2 1/4 in. dia.
Escutcheon 9 1/2 x 3 1/2 in.
Cast Metal with lugs cast on back.For use with Rim Exit Fixtures
Nos. 2927 or 2927 1/2 when it is
desired to connect Escutcheon
to Exit Fixture Case with thru
bolts.These Escutcheons have lugs cast on back for use with Exit
Fixtures Nos. 121, 124, 125, 127, 127 1/2, 128, 147 or 147 1/2 when
it is desired to connect outside Escutcheon to Exit Fixture Case
with thru bolts.


76580

76580NT. Same less
Thumb Piece.76580DNT. Same less
Thumb Piece, less Cylin-
der hole. Size 15 x 3
in. Extruded Metal.For use with Exit Fixtures
Nos. 126, 126NT, t26 1/2,
126 1/2 NT, 146, 146 1/2, 2926,
2926NT, 2926 1/2 or 2826NT in
place of regular trim.

76584

76584NT. Same less
Thumb Piece.76584DNT. Same less
Thumb Piece, less Cylin-
der Collar. Handle 12 3/8
x 1 1/2 in. Cylinder Collar
2 1/4 x 1 1/2 in. Extruded
Metal.For use with Exit Fixtures
t26, 126 1/2, 126NT, 126 1/2 NT,
146, 146 1/2, 2926, 2926 1/2,
2926NT or 2826NT in place
of regular outside trim.

76589

76589DL. Same but rigid
Lever, less Cylinder
hole.76589DNL. Same but
less Lever, less Cylinder
hole.Size 13 3/8 x 1 1/2 in. Ex-
truded Metal. Cast
Lever.For use with Exit Fixtures
Nos. 12t, 124, t25, 128 in
place of regular trim.

76599

76599DL. Same but with
rigid Lever, less Cylin-
der.76599DNL. Less Lever,
less Cylinder. Size 15 x
3 in.For use with Exit Bolts
Nos. 121, 124, 125, 128 in
place of regular outside
trim.
Nos. 76598, 76598DL and
76598DNL same as above
but with lugs on back to
connect through bolt to exit
fixture case.


Specify number and finish. See pages 1 and 2.

Automatic Exit Fixtures

115


Rev. 6-1-57

STRIKES FOR VERTICAL EXIT BOLTS




No. 682

Top strike for bolts Nos. 120, 124, 125, 134, 135 and 140.



No. 122S

Top strike for bolts Nos. 122, 128, 138 and 142.



No. 5087S

Top strike for bolt No. 5087.



No. 681

Bottom strike for bolts Nos. 120, 124, 125, 134, 135, 140 for single doors.




No. 122FT

Bottom strike for bolts Nos. 122, 128, 138 and 142.




No. 5087FT

Bottom strike for bolt No. 5087.



No. 683

Bottom strike furnished with bolts Nos. 120, 140 for pairs of doors.




No. 693

Stop for bottom of active door of pairs of doors.


STRIKES FOR MORTISE LOCKS

*NOT REVERSIBLE



No. 608

For mortise exit locks Nos. 5683, 5683 $\frac{1}{2}$, 5683 $\frac{3}{4}$




No. 676

Jamb strike for mortise exit locks Nos. 5785, 5784, 5585 and 5584.

No. 678

For mortise exit latches Nos. 180, 185



No. 605 for 5683 exit lock.
No. 606 for 5784 exit lock.
No. 607 for 180 latch.

Open back strikes furnished with all exit locks when used on pairs of doors.

Allow doors to open and close independently of each other.

*State hand of door.

Specify number and finish. See pages 1 and 2.




116

Rev. 6-1-57

Automatic Exit Fixtures

STRIKES FOR RIM EXIT FIXTURES




674


Size $3\frac{3}{4} \times 1\frac{1}{2}$ in.

Cast Brass, Bronze or Aluminum



Adjustable to compensate for shrinkage of doors

Furnished regularly for all Rim Exit Fixtures,
pages 98 to 100.

No. 666A

Strike for rim exit fixtures for single
doors with channel iron jambs.Adjustable to compensate for
shrinkage of doors.

No. 655

Strike for rim exit fixtures when
used on pairs of doors with vertical
bolt on inactive door.STEEL REINFORCING TUBE
FOR CROSS BARSSTEEL
REINFORCING
TUBECross bars of rim bolts pages 98 to 100 and 120
line of bolts pages 102 to 107 can be furnished
with steel reinforcing tube. To order affix **RC** to
number, thus: **2926RC**, **126RC**, etc.

Specify number and finish. See pages 1 and 2.




Automatic Exit Fixtures

117

Rev. 6-1-57

CROSS BAR ASSEMBLY

For Rim Bolts Pages 98 to 100 and 120 Line of Bolts Pages 102 to 107.




Cross bars now assembled to lever arms with socket type set screws in lever arms which are covered by sleeve after being applied.

Cross bar is provided with a scribe line for use as a guide for drilling hole on one end for set screw after bar is cut down to required length.

Automatic Co-ordinating Device


FOR DOUBLE DOORS WITH RABBETED FACE OR OVERLAPPING ASTRAGAL PREVENTS THE ACTIVE DOOR FROM CLOSING AHEAD OF THE INACTIVE DOOR



2359

View Applied

Shown with active door right hand reverse bevel.



In ordering state thickness of door (A) and recess (B). If with trim state "C" and "D." At additional price when required to meet unusual conditions.



When the inactive door is open the arm prevents active door from closing as shown in illustration. When the inactive door is closed it makes contact with the trip of the device which raises the arm so that active door will close beneath it.

*Not Reversible

No.	Projection of Arm (A)	Material and Finish	Plate, Inches	Weight, Each
2359	5 1/4 in.	Cast Brass or Bronze Polished	1 3/8 x 4 1/8	1 3/4 lbs.

Packed with screws. *State hand.

Specify number and finish. See pages 1 and 2.



Thresholds



702*



704*



705*




706*

No.	Length	Material	Width Inches	Height of Threshold
702	To Order	Extruded Aluminum	2½	¼ in.
704	To Order	Extruded Aluminum	4	½ in.
705	To Order	Extruded Aluminum	5	½ in.
706	To Order	Extruded Aluminum	6	½ in.

*When ordering specify length required.


WEATHER PROOF, FOR EXTERIOR DOORS



"A" Length of threshold — extreme width of opening between jambs.

NOTE: These thresholds provided with stop index line, for aligning with side stops of door frame, to assure bottom of doors making even contact with stop part of threshold.

For doors up to 2¼ in. thick
In ordering state (A) length of threshold required.
Thresholds furnished 1 in. longer than ordered to allow them to be cut for close fit in opening.



No.	Length	Material	Width Inches	Height of Threshold	Height of Stop from Floor Line
2584	To Order	Extruded Bronze	5	¾ in.	¾ in.
6584	To Order	Extruded Aluminum	5	¾ in.	¾ in.

Furnished with 1¼ in. — 10 x 18 F. H. machine screws and expansion shields.

Specify number and size.





CANADA

EXTERIOR DOOR HARDWARE

ENTRANCE HANDLES

STORE DOOR HANDLES

DOOR PULLS

PUSH BARS

PUSH PLATES

DOOR KNOCKERS

ELECTRIC PUSH BUTTONS

LETTER DROP PLATES






INDEX OF

Item	Page
DOOR PULLS	121, 128
PUSH AND PULL PLATES	128, 130
KICK PLATES	131
PUSH BARS	131, 135
SECTIONAL LOCK SETS	136, 138
STORE DOOR LOCK SETS	139, 140
DOOR KNOCKERS	141
PUSH BUTTONS	141
LETTER DROP PLATES	142, 143

Flush Door Pulls

121



2102




2103, 02103

No.	Size Inches	Material and Finish	Opening Inches	Outside Depth of Cup	Packed in a Box	Weight Dozen
2102	3 1/4 x 2 7/8	Cast Brass or Bronze Polished	2 3/4 x 1 7/8	From Back of Plate 3/4 in.	6	8 1/4 lbs.
2103	3 3/4 x 2	Polished	2 1/8 x 7/8	1 1/32 in.	6	3 lbs.
02103	3 3/4 x 2	Cast Iron Plated	2 1/8 x 7/8	1 1/32 in.	6	3 lbs.

Packed with screws.

Door Pulls



4337


Base 2 7/8 x 1 1/8 in.



04398



T04328



4335

Large Base 1 7/8 x 1 1/2 in.

No.	Overall Size Inches	Material and Finish	Projection Inches	Clearance Inches	Packed in a Box	Weight Dozen
J04398	4 3/4 x 1 1/16	Wrought Steel Japanned	1 1/16	3/4	3 Dozen	1 lb.
J04398 1/2	4 3/4 x 1 1/16	Japanned	1 1/16	3/4	3 Dozen	1 lb.
G04398	4 3/4 x 1 1/16	Zinc Plated	1 1/16	3/4	3 Dozen	1 lb.
G04398 1/2	4 3/4 x 1 1/16	Zinc Plated	1 1/16	3/4	3 Dozen	1 lb.
04398	4 3/4 x 1 1/16	Plated	1 1/16	3/4	3 Dozen	1 lb.
T04328	5 3/4 x 1 3/4	Cast Iron Plated	1 7/16	1 1/4	6 Dozen	4 1/2 lbs.

No. 04398 1/2 without screws. All others packed with screws.

Hook Type for Hospital Use

Enables a person bearing a loaded tray to pull a door open.


No.	Size Inches	Material and Finish	Projection Inches	Clearance Inches	Packed in a Box	Weight Dozen
4335	9 1/8 x 1 1/2	Cast Brass, Bronze or Aluminum Polished	3 7/8	3 1/8	6	12 1/2 lbs.
4337	5 1/4 x 1 3/4	Polished	3 7/8	2 7/8	6	9 lbs.

Packed with screws.


Specify number and finish. See pages 1 and 2.



Door Pulls



4330, 4331



4332, 4333



4408



4409



4414

No.	Overall Size Inches	Material and Finish	Projection Inches	Clearance Inches	Cen. to Cen. of Machine Screw	Packed in a Box	Weight Dozen
		Cast Brass, Bronze or Aluminum					
4330	7½ x 2	Polished	2¼	1⅛	5½ in.	2	14¼ lbs.
4331	10 x 2	Polished	2⅝	1⅝	7⅞ in.	2	18¾ lbs.
4332	7½ x 2	Polished	2¼	1⅞	////	2	13½ lbs.
4333	10 x 2	Polished	2⅝	1⅞	////	2	14¼ lbs.
4408	9¾ x 1⅛	Polished	2⅞	1⅞	8 in.	2	16 lbs.
4409	9¾ x 1⅛	Polished	2⅞	1⅞	8 in.	2	16 lbs.
		Cast Brass or Bronze					
4414	15¾	Polished	2¾	1¾	14 in.	2	36 lbs.

Packed with screws or through bolts.

Specify number and finish. See pages 1 and 2.

Door Pulls


123




4370



4371



4372




4373



4374



4375



4376

NO.	Overall Size Inches	Size of Base of Bracket Inches	Material and Finish	Projection Inches	Clearance Inches	Cen. to Cen. of Machine Screw	Packed in a Box	Weight Each
4370	18¼	3¾x1½	Brass Bronze or Aluminum Polished	2⅝	1¼	14½ in.	2	3⅝ lbs.
4371	18¼	3¾x1½	Polished	2⅝	1¼	14½ in.	2	3⅝ lbs.
4372	12½	1⅞	Polished	1⅞	1½	8 in.	2	3¼ lbs.
4373	11½	11½x1½	Polished	2¼	...	5½ in.	2	3¾ lbs.
4374	12	2	Polished	2⅜	...	9¼ in.	2	3½ lbs.
4375	17¾	2⅞x1⅝	Polished	2⅜	1¾	15½ in.	2	3 lbs.
4376	12	2⅞x1⅝	Cast Brass or Bronze Polished	2⅞	1⅞	10 in.	2	2⅞ lbs.

Packed with through bolts for attaching through door.

Specify number and finish. See pages 1 and 2.



Door Pulls


Furnished on push plates as door pulls when so ordered.



4410, 04410



4416



4419



4412



4408 1/2



4420

4455 to 4457



04421

No.	Size, Center to Center, Inches	Material and Finish	Projection Inches	Clearance Inches	Type
Cast Brass or Bronze					
*4408 1/2	8	Polished	2 1/4	1 3/8	Straight
4410	4 3/8	Polished	1 3/4	1 1/8	Straight
*4412	5 3/8	Polished	1 7/8	1 1/4	Straight
4416	5 1/4	Polished	2 1/8	1 5/8	Straight
*4419	5 3/4	Polished	2 1/4	1 3/4	Straight
*4420	7 1/2	Polished	2 5/8	1 3/4	Straight
*4455	5 1/4	Polished	2	1 3/8	Straight
*4456	6	Polished	2 7/8	1 3/8	Straight
*4457	6 5/8	Polished	2	1 1/4	Straight
Cast Iron					
04410	4 3/8	Plated	1 3/4	1 1/8	Straight
04421	4 3/8	Plated	1 7/8	1 3/8	1 inch offset
04455	5 1/4	Plated	2	1 3/8	Straight

With machine screws and nuts to fasten to push plates or through door.

*Also furnished cast aluminum.

Specify number and finish. See pages 1 and 2.



Door Pulls

125

FURNISHED ON PUSH PLATES AS DOOR PULLS WHEN SO ORDERED



4334



4436



4451



4454

No.	Size, Center to Center, Inches	Material and Finish	Projection Inches	Clearance Inches	Type
*4334	7	Cast Brass or Bronze			
4436	5 $\frac{3}{4}$	Polished	2 $\frac{1}{8}$	1 $\frac{1}{2}$	Straight
4451	5 $\frac{3}{4}$	Polished	2 $\frac{1}{8}$	1 $\frac{5}{8}$	Straight
4454	7 $\frac{5}{8}$	Polished	1 $\frac{7}{8}$	1 $\frac{5}{8}$	Straight
		Polished	1 $\frac{3}{4}$	1 $\frac{1}{8}$	Straight

With Machine Screws and Nuts to fasten to Push Plate or Through Door.

*Also furnished in aluminum.

Specify number and finish. See pages 1 and 2.



Door Pulls



4485 to 4487




74186



73986



74586



76786

No.	Plate Size Inches	Material and Finish	Grip		Projection Inches	Packed in a Box	Weight Each
			No.	Cen. to Cen.			
		Cast Brass Bronze or Aluminum					
4485	12x3	Polished	4456	6 in.	$2\frac{7}{16}$	2	2¼ lbs.
4486	15x3½	Polished	4456	6 in.	$2\frac{7}{16}$	2	3¼ lbs.
4487	16x4	Polished	4457	6½ in.	$2\frac{7}{16}$	2	3¾ lbs.
73986	12x3	Polished	4334	7 in.	$2\frac{1}{16}$	2	2¾ lbs.
74186	12x3	Polished	4412	5¾ in.	$2\frac{1}{16}$	2	2 lbs.
*74586	14x3	Polished	4436	5¾ in.	$2\frac{3}{8}$	2	2¾ lbs.
76786	14x3	Polished	4334	7 in.	$2\frac{1}{16}$	2	3¼ lbs.

Packed with screws and through bolts for grip.

Door pulls on plates have the grip regularly placed on the center of plate except when special features of the plate makes this impractical, in which case grips are placed in position which we believe gives the most balanced appearance.

Grips can be placed in any position on plate which is desired providing detail is furnished showing the required position.

*Furnished cast Brass or Bronze only.

Specify number and finish. See pages 1 and 2.

Door Pulls

127




4470, 04470



4472, 04472



52986



4475 to 04476

No.	Plate Size Inches	Material and Finish	Grip		Projeciton Inches	Packed in a Box	Weight Dozen
			No.	Cent. to Cent.			
Wrought Brass or Bronze							
4470	10x2¾	Polished	4410	4⅜ in.	2⅛	2	15¾ lbs.
4472	14x3	Polished	4455	5¼ in.	2¼	2	19½ lbs.
4475	10x2¾	Polished	4410	4⅜ in.	2	2	15½ lbs.
4476	12x3	Polished	4455	5¼ in.	2⅜	2	18½ lbs.
52986	15x3	Polished	4451	5¾ in.	2½	2	22½ lbs.
Wrought Steel							
04470	10x2¾	Plated	04410	4⅜ in.	2⅛	2	12¾ lbs.
04472	14x3	Plated	04455	5¼ in.	2¼	2	18 lbs.
04475	10x2¾	Plated	04410	4⅜ in.	2	2	12¾ lbs.
04476	12x3	Plated	04455	5¼ in.	2⅜	2	15¾ lbs.

Packed with screws and through bolts for grip.

Door Pulls on plate have the grip regularly placed on the center of plate except when special features of the plate makes it impractical, in which case grips are placed in position which we believe gives the most balanced appearance.

Grips can be placed in any position on plate which is desired providing detail is furnished showing the required position.

Specify number and finish. See pages 1 and 2.




128 Push and Pull Plate

Door Pulls



2324



4466, 4467

4462
Type of 4463
and 4464

PUSH AND PULL PLATE

No.	Size	Material and Finish	Pull End		Packed in a Box	Weight Each
			Projection	Clearance		
2324	16 x 3½	Heavy Solid Extruded Brass, Bronze or Aluminum Polished	1½ in.	⅞ in.	2	3¼ lbs.

DOOR PULLS

No.	Plate Size Inches	Material and Finish	Grip		Projection Inches	Packed in a Box	Weight Dozen
			No.	Cen. to Cen.			
4462	12x3	Solid Wrought Brass, Bronze or Aluminum With Cast Grip	4455	5¼ in.	2¼ ₁₆	2	22½ lbs.
4463	14x3½	Polished	4455	5¼ in.	2¼ ₁₆	2	26½ lbs.
4464	16x4	Polished	4455	5¼ in.	2¼ ₁₆	2	28½ lbs.
4466	15x7½	Extruded Brass, Bronze or Aluminum, 16 Ga.	7½x1 in.	1
4467	12x6	Polished	7½x1 in.	1

Packed with screws and through bolts for grip.

Specify number and finish. See pages 1 and 2.



Push Plates

129



2343



73990, 73991



74190 to 74194



76790



2300 (Glass)

No.	Overall Size Inches	Material and Finish	Packed in a Box	Weight Each
		Cast Brass, Bronze or Aluminum		
2343	12x3	Polished	6	1 ¹ / ₁₆ lbs.
2343	15x3 ¹ / ₂	Polished	6	2 ¹ / ₄ lbs.
2343	16x4	Polished	6	2 ¹ / ₂ lbs.
73990	12x3	Polished	6	1 ¹ / ₄ lbs.
73991	15x3 ¹ / ₂	Polished	6	1 ¹ / ₂ lbs.
74190	12x3	Polished	6	1 ³ / ₈ lbs.
74192	15x3 ¹ / ₂	Polished	6	1 ⁵ / ₈ lbs.
74193	16x4	Polished	6	1 ⁷ / ₈ lbs.
74194	20x4	Polished	6	2 ³ / ₈ lbs.
76790	14x3	Polished	6	1 ¹ / ₂ lbs.
2300	12x3	Glass	2	9 oz.

Packed with screws.

Specify number, size and finish. See pages 1 and 2.


Push Plates



2354



2353, 02353



2336, 2337



2352, 02352



52991

No.	Overall Size Inches	Material and Finish	Packed in a Box	Weight Dozen
		Wrought Brass, Bronze or Aluminum		
2336	15x7½	Polished	1
2337	12x6	Polished	1
2354	10x3	Polished	6	6¾ lbs.
2354	12x3	Polished	6	8¼ lbs.
2354	15x3½	Polished	6	13½ lbs.
2354	16x4	Polished	6	15 lbs.
2354	20x4	Polished	6	18½ lbs.
		Wrought Brass or Bronze		
2352	10x2¾	Polished	6	3¾ lbs.
2352	14x3	Polished	6	6¾ lbs.
2353	10x2¾	Polished	6	3¾ lbs.
2353	12x3	Polished	6	6 lbs.
52991	15x3	Polished	6	7½ lbs.
		Wrought Steel		
02352	10x2¾	Plated	6	3¾ lbs.
02352	14x3	Plated	6	6¾ lbs.
02353	10x2¾	Plated	6	3¾ lbs.
02353	12x3	Plated	6	6 lbs.

Packed with screws.

Specify number, size and finish. See pages 1 and 2.

Kick Plates

131



2316


No.	Size	Material and Finish	Thickness		Type
			B&S Gauge	Inches	
2316	State Size Required	Wrought Brass, Bronze or Aluminum Polished	16	.050	Edges not beveled

Packed with screws.

All kick plates can be furnished bevelled when so ordered.

Push Bars

FURNISHED WITH TWO OR THREE BARS.



2209

No.	†With Bars	Bracket			Bars				Projection Inches	Clearance Inches
		Length Inches	Width Inches	Material and Finish	*Length Inches	Diameter Inches	Spacing Inches	Material and Finish		
2209	2	6	3/4	Cast Brass or Bronze Polished	Cen. to Cen. 24	1/2	3	Wrought Brass or Bronze Polished	13/16	5/16
2209	3	9	3/4	Polished	24	1/2	3	Polished	13/16	5/16

†In ordering specify number of bars.

*Bars furnished any length desired when so ordered.

No. 2209 furnished to fasten from back with machine screws when so ordered.

Measurements, center to center of bases.

Packed with screws.

Specify number, size and finish. See pages 1 and 2.

132 Push and Pull Bars



2202



2203


No.	Length Inches	Bases		Bars		Projection Inches	Clearance Inches	Weight Each
		Size Inches	Material and Finish	Size Inches	Material and Finish			
2202	24	2	Cast Brass or Bronze	1	Wrought Brass or Bronze	2 1/4	1 1/4	3 lbs.
2203	24	2	Polished Polished	1	Polished Polished	2 1/4	1 1/4	3 lbs.

2202 attached by machine screws through door from opposite side.

2203 packed with screws.

Measurements, centre to center of bases.

Furnished any length desired when so ordered.



2220

No.	Length Inches	Bases		Bars		Projection Inches	Clearance Inches	Weight Each
		Diameter Inches	Material and Finish	Diameter Inches	Material and Finish			
2220	16	3 1/4 x 1 1/2	Cast Brass Bronze or Aluminum	1 1/4	Wrought Brass Bronze or Aluminum	2 5/8	1 1/4	3 lbs.

Attached by machine screws through door from opposite side.


Standard length as shown. Special lengths to order.

When double bars are required, one for each side of door suffix "D" to number i.e. 2220D.


Specify number, size and finish. See pages 1 and 2.

Push and Pull Bars

133



2225



2223



2224

No.	Length Inches	Bases		Bars		Projection Inches	Clearance Inches
		Size Inches	Material and Finish	Size Inches	Material and Finish		
2223	24	2x 3½	Extruded Brass Bronze or Aluminum		Extruded Brass Bronze or Aluminum		
2224	24	2x 9½	Polished	1¾ x ¾	Polished	2½	2⅛
2225	24	2x 15	Polished	1¾ x ¾	Polished	2½	2⅛
			Polished	1¾ x ¾	Polished	2½	2⅛

Measurements center to center of bases.

Furnished any length desired when so ordered.

Packed with screws.

Specify number, size and finish. See pages 1 and 2.




Push and Pull Bars

BRACKETS AND GRIPS CAST BRASS, BRONZE OR ALUMINUM, BARS EXTRUDED BRASS, BRONZE OR ALUMINUM.




2231




2232

2233 Push Grip



2234 Push Bar Set

2236 Push Bar Set
For Double Acting doors.

2232G



2231A



2231B



2231BS

2231 SINGLE BAR

Cast Brackets. Extruded bars.

Length: Stock size 36 in.

Brackets: $1\frac{1}{2}$ x $2\frac{3}{8}$ in. Bar $1\frac{1}{4}$ x $\frac{3}{8}$ in.Projection: $\frac{3}{4}$ in.

Regularly attached with Thru Bolts.

Wood or Machine Screws to order.

2232 DOUBLE BAR With Pull Grip

Brackets and Grip Cast. Extruded bars.

Length: Stock size 36 in.

Brackets: $1\frac{1}{2}$ x $2\frac{3}{8}$ in. Bars $1\frac{1}{4}$ x $\frac{3}{8}$ in.Grip: $8\frac{1}{2}$ x $1\frac{1}{2}$ in. Projection: $1\frac{1}{4}$ in.Spacing: $6\frac{1}{2}$ in. center to center of bars.

Regularly attached with Thru Bolts.

Wood or Machine Screws to order.

2233 DOUBLE BAR With Push Grip

Same as 2232 except word Push on Grip.

Set No. 2234 consists of 2232 Double Bar with Pull Grip outside and two Single Bars 2231 inside connected with Thru Bolts.

Set No. 2236 consists of two 2233 Double Bars with Push Grip, one for each side of door, connected with Thru Bolts. For Double Acting Doors.

PARTS**2231A** Bar only, no Brackets.Size $1\frac{1}{4}$ x $\frac{3}{8}$ in. Length for 36 in. Bars.**2231B** Bracket for Thru Bolt, $1\frac{1}{2}$ x $2\frac{3}{8}$ x $\frac{3}{4}$ in.**2231BS** Bracket for surface screws $1\frac{1}{2}$ x $2\frac{3}{8}$ x $\frac{3}{4}$ in.**2232G** (Pull) Grip $8\frac{1}{2}$ x $1\frac{1}{2}$ in. $6\frac{1}{2}$ in. center to center. $1\frac{1}{4}$ in. projection.**2233G** (Push) Grip $8\frac{1}{2}$ x $1\frac{1}{2}$ in. $6\frac{1}{2}$ in. center to center. $1\frac{1}{4}$ in. projection.


Shipped not assembled for doors up to 36 in. wide. Bars can be cut to desired size before applying. Reversible for right or left hand doors.

Specify number and finish. See pages 1 and 2.




Push and Pull Bars

135



2237

Attached by machine screws through door from opposite side.



2238

Can be supplied in pairs when so ordered.

No.	*Length, Inches	Material and Finish	Bases		Projection Inches	Clearance Inches
			Width Inches	Length Inches		
2237	*State Length	Cast Brass or Bronze	1 5/8	2 1/8	2 1/4	1 3/4
2238	*State Length	Polished	1 5/8	2 1/8	2 1/4	1 3/4

*Furnished only in 24 1/2, 26 5/8, 27 1/2, 30, 30 1/2, 32 1/4, 32 1/2, 34 1/2, 37 1/4 in. center to center of bases.



2240

Attached by machine screws through door from opposite side. Can be furnished in pairs when so ordered.



2250

Grip, cast brass or bronze.

Spacing, center to center of bars, 7 1/8 in.

Center of base plate to center of grip, 3 in.

Number covers double bars and grip outside with two single bars inside, complete as illustrated.

Outside bars attached with machine screws through bases of inside bars.

Furnished any length desired, when so ordered.

No.	Length Inches	Bases		Bars		Projection		Clearance Inches	Weight Each
		Size Inches	Material and Finish	Size Inches	Material and Finish	Grip Inches	Bars Inches		
2240	24	1 3/8 x 1 3/8	Cast Brass or Bronze	3/4 x 1/2	Wrought Brass or Bronze Tubing	...	1 5/8	1	2 3/4 lbs.
2250	24	1 3/8 x 1 3/8	Polished	3/4 x 1/2	Polished	3	1 5/8	1	11 1/2 lbs.

Specify number, size and finish. See pages 1 and 2.



136

Sectional Handle Locksets

CAST BRASS OR BRONZE



34184



36484



42084



74583



80784

ENTRANCE DOOR HANDLES

No.	Handle Size Inches	Projection Inches	Cylinder Collar	
			No.	Size, Inches
34184	11 $\frac{3}{4}$ x 2 $\frac{1}{2}$	2 $\frac{7}{16}$	34113	4 $\frac{1}{8}$ x 2 $\frac{1}{8}$
36484	13 $\frac{1}{4}$ x 2 $\frac{3}{4}$	2 $\frac{7}{8}$	36413	2 $\frac{5}{8}$ x 2 $\frac{5}{8}$
42084	11 $\frac{3}{4}$ x 2 $\frac{7}{8}$	2	42013	2 $\frac{3}{4}$ x 2 $\frac{1}{2}$
74583	10 $\frac{3}{4}$ x 2 $\frac{1}{4}$	2	74514	3 x 2 $\frac{1}{4}$
80784	10 x 2	2 $\frac{1}{4}$	80713	4 $\frac{1}{8}$ x 2

LOCKSETS WITH HANDLE OUTSIDE AND KNOB INSIDE

Set No.	Lock		$\frac{1}{2}$ Pair Handles No.	One Knob with 45 $\frac{1}{2}$ Spindle No.	Thumb Knob No.	Packed in a Box	Weight Set
	No.	See Page					
341-880	5743	166	34184	1419x1118	2140	1	4 $\frac{3}{8}$ lbs.
364-880	5743	166	36484	1419x1118	2140	1	4 $\frac{5}{8}$ lbs.
420-880	5743	166	42084	1419x1118	2140	1	5 $\frac{1}{4}$ lbs.
745-879	5743	166	74583	1419x1118	2140	1	5 $\frac{1}{2}$ lbs.
807-880	5743	166	80784	1419x1118	2140	1	4 lbs.

LOCKSETS WITH HANDLES BOTH SIDES

Set No.	Lock		One Pair Handles No.	Packed in a Box	Weight Set
	No.	See Page			
341-994	5262	167	34184	1	6 lbs.
364-994	5262	167	36484	1	6 lbs.
420-994	5262	167	42084	1	6 lbs.
745-993	5262	167	74583	1	7 lbs.
807-994	5262	167	80784	1	5 $\frac{1}{4}$ lbs.

Packed with screws.

Specify number, thickness of door and finish. See pages 1 and 2.



Sectional Handle Locksets

CAST BRASS OR BRONZE

137

Rev. 6-1-57



14684



50384



50584



*54184



*56484

ENTRANCE DODR HANDLES

No.	Handle Size Inches	Projection Inches	Cylinder Collar	
			No.	Size, Inches
14684	11 x 2 $\frac{5}{8}$	2	14613	2 $\frac{1}{2}$ x 2 $\frac{1}{2}$
50384	9 $\frac{3}{8}$ x 2 $\frac{3}{8}$	2	50313	3 $\frac{1}{8}$ x 2 $\frac{1}{2}$
50584	11 $\frac{1}{8}$ x 2 $\frac{1}{2}$	1 $\frac{3}{4}$	50513	2 $\frac{3}{8}$ x 2 $\frac{1}{4}$
*54184	11 $\frac{3}{4}$ x 2 $\frac{1}{2}$	2 $\frac{3}{8}$	54113	4 $\frac{1}{8}$ x 2 $\frac{1}{8}$
*56484	13 $\frac{1}{4}$ x 2 $\frac{3}{4}$	2 $\frac{3}{8}$	56413	2 $\frac{5}{8}$ x 2 $\frac{5}{8}$

LOCKSETS WITH HANDLE OUTSIDE AND KNOB INSIDE

Set No.	Lock		$\frac{1}{2}$ Pair Handles No.	One Knob with 45 $\frac{1}{2}$ Spindle No.	Thumb Knob No.	Packed in a Box	Weight Set
	No.	See Page					
146-880	5743	166	14684	1419 x 1118	2140	1	5 $\frac{3}{8}$ lbs.
503-880	5743	166	50384	1419 $\frac{1}{2}$ x 1109	2140	1	4 $\frac{1}{2}$ lbs.
505-880	5743	166	50584	1419 $\frac{1}{2}$ x 1109	2140	1	5 lbs.
*541-880	5743	166	54184	1419 x 1118	2140	1	5 lbs.
*564-880	5743	166	56484	1419 x 1118	2140	1	5 lbs.

LOCKSETS WITH HANDLES BOTH SIDES

Set No.	Lock		One Pair Handles No.	Packed in a Box	Weight Set
	No.	See Page			
146-994	5262	167	14684	1	6 $\frac{5}{8}$ lbs.
*541-994	5262	167	54184	1	6 lbs.
*564-994	5262	167	56484	1	6 lbs.

Packed with screws. *Furnished in colonium metal.

Specify number, thickness of door and finish. See pages 1 and 2.



138

Rev. 6-1-57

Sectional Handle Locksets

CAST BRASS OR BRONZE



40084




*42184




*42284



*76584



75383



Type of 75384

Cast Brass, Bronze or Aluminum

*Extruded Brass, Bronze or Aluminum

ENTRANCE DDDR HANDLES

No.	Handle Size Inches	Projection Inches	Grip No.	Cylinder Collar	
				No.	Size
40084	9 $\frac{3}{4}$ x2 $\frac{3}{4}$	1 $\frac{15}{16}$	40013	3 $\frac{1}{4}$ x2 $\frac{5}{8}$
42184	11 $\frac{1}{2}$ x1 $\frac{1}{2}$	2 $\frac{1}{4}$	42113	2 $\frac{1}{4}$ x1 $\frac{1}{2}$
42284	11 $\frac{1}{2}$ x1 $\frac{1}{2}$	2 $\frac{3}{8}$	42213	2 $\frac{1}{4}$ x1 $\frac{1}{2}$
75383	8 $\frac{3}{4}$ x2 $\frac{3}{4}$	2 $\frac{3}{8}$	4419	75314	2 $\frac{1}{4}$ x2 $\frac{1}{4}$
75384	10 $\frac{1}{2}$ x2 $\frac{3}{4}$	2 $\frac{7}{8}$	4420	75314	2 $\frac{1}{4}$ x2 $\frac{1}{4}$
76584	12 $\frac{1}{8}$ x1 $\frac{1}{2}$	1 $\frac{15}{16}$	76513	2 $\frac{1}{4}$ x1 $\frac{1}{2}$

LOCKSETS WITH HANDLE OUTSIDE AND KNOB INSIDE

Set No.	Lock		$\frac{1}{2}$ Pair Handles No.	One Knob with 45 $\frac{1}{2}$ Spindle No.	Thumb Knob No.	Packed in a Box	Weight Set
	No.	See page					
400-880	5743	166	40084	1419x1118	2140	1	5 lbs.
421-880	5743	166	42184	1419x1118	2140	1
422-880	5743	166	42284	1419x1118	2140	1
753-879	5743	166	75383	1419x1118	2140	1	5 $\frac{1}{4}$ lbs.
753-880	5743	166	75384	1419x1118	2140	1	6 lbs.
765-880	5743	166	76584	1419x1118	2140	1

LOCKSETS WITH HANDLES BOTH SIDES

Set No.	Lock		One Pair Handles No.	Packed in a Box	Weight Set
	No.	See Page			
400-994	5262	167	40084	1	5 $\frac{1}{2}$ lbs.
421-994	5262	167	42184	1
422-994	5262	167	42284	1
753-993	5262	167	75383	1	6 $\frac{1}{2}$ lbs.
753-994	5262	167	75384	1	7 $\frac{3}{4}$ lbs.
765-994	5262	167	76584	1

Packed with screws.

Specify number, thickness of door and finish. See pages 1 and 2.



Store Door Handle Locksets

139

WROUGHT BRASS OR BRONZE

WROUGHT STEEL



70081

Canada Design



70281

Portland Design



52980

Barre Design



60281

Portland Design

WROUGHT BRASS OR BRONZE

Set No.	Lock		One Pair Handles				Packed in a Box	Weight Set
	No.	See Page	No.	Size Inches	Grip No.	Projection Inches		
700-991	5262	167	70081	12x3	4410	2 $\frac{1}{8}$	1	5 $\frac{1}{2}$ lbs.
702-991	5262	167	70281	14x3	4416	2 $\frac{3}{8}$	1	5 $\frac{1}{2}$ lbs.
529-990	5262	167	52980	15x3	4451	2 $\frac{5}{8}$	1	5 lbs.

Packed with screws.

WROUGHT STEEL

Set No.	Lock		One Pair Handles				Packed in a Box	Weight Set
	No.	See Page	No.	Size Inches	Grip No.	Projection Inches		
602-933	0186	172	60281	14x3	04416	2 $\frac{1}{8}$	1	5 lbs.

Packed with screws.


Specify number, thickness of door and finish. See pages 1 and 2.




140

Store Door Handle Locksets

CAST BRASS OR BRONZE




74081

74180
Type of 74181

74580



78880



86280

Set No.	Lock		One Pair Handles				Packed in a Box	Weight Set
	No.	See Page	No.	Size Inches	Grip No.	Projection Inches		
740-991	5262	167	74081	15x3	4416	2½	1	7¼ lbs.
741-990	5262	167	74180	15x3	4419	2⅞	1	9 lbs.
741-991	5262	167	74181	16x4	4420	2⅞	1	11⅞ lbs.
745-990	5262	167	74580	16x3	4436	2⅞	1	7 lbs.
788-990	5262	167	78880	16x4	4451	2⅞	1	11⅞ lbs.
862-990	5262	167	86280	18x3¾	4455	2¼	1	10 lbs.

Packed with screws.

Specify number, thickness of door and finish. See pages 1 and 2.


Door Knockers

FOR ENTRANCE DOORS

141




75368



75369



54068



54168

No.	Overall Size Inches	Material and Finish	Plate Size Inches	Projection Inches	Packed in a Box	Weight Each
75368	5 1/4 x 2 1/2	Cast Brass or Bronze	2 x 2	1 1/4	1	3/4 lbs.
75369	5 x 4 1/8	Polished	2 1/4 x 2 1/4	1 9/16	1	1 1/2 lbs.
*54068	6 7/8 x 3 3/4	Hammered	3 3/4 x 2 1/2	1 3/16	1	1 1/2 lbs.
*54168	7 x 3	Hammered	4 3/4 x 2 7/16	1 3/16	1	1 1/6 lbs.

Attached by through bolts through door from opposite side.

*Furnished HPE finish only.

Electric Push Buttons



70061

Canada Design



70261

Portland Design



50761

Somerset Design



54161

Warden Design



80761

Somerset Design

No.	Size Inches	Material and Finish	Packed in a Box	Weight Dozen
*50761	3 x 1	Cast Brass or Bronze		
*54161	4 1/8 x 2 1/8	Hammered	6	1 1/2 lbs.
80761	3 x 1	Hammered	6	1 7/8 lbs.
		Polished	6	1 1/2 lbs.
		Wrought Brass or Bronze		
70061	3 1/8 x 1 5/8	Polished	6	12 oz.
70261	3 1/4 x 1 1/2	Polished	6	12 oz.

All with pearl button. *Furnished HPE finish only.

Packed with screws.

Specify number and finish. See pages 1 and 2.


Letter Drop Plates

143


OPENING $1\frac{1}{2}$ x 7 IN. TO CONFORM TO
POSTAL REGULATIONS FOR OFFICE BUILDINGS



74070 to 74074




Cross section 74074 applied
to $1\frac{3}{4}$ in. hollow metal door
in horizontal position



Cross section 74074 applied to $1\frac{3}{4}$ in.
hollow metal door in vertical position

No.	Letter Drop Plate			Back Plate			Packed in a Box	Weight Dozen
	Size Inches	Material and Finish	Opening Inches	Description	Size Inches	Opening Inches		
		Cast Brass or Bronze						
74070	$3\frac{1}{4}$ x $10\frac{1}{4}$	Polished	$1\frac{1}{2}$ x 7	Without			6	$18\frac{5}{8}$ lbs.
74071	$3\frac{1}{4}$ x $10\frac{1}{4}$	Polished	$1\frac{1}{2}$ x 7	Flat—Cast Brass or Bronze	$3\frac{1}{4}$ x $10\frac{1}{4}$	$2\frac{1}{8}$ x $7\frac{1}{8}$	6	29 lbs.
74072	$3\frac{1}{4}$ x $10\frac{1}{4}$	Polished	$1\frac{1}{2}$ x 7	Hooded—Cast Brass or Bronze	$3\frac{1}{4}$ x $10\frac{1}{4}$	3	40 lbs.
74073	$3\frac{1}{4}$ x $10\frac{1}{4}$	Polished	$1\frac{1}{2}$ x 7	Flat with Wrought Metal Chute	$3\frac{1}{4}$ x $10\frac{1}{4}$	$2\frac{1}{8}$ x $7\frac{1}{8}$	3	$36\frac{3}{8}$ lbs.
74074	$3\frac{1}{4}$ x $10\frac{1}{4}$	Polished	$1\frac{1}{2}$ x 7	Hooded with Wgt. Metal Chute	$3\frac{1}{4}$ x $10\frac{1}{4}$	3	$46\frac{3}{8}$ lbs.

With through bolts which pass through inside plate and door engaging lugs cast on back of letter drop plate.
Wrought metal chutes can be furnished for doors $1\frac{3}{4}$ to $2\frac{1}{4}$ in. thick.



Back Plate for 74071 and 74073



Hooded Back Plate for 74072 and 74074

Specify number and finish. See pages 1 and 2.





CANADA

LOCKS AND ACCESSORIES

MORTISE LOCKS

RIM LOCKS

NIGHT LATCHES

LOCK, CYLINDER AND
KNOB PARTS


KEYS

DOOR KNOBS

LEVER HANDLES

ESCUTCHEONS

CUP HANDLES






 INDEX OF

Item	Page
LOCK INFORMATION	147, 148
7000 STANDARDIZED LOCKS, MORTISE	149, 164
CYLINDER LOCKS:	
Dead, Mortise	181, 183
Exit Fixture, Mortise	169, 170
Front Door, Mortise	165, 166
Store Door, Mortise	167
LATCHES:	
Exit Fixture, Mortise	168
Friction, Mortise	180
Knob, Mortise	179, 180
Knob, Tubular	251
Night Latches, Mortise	185
Night Latches, Rim	186, 188
Sliding Door, Mortise	170, 181
Store Door, Mortise	172
BIT KEY LOCKS:	
Dead, Mortise	182
Front Door, Mortise	171
Inside, Mortise	173, 176
Rim	177
School House, Mortise	177
Store Door, Mortise	172
BATHROOM AND COMMUNICATING	178
RIM BAR BOLTS	184
PADLOCKS	189
CABINET LOCKS	190
CYLINDERS AND PARTS	192, 193
KEY BLANKS	194, 196
STRIKES	197
ELECTRIC DOOR OPENERS	198
LOCK ACCESSORIES	199, 200
SPINDLES	201, 202
DOOR KNOBS	204, 206
LEVER HANDLES	207
ROSES	208
KEY PLATES	209
FLUSH CUP HANDLES	210


Corbin Bitted-Key Locks

147


WITH WARDS AND LEVER TUMBLERS

**Type A**


A lock for inside doors, insuring privacy and a proper degree of security for general use.

**Type C**

A three-tumbler lock with light, resilient spring on the latch bolt and a stronger spring on the knob action.

**Type D**

A heavy, master-keyed, three-tumbler lock, with long, lively, easy spring on the latch bolt and a quick, snappy knob action.

**Type E**

A lock for use with lever handles, having a strong French spring on the hub to insure quick return of the handle to a horizontal position.

CORBIN locks of this type have three methods of changing the key combination. One of these employs projections on the side of keyhole and corresponding cuts or channels in the bit of the key to enable it to enter the lock. In a second, the projections are placed on the inside of the case, and the edge of the bit of the key is cut so that it will pass them. The third is the use of lever tumblers which must be lifted by the key before it can move the bolt, and which the key must be cut to raise to exactly the right point. All of these three factors can be changed in location and form, making a like change in the key necessary. The number of the possible variations is different, depending largely upon the kind of lock, and the number of tumblers, and is increased in many locks by employing end wards, side wards, and lever tumblers in combination in the same lock. Corbin bitted-key locks can be obtained with the maximum number of key changes possible with this type of mechanism and with functions suited to the doors they are required to secure.


All parts of the mechanism are finely proportioned and accurately adjusted. The tumblers, in addition to limiting the use of the key, lock the dead bolt firmly in either the thrown or retracted position.

The roll-backs actuated by the knob have abundant leverage and retract the latch bolt easily, the strong spring giving a quick and positive return when the knob is released. The latch bolt has a lighter resilient spring, and the impact of the latch bolt with the strike causes a minimum of resistance to the closing of the door. Every detail has been carefully developed in order that the user of a Corbin lock may have security, proper service and absence from trouble so long as the lock is in use.


The illustrations show the varying forms of the principal elements in locks of this type. Various functions are added by changing the mechanism, to adapt the locks to the manifold demands of the complex existence of to-day, and Corbin locks can be supplied that will answer perfectly and conveniently any requirement of the most exacting conditions.




Parts of Corbin Locks



Type A



Type D



Cylinder Front Door Lock


Corbin Locks illustrated, with the names of the various parts indicated and the terms "spacing" and "backset" graphically defined.



Standardized Template Cylinder Locks

149

FOR HOLLOW METAL DOORS



HEAVY DUTY SERIES — 7300, 7500, 7700, 7900

All locks of this series have standardized front 8 x 1 1/4 in. adjustable from flat to standard bevel 1/8 in. in 2 in. with minimum thickness of 7/32 in. Strike has a standard size of 5 3/4 x 1 1/4 in. with lip standard height 3 1/2 in. Lock fronts and strikes furnished with 1/2 in. 12 x 24 machine serews. Standardized locks in heavy duty series can also be furnished with front 8 x 1 1/8 in. adjustable from flat to standard bevel 1/8 in. in 2 in. Strike 5 x 1 1/8 in.

NOTE:—When furnished in the 1 1/8 in. series, center line of strike is raised 1/16 in. from center line of front. For detail information see pages: 153, 159.

STANDARD DUTY SERIES — 7000, 7200, 7400, 7600

All locks of this series have standardized front 8 x 1 1/4 in. adjustable from flat to standard bevel 1/8 in. in 2 in. with minimum thickness of 7/32 in. Strike has a standard size of 5 3/4 x 1 1/4 in. with lip standard height 3 1/2 in. Lock fronts and strikes furnished with 1/2 in. 12 x 24 machine serews. This series can also be furnished with strike 5 x 1 1/8 in.

NOTE:—When strike is furnished in the 1 1/8 in. series center line is raised 1/16 in. from center line of front.

INDEX TO LOCKS AVAILABLE IN THESE SERIES

HEAVY DUTY

- 7300 SERIES WITH PLAIN LATCH BOLT 9/16 IN. THROW—REGULAR DEAD BOLT 5/8 IN. THROW. SEE PAGE 159
 7500 SERIES WITH ANTI-FRICTION LATCH BOLT 5/8 IN. THROW—REGULAR DEAD BOLT 5/8 IN. THROW. SEE PAGE 159
 7700 SERIES SAME AS 7300 EXCEPT DEAD BOLT HAS 1 IN. THROW WITH HARDENED STEEL INSERTS. SEE PAGE 159
 7900 SERIES SAME AS 7500 EXCEPT DEAD BOLT HAS 1 IN. THROW WITH HARDENED STEEL INSERTS. SEE PAGE 159

STANDARD DUTY

- 7000 SERIES WITH PLAIN LATCH BOLT 9/16 IN. THROW—REGULAR DEAD BOLT 5/8 IN. THROW. SEE PAGE 153
 7200 SERIES WITH ANTI-FRICTION LATCH BOLT 5/8 IN. THROW—REGULAR DEAD BOLT 5/8 IN. THROW. SEE PAGE 153
 7400 SERIES SAME AS 7000 EXCEPT DEAD BOLT HAS 1 IN. THROW WITH HARDENED STEEL INSERTS. SEE PAGE 153
 7600 SERIES SAME AS 7200 EXCEPT DEAD BOLT HAS 1 IN. THROW WITH HARDENED STEEL INSERTS. SEE PAGE 153

The above standardization applies to locks most generally used for template work but locks and latches not included in this plan can also be furnished to template with machine screws. See following page.

We recommend the use of the standardized line for template work where the desired function can be secured.



INDEX TO LOCKS, NOT STANDARDIZED, FURNISHED TO TEMPLATE WITH
FRONT AS CATALOGUED AND STRIKES $5\frac{3}{4}$ x $1\frac{1}{4}$ IN. OR 5 x $1\frac{1}{8}$ IN.

No.	See Page	Type of Lock
180	168	Exit Bolt Latch
185	168	Exit Bolt Latch
5372	166	Apartment or Public Bldg.
5683	169	Exit Bolt Lock
5683 $\frac{1}{2}$	169	Exit Bolt Lock
5683 $\frac{3}{4}$	169	Exit Bolt Lock
5584	170	Exit Bolt Lock
5585	170	Exit Bolt Lock
5784	170	Exit Bolt Lock
5785	170	Exit Bolt Lock
5111	183	Dead Lock
5112	183	Dead Lock
5113	183	Dead Lock
5211	183	Dead Lock
5212	183	Dead Lock
5213	183	Dead Lock
5192	185	Mortise Night Latch
5193	185	Mortise Night Latch
5592	185	Mortise Night Latch
5593	185	Mortise Night Latch
5597	185	Mortise Night Latch
5598	185	Mortise Night Latch
123	182	Bit Key Dead Lock
132	182	Bit Key Dead Lock
133	182	Bit Key Dead Lock
685 $\frac{3}{4}$	174	Bit Key Knob Lock
364	174	Bit Key Knob Lock
365	175	Bit Key Knob Lock
383	175	Bit Key Knob Lock
303	176	Bit Key Knob Lock
203	176	Bit Key Bathroom Lock
274	177	Bit Key School House Lock
274A	177	Bit Key School House Lock
159 $\frac{1}{2}$	178	Bathroom Lock
159 $\frac{3}{4}$	178	Communicating Lock
29	179	Knob Latch
90	180	Knob Latch

The 7000 Line of Standardized Mortise Locks

These locks offer many advantages to the dealer, architect, contractor and owner of the building.

Whenever specified they assure the same uniform quality throughout the building.

Change in swing of door will not add to the cost of hardware as they are completely reversible.

Alterations to suit new tenants after building is in use, will not present a problem as all functions are interchangeable in the same mortise.

Two-lines—Standard and Heavy Duty.

Standard line with fronts $8 \times 1\frac{1}{16}$ in. for doors not less than $1\frac{3}{4}$ in. thick, with uniform size of case for all locks making them interchangeable in the same mortise. See pages 153 to 158.

Heavy Duty line with fronts $8 \times 1\frac{1}{4}$ in. for doors not less than $1\frac{3}{4}$ in. thick, with uniform size of case for all locks making them interchangeable in the same mortise. Also furnished with fronts $8 \times 1\frac{1}{8}$ in. and strikes $5 \times 1\frac{1}{8}$ in. for hollow metal doors and frames. See pages 159 to 164.

Dimensions of Heavy Duty locks conform to standards adopted for hollow metal door manufacturers. See page 159.

Fronts—All locks with armored fronts for added security. Fronts are adjustable from flat front to standard bevel $\frac{1}{8}$ in. in 2 in.

Reversible—All locks are completely reversible, whether with plain or anti-friction latch bolt or with auxiliary latch, or beveled front.

However on contract work if hand of door and bevel are specified, locks will leave the factory set up to meet these requirements.



Latch Bolts—Extra heavy, long throw cast bronze. Plain latch $\frac{9}{16}$ in. throw. Anti-friction latch $\frac{5}{8}$ in. throw. Compression Spring.

Dead Bolts—Extra heavy, cast bronze. Regular dead bolt $\frac{5}{8}$ in. throw. Also available 1 in. throw with hardened steel inserts.

Hubs—Forged brass for endurance and long operation. Spring is coil torsion type.

Balanced Knob Action—Equal pressure on knob in either direction reduces strain on working parts and assures easy operation.


Interior Parts—All interior operating levers are made from heavy gauge cold formed steel for strength and durability.

All Functions—Every desired standard lock function available.


Two Backsets— $2\frac{1}{2}$ in. or $2\frac{3}{4}$ in. backset available in either line.



The 7000 Line of Standardized Mortise Locks



263




253


Cylinders—Standard and Heavy Duty with No. 263 excepting Class Room Locks Nos. 7035, 7235, 7055, 7255, 7335, 7535, 7355 and 7555 which have cylinders No. 253.

Hotel Locks Nos. 7027, 7227, 7427, 7627, 7327, 7527, 7727 and 7927 which takes cylinder No. 263 special to suit keying.


Locks Nos. 7034, 7234, 7054, 7254, 7334, 7534, 7354 and 7554 require cylinder with pin to prevent inserting too far into case. When cylinders only required for these locks specify lock number.



701



711



721

Strikes—Wrought brass, bronze or aluminum. $5\frac{3}{4} \times 1\frac{1}{4} \times \frac{3}{8}$ in., lip $1\frac{1}{4}$ in. to center.

Also furnished $5 \times 1\frac{1}{8}$ in. when so ordered.

No.

701 For locks with latch bolt only.


711 For locks with dead bolt only.

721 For locks with both latch bolt and dead bolt.

727 Open back strike can be furnished when so ordered. See page 116, type of 606.



Strike for
Rabbeted
Locks



Rabbeted
Lock
applied



Rim piece
for Rabbeted
doors

Rabbeted Doors—Heavy Duty lines only Series 7300 and 7500 can be furnished for rabbeted doors with $\frac{1}{2}$ in. rabbet. In ordering suffix **Rab.** to lock number, thus: 7343**Rab.**, 7551**Rab.** etc.

The rabbet of the door is cut to receive a rim piece $9\frac{1}{4}$ in. long, $\frac{5}{8}$ in. wide and $\frac{1}{2}$ in. thick, which is inserted in the cut on top of the lock front.

The strike for these rabbeted locks is not reversible. State hand.

7000 Line of Mortise Locks

153

Standard Duty for Door at least $1\frac{3}{8}$ in. thick. Front $8 \times 1\frac{1}{16}$ in.


Backset: Regular $2\frac{1}{2}$ in., Special $2\frac{3}{4}$ in. Reversible.

7000 SERIES WITH PLAIN LATCH BOLT $\frac{5}{16}$ IN. THROW—REGULAR DEAD BOLT $\frac{5}{8}$ IN. THROW.


7200 SERIES WITH ANTI-FRICTION LATCH BOLT $\frac{5}{8}$ IN. THROW—REGULAR DEAD BOLT $\frac{5}{8}$ IN. THROW.

7400 SERIES SAME AS 7000 EXCEPT DEAD BOLT HAS 1 IN. THROW WITH HARDENED STEEL INSERTS.

7600 SERIES SAME AS 7200 EXCEPT DEAD BOLT HAS 1 IN. THROW WITH HARDENED STEEL INSERTS.




Strike



7000 SERIES

PLAIN LATCH BOLT



7200 SERIES

ANTI-FRICTION LATCH BOLT

Case Cast Iron, Green Wrinkle Lacquer Finish, size $5\frac{3}{4} \times 3\frac{3}{4} \times \frac{7}{8}$ in.

Armored Front ... Front forged Brass $8 \times 1\frac{1}{16} \times \frac{7}{32}$ in. with armored scalp Wrought Brass, Bronze or Aluminum. Front can be adjusted from flat front to standard bevel $\frac{1}{8}$ in. in 2 in.—any hand.

Backset $2\frac{1}{2}$ in. regular—special $2\frac{3}{4}$ in. Width of case is $1\frac{1}{4}$ in. more than backset.

Spacing Center of Knob to center of cylinder $3\frac{5}{8}$ in.
Center of Knob to center of thumb knob $2\frac{7}{16}$ in.

Latch Bolts Cast Bronze. Plain $\frac{5}{8} \times 1$ in. $\times \frac{5}{16}$ in. throw.
Anti-friction $\frac{5}{8} \times 1$ in. $\times \frac{5}{8}$ in. throw.

Dead Bolts Cast Bronze. Regular—Plain— $1\frac{1}{32} \times 1\frac{1}{4}$ in. $\times \frac{5}{8}$ in. throw.
With hardened steel inserts $1\frac{9}{32} \times 1\frac{1}{4}$ in. $\times 1$ in. throw.

Hubs Forged Brass $\frac{3}{8} \times \frac{5}{16}$ in. swivel or $\frac{5}{16}$ in. to suit lock.

Springs TS—compression and coiled torsion.

Strikes Wrought Brass, Bronze or Aluminum, $5\frac{3}{4}$ in. $\times 1\frac{1}{4}$ in. $\times \frac{3}{32}$ in. thick.
Lip, $1\frac{1}{4}$ in. to center.

Cylinders No. **263** Brass or Bronze for all except Locks Nos. **7035**, **7055**, **7235** and **7255** which take cylinder No. **253** and locks Nos. **7027**, **7227**, **7427** and **7627** which take cylinder No. **263** special to suit keying.

Keys Two Nickel Silver Class **77** to each lock. Master key Class **077**.

For the different functions available, see following pages.

Specify finish. See pages 1 and 2.



7000 Line of Mortise Locks

Standard Duty for Doors at least $1\frac{3}{8}$ in. thick. Front $8 \times 1\frac{1}{16}$ in.Backset: Regular $2\frac{1}{2}$ in., Special $2\frac{3}{4}$ in. Reversible.**7000 SERIES WITH PLAIN LATCH BOLT $\frac{5}{8}$ IN. THROW—REGULAR DEAD BOLT $\frac{5}{8}$ IN. THROW.****7200 SERIES WITH ANTI-FRICTION LATCH BOLT $\frac{5}{8}$ IN. THROW—REGULAR DEAD BOLT $\frac{5}{8}$ IN. THROW.****7400 SERIES SAME AS 7000 EXCEPT DEAD BOLT HAS 1 IN. THROW WITH HARDENED STEEL INSERTS.****7600 SERIES SAME AS 7200 EXCEPT DEAD BOLT HAS 1 IN. THROW WITH HARDENED STEEL INSERTS.****For Communicating Doors****Nos. 7000 and 7200** Latch Bolt operated by Knobs from either side.

Split Dead Bolt operated by Thumb Knobs from both sides; each locking against opposite side.

Dead Locks For Storage Rooms, Closet**Nos. 7011 and 7411** Dead Bolt operated by Key from outside only.**Dead Locks For Store Doors, Entrance Doors, Storage Rooms, etc.****Nos. 7012 and 7412** Dead Bolt operated by Key from either side.**Nos. 7013 and 7413** Dead Bolt operated by Key from the outside and by Thumb Knob from the inside.**For Bathroom or Toilet Doors****Nos. 7020 and 7220** Latch Bolt operated by Knobs from either side.

Dead Bolt operated by Thumb Knob from inside only. Can be furnished to operate by Emergency Key from outside when so ordered.

For Storage Rooms, Closet Doors**Nos. 7021, 7221, 7421 and 7621** Latch Bolt operated by Knob from either side.

Dead Bolt operated by Key from outside only.

For Entrance Doors, Store Doors, Communicating Doors**Nos. 7022, 7222, 7422 and 7622** Latch Bolt operated by Knobs from either side.

Dead Bolt operated by Key from either side.

For Entrance Doors, Store Doors, Storage Rooms, etc.**Nos. 7023, 7223, 7423 and 7623** Latch Bolt operated by Knobs from either side.

Dead Bolt operated by Key from the outside and by Thumb Knob from the inside.

Special Purpose Lock**Nos. 7023 $\frac{1}{4}$, 7223 $\frac{1}{4}$** same as Nos. 7023, etc., except that thumb knob will retract dead bolt from inside but will not project it.**Special Purpose Locks****Nos. 7025, 7225, 7425 and 7625** Latch Bolt by Key from the outside and Knob from the inside. Outside Knob always rigid.

Dead Bolt operated by Key from the outside and Thumb Knob from the inside.

For Hotel Corridor Doors**Nos. 7027, 7227, 7427 and 7627** Latch Bolt operated by Knob from the inside and by Guest Key, Master Key and Grand Master Key from the outside except when Dead Bolt is projected from the inside. Outside Knob always rigid.

The Dead Bolt is operated by Thumb Knob only from the inside. When Dead Bolt is projected by Thumb Knob from the inside all Keys except Display Key and Emergency Key are inoperative.

Furnished with Display Key and Emergency Key which are operative at all times and which act as a Shutout Key against all other Keys. Can be furnished with Button Indicator.

Special Purpose Locks**Nos. 7042, 7242, 7442 and 7642** Latch Bolt operated by Key from the outside at all times and by Knobs from either side except when outside Knob is locked by Stop in Face.

Dead Bolt operated by Key from either side.

For Entrance and Apartment Doors**Nos. 7043, 7243, 7443 and 7643** Latch Bolt operated by Key from outside at all times and by Knob from either side except when outside Knob is locked by Stop in Face.

Dead Bolt operated by Key from outside and by Thumb Knob from the inside.

For further description, dimensions, etc., see page 153.

Specify finish. See pages 1 and 2.



7000 Line of Mortise Locks

155

Standard Duty for Doors at least 1 $\frac{3}{8}$ in. thick. Front 8 x 1 $\frac{1}{16}$ in.


Backset: Regular 2 $\frac{1}{2}$ in., Special 2 $\frac{3}{4}$ in. Reversible.

7000 SERIES WITH PLAIN LATCH BOLT $\frac{9}{16}$ IN. THROW—REGULAR DEAD BOLT $\frac{5}{8}$ IN. THROW.


7200 SERIES WITH ANTI-FRICTION LATCH BOLT $\frac{5}{8}$ IN. THROW—REGULAR DEAD BOLT $\frac{5}{8}$ IN. THROW.

7400 SERIES SAME AS 7000 EXCEPT DEAD BOLT HAS 1 IN. THROW WITH HARDENED STEEL INSERTS.


7600 SERIES SAME AS 7200 EXCEPT DEAD BOLT HAS 1 IN. THROW WITH HARDENED STEEL INSERTS.




7000 Plain Latch
7200 Anti-Friction Latch




7011, 7411




7012, 7412




7013, 7413




7020 Plain Latch
7220 Anti-Fric. Latch




7021 Plain Latch 7421
7221 Anti-Fric. Latch 7621




7022 Plain Latch 7422
7222 Anti-Fric. Latch 7622




7023 Plain Latch 7423
7223 Anti-Fric. Latch 7623
7023 $\frac{1}{4}$, etc.




7025 Plain Latch 7425
7225 Anti-Fric. Latch 7625



7027 Plain Latch 7427
7227 Anti-Fric. Latch 7627



7042 Plain Latch 7442
7242 Anti-Fric. Latch 7642



7043 Plain Latch 7443
7243 Anti-Fric. Latch 7643

Specify finish. See pages 1 and 2.



7000 Line of Mortise Locks

Standard Duty for Doors at least 1 $\frac{3}{8}$ in. thick. Front 8 x 1 $\frac{1}{16}$ in.

Backset: Regular 2 $\frac{1}{2}$ in., Special 2 $\frac{3}{4}$ in. Reversible.

7000 SERIES WITH PLAIN LATCH BOLT

7200 SERIES WITH ANTI-FRICTION LATCH BOLT

Latch For Passage and Closet Doors

Nos. 7010 and 7210 Latch Bolt operated by Knob from either side at all times.

For Office and Vestibule Doors

Nos. 7031 and 7231 Latch Bolt operated by Key from outside at all times and by Knobs from either side except when outside Knob is locked by Stop in Face.

For Conference Rooms, Dark Rooms, etc.

Nos. 7033 and 7233 Latch Bolt operated by Knobs from either side except when outside Knob is locked by Stop in Face and by Key from outside except when Thumb Knob inside has been turned, dead locking Latch Bolt and making all Keys inoperative.

For Office and Apartment Vestibule Entrance Doors, Rest Rooms, etc.

Nos. 7034 and 7234 Latch Bolt operated by Key from outside at all times and by Knobs from either side except when outside Knob is locked from inside by Master Key only unless otherwise specified.

For Classroom Doors

Nos. 7035 and 7235 Latch Bolt by Knobs from either side except when outside Knob is locked by Key from outside. Inside Knob always operative.

For Storage Rooms, Closets

Nos. 7037 and 7237 Latch Bolt operated by Key from the outside and Knob from the inside. Outside Knob always rigid.

For Office and Vestibule Doors

Nos. 7051 and 7251 Latch Bolt operated by Key from outside at all times and by Knobs from either side except when outside Knob is locked by Stop in Face.
*Has Auxiliary Latch.

For Office and Apartment Vestibule Entrance Doors, Rest Rooms

Nos. 7054 and 7254 Latch Bolt operated by Key from outside at all times and by Knobs from either side except when outside Knob is locked from inside by Master Key only unless otherwise specified.
*Has Auxiliary Latch.

For Classroom Doors

Nos. 7055 and 7255 Latch Bolt by Knobs from either side except when outside Knob is locked by Key from outside. Inside Knob always operative.
*Has Auxiliary Latch.

For Storage Rooms, Closets, etc.

Nos. 7057 and 7257 Latch Bolt by Key from the outside and Knob from the inside. Outside Knob always rigid.
*Has Auxiliary Latch.

For further descriptions, dimensions, etc., see page 153.

*Auxiliary Latch automatically Dead Locks the Latch Bolt so that it cannot be forced back by end pressure when the door is closed.

Specify finish. See pages 1 and 2.



7000 Line of Mortise Locks


157

Standard Duty for Doors at least 1 3/8 in. thick. Front 8 x 1 1/16 in.


Backset: Regular 2 1/2 in., Special 2 3/4 in. Reversible.

7000 SERIES WITH PLAIN LATCH BOLT


7200 SERIES WITH ANTI-FRICTION LATCH BOLT




7010 Plain Latch
7210 Anti-Fric. Latch




7031 Plain Latch
7231 Anti-Fric. Latch




7033 Plain Latch
7233 Anti-Fric. Latch




7034 Plain Latch
7234 Anti-Fric. Latch




7035 Plain Latch
7235 Anti-Fric. Latch




7037 Plain Latch
7237 Anti-Fric. Latch




7051 Plain Latch
7251 Anti-Fric. Latch



7054 Plain Latch
7254 Anti-Fric. Latch




7055 Plain Latch
7255 Anti-Fric. Latch




7057 Plain Latch
7257 Anti-Fric. Latch

Specify finish. See pages 1 and 2.


7000 Line of Mortise Locks

Standard Duty for use with Entrance Handles on Doors at least 1 $\frac{3}{8}$ in. thickFront 8x1 $\frac{1}{16}$ in.—Reversible—Backset: Regular 2 $\frac{1}{2}$ in., Special 2 $\frac{3}{4}$ in.**7000 SERIES WITH PLAIN LATCH BOLT $\frac{1}{16}$ IN. THROW, REGULAR DEAD BOLT $\frac{5}{8}$ IN. THROW.****7200 SERIES WITH ANTI-FRICTION LATCH BOLT $\frac{5}{8}$ IN. THROW, REGULAR DEAD BOLT $\frac{5}{8}$ IN. THROW.****7400 SERIES SAME AS 7000 EXCEPT THAT DEAD BOLT HAS 1 IN. THROW AND HARDENED STEEL INSERTS.****7600 SERIES SAME AS 7200 EXCEPT THAT DEAD BOLT HAS 1 IN. THROW AND HARDENED STEEL INSERTS.**


7047 Plain Latch
7247 Anti-Fric. Latch




7048 Plain Latch 7448
7248 Anti-Fric. Latch 7648




7071 Plain Latch
7271 Anti-Fric. Latch



7072 Plain Latch 7472
7272 Anti-Fric. Latch 7672



7073 Plain Latch 7473
7273 Anti-Fric. Latch 7673



7088 Plain Latch 7488
7288 Anti-Fric. Latch 7688

For Residence and Apartment Vestibule Doors

Nos. 7047 and 7247 Latch Bolt operated by thumb piece from outside, except when thumb piece is locked by stops in face, and by knob from the inside and key from the outside at all times.

For Residence and Apartment Entrance Doors

Nos. 7048, 7243, 7448 and 7648 Latch bolt operated by thumb piece from the outside except when thumb piece is locked by stops in face and by knob from the inside and key from the outside at all times.

Dead bolt by key from the outside and thumb knob from the inside.

For Apartment and Public Building Vestibule Doors

Nos. 7071 and 7271 Latch bolt operated by key from the outside at all times and by thumb piece from either side except when outside thumb piece is locked by stops in face.

For further descriptions, dimensions, etc., see page 153.

For Apartment and Public Building Entrance Doors

Nos. 7072, 7272, 7472 and 7672 Latch bolt operated by key from the outside at all times and by thumb piece from either side, except when outside thumb piece is locked by stops in face.

Dead bolt by key from either side.

For Apartment and Public Building Entrance Doors

Nos. 7073, 7273, 7473 and 7673 Latch bolt operated by key from the outside at all times and by thumb piece from either side, except when outside thumb piece is locked by stops in face.

Dead bolt by key from the outside and thumb knob from the inside.

For Store Doors and Entrance Doors for Public Buildings

Nos. 7088, 7288, 7488 and 7688 Latch bolt operated by thumb piece from either side.

Dead bolt by key from either side.

Specify finish. See pages 1 and 2.



7000 Line of Mortise Locks

159

Rev. 6-1-57

Heavy Duty for Doors at least $1\frac{3}{4}$ in. thick. *Front $8 \times 1\frac{1}{4}$ in.


Backset: Regular $2\frac{3}{4}$ in., Special $2\frac{1}{2}$ in. Reversible.

7300 SERIES WITH PLAIN LATCH BOLT $\frac{5}{16}$ IN. THROW—REGULAR DEAD BOLT $\frac{5}{8}$ IN. THROW.

7500 SERIES WITH ANTI-FRICTION LATCH BOLT $\frac{5}{8}$ IN. THROW—REGULAR DEAD BOLT $\frac{5}{8}$ IN. THROW.

7700 SERIES SAME AS 7300 EXCEPT DEAD BOLT HAS 1 IN. THROW WITH HARDENED STEEL INSERTS.

7900 SERIES SAME AS 7500 EXCEPT DEAD BOLT HAS 1 IN. THROW WITH HARDENED STEEL INSERTS.



Case Cast Iron, Green Wrinkle Lacquer finish, size $5\frac{3}{4} \times 4 \times \frac{7}{8}$ in.

***Armored Front** .. Front Forged Brass $8 \times 1\frac{1}{4} \times \frac{7}{32}$ in. with armored scalp Wrought Brass, Bronze or Aluminum. Front can be adjusted from flat front to standard bevel $\frac{1}{8}$ in. in 2 in.—any hand.

Backset Regular $2\frac{3}{4}$ in. Special $2\frac{1}{2}$ in. width of Case, $1\frac{1}{4}$ in. more than backset.

Spacing Center of knob to center of cylinder $3\frac{5}{8}$ in.
Center of knob to center of thumb knob $2\frac{7}{16}$ in.

Latch Bolts Cast Bronze, Plain, $\frac{5}{8} \times 1$ in. $\times \frac{9}{16}$ in. throw.
Anti-Friction $\frac{5}{8} \times 1$ in. $\times \frac{5}{8}$ in. throw.

Dead Bolts Cast Bronze, Regular—plain $1\frac{9}{32} \times 1\frac{1}{4}$ in. by $\frac{5}{8}$ in. throw.
With hardened steel inserts $1\frac{9}{32} \times 1\frac{1}{4}$ in. $\times 1$ in. throw.

Hubs Forged Brass, $\frac{3}{8} \times \frac{5}{16}$ in. swivel or $\frac{5}{16}$ in. to suit lock.

Springs TS—compression and coiled torsion.

***Strikes** Wrought Brass, Bronze or Aluminum, $5\frac{3}{4} \times 1\frac{1}{4}$ in. $\times \frac{3}{32}$ in. thick. Lip $1\frac{1}{4}$ in. to center.

Cylinders No. 263 Brass or Bronze, for all except locks Nos. 7335, 7355, 7535 and 7555 which take cylinder No. 253 and locks 7327, 7527, 7727 and 7927 which take cylinder 263 special to suit keying.

Keys Two Nickel Silver keys Class 77 to each lock. Master key Class 077.

Dimensions conform to standards adopted for hollow metal door manufacturers. See page 149.

For the different functions available see following pages.

Heavy duty locks can be furnished rabbeted front in ordering, affix **RAB.** to number, thus: **7343RAB.** Regular backset $2\frac{3}{4}$ in. short side; special backset $2\frac{1}{2}$ in. short side. $\frac{1}{2}$ inch rabbet. Strikes for rabbeted locks not reversible, state hand.

*Can be furnished with front $8 \times 1\frac{1}{4}$ in. and strike $5 \times 1\frac{1}{8}$ in. For hollow metal doors and frames when so ordered.

Specify finish. See pages 1 and 2.



7000 Line of Mortise Locks

Heavy Duty for Doors at least 1 3/4 in. thick. *Front 8 x 1 1/4 in.

Backset: Regular 2 3/4 in., Special 2 1/2 in., Reversible.

7300 SERIES WITH PLAIN LATCH BOLT 5/8 IN. THROW—REGULAR DEAD BOLT 5/8 IN. THROW.

7500 SERIES WITH ANTI-FRICTION LATCH BOLT 5/8 IN. THROW—REGULAR DEAD BOLT 5/8 IN. THROW.

7700 SERIES SAME AS 7300 EXCEPT DEAD BOLT HAS 1 IN. THROW WITH HARDENED STEEL INSERTS.

7900 SERIES SAME AS 7500 EXCEPT DEAD BOLT HAS 1 IN. THROW WITH HARDENED STEEL INSERTS.

For Communicating Doors

Nos. 7300 and 7500 Latch Bolt operated by Knobs from either side.

Split Dead Bolt operated by Thumb Knobs from both sides; each locking against opposite side.

Dead Locks For Storage Rooms, Closet

Nos. 7311 and 7711 Dead Bolt operated by Key from outside only.

Dead Locks For Store Doors, Entrance Doors, Storage Rooms, etc.

Nos. 7312 and 7712 Dead Bolt operated by Key from either side.

Nos. 7313 and 7713 Dead Bolt operated by Key from the outside and by Thumb Knob from the inside.

For Bathroom or Toilet Doors

Nos. 7320 and 7520 Latch Bolt operated by Knobs from either side.

Dead Bolt operated by Thumb Knob from inside only. Can be furnished to operate by Emergency Key from outside when so ordered.

For Storage Rooms, Closet Doors

Nos. 7321, 7521, 7721 and 7921 Latch Bolt operated by Knob from either side.

Dead Bolt operated by Key from outside only.

For Entrance Doors, Store Doors, Communicating Doors

Nos. 7322, 7522, 7722 and 7922 Latch Bolt operated by Knobs from either side.

Dead Bolt operated by Key from either side.

For Entrance Doors, Store Doors, Storage Rooms, etc.

Nos. 7323, 7523, 7723 and 7923 Latch Bolt operated by Knobs from either side.

Dead Bolt operated by Key from the outside and by Thumb Knob from the inside.

*Can be furnished with front 8 x 1 1/4 in. and strike 5 x 1 1/4 in. for hollow metal doors and frames when so ordered. For further description, dimensions, etc., see page 159.

Specify finish. See pages 1 and 2.

Special Purpose Lock

Nos. 7323 1/4, 7523 1/4 same as Nos. 7323, etc., except that thumb knob will retract dead bolt from inside but will not project it.

Special Purpose Locks

Nos. 7325, 7525, 7725 and 7925 Latch Bolt by Key from the outside and Knob from the inside. Outside Knob always rigid.

Dead Bolt operated by Key from the outside and Thumb Knob from the inside.

For Hotel Corridor Doors

Nos. 7327, 7527, 7727 and 7927 Latch Bolt operated by Knob from the inside and by Guest Key, Master Key and Grand Master Key from the outside except when Dead Bolt is projected from the inside. Outside Knob always rigid.

The Dead Bolt is operated by Thumb Knob only from the inside. When Dead Bolt is projected by Thumb Knob from the inside all Keys except Display Key and Emergency Key are inoperative.

Furnished with Display Key and Emergency Key which are operative at all times and which act as a Shutout against all other Keys. Can be furnished with Button Indicator.

Special Purpose Locks

Nos. 7342, 7542, 7742 and 7942 Latch Bolt operated by Key from the outside at all times and by Knobs from either side except when outside Knob is locked by Stop in Face.

Dead Bolt operated by Key from either side.

For Entrance and Apartment Doors.

Nos. 7343, 7543, 7743 and 7943 Latch Bolt operated by Key from outside at all times and by Knob from either side except when outside Knob is locked by Stop in Face.

Dead Bolt operated by Key from outside and by Thumb Knob from the inside.



7000 Line of Mortise Locks

161

Heavy Duty for Doors at least 1 3/4 in. thick. *Front 8 x 1 1/4 in.


Backset: Regular 2 3/4 in., Special 2 1/2 in. Reversible.

7300 SERIES WITH PLAIN LATCH BOLT 9/16 IN. THROW—REGULAR DEAD BOLT 5/8 IN. THROW.


7500 SERIES WITH ANTI-FRICTION LATCH BOLT 5/8 IN. THROW—REGULAR DEAD BOLT 5/8 IN. THROW.

7700 SERIES SAME AS 7300 EXCEPT DEAD BOLT HAS 1 IN. THROW WITH HARDENED STEEL INSERTS.


7900 SERIES SAME AS 7500 EXCEPT DEAD BOLT HAS 1 IN. THROW WITH HARDENED STEEL INSERTS.




7300 Plain Latch
7500 Anti-Fric. Latch




7311, 7711




7312, 7712




7313, 7713




7320 Plain Latch
7520 Anti-Fric. Latch




7321 Plain Latch 7721
7521 Anti-Fric. Latch 7921




7322 Plain Latch 7722
7522 Anti-Fric. Latch 7922




7323 Plain Latch 7723
7523 Anti-Fric. Latch 7923
7323 1/4, etc.




7325 Plain Latch 7725
7525 Anti-Fric. Latch 7925



7327 Plain Latch 7727
7527 Anti-Fric. Latch 7927



7342 Plain Latch 7742
7542 Anti-Fric. Latch 7942



7343 Plain Latch 7743
7543 Anti-Fric. Latch 7943

*Can be furnished with front 8 x 1 1/4 in. and strike 5 x 1 1/4 in. for hollow metal doors and frames when so ordered.

Specify finish. See pages 1 and 2.



7000 Line of Mortise Locks

Heavy Duty for Doors at least 1 $\frac{3}{4}$ in. thick. †Front 8 x 1 $\frac{1}{4}$ in.

Backset: Regular 2 $\frac{3}{4}$ in., Special 2 $\frac{1}{2}$ in. Reversible.

7300 SERIES WITH PLAIN LATCH BOLT

7500 SERIES WITH ANTI-FRICTION LATCH BOLT

Latch For Passage and Closet Doors

Nos. 7310 and 7510 Latch Bolt operated by Knob from either side at all times.

For Office and Vestibule Doors

Nos. 7331 and 7531 Latch Bolt operated by Key from outside at all times and by Knobs from either side except when outside Knob is locked by Stop in Face.

For Conference Rooms, Dark Rooms, etc.

Nos. 7333 and 7533 Latch Bolt operated by Knobs from either side except when outside Knob is locked by Stop in Face and by Key from outside except when Thumb Knob inside has been turned, dead locking Latch Bolt and making all Keys inoperative.

For Office and Apartment Vestibule Entrance Doors, Rest Rooms, etc.

Nos. 7334 and 7534 Latch Bolt operated by Key from outside at all times and by Knobs from either side except when outside Knob is locked from inside by Master Key only unless otherwise specified.

For Classroom Doors

Nos. 7335 and 7535 Latch Bolt by Knobs from either side except when outside Knob is locked by Key from outside. Inside Knob always operative.

For further descriptions, dimensions, etc., see page 159.

*Auxiliary Latch automatically Dead Locks the Latch Bolt so that it cannot be forced back by end pressure when the door is closed.

†Can be furnished with front 8 x 1 $\frac{1}{8}$ in. and strike 5 x 1 $\frac{1}{8}$ in. for hollow metal doors and frames when so ordered.

Specify finish. See pages 1 and 2.

For Storage Rooms, Closets

Nos. 7337 and 7537 Latch Bolt operated by Key from the outside and Knob from the inside. Outside Knob always rigid.

For Office and Vestibule Doors

Nos. 7351 and 7551 Latch Bolt operated by Key from outside at all times and by Knobs from either side except when outside Knob is locked by Stop in Face.

*Has Auxiliary Latch.

For Office and Apartment Vestibule Entrance Doors, Rest Rooms

Nos. 7354 and 7554 Latch Bolt operated by Key from outside at all times and by Knobs from either side except when outside Knob is locked from inside by Master Key only unless otherwise specified.

*Has Auxiliary Latch.

For Classroom Doors

Nos. 7355 and 7555 Latch Bolt by Knobs from either side except when outside Knob is locked by Key from outside. Inside Knob always operative.

*Has Auxiliary Latch.

For Storage Rooms, Closets, etc.

Nos. 7357 and 7557 Latch Bolt by Key from the outside and Knob from the inside. Outside Knob always rigid.

*Has Auxiliary Latch.



7000 Line of Mortise Locks











163

Heavy Duty for Doors at least 1 3/4 in. thick. *Front 8 x 1 1/4 in.

Backset: Regular 2 3/4 in., Special 2 1/2 in. Reversible.

7300 SERIES WITH PLAIN LATCH BOLT

7500 SERIES WITH ANTI-FRICTION LATCH BOLT

7310 Plain Latch
7510 Anti-Fric. Latch7331 Plain Latch
7531 Anti-Fric. Latch7333 Plain Latch
7533 Anti-Fric. Latch7334 Plain Latch
7534 Anti-Fric. Latch7335 Plain Latch
7535 Anti-Fric. Latch7337 Plain Latch
7537 Anti-Fric. Latch7351 Plain Latch
7551 Anti-Fric. Latch7354 Plain Latch
7554 Anti-Fric. Latch7355 Plain Latch
7555 Anti-Fric. Latch7357 Plain Latch
7557 Anti-Fric. Latch

*Can be furnished with front 8 x 1 1/8 in. and strike 5 x 1 1/8 in. for hollow metal doors and frames when so ordered.

Specify finish. See pages 1 and 2.



7000 Line of Mortise Locks

Heavy Duty for use with Entrance Handles on Doors at least 1 3/4 in. thick


*Front 8x1 1/4 in.—Reversible—Backset: Regular 2 3/4 in., Special 2 1/2 in.

7300 SERIES WITH PLAIN LATCH BOLT 5/8 IN. THROW. REGULAR DEAD BOLT 5/8 IN. THROW.


7500 SERIES WITH ANTI-FRICTION LATCH BOLT 5/8 IN. THROW. REGULAR DEAD BOLT 5/8 IN. THROW.

7700 SERIES SAME AS 7300 EXCEPT THAT DEAD BOLT HAS 1 IN. THROW AND HARDENED STEEL INSERTS.


7900 SERIES SAME AS 7500 EXCEPT THAT DEAD BOLT HAS 1 IN. THROW AND HARDENED STEEL INSERTS.




7347 Plain Latch
7547 Anti-Fric. Latch




7348 Plain Latch 7748
7548 Anti-Fric. Latch 7948




7371 Plain Latch
7571 Anti-Fric. Latch



7372 Plain Latch 7772
7572 Anti-Fric. Latch 7972



7373 Plain Latch 7773
7573 Anti-Fric. Latch 7973



7388 Plain Latch 7788
7588 Anti-Fric. Latch 7988

For Residence and Apartment Vestibule Doors

Nos. 7347 and 7547 Latch Bolt operated by thumb piece from outside, except when thumb piece is locked by stops in face, and by knob from the inside and key from the outside at all times.

For Residence and Apartment Entrance Doors

Nos. 7348, 7548, 7748 and 7948 Latch bolt operated by thumb piece from the outside except when thumb piece is locked by stops in face and by knob from the inside and key from the outside at all times.

Dead bolt by key from the outside and thumb knob from the inside.

For Apartment and Public Building Vestibule Doors

Nos. 7371 and 7571 Latch bolt operated by key from the outside at all times and by thumb piece from either side except when outside thumb piece is locked by stops in face.

*Can be furnished with front 8 x 1 1/4 in. and strike 5 x 1 1/8 in. for hollow metal doors and frames when so ordered. For further description, dimensions, etc., see page 159.

For Apartment and Public Building Entrance Doors

Nos. 7372, 7572, 7772 and 7972 Latch bolt operated by key from the outside at all times and by thumb piece from either side, except when outside thumb piece is locked by stops in face.

Dead bolt by key from either side.

For Apartment and Public Building Entrance Doors

Nos. 7373, 7573, 7773 and 7973 Latch bolt operated by key from the outside at all times and by thumb piece from either side, except when outside thumb piece is locked by stops in face.

Dead bolt by key from the outside and thumb knob from the inside.

For Store Doors and Entrance Doors for Public Buildings

Nos. 7388, 7588, 7788 and 7988 Latch bolt operated by thumb piece from either side.

Dead bolt by key from either side.

Specify finish. See pages 1 and 2.




7000 Line of Mortise Locks

164A


HEAVY DUTY HOTEL CORRIDOR LOCK

FOR DOORS AT LEAST 1 1/4 INCH THICK, FRONT 8 x 1 1/4 INCH, BACKSET 2 3/4 INCH




7529
Reversible

For Other Lock Details
See 7500 Series — Page 159



7529



7539

Operation

No. **7529** Latch bolt operated by knob from the inside and by Guest Key, Master Key and Grand Master Key from the outside except when Dead Bolt is projected from the inside. Outside knob always rigid.

The dead bolt is operated by thumb knob from the inside. When dead bolt is projected by thumb knob from the inside all keys except Emergency Key are inoperative.

Furnished with an Emergency Key which is operative at all times and which acts as a Shutout Key against all other Keys. Can be furnished with Button Indicator.

When so ordered can be furnished with Display Key which is operative at all times and which will shutout all keys except Emergency Key.

No. **7539** same as **7529** except that inside knob will retract latch bolt only.

No.	Front	Bolts	Backset Inches	Cylinder Cast Brass or Bronze	2 Keys Nickel-silver Class	Master Key Class	Weight Each
7529	Cast Brass or Bronze						
	Polished						
7539	Cast Bronze	Cast Bronze	2 3/4	253 1/4 H	74	074	3 1/4 Lbs.
	Polished	Cast Bronze	2 3/4	253 1/4 H	74	074	3 1/4 Lbs.

One in a box, with screws.

When above locks are required to replace old locks it is advisable to furnish us with a complete sample of the old lockset including trim and strike so that we can furnish set to fit into the old mortises with a minimum of patching.

While these locks are reversible, contractor can save time in applying if hand of door is specified on order.


Specify number and finish. See pages 1 and 2.



164B

Mortise Store Door Locks

BALL BEARING CYLINDER



5565, 5566

*Reversible

CaseJapanned iron, $5\frac{1}{4}$ x $3\frac{3}{4}$ x $\frac{3}{4}$ in.**Front**8 x $1\frac{1}{4}$ in.**Spacing** $4\frac{3}{16}$ in. latch trip to center of cylinder.**Latch Bolt**Easy spring, $\frac{1}{2}$ in. throw.**Dead Bolt** $\frac{1}{2}$ in. throw.**Strike**Lip to center, $1\frac{1}{4}$ in.

Operation **5566:** Latch Bolt by Thumb Piece from either side except when outside Thumb Piece is locked by stop in front; then by key only outside. Dead Bolt by key from both sides. Continuous turn of key will withdraw both Latch and Dead Bolts. Inside Thumb Piece always operative.

5565: Same operation as No. 5566 except one Cylinder. Dead Bolt by Turn Piece inside and Cylinder outside.

Master-keying ..Can be master-keyed with other cylinder locks.

No.	Front	Bolts	Backset Inches	Cylinder Cast Brass or Bronze	2 Keys Nickel-silver Class	Changes	Packed in a Box	Weight Each
5566	Cast Brass or Bronze Polished	Cast Bronze Polished	$2\frac{3}{4}$	2 No. 253	77	Unlimited	1	$3\frac{1}{2}$ lbs.
5565			$2\frac{3}{4}$	1 No. 253	77	Unlimited	1	$3\frac{3}{4}$ lbs.

Packed with screws. *Can be furnished bevel front $\frac{1}{8}$ in 2 inches. State hand.



5567

*Reversible

CaseJapanned iron, $5\frac{1}{4}$ x $3\frac{3}{4}$ x $\frac{3}{4}$ in.**Front**8 x $1\frac{1}{4}$ in.**Spacing** $4\frac{3}{16}$ in. latch trip to center of cylinder.**Latch Bolt**Easy spring, $\frac{1}{2}$ in. throw.**Strike**Lip to center, $1\frac{1}{4}$ in.

Operation **5567:** Latch Bolt by Thumb Piece from either side except when outside Thumb Piece is locked by stop in front, then by key only outside. Inside Thumb Piece always operative.

Master-keying ..Can be master-keyed with other cylinder locks.

No.	Front	Bolts	Backset Inches	Cylinder Cast Brass or Bronze	2 Keys Nickel-silver Class	Changes	Packed in a Box	Weight Each
5567	Cast Brass or Bronze Polished	Cast Bronze Polished	$2\frac{3}{4}$	2 No. 253	77	Unlimited	1	$3\frac{1}{2}$ lbs.

Packed with screws. *Can be furnished bevel front $\frac{1}{8}$ in 2 inches. State hand.


Specify number and finish. See pages 1 and 2.



Mortise Front Door Locks

164C

BALL BEARING CYLINDER
FOR NARROW STILE DOORS



5422, 5423
Reversible

CaseJapanned iron, $6\frac{1}{4} \times 2\frac{1}{8} \times 1\frac{3}{16}$ in. On special backsets width of case is $\frac{7}{8}$ in. more than backset.

Front8 x $1\frac{1}{8}$ in.

Spacing $4\frac{1}{16}$ in. center of knob hub to center of cylinder,
 $4\frac{1}{16}$ in. center of knob hub to center of thumb knob.

Latch BoltEasy spring $\frac{1}{16}$ in. throw.

Dead Bolt $\frac{1}{2}$ in. throw.

HubsBronze, $\frac{5}{16}$ in.

StrikeLip to center $1\frac{1}{4}$ in.


Operation5423: Latch bolt by Knobs or levers from either side. Dead bolt by Key from outside and by thumb turn from inside.

5422: Same as 5423 except: Latch bolt by levers or Knobs either side. Dead bolt by Key from both sides.

Master-keying ..Can be master-keyed with other cylinder locks.

No.	Front	Bolts	Backset		Cylinders Cast Brass or Bronze	2 Keys Nickel-silver Class	Changes	Packed in a Box	Weight Each
			Regular Inches	Special Inches					
5423	Cast Brass or Bronze	Cast Bronze	$1\frac{1}{4}$	$\{1\frac{1}{2}, 1\frac{3}{4}\}$	1 No. 253	77	Unlimited	1	$2\frac{1}{2}$ lbs.
5422	Polished	Polished	$1\frac{1}{4}$	$\{2, 2\frac{1}{4}\}$	2 No. 253	77	Unlimited	1	$2\frac{3}{4}$ lbs.
	Polished	Polished		$\{1\frac{1}{2}, 1\frac{3}{4}\}$					
				$\{2, 2\frac{1}{4}\}$					

Packed with screws. Specify thickness of door.



5431 5464
Reversible

CaseJapanned iron, $6\frac{1}{4} \times 2\frac{1}{8} \times \frac{7}{8}$ in. On special backsets width of case is $\frac{7}{8}$ in. greater than backset.

Front8 x $1\frac{1}{8}$ in.

Spacing $4\frac{1}{16}$ in. center of knob hub to center of cylinder.

Latch BoltEasy spring, $\frac{1}{2}$ in. throw.

HubBronze, $\frac{1}{16}$ in. swivel.

StrikeLip to center, $1\frac{1}{4}$ in.

OperationNo. 5431 latch bolt operated by key from the outside at all times and by Knobs or levers from either side except when outside Knob or lever is locked by stops in face.

No. 5464 latch bolt operated by key only from outside and by Thumb Turn 2248 from inside. Key in inside cylinder retracts latch bolt and auxiliary latch and holds them retracted. Auxiliary latch deadlocks main latch against end pressure.

Master-keying ..Can be master-keyed with other cylinder locks.

No.	Front	Bolts	Backset		Cylinders Cast Brass or Bronze	2 Keys Nickel-silver Class	Changes	Packed in a Box	Weight Each
			Regular Inches	Special Inches					
5431	Cast Brass or Bronze	Cast Bronze	$1\frac{1}{4}$	$\{1\frac{1}{2}, 1\frac{3}{4}\}$	1 No. 253	77	Unlimited	1	$2\frac{1}{2}$ lbs.
5464	Polished	Polished	$1\frac{1}{4}$	& 2	2 No. 253	77	Unlimited	1	$2\frac{3}{4}$ lbs.
	Polished	Polished		None					

Packed with screws. Specify thickness of door.


Specify number and finish. See pages 1 and 2.



164D

Mortise Exit Door Locks

BALL BEARING CYLINDER



5680, 5682
Not Reversible

CaseJapanned iron, $5\frac{7}{8}$ x 4 x 1 in. Beveled $\frac{1}{8}$ in 2 in.

Front8 x $1\frac{3}{8}$ in.

Spacing $4\frac{3}{4}$ in. latch trip to center of cylinder.

Latch BoltRoll back type.

StrikeLip to center, $1\frac{1}{4}$ in.

Operation**5680:** The roll back feature assures positive action even if latch is bound in strike by warped door. When door is closing, main latch bolt retracts into lock case, but when opening latch bolt rolls back. Auxiliary latch deadlocks main latch against end pressure. With door in closed position, not locked by key, a slight pressure on outside thumb lift or any point on inside cross bar, releases locking mechanism, allowing the latch bolt to pivot or roll back into lock case. Key or thumb lift does not retract latch bolt at any time. Key locks or unlocks outside thumb lift only.

5682: Same as 5680 except there is no outside thumb peice and consequently no outside operation except by key.

These locks for use with fire exit bolt nos. 76, $76\frac{1}{2}$, $76\frac{3}{4}$, 77, $77\frac{1}{2}$ and $77\frac{3}{4}$ only.

No.	Front	Bolts	Backset Inches	Cylinder Cast Brass or Bronze	2 Keys Nickel-silver Class	Master Key Class	Changes	Packed in a Box	Weight Each
5680	Cast Brass	Cast							
5682	or Bronze	Bronze							
	Polished	Polished	$2\frac{3}{4}$	No. 253	77	077	Unlimited	1	3 lbs.
	Polished	Polished	$2\frac{3}{4}$	No. 253	77	077	Unlimited	1	3 lbs.

Packed with screws.


Specify number and finish. See pages 1 and 2.



Mortise Front Door Locks

165

BALL BEARING CYLINDER



5243

Reversible

CaseJapanned Iron, $5\frac{1}{2}$ x $3\frac{3}{8}$ x $\frac{3}{4}$ in.

Front8 x $1\frac{1}{8}$ in.

Spacing $3\frac{3}{8}$ in. center of knob hub to center of cylinder
 $3\frac{3}{8}$ in. center of knob hub to center of thumb knob

Latch BoltEasy spring $\frac{7}{16}$ in. throw

Dead Bolt $\frac{1}{2}$ in. throw

HubsBronze, $\frac{3}{8}$ x $\frac{5}{16}$ swivel and $\frac{3}{16}$ in.


StrikeLip to center $1\frac{1}{4}$ in.

OperationLatch bolt by knob from either side and by key from outside at all times. Dead bolt by key from outside and by thumb knob from inside. Outside knob is locked by stops in face.

Master-keying ..Can be master-keyed with other cylinder locks.

No.	Front	Type Front	Bolts	Backset		Cylinders Cast Brass or Bronze	2 Keys Nickel-silver Class	Changes	Packed in a Box	Weight Each
				Regular Inches	Special Inches					
5243	Cast Brass or Bronze Polished	Flat	Cast Bronze Polished	2 $\frac{3}{4}$	1 No. 253	77	Unlimited	1	3 $\frac{1}{4}$ lbs.

Packed with screws. Specify thickness of door.



15443

*Not reversible

For use with Lever Handles on Narrow Stile Doors.

Case $5\frac{1}{2}$ x $2\frac{1}{2}$ x $\frac{3}{4}$ in.

Front8 x $1\frac{1}{8}$ in. bevelled $\frac{1}{8}$ in. 2 in.

Spacing $3\frac{3}{8}$ in. center of knob hub to center of cylinder.
 $3\frac{3}{8}$ in. center of knob hub to center of thumb knob.

Latch BoltEasy spring $\frac{7}{16}$ in. throw.

Dead Bolt $\frac{1}{2}$ in. throw.

HubBronze $\frac{3}{8}$ x $\frac{5}{16}$ swivel and $\frac{3}{16}$ in.

StrikesLip to center $1\frac{1}{4}$ in.

OperationLatch bolt by key from the outside at all times and lever handles from either side, except when outside lever is locked by stops in face.

Dead bolt by key from the outside and by the thumb knob from the inside.

Master-keying ..Can be master-keyed with other cylinder locks.

No.	Front	Type Front	Bolts	Backset		Cylinders Cast Brass or Bronze	2 Keys Nickel-silver Class	Changes	Packed in a Box	Weight Each
				Regular Inches	Special Inches					
5443	Cast Brass or Bronze Polished	Flat	Cast Bronze Polished	1 $\frac{1}{2}$	1	1 No. 253	77	Unlimited	1	2 $\frac{1}{2}$ lbs.
15443	Polished	Rab'td	Polished	1 $\frac{1}{2}$ long side	1 No. 253	77	Unlimited	1	3 lbs.

Packed with screws.

*Specify hand and thickness of door. Width of case for 1 in. backset 2 in.


Specify number and finish. See pages 1 and 2.



Mortise Front Door Locks

For Door Handle Outside and Knob Inside

BALL BEARING CYLINDER



5743

Reversible

Case $5\frac{1}{4}$ x $3\frac{3}{4}$ x $\frac{3}{4}$ in.Front 8 x $1\frac{1}{8}$ in.Spacing $3\frac{3}{8}$ in. from center of knob hub to center of thumb knob.
 $4\frac{1}{4}$ in. latch trip to center of cylinder.Latch Bolt Easy spring, $\frac{7}{16}$ throw.Dead Bolt $\frac{1}{2}$ in. throw.Hub Bronze, $\frac{5}{16}$ in.Strike Lip to center, $1\frac{1}{4}$ in.Operation Latch bolt by thumb piece from the outside except when thumb piece is locked by stops in face and by knob from the inside and key from the outside at all times.
Dead bolt by key from the outside and thumb knob from the inside.

Master-keying ..Can be master-keyed with other cylinder locks.

No.	Front	Bolts	Backset Inches	Cylinder Cast Brass or Bronze	2 Keys Nickel-silver Class	Changes	Packed in a Box	Weight Each
5743	Cast Brass or Bronze Polished	Cast Bronze Polished	2 $\frac{3}{4}$	1 No. 253	77	Unlimited	1	3 $\frac{1}{2}$ lbs.

Packed with screws. Specify thickness of door.


FOR DOOR HANDLES BOTH SIDES

Case Japanned iron, $5\frac{1}{4}$ x $3\frac{3}{4}$ x $\frac{3}{4}$ in.Front 3 x $1\frac{1}{8}$ in., beveled $\frac{1}{8}$ in 2 in.Spacing $4\frac{1}{4}$ in. latch trip to center of cylinder.Latch Bolt Anti-friction, $\frac{1}{2}$ in. throw.Strike Lip to center, $1\frac{1}{2}$ in.

Auxiliary Latch.. Automatically locks the latch bolt so that it cannot be forced back by end pressure when the door is locked, but does not prevent the key, or thumb latches from operating the latch bolt. Retracting latch bolt by any means also retracts the auxiliary latch.

Operation With hold-back feature. Latch bolt is operated by thumb latch from outside except when thumb latch is locked from the inside by master-key only, unless otherwise ordered. The thumb latch inside operates latch bolt at all times. The key in outside cylinder will operate latch bolt at all times.

Master-keying ..Can be master-keyed with other cylinder locks.



5372

*Not Reversible

No.	Front	Bolts	Backset Inches	Cylinders Cast Brass or Bronze	2 Keys Nickel-silver Class	Changes	Weight Each
5372	Cast Brass or Bronze Polished	Cast Bronze Polished	2 $\frac{3}{4}$	1 No. 253 1 No. 253 Spec.	77	Unlimited	3 $\frac{1}{2}$ lbs.

Packed with screws. Specify hand and thickness of door.


Specify number and finish. See pages 1 and 2.



Mortise Front Door Locks

165

BALL BEARING CYLINDER



5243

Reversible

CaseJapanned Iron, 5½ x 3½ x ¾ in.

Front8 x 1½ in.

Spacing3⅝ in. center of knob hub to center of cylinder
3⅞ in. center of knob hub to center of thumb knob

Latch BoltEasy spring ⅞ in. throw

Dead Bolt½ in. throw

HubsBronze, ¾ x ⅝ swivel and ⅜ in.


StrikeLip to center 1¼ in.

OperationLatch bolt by knob from either side and by key from outside at all times. Dead bolt by key from outside and by thumb knob from inside. Outside knob is locked by stops in face.

Master-keying ..Can be master-keyed with other cylinder locks.

No.	Front	Type Front	Bolts	Backset		Cylinders Cast Brass or Bronze	2 Keys Nickel-silver Class	Changes	Packed in a Box	Weight Each
				Regular Inches	Special Inches					
5243	Cast Brass or Bronze Polished	Flat	Cast Bronze Polished	2¾	1 No. 253	77	Unlimited	1	3¼ lbs.

Packed with screws. Specify thickness of door.



15443

5443

*Not reversible

For use with Lever Handles on Narrow Stile Doors.

Case5½ x 2½ x ¾ in.

Front8 x 1½ in. bevelled ⅜ in. 2 in.

Spacing3⅝ in. center of knob hub to center of cylinder.
3⅞ in. center of knob hub to center of thumb knob.

Latch BoltEasy spring ⅞ in. throw.

Dead Bolt½ in. throw.

HubBronze ¾ x ⅝ swivel and ⅜ in.

StrikesLip to center 1¼ in.

OperationLatch bolt by key from the outside at all times and lever handles from either side, except when outside lever is locked by stops in face.

Dead bolt by key from the outside and by the thumb knob from the inside.

Master-keying ..Can be master-keyed with other cylinder locks.

No.	Front	Type Front	Bolts	Backset		Cylinders Cast Brass or Bronze	2 Keys Nickel-silver Class	Changes	Packed in a Box	Weight Each
				Regular Inches	Special Inches					
5443	Cast Brass or Bronze Polished	Flat	Cast Bronze Polished	1½	1	1 No. 253	77	Unlimited	1	2½ lbs.
15443	Polished	Rab'td	Polished	1½ long side	1 No. 253	77	Unlimited	1	3 lbs.

Packed with screws.

*Specify hand and thickness of door. Width of case for 1 in. backset 2 in.

Specify number and finish. See pages 1 and 2.



5262

CaseJapanned iron, 5 x 3 $\frac{3}{4}$ x $\frac{3}{4}$ in.

Front8 x 1 $\frac{1}{8}$ in.

Spacing4 $\frac{1}{16}$ in. latch trip to center of cylinder.

Latch BoltEasy spring, $\frac{7}{16}$ in. throw.

Dead Bolt $\frac{1}{2}$ in. throw.

StrikeLip to center, 1 $\frac{1}{4}$ in.

OperationLatch bolt by thumb piece from either side.
Dead bolt by key from either side.
Latch bolt can be held retracted by turn of key. Suffix A to
number as 5262A.

Master-keying ..Can be master-keyed with other cylinder locks.

No.	Front	Bolts	Backset Inches	Cylinder Cast Brass or Bronze	2 Keys Nickel-silver Class	Changes	Packed in a Box	Weight Each
5262	Cast Brass or Bronze Polished	Cast Bronze Polished	2¾	2 No. 253	77	Unlimited	1	3½ lbs.

Packed with screws.

Button Indicators

INDICATORS TO INDICATE IF ROOM IS OCCUPIED

Indicators are not included in the price of locks.



Type B

Type B (Patented). When locks are supplied with this indicating device, the outside escutcheon has a "Push Button" attachment.

For use with locks operated by key as Nos. 7027, 7227, 7427, 7627, 7327, 7527, 7727 and 7927.

When the door is locked from the inside by the key, the "Push Button" cannot be depressed, thus indicating that the room is occupied. This type of indicator is superior to all other similar devices for use with locks operated by key.

Specify number and finish. See pages 1 and 2.



168

Mortise Exit Latches



180

Reversible


Case.....Japanned iron, $4\frac{1}{4}$ x $3\frac{3}{8}$ x $\frac{3}{4}$ in.Front..... $6\frac{3}{8}$ x $1\frac{1}{8}$ in.Latch Bolt..... $\frac{5}{16}$ in. throw.Hub.....Bronze, $\frac{3}{16}$ in.Strike.....Lip to center, $1\frac{1}{4}$ in.

Auxiliary Latch. Automatically locks the latch bolt, so that it cannot be forced back by end pressure when the door is closed, but does not prevent exit bar from operating latch bolt.

Operation......By exit bar or push lever from the inside only at all times.

No.	Front	Bolt	Backset Inches	Packed in a Box	Weight Each
180	Cast Brass or Bronze Polished	Cast Bronze Polished	2 $\frac{3}{4}$	1	2 $\frac{1}{4}$ lbs.

Packed with screws.



185

Reversible

Case.....Japanned iron, $4\frac{1}{4}$ x $3\frac{3}{8}$ x $\frac{3}{4}$ in.Front..... $6\frac{3}{8}$ x $1\frac{1}{8}$ in.Latch Bolt..... $\frac{5}{16}$ in. throw.Strike.....Lip to center, $1\frac{1}{4}$ in.

Auxiliary Latch. Automatically locks the latch bolt, so that it cannot be forced back by end pressure when the door is closed, but does not prevent exit bar from operating latch bolt.

Operation......By exit bar or push lever from the inside only at all times.

No.	Front	Bolt	Backset Inches	Packed in a Box	Weight Each
185	Cast Brass or Bronze Polished	Cast Bronze Polished	2 $\frac{3}{4}$	1	2 $\frac{1}{4}$ lbs.

Packed with screws.


When ordered for double doors, they are furnished with open back strike. Specify whether for single or double doors.

Specify number and finish. See pages 1 and 2.



Mortise Exit Door Locks

169



5683

Type of 5683½, 5683¾

*Not Reversible

BALL BEARING CYLINDER

Case.....5 x 3¾ x ¾ in.

Front.....7½ x 1¼ x 1½ in. Beveled ¼ in 2 in.

Spacing.....4¾ in. latch trip to center of cylinder.

Latch Bolt.....Long swing latch bolt, ⅝ in. throw, encased in housing to prevent foreign matter being forced into works.

Strike.....Cast box 4½ x 1¼ in. Lip to center 1¼ in.

Auxiliary Latch..When door is locked on the outside the auxiliary latch automatically locks the latch bolt so that it cannot be forced back by end pressure, but does not interfere with the normal operation of latch bolt.

Master-keying...Can be Master-keyed with other Cylinder Locks.

No.	Front	Bolts	Backset Inches	Cylinders Cast Brass or Bronze	2 Keys Nickel-silver Class	Master-key Class	Changes	Packed in a Box	Weight Each
5683	Cast Brass or Bronze	Cast Bronze							
5683½	Polished	Polished	2¾	1 No. 253	77	077	Unlimited	1	3½ lbs.
5683¾	Polished	Polished	2¾	2 No. 253	77	077	Unlimited	1	3½ lbs.
5683¾	Polished	Polished	2¾	1 No. 253	77	077	Unlimited	1	3½ lbs.

Packed with screws.

OPERATIONS

No. 5683—By Exit Push Bar from the Inside at all times. When the Thumb Piece of Outside Handle is locked, a turn of key in outside Cylinder toward face of Lock to first click, releases Locking Mechanism, permitting entrance from outside by means of Thumb Piece. A further turn of Key in same direction to the second click, sets mechanism so that first operation of Latch Bolt by Exit Push Bar from the inside or Thumb Piece from the outside retracts Latch Bolt and locks it in retracted position, permitting door to be operated on Push and Pull basis. A turn of Key in opposite direction to the limit of operation again projects the Latch Bolt and locks the Outside Thumb Piece.

No. 5683½—By Exit Push Bar from Inside at all times and cylinders both sides. When in locked position outside cylinder operated by key. A turn of inside cylinder key towards face of lock to first click unlocks the outside thumb piece. A further turn of key in same direction prepares lock so that the first operation of cross bar or thumb piece holds the bolt retracted. A turn of inside cylinder key in opposite direction locks outside thumb piece.

No. 5683¾—By Exit Push Bar from Inside at all times, Latch bolt operated by key only from the outside. When latch bolt is locked in retracted position by means of dogging key, the door can be opened from outside by door pull.

Strike as illustrated furnished with above locks when ordered for single doors. When ordered for double doors, they are furnished with open back strike.

*Specify hand and thickness of door. Specify whether for single or double doors.


Specify number and finish. See pages 1 and 2.



170

Mortise Exit Door Locks

BALL BEARING CYLINDER



5584 to 5785

*Not reversible

Case..... $5\frac{1}{4} \times 3\frac{13}{16} \times \frac{7}{8}$ in.Front..... $8 \times 1\frac{1}{4}$ in. Beveled $\frac{1}{8}$ in 2 in.Spacing..... $3\frac{3}{8}$ in. center of knob to center of cylinder.Latch Bolt.....Anti-friction $\frac{9}{16}$ in. throw.Strike.....Lip to center $1\frac{1}{4}$ in.

Auxiliary Latch. When door is locked on the outside the auxiliary latch automatically locks the latch bolt so that it cannot be forced back by end pressure, but does not interfere with the normal operation of latch bolt.

Operation...... No. 5584, by Exit Bar or Push Lever from Inside and by key or knob from outside. Key in inside cylinder locks the outside knob or holds the bolt retracted.

No. 5585, by Exit Bar or Push Lever from Inside at all times and from outside by knob. Knob outside is automatically locked when bolt is retracted by key. A reverse turn of the key releases the knob. When knob is deadlocked the bolt may be held retracted by pushing it inward and turning the key.

Master-keying....No. 5784 same as No. 5584 except operated by handle and thumb piece outside.

No. 5785 same as No. 5585 except operated by handle and thumb piece outside.


No.	Front	Bolts	Backset Inches	Cylinders Cast Brass or Bronze	2 Keys Nickel-silver Class	Master-key Class	Changes	Packed in a Box	Weight Each
	Cast Brass or Bronze	Cast Bronze							
5584	Polished	Polished	$2\frac{3}{4}$	2 No. 253	77	077	Unlimited	1	$3\frac{3}{8}$ lbs.
5585	Polished	Polished	$2\frac{3}{4}$	1 No. 253	77	077	Unlimited	1	$3\frac{3}{4}$ lbs.
5784	Polished	Polished	$2\frac{3}{4}$	2 No. 253	77	077	Unlimited	1	$3\frac{3}{8}$ lbs.
5785	Polished	Polished	$2\frac{3}{4}$	1 No. 253	77	077	Unlimited	1	$3\frac{3}{4}$ lbs.

Packed with screws.

*Specify hand and thickness of door. Specify whether for single or double doors.

Mortise Sliding Door Locks

BALL BEARING CYLINDER



1385, 1385½

Case..... $3\frac{1}{4} \times 3\frac{5}{8} \times \frac{3}{4}$ in.Front..... $5\frac{5}{16} \times 1\frac{5}{16}$ in.

Operation...... No. 1385: Dead Bolt by Key in Outside Cylinder. Inside by cup handle No. 053.

No. 1385½: Dead Bolt by Key from either side.

Cup Handle No. 053—2 in. dia. depth of mortise $\frac{9}{16}$ in., projection $\frac{1}{16}$ in., spindle $\frac{3}{16}$ in.

Master-keying.... Can be master keyed with other cylinder locks.

No.	Front	Bolt	Backset Inches	Cylinders Cast Brass or Bronze	2 Keys Nickel-silver Class	Changes	Packed in a Box	Weight Each
	Cast Brass or Bronze	Cast Bronze						
1385	Polished	Polished	$2\frac{3}{4}$	1 No. 253	77	Unlimited	1	$1\frac{3}{4}$ lbs.
1385½	Polished	Polished	$2\frac{3}{4}$	2 No. 253	77	Unlimited	1	2 lbs.


Packed with screws.

Specify number and finish. See pages 1 and 2.



Mortise Front Door Locks

171




0251

Reversible

CaseJapanned iron, $4\frac{5}{8}$ x $3\frac{3}{16}$ x $1\frac{1}{16}$ in.**Front**7 x 1 in.**Spacing**3 in. center of knob hub to center of key post.**Latch Bolt**Easy spring, $\frac{1}{2}$ in. throw.**Dead Bolt** $\frac{1}{2}$ in. throw.**Hub**Iron, $\frac{3}{8}$ x $\frac{5}{16}$ in. swivel.**Strike**Lip to center, $1\frac{1}{4}$ in.**Operation**Latch bolt by knobs from either side except when outside knob is locked by stops in face and by key from outside at all times.
Dead bolt by key from either side.

No.	Front	Bolts	Backset Inches	2 Keys N-P Steel Class	Tumblers	Changes	Packed in a Box	Weight Dozen
0251	Wrought Steel Plated	Cast Iron Brass Plated	2½	80%	2	48	1	24½ lbs.

Packed with screws.



0261

Reversible

CaseJapanned iron, $4\frac{5}{8}$ x $3\frac{3}{16}$ x $1\frac{1}{16}$ in.**Front**7 x 1 in.**Spacing**3 in. center of knob hub to center of key post.**Latch Bolt**Easy spring, $\frac{1}{2}$ in. throw.**Dead Bolt** $\frac{1}{2}$ in. throw.**Hub**Iron, $\frac{5}{16}$ in.**Strike**Lip to center, $1\frac{1}{4}$ in.**Operation**Latch bolt by knob from either side. Dead bolt by key from either side.

No.	Front	Bolts	Backset Inches	2 Keys N-P Steel Class	Tumblers	Changes	Packed in a Box	Weight Dozen
0261	Wrought Steel Plated	Cast Iron Brass Plated	2½	80%	2	48	1	22½ lbs.

Packed with screws.

Specify number and finish. See pages 1 and 2.



172

Mortise Store Door Locks



0186

Reversible

Case $4\frac{3}{4}$ x $3\frac{1}{4}$ x $1\frac{1}{16}$ in.Front $6\frac{1}{2}$ x 1 in.Spacing $2\frac{13}{16}$ in.Latch Bolt Easy spring $\frac{7}{16}$ in. throw.Dead Bolt $\frac{7}{16}$ in. throw.Strike Lip to center, $1\frac{1}{2}$ in.


Operation Latch bolt by thumb piece from either side. Dead bolt by key from either side at all times.

No.	Front	Bolts	Backset Inches	2 Keys N.P. Steel Class	Tumblers	Changes	Packed in a Box	Weight Each
0186	Wrought Steel Plated	Cast Iron Brass Plated	$2\frac{3}{4}$	$96\frac{1}{4}$	4	36	1	$1\frac{7}{8}$ lbs.

Packed with screws.

Mortise Door Latches

FOR DOOR HANDLES BOTH SIDES



177

Reversible

Case Japanned iron, $2\frac{1}{4}$ x $3\frac{1}{2}$ x $1\frac{1}{16}$ in.Front $4\frac{1}{4}$ x $1\frac{1}{8}$ in.Latch Bolt Easy spring, $\frac{7}{16}$ in. throw.Strike Lip to center, $1\frac{1}{4}$ in.

Operation Latch bolt operated by thumb piece of handle from either side.

No.	Front	Bolt	Backset Inches	Packed in a Box	Weight Each
177	Cast Brass or Bronze Polished	Cast Bronze Polished	$2\frac{7}{16}$	1	$1\frac{1}{8}$ lbs.

Packed with screws.

Specify number and finish. See pages 1 and 2.





285, 0285
Reversible

CaseJapanned iron, 3 $\frac{5}{8}$ x 3 $\frac{3}{8}$ x $\frac{3}{16}$ in.
FrontFlat, 5 $\frac{1}{4}$ x $\frac{7}{8}$ in.
 Rabbeted, 5 $\frac{3}{4}$ x 1 $\frac{1}{16}$ in., $\frac{1}{2}$ in. rabbet.
Spacing2 $\frac{1}{16}$ in. center of knob hub to center of key post.
Latch BoltType A construction, $\frac{3}{8}$ in. throw.
Dead Bolt $\frac{7}{16}$ in. throw.
HubIron, $\frac{5}{16}$ in.
StrikeLip to center, 1 in.
OperationLatch bolt by knobs from either side.
 Dead bolt by key from either side.

No.	Front	Type Front	Bolts	Backset Inches	1 Key Class	Tumbler	Changes	Packed in a Box	Weight Dozen
285 1285	Wrought Brass or Bronze Polished Polished	Flat Rabbeted	Bronze Polished Polished	2 3/4 2 3/4 Longside	179 1/4 179 1/4	1 Cast 1 Cast	12 12	6 6	12 1/4 lbs. 16 lbs.
0285 01285	Wrought Steel Plated Plated	Flat Rabbeted	Iron Brass Plated Brass Plated	2 3/4 2 3/4 Longside	179 1/4 179 1/4	1 Cast 1 Cast	12 12	6 6	12 lbs. 15 lbs.


Packed with screws.

Specify number and finish. See pages 1 and 2.



174

Mortise Knob Locks



685, 685 3/4

Reversible

CaseJapanned iron, 3 3/4 x 3 1/2 x 1/16 in.

Front5 1/2 x 7/8 in.

Spacing2 3/16 in. center of knob hub to center of key post.

Latch BoltEasy spring, type C, 3/8 in. throw

Dead Bolt1/2 in. throw.

HubIron, 1/16 in.

StrikeLip to center, 1 in.

OperationLatch bolt by knobs from either side.

Dead bolt by key from either side.

Master-keying ... No. 685 3/4 MK master-keyed in 5 sets of 50 each, the 250 all different, with a master-key to pass each set, and when so ordered, with a grand master-key to pass all.

Master-keyed with other locks having 195 class master-key.

No.	Front	Bolts	Backset Inches	1 Key N-P Steel Class	Master- key Class	Tumblers	Changes	Packed in a Box	Weight Dozen
685 685 3/4	Cast Brass or Bronze Polished Polished	Cast Bronze Polished Polished	2 3/4 2 3/4	179 3/4 179 3/4	... 195	1 Wrought 3 Wrought	24 250	6 6	16 lbs. 16 1/4 lbs.

Packed with screws.

Mortise Knob Locks

Case3 3/8 x 3 3/8 x 3/8 in.

Front5 1/2 x 1.

Spacing2 3/16 in. center of knob hub to center of key post.

Latch BoltEasy spring, type C, 3/8 in. throw.

Dead Bolt1/16 in. throw.

HubBronze, 1/16 in.

StrikeLip to center, 1 in.

OperationLatch bolt by knobs from either side.

Dead bolt by key from either side.

Master-keying ... Master-keyed in 4 sets of 160 each, or 16 sets of 40 each, the 640 all different, with master keys to pass each set, and when so ordered, with grand master-key to pass all. Master-keyed with other locks having 080 7/8 class master-key.



364

Reversible

No.	Front	Bolts Cast Bronze	Backset Inches	1 Key N-P Steel Class	Master- key Class	Tumblers	Changes	Packed in a Box	Weight Dozen
364	Cast Brass or Bronze Polished	Polished	2 3/8	80 7/8	080 7/8	3	640	6	20 1/2 lbs.

Packed with screws.

Specify number and finish. See pages 1 and 2.




Mortise Knob Locks

175



1365

Not reversible




365

Reversible

CaseJapanned iron, $4\frac{1}{4} \times 3\frac{1}{2} \times \frac{5}{8}$ in.**Front**Flat $6\frac{1}{4} \times 1$ in.Rabbeted $6\frac{1}{2} \times 1\frac{3}{16}$ in. $\frac{1}{2}$ in. rabbet, beveled $\frac{1}{8}$ in. 2 in.**Spacing** $2\frac{5}{8}$ in. center of knob hub to center of key post.**Latch Bolt**Easy spring, type D, $\frac{3}{8}$ in. throw.**Dead Bolt** $\frac{7}{16}$ in. throw**Hub**Bronze, $\frac{5}{16}$ in.**Strike**Flat, lip to center, $1\frac{1}{8}$ in. Rabbeted, lip to center 1 in.**Operation**Latch bolt by knobs from either side.
Dead bolt by key from either side.**Master-keying** ... Master-keyed in 4 sets of 160 each, or in 16 sets of 40 each, the 640 all different with master keys to pass each set, and when so ordered, with a grand master to pass all. Master-keyed with other locks having 0807 $\frac{1}{8}$ class master key.

No.	Front	Type Front	Bolts	Backset Inches	1 Key N-P Steel Class	Master-key Class	Tumblers	Changes	Packed in a Box	Weight Dozen
365	Cast Brass or Bronze		Cast Bronze							
*1365	Polished	Flat	Polished	$2\frac{3}{4}$	$80\frac{7}{8}$	0807 $\frac{1}{8}$	3	640	6	21 $\frac{1}{2}$ lbs.
	Polished	Rabt'd	Polished	$2\frac{3}{4}$ long side	$80\frac{7}{8}$	0807 $\frac{1}{8}$	3	640	6	23 lbs.

Packed with screws. *Specify hand of door.



383

Reversible

CaseJapanned iron, $3\frac{3}{8} \times 3\frac{3}{8} \times 1\frac{1}{16}$ in.**Front** $5\frac{3}{8} \times 1\frac{1}{16}$ in.**Spacing** $2\frac{3}{16}$ in. center of knob hub to center of key post.**Latch Bolt**Easy spring, type D, $\frac{1}{16}$ in. throw.**Dead Bolt** $1\frac{5}{16}$ in. throw.**Hub**Bronze $\frac{5}{16}$ in.**Strike**Lip to center, $1\frac{1}{8}$ in.**Operation**Latch bolt by knobs from either side. Dead bolt by key from either side.**Master-keying** ... Master keyed in one set of 2100 all different, or in sets as desired with master key to pass each set, and when so ordered, with grand master key to pass all. Master-keyed with other locks having 0306 class master key.


No.	Front	Bolts Cast Bronze	Backset Inches	1 Key N-P Steel Class	Master-key Class	Tumblers	Changes	Packed in a Box	Weight Dozen
383	Cast Brass or Bronze								
	Polished	Polished	$2\frac{9}{16}$	306	0306	3	2100	6	20 lbs.

Packed with screws.

Specify number and finish. See pages 1 and 2.



Mortise Knob Locks



303

Reversible


CaseJapanned Iron, $4\frac{3}{4}$ x $3\frac{1}{2}$ x $1\frac{1}{16}$ in.Front $6\frac{3}{16}$ x $1\frac{1}{8}$ in.Spacing $2\frac{9}{16}$ in. center of knob hub to center of key post.Latch BoltEasy spring, type D, $\frac{7}{16}$ in. throw.Dead Bolt $1\frac{1}{32}$ in. throw.HubsBronze, $\frac{5}{16}$ in.StrikeLip to center $1\frac{1}{8}$ in.

OperationLatch Bolt by knobs from either side. Dead bolt by key from either side.

Master-keying ... Master-keyed in one set of 2100 all different, or in sets as desired with master key to pass each set and when so ordered, with grand master key to pass all. Master-keyed with other locks having 0306 class master key.

No.	Front	Bolts	Backset Inches	1 Key N-P Steel Class	Master-key Class	Tumblers	Changes	Packed in a Box	Weight Dozen
303	Cast Brass or Bronze Polished	Cast Bronze Polished	$2\frac{1}{16}$	306	0306	3	2100	6	$21\frac{1}{2}$ lbs.

Packed with screws.



203

Reversible

CaseJapanned Iron, $4\frac{3}{4}$ x $3\frac{1}{2}$ x $\frac{5}{8}$ in.Front $6\frac{3}{8}$ x $1\frac{1}{16}$ in.Spacing $3\frac{1}{8}$ in. center of knob hub to center of key post. $1\frac{1}{16}$ in. center of knob hub to center of thumb knob hub.Latch BoltEasy spring, type D $\frac{7}{16}$ in. throw.Dead Bolt $1\frac{1}{32}$ in. throw.HubsBronze $\frac{5}{16}$ and $\frac{3}{16}$ in.StrikeLip to center, $1\frac{1}{8}$ in.

OperationLatch bolt by knobs from either side. Dead bolt operated at all times by key from outside and by turn knob inside.

Master-keying ... Master-keyed in one set of 2100 all different, or in sets as desired with master key to pass each set, and when so ordered with grand master key to pass all. Master-keyed with other locks having 0306 class master key.

No.	Front	Bolts	Backset Inches	1 Key N-P Steel Class	Master-key Class	Tumblers	Changes	Packed in a Box	Weight Dozen
203	Cast Brass or Bronze Polished	Cast Bronze Polished	$2\frac{1}{16}$	306	0306	3	2100	6	24 lbs.


Packed with screws.

Specify number and finish. See pages 1 and 2.



Rim Knob Locks

177



961

Case $3\frac{3}{8} \times 3\frac{1}{4} \times 1\frac{1}{16}$ in.Spacing $2\frac{3}{16}$ in.Latch Bolt $\frac{3}{8}$ in. throw.Dead Bolt $\frac{7}{16}$ in. throw.Hub $\frac{7}{16}$ in. iron.Rim Strike $3\frac{3}{8} \times \frac{3}{4} \times \frac{3}{4}$ in. cast iron japanned.

Operation Latch bolt by knobs from either side except when it is locked by stop in case. Dead bolt by key from either side.

No.	Case	Bolts	Backset Inches	1 Key Class	Tumblers	Changes	Packed in a Box	Weight Dozen
961	Cast Iron Japanned	Cast Iron	2 $\frac{3}{8}$	N-P Cast Iron 011 $\frac{1}{4}$	1	6	6	12 $\frac{1}{4}$ lbs.

Packed with screws, plate escutcheon and screws for knob rose.

Mortise School House Lock



274

Type of 274A

Reversible

Case Japanned iron, $5\frac{3}{8} \times 3\frac{3}{8} \times \frac{3}{4}$ in. width of case for 5" BS $6\frac{1}{8}$ in.Front $8 \times 1\frac{1}{8}$ in.Spacing $2\frac{3}{8}$ in. center of knob hub to center of key post.Latch Bolt Easy spring, $\frac{1}{2}$ in. throw.Hub Bronze, $\frac{3}{8} \times \frac{5}{16}$ in. swivel.Strike Lip to center, $1\frac{1}{4}$ in.

Operation By knob from either side. Outer knob may be locked or released by key from either side. When locked auxiliary bolt automatically dead locks the latch bolt, but when released auxiliary bolt is held retracted. Inside knob is operative at all times.

Master-keying ... Master-keyed in one set of 2100 all different, or in sets as desired with master key to pass each set, and when so ordered with a grand master key to pass all. Master-keyed with other locks having 0306 class master key.

No.	Front	Bolts	Backset		1 Key N-P Steel Class	Master-key Class	Tumblers	Changes	Packed in a Box	Weight Dozen
			Regular Inches	Special Inches						
274	Cast Brass or Bronze	Cast Bronze								
*274A	Polished	Polished	2 $\frac{3}{4}$	5	306	0306	3	2100	3	32 $\frac{3}{8}$ lbs.
	Polished	Polished	2 $\frac{3}{4}$	306	0306	3	2100	3	31 lbs.

Packed with screws.

*Without auxiliary latch.

Specify number and finish. See pages 1 and 2.



178

Mortise Knob Locks


FOR COMMUNICATING AND BATHROOM DOORS

359, 0359
Reversible

CaseJapanned iron, $3\frac{3}{8} \times 3\frac{3}{8} \times \frac{5}{16}$ in.
Front $5\frac{1}{4} \times \frac{7}{8}$ in.
Spacing $2\frac{3}{16}$ in. center of knob hub to center of thumb knob.
Latch Bolt $\frac{3}{8}$ in. throw.
Dead Bolt $\frac{7}{16}$ in. throw.
HubsIron, $\frac{5}{16}$ in. and $\frac{3}{16}$ in.
StrikeLip to center, 1 in.
OperationLatch bolt by knobs from either side.
 Dead bolt by thumb knob from inside only.
 With Emergency Key No. 359½ which will operate Dead Bolt from the
 outside in case of emergency.

No.	Front	Bolts	Backset Inches	Packed in a Box	Weight Dozen
359	Wrought Brass or Bronze Polished	Cast Bronze Polished	2¾	6	12¼ lbs.
0359	Wrought Steel Plated	Cast Iron Brass Plated	2¾	6	12¼ lbs.

Packed with screws.

159½
Reversible

CaseJapanned iron, $3\frac{3}{4} \times 3\frac{3}{4} \times \frac{5}{8}$ in.
Front $5\frac{3}{8} \times 1\frac{1}{4}$ in.
Spacing $2\frac{3}{16}$ in. center of knob hub to center of thumb knob.
Latch BoltEasy spring, $\frac{3}{8}$ in. throw.
Dead Bolt $\frac{7}{16}$ in. throw.
HubsIron, $\frac{5}{16}$ in. and $\frac{3}{16}$ in.
StrikeLip to center, 1 in.
OperationLatch bolt by knobs from either side.
 Dead bolt by thumb from the inside only.
 With Emergency Key No. 359½ which will operate Dead Bolt from
 the outside in case of emergency.

No.	Front	Bolts	Backset Inches	Packed in a Box	Weight Dozen
159½	Cast Brass or Bronze Polished	Cast Bronze Polished	2¾ in.	6	15½ lbs.

Packed with screws.

159¾
Reversible

CaseJapanned iron, $3\frac{3}{4} \times 3\frac{3}{4} \times \frac{5}{8}$ in.
Front $5\frac{3}{8} \times 1\frac{1}{4}$ in.
Spacing $2\frac{3}{16}$ in. center of knob hub to center of thumb knob.
Latch BoltEasy spring, $\frac{3}{8}$ in. throw.
Dead Bolt $\frac{7}{16}$ in. throw, (split type).
HubsIron, $\frac{5}{16}$ in. and $\frac{3}{16}$ in.
StrikesLip to center, 1 in.
OperationLatch bolt by knobs from either side.
 Split dead bolt by thumb knobs from both sides, each locking against the
 opposite side.

No.	Front	Bolts	Backset Inches	Packed in a Box	Weight Dozen
159¾	Cast Brass or Bronze Polished	Cast Bronze Polished	2¾	6	16¾ lbs.


Packed with screws.

Specify number and finish. See pages 1 and 2.



Mortise Knob Latches

179



10, 01

Reversible

CaseJapanned iron, $1\frac{1}{16}$ x $3\frac{1}{16}$ x $\frac{1}{2}$ in.Front $2\frac{7}{8}$ x $\frac{7}{8}$ in.Latch Bolt $\frac{3}{8}$ in. throw.HubIron, $\frac{5}{16}$ in.

StrikeLip to center, 1 in.

OperationBy knob from either side.

No.	Front	Bolt	Backset Inches	Packed in a Box	Weight Dozen
10	Wrought Brass or Bronze Polished	Cast Bronze Polished	$2\frac{7}{16}$	6	4 lbs.
01	Wrought Steel Plated	Cast Iron Brass Plated	$2\frac{7}{16}$	6	4 lbs.

Packed with screws.



29

Reversible

CaseJapanned iron, $1\frac{3}{4}$ x $3\frac{1}{4}$ x $\frac{5}{8}$ in.Front $3\frac{7}{16}$ x $1\frac{1}{4}$ in.Latch BoltEasy spring, double compression spring on hub, $\frac{3}{8}$ in. throw.HubIron, $\frac{5}{16}$ in.

StrikeLip to center, 1 in.

OperationBy knob from either side.

No.	Front	Bolt	Backset Inches	Packed in a Box	Weight Dozen
29	Cast Brass or Bronze Polished	Cast Bronze Polished	$2\frac{7}{16}$	6	6½ lbs.

Packed with screws.


FOR TUBULAR LATCHES SEE PAGE 251

Specify number and finish. See pages 1 and 2.



180

Mortise Knob Latches




45

CaseJapanned iron, $1\frac{3}{8}$ x $3\frac{1}{2}$ x $\frac{1}{2}$ in.
 Front3 x $1\frac{1}{16}$ in.
 Latch BoltEasy spring, $\frac{3}{8}$ in. throw.
 HubIron, $\frac{7}{16}$ in.
 StrikeLip to center, 1 in.
 OperationBy knobs from either side.

No.	Front	Bolt	Backset Inches	Packed in a Box	Weight Dozen
45	Cast Brass or Bronze Polished	Cast Bronze Polished	$2\frac{7}{16}$ in.	6	5 lbs.

Packed with screws.



90

CaseJapanned iron, $2\frac{7}{16}$ x $3\frac{1}{2}$ x $\frac{5}{8}$ in.
 Front $4\frac{3}{8}$ x $1\frac{1}{8}$ in.
 Latch BoltEasy spring, $\frac{1}{8}$ in. throw. Double compression spring on hub.
 HubIron, $\frac{7}{16}$ in.
 StrikeLip to center, $1\frac{1}{4}$ in.
 OperationBy knobs from either side.

No.	Front	Bolt	Backset Inches	Packed in a Box	Weight Dozen
90	Cast Brass or Bronze Polished	Cast Bronze Polished	$2\frac{3}{4}$	3	$11\frac{1}{2}$ lbs.

Packed with screws.

Friction Latch

RECOMMENDED FOR HOSPITAL DOORS

Composition plunger and adjustable spring tension deaden sound of operation.


The use of a door closer is recommended on all doors equipped with this latch to supplement the functions of latch in keeping door closed in case of strong draughts.

The use of this latch is especially desirable on doors equipped with arm door pulls, type of 4337, page 121.

Case1 in. dia., $1\frac{1}{8}$ in. long.

Front $2\frac{1}{2}$ x $1\frac{1}{8}$ in.

Strike $2\frac{1}{2}$ x 1 in., lip to center, $1\frac{1}{8}$ in.



1825

No.	Material and Finish	Plunger	Packed in a Box	Weight Dozen
1825	Cast Brass or Bronze Polished	Composition	12	6 lbs.


Packed with screws.

Specify number and finish. See pages 1 and 2.




Mortise Sliding Door Latches

181



91, 091

CaseJapanned iron, 3 x 3 $\frac{1}{8}$ x $\frac{5}{8}$ in.
Front5 x 1 in.
Strike5 x 1 in.
Cup Escutcheon ..3 $\frac{3}{4}$ x 2 in. cast metal.
OperationBy lift lever from either side.



Outline of 291 and 0291

No.	Front and Escutcheons	Bolt and Lift Lever	For Doors	Cup Escutcheons No. 2103	Packed in a Box	Weight Dozen
91 291	Wrought Brass or Bronze Polished Polished	Cast Bronze Polished Polished	Single Double	Two Four	1 Set 1 Set	16 lbs. 20 $\frac{1}{4}$ lbs.
091 0291	Wrought Steel Plated Plated	Polished Polished	Single Double	Two Four	1 Set 1 Set	16 lbs. 20 $\frac{1}{4}$ lbs.





Packed with screws.

Mortise Dead Locks

BALL BEARING CYLINDER



4292

Top or Bottom
Strike.Furnished with Expansion
Shields when so
required.

CaseJapanned iron, 1 $\frac{7}{8}$ x 4 $\frac{1}{2}$ x $\frac{1}{16}$ in.
Front5 $\frac{3}{16}$ x 1 $\frac{1}{2}$ in.
Dead Bolt $\frac{1}{2}$ in. throw.
OperationNo. 5255 by key from either side.
 No. 5256 by key from outside and thumb knob
 from the inside.

No.	Front	Bolt	Backset Inches	Thumb Knob Cast Brass or Bronze	Cylinders Cast Brass or Bronze
5255 5256	Cast Brass or Bronze Polished Polished	Cast Bronze Polished Polished	$\frac{1}{16}$ $\frac{1}{16}$	None 1 No. 4292	2 No. 253 1 No. 253


Packed with screws.

Specify number and finish. See pages 1 and 2.



182

Mortise Dead Locks



123

Reversible


CaseJapanned iron, $2\frac{3}{16}$ x $3\frac{1}{2}$ x $\frac{1}{16}$ in.Front $4\frac{1}{4}$ x 1 in.Bolt $\frac{7}{16}$ in. throw.

OperationBy key from either side.

Master-keying ... Master keyed in one set of 2100 all different, or in sets as desired, with master keys to pass each set, and when so ordered with grand master key to pass all. Master keyed with other locks having 0306 class master key.

No.	Front	Bolt	Backset Inches	1 Key N-P Steel Class	Master-key Class	Tumblers	Changes	Packed in a Box	Weight Dozen
123	Cast Brass or Bronze Polished	Cast Bronze Polished	$2\frac{1}{16}$	306	0306	3	2100	6	$12\frac{3}{8}$ lbs.

Packed with screws.



131, 132

Reversible


CaseJapanned iron, $2\frac{1}{8}$ x $3\frac{1}{4}$ x $\frac{9}{16}$ in.Front4 x $\frac{13}{16}$ in.Bolt $\frac{1}{2}$ in. throw.

OperationBy key from either side.

Master-keying ... No. 132 can be master keyed in 5 sets of 50 each, the 250 all different with master keys to pass each set, and when so ordered with a grand master key to pass all. Master keyed with other locks having 195 class master key.

No.	Front	Bolts	Backset Inches	1 Key N-P Steel Class	Master-key Class	Tumblers	Changes	Packed in a Box	Weight Dozen
131	Cast Brass or Bronze Polished	Cast Bronze Polished	$2\frac{9}{16}$	$179\frac{3}{4}$	1	24	6	$6\frac{3}{8}$ lbs.
132	Cast Brass or Bronze Polished	Cast Bronze Polished	$2\frac{9}{16}$	$179\frac{3}{4}$	195	3	250	6	$7\frac{7}{8}$ lbs.

Packed with screws.



133

Reversible

CaseJapanned iron, $2\frac{1}{8}$ x $3\frac{1}{2}$ x $\frac{5}{8}$ in.

Front4 x 1 in.

Bolt $1\frac{1}{2}$ in. throw.

OperationBy key from either side.

Master-keying ... Master keyed in 4 sets of 160 each, or in 16 sets of 40 each, the 640 all different with master keys to pass each set, and when so ordered with a grand master key to pass all. Master keyed with other locks having 080 $\frac{7}{8}$ class master key.

No.	Front	Bolts	Backset Inches	1 Key N-P Steel Class	Master-key Class	Tumblers	Changes	Packed in a Box	Weight Dozen
133	Cast Brass or Bronze Polished	Cast Bronze Polished	$2\frac{3}{4}$	$80\frac{7}{8}$	080 $\frac{7}{8}$	3	640	6	$9\frac{3}{8}$ lbs.

Packed with screws.

Specify number and finish. See pages 1 and 2.



Mortise Dead Locks

183

BALL BEARING CYLINDER

5111 to 5113
Reversible

15111-15113

CaseJapanned iron, $2\frac{1}{2}$ x $3\frac{3}{4}$ x $\frac{3}{4}$ in. Width of case on special backsets $\frac{7}{8}$ in. more than backset.

Front $4\frac{1}{8}$ x $1\frac{1}{8}$ in. Furnished with rounded, or beveled front, when so ordered.

Dead Bolt $\frac{7}{16}$ in. throw.

OperationNo. 5111 by key from one side only.

No. 5112 by key from either side.

No. 5113 by key from the outside and thumb knob from the inside.

Master-keying... Can be master-keyed with other cylinder locks.

No.	Front	Bolt	Backset		Thumb Knob Cast Brass or Bronze	Cylinder Cast Brass or Bronze	2 Keys Nickel-silver Class	Master- Key Class	Changes	Packed in a Box	Weight Dozen
			Regular Inches	Special Inches							
	Cast Brass or Bronze	Cast Bronze									
5111	Polished	Polished	$2\frac{3}{4}$	$1\frac{1}{4}, 1\frac{1}{2}$	Without	1 No. 253	77	077	Unlimited	1	19½ lbs.
5112	Polished	Polished	$2\frac{3}{4}$	$1\frac{1}{4}, 1\frac{1}{2}$	Without	2 No. 253	77	077	Unlimited	1	23¼ lbs.
5113	Polished	Polished	$2\frac{3}{4}$	$1\frac{1}{4}, 1\frac{1}{2}$	1 No. 2140	1 No. 253	77	077	Unlimited	1	21 lbs.
*15111	Polished	Polished	$3\frac{1}{4}$	Without	1 No. 253	77	077	Unlimited	1	22½ lbs.
*15112	Polished	Polished	$3\frac{1}{4}$	Without	2 No. 253	77	077	Unlimited	1	25½ lbs.
*15113	Polished	Polished	$3\frac{1}{4}$	1 No. 2140	1 No. 253	77	077	Unlimited	1	24 lbs.

†Rounded front to 3-9/16 in. radius, unless otherwise ordered.

*Not reversible, specify hand, backset long side.

Packed with screws.

5211 to 5213
Reversible

CaseJapanned iron, $3\frac{1}{4}$ x $3\frac{3}{4}$ x $\frac{3}{4}$ in. Width of case on special backsets 1 in. more than backset.

Front $5\frac{1}{2}$ x $1\frac{1}{4}$ in. †Furnished rounded or beveled front when so ordered.

Dead Bolt $\frac{1}{2}$ in. throw.

OperationNo. 5211 by key from one side only.

No. 5212 by key from either side.

No. 5213 by key from outside and thumb knob from the inside.

Master-keying... Can be master-keyed with other cylinder locks.

No.	Front	Bolts	Backset		Thumb Knob Cast Brass or Bronze	Cylinders Cast Brass or Bronze	2 Keys Nickel-silver Class	Master- Key Class	Changes	Packed in a Box	Weight Dozen
			Regular Inches	Special Inches							
	Cast Brass or Bronze	Cast Bronze									
5211	Polished	Polished	$2\frac{3}{4}$	2	Without	1 No. 253	77	077	Unlimited	1	22½ lbs.
5212	Polished	Polished	$2\frac{3}{4}$	2	Without	2 No. 253	77	077	Unlimited	1	25½ lbs.
5213	Polished	Polished	$2\frac{3}{4}$	2	1 No. 2140	1 No. 253	77	077	Unlimited	1	24 lbs.

†Rounded front to 3-9/16 in. radius unless otherwise ordered.

Packed with screws.

Specify number, thickness of door and finish. See pages 1 and 2.




184

Rim Bar-Bolt Dead Locks


Reversible

BALL BEARING CYLINDER

For doors 1 to 2½ in. thick

Strike
for
1447Strike
for
1446

1446, 1447

Strike
for
2447Strike
for
2446

2446, 2447

Case 2⅞ x 4⅜ x ⅞ in. Projection of bolt housing 1 in.

Knob Wrought brass.

Strikes No. 1446 and 2446 flat strike cast brass, size 3⅞ x 1 in. for single doors opening out and for single and double sliding doors.

No. 1447 and 2447 angle strike cast brass, size 3⅞ x 1 in. with ⅞ in. flange for single doors opening in and for double doors opening in or out.

Operation No. 1446 and 1447 by key from outside and knob from inside at all times.
No. 2446 and 2447 by key from either side at all times.

No.	Case	Type of Strike Cast Brass	Bar Bolts Steel	†Regular Backset Inches	Cylinder Cast Brass	2 Keys Nickel-silver Class	Changes	Packed in a Box	Weight Dozen
1446	Die Cast	Flat	Hardened	2⅞	1 No. 251	77	Unlimited	1	21 lbs.
1447	Brass Plated	Angle	Hardened	2⅞	1 No. 251	77	Unlimited	1	22¼ lbs.
2446	Brass Plated	Flat	Hardened	2⅞	2 No. 251*	77	Unlimited	1	25 lbs.
2447	Brass Plated	Angle	Hardened	2⅞	2 No. 251*	77	Unlimited	1	25¼ lbs.

Packed with screws.

Can also be furnished in CR (chromium plated) finish.

For double doors opening out the lock is applied to the inactive leaf and the angle strike to the active leaf.

*Inside cylinder is special with plug in center.

†The regular backset does not include the projection of the bolt housing. The overall backset including bolt housing is 3-7/16 in.

Rim Dead Locks

Reversible

Case 2⅞ x 3⅞ in.

BALL BEARING CYLINDER


Knob Wrought brass.

Dead Bolt ½ in. throw.

Strikes Rim type 2⅞ x 2 in. with ¾ in. flange, cast iron black wrinkle japan finish for doors opening in, regularly furnished.
Angle type 2½ x 1¼ in. wrought steel, brass plated, for doors opening out. Furnished only when so ordered.

Operation By key from outside and turn knob inside.

Master-keying ... Can be master-keyed with other cylinder locks.



360

No.	Case	Bolts	Backset Inches	Cylinder	2 Keys Nickel-silver Class	Master- key Class	Changes	Packed in a Box	Weight Dozen
360	Cast Iron Black Wrinkle Japan	Cast Bronze Polished	2⅞	Cast Brass 1 No. 251	77	077	Unlimited	1	19⅞ lbs.

Packed with screws.


Can be furnished in EAW, HBW, or ALW finishes when so ordered.

Specify number and finish. See pages 1 and 2.




Mortise Night Latches

185

*15192,
151935192, 5193
ReversibleCaseJapanned Iron, $3\frac{1}{4} \times 3\frac{1}{2} \times \frac{3}{4}$ in.FrontFlat $5\frac{1}{8} \times 1\frac{1}{8}$ in.
Rabbeted $5\frac{3}{4} \times 1\frac{1}{16}$ in. $\frac{1}{2}$ in. rabbet, bevelled $\frac{1}{8}$ in.
2 in.Spacing $1\frac{3}{4}$ in.Latch BoltEasy spring, $\frac{7}{16}$ in. throw.HubBronze, $\frac{3}{16}$ in.StrikeLip to center, $1\frac{1}{4}$ in.OperationNo. 5192 by key from either side.
No. 5193 by key from outside and thumb knob inside.
Latch bolt held retracted by stop in face.

Master-keying... Can be master-keyed with other cylinder locks.

No.	Front	Type Front	Bolt	Backset Inches	One Knob Cast Brass or Bronze	Cylinder Cast Brass or Bronze	2 Keys Nickel-silver Class	Master Key Class	Changes	Packed in a Box	Weight Dozen
	Cast Brass or Bronze		Cast Bronze								
5192	Polished	Flat	Polished	$2\frac{3}{4}$	Without	2 No. 253	77	077	Unlimited	1	25 $\frac{1}{2}$ lbs.
5193	Polished	Flat	Polished	$2\frac{3}{4}$	2248	1 No. 253	77	077	Unlimited	1	25 $\frac{1}{2}$ lbs.
*15192	Polished	Rab'td	Polished	$2\frac{3}{4}$	Without	2 No. 253	77	077	Unlimited	1	31 $\frac{1}{2}$ lbs.
*15193	Polished	Rab'td	Polished	$2\frac{3}{4}$	2248	1 No. 253	77	077	Unlimited	1	31 $\frac{1}{2}$ lbs.

Packed with screws.
*Not reversible, specify hand.5597
Type of
55985592, 5593
ReversibleCase $4\frac{1}{2} \times 3\frac{3}{4} \times \frac{3}{4}$ in.Front $6 \times 1\frac{1}{16}$ in.Spacing $2\frac{1}{2}$ in. center of knob hub to center of cylinder.Latch BoltEasy spring, $\frac{5}{8}$ in. throw.HubBronze, $\frac{3}{16}$ in.StrikeLip to center, $1\frac{1}{4}$ in.

Auxiliary Latch... Automatically locks the latch bolt so that it cannot be forced back by end pressure when the door is closed, but does not prevent key or knob from operating latch bolt.

OperationNo. 5592 by key from either side.
No. 5593 Latch bolt by key from outside and knob from the inside.

Latch bolt is held retracted by stop in face.

No. 5597 by key from outside and knob from the inside. Both latch and auxiliary bolts can be held retracted by the key.

No. 5598 latch bolt by key from outside. Inside cylinder retracts latch and auxiliary bolts.

Master-keying... Can be master-keyed with other cylinder locks.

No.	Front	Bolts	Backset Inches	One Knob Cast Brass or Bronze	Cylinder Cast Brass or Bronze	2 Keys Nickel-silver Class	Master Key Class	Changes	Packed in a Box	Weight Dozen
	Cast Brass or Bronze	Cast Bronze								
5592	Polished	Polished	$2\frac{3}{4}$	Without	2 No. 253	77	077	Unlimited	1	34 $\frac{1}{2}$ lbs.
5593	Polished	Polished	$2\frac{3}{4}$	2248	1 No. 253	77	077	Unlimited	1	34 $\frac{1}{2}$ lbs.
5597	Polished	Polished	$2\frac{3}{4}$	2248	1 No. 253	77	077	Unlimited	1	34 $\frac{1}{2}$ lbs.
*5598	Polished	Polished	$2\frac{3}{4}$	Without	2 No. 253	77	077	Unlimited	1	34 $\frac{1}{2}$ lbs.

Packed with screws.
*Not reversible, specify hand.


Specify number, thickness of door and finish. See pages 1 and 2.



186

The Modern Aluminum Night Latch

FREE HAND OPERATION

CAST BRASS, BALL BEARING, PIN TUMBLER CYLINDER
FOR DOORS 1½ TO 2¾ IN. THICK

3A6

Case Aluminum die cast, 2 $\frac{7}{16}$ x 3 $\frac{3}{8}$ x 1 $\frac{1}{16}$ in.

Knob Wrought brass.

Latch Bolt Aluminum die cast, $\frac{9}{16}$ in. throw.

Strikes Regularly furnished with aluminum die cast rim strike, for doors opening in. Wrought steel brass plated angle strike for doors opening out can be furnished in place of rim strike, when ordered.

FREE HAND OPERATION: When the Latch Bolt has been secured in retracted position by either the Key or Turn Knob, the hand is left free to operate the door knob, which is a distinct advantage to a person wishing to leave or enter with an arm full of bundles.

No.	Finish	Backset	Cylinder Cast Brass	2 Keys Nickel-Silver Class	Changes	Packed in a Box	Weight Dozen
3A6	Neutral Gun Metal	2 $\frac{3}{8}$ in.	1 No. 251	77	Unlimited	1	12 $\frac{1}{4}$ lbs.

Packed with screws. Other metallescent finishes available, Dull Brass, Maroon Bronze and Aluminum.

Counter Demonstrator

FOR 3A6 NIGHT LATCH



No. K10

Overall size: 7 $\frac{7}{8}$ in. long, 5 $\frac{1}{16}$ in. high and 4 $\frac{3}{8}$ in. wide.

An operating wooden mount arrestingly lacquered in rich blue and bright yellow and complete with factory installed 3A6 latch.

Packed one in a box


Weight each 2 $\frac{1}{2}$ lbs.

Rim Night Latches

187

BALL BEARING CYLINDER

For doors 1 to 2½ in. thick



3R6
Reversible

Case 2⅝ x 3⅝ x 1⅞ in.

Knob Wrought brass.

Latch Bolt ⅞ in. throw.

Strikes Regularly furnished with rim strike for door opening in,
Angle strike for door opening out furnished only when ordered.


Operation By key from outside and knob inside. The stop in case holds
the latch bolt retracted.

Master-keying ... Can be master-keyed with other cylinder locks.

No.	Case	Bolt	Backset Inches	Cylinder Cast Brass	2 Keys Nickel-silver Class	Master- key Class	Changes	Packed in a Box	Weight Dozen
3R6	Cast Iron Black Wrinkle Japan	Cast Iron Brass Plated	2⅞	1 No. 251	77	077	Unlimited	1	21 lbs.

Packed with screws.

Can be furnished in EAW, HBW or ALW finishes when so ordered.



3D6
Reversible

Case 2⅝ x 3⅝ x 1⅞ in.

Knob Wrought brass.

Latch Bolt ⅞ in. throw.

Strikes None.

Operation Key from outside and knob inside retracts spring bolt. Bolt
held retracted by stop in case.

Recommended for overhead type doors.

No.	Case	Bolts	Backset Inches	Cylinder Cast Brass	2 Keys Nickel-silver Class	Changes	Packed in a Box	Weight Dozen
3D6	Cast Iron Black Wrinkle Japan	Cast Iron Brass Plated	2⅞	1 No. 251	77	Unlimited	1	16½ lbs.

Packed with screws.

Can be furnished in EAW, HBW or ALW finishes when so ordered.

Specify number and finish. See pages 1 and 2.




188

Rev. 6-1-57

Rim Night Latches

BALL BEARING CYLINDER

For doors 1 to 2½ in. thick




356
Reversible

- Case** 2¾ x 3½ x 1¼ in.
Knob Wrought brass.
Latch Bolt ¾ in. throw.
Strikes Regularly furnished with rim strike for door opening in.
 Angle strike for door opening out furnished only when ordered.
Operation By key from outside and knob inside. The stop in case holds the bolt retracted.
Master-keying ... Can be master-keyed with other cylinder locks.

No.	Case	Bolt	Backset Inches	Cylinder Cast Brass	2 Keys Nickel-silver Class	Master-key Class	Changes	Packed in a Box	Weight Dozen
356	Cast Iron Black Wrinkle Japan	Cast Bronze Polished	2¾	1 No. 251	77	077	Unlimited	1	21 lbs.

Packed with screws. Can be furnished in EAW, HBW or ALW finishes when so ordered.



456¾
Reversible

- Case** 2½ x 3½ x 1½ in.
Knob Wrought brass.
Latch Bolt ¾ in. throw.
 The trip in center of latch bolt is held retracted by contact with the strike and secures the latch bolt from being forced back by end pressure.
Strikes Regularly furnished with rim strike for door opening in.
 Angle strike for door opening out furnished only when ordered.
Operation By key from the outside and knob from the inside. The stop in case holds the bolt retracted.
Master-keying .. Can be master-keyed with other cylinder locks.


No.	Case	Bolts	Backset Inches	Cylinder Cast Brass	2 Keys Nickel-silver Class	Master-key Class	Changes	Packed in a Box	Weight Dozen
456¾	Cast Iron Black Wrinkle Japan	Cast Bronze Polished	2¾	1 No. 251	77	077	Unlimited	1	23¼ lbs.

Packed with screws. Can be furnished in EAW, HBW or ALW finishes when so ordered.

Tubular Dead Locks

BALL BEARING CYLINDER

For Doors 1½ in. to 2 in. Thick

Case Die cast 1 in. diameter, 3¼ in. long.**Front** 2½ x 1¼ in.**Dead Bolt** Full ½ in. throw.**Turn Knob** Wrought brass or bronze, plate 2½ in. diameter.**Strike** 2¼ x 1½ in.**Operation** By key from the outside and by turn knob from the inside.

760
Reversible

No.	Front and Strike	Bolt	Backset Inches	Cylinder Cast Brass or Bronze	2 Keys Nickel-silver Class	Changes	Packed		Weight Dozen
							in a Box	in a Case	
760	Wrought Brass or Bronze Polished	Forged Brass	2½	1 No. 245	77	Unlimited	1	1 Doz.	17¼ Lbs.

Packed with screws.

Specify number and finish. See pages 1 and 2.



Padlocks

189

BALL BEARING CYLINDER



2863 1/4

Made from solid block of extruded brass bored out to receive mechanism.

Heavy wrought spring shackle, $1\frac{1}{32}$ in. diameter. Height of opening, $1\frac{3}{16}$ in.

Master-keying ..Nos. 2863 1/4 and 2863 1/4 C can be master-keyed in sets as desired with other 6 pin Corbin master-keyed cylinder locks.

No.	Overall Size of Case		Material and Finish		2 Keys Nickel-silver Class	Master-key Class	Changes	Packed in a Box	Weight Each
	Height	Width	Case	Shackle					
2863 1/4	1 23/32	1 15/16	All Brass	Wrought Brass	73 3/4	073 3/4	Unlimited	1	1 lb.
2863 1/4 A	1 23/32	1 15/16	All Brass	Steel, Case Hardened, Zinc Plated, Dichromate	73 3/4	073 3/4	Unlimited	1	1 lb.

Can be furnished with 9 in. brass chain. In ordering affix letter C to number, thus 2863 1/4 C, 2863 1/4 AC.



2882

Made from solid block of extruded brass bored out to receive mechanism.

Heavy wrought spring shackle, $1\frac{1}{32}$ in. diameter. Height of opening, $\frac{3}{4}$ inches.

Master-keying ..Nos. 2882 1/4 and 2882 1/4 A can be master-keyed with other 5 Pin Corbin cylinder locks in the average installation. Where large groups are to be master-keyed use No. 2863 1/4 padlock.

No.	Overall Size of Case		Material and Finish		2 Keys Nickel-silver Class	Master-key Class	Changes	Packed in a Box	Weight Each
	Height	Width	Case	Shackle					
2882	1 1/16 in.	1 3/4 in.	All Brass	Wrought Brass	77	...	Unlimited	1	11 1/2 oz.
2882 1/4	1 1/16 in.	1 3/4 in.	All Brass	Wrought Brass	77	077	Unlimited	1	11 1/2 oz.
2882 A	1 1/16 in.	1 3/4 in.	All Brass	Steel, Case Hardened, Zinc Plated, Dichromate	77	...	Unlimited	1	11 1/2 oz.
2882 1/4 A	1 1/16 in.	1 3/4 in.	All Brass	Steel, Case Hardened, Zinc Plated, Dichromate	77	077	Unlimited	1	11 1/2 oz.

Can be furnished with 9 in. brass chain. In ordering affix letter C to number, thus 2882 C, 2882 1/4 AC.



2883

Made from solid block of extruded brass bored out to receive mechanism.

Heavy wrought spring shackle, $1\frac{1}{32}$ in. diameter. Height of opening, $1\frac{3}{16}$ inches.

Master-keying ..Nos. 2883 1/4 and 2883 1/4 A can be master-keyed with other 5 Pin Corbin cylinder locks in the average installation. Where large groups are to be master-keyed use No. 2863 1/4 padlock.

No.	Overall Size of Case		Material and Finish		2 Keys Nickel-silver Class	Master-key Class	Changes	Packed in a Box	Weight Each
	Height	Width	Case	Shackle					
2883	1 5/8 in.	2 in.	All Brass	Wrought Brass	77	...	Unlimited	1	14 oz.
2883 1/4	1 5/8 in.	2 in.	All Brass	Wrought Brass	77	077	Unlimited	1	14 oz.
2883 A	1 5/8 in.	2 in.	All Brass	Steel, Case Hardened, Zinc Plated, Dichromate	77	...	Unlimited	1	14 oz.
2883 1/4 A	1 5/8 in.	2 in.	All Brass	Steel, Case Hardened, Zinc Plated, Dichromate	77	077	Unlimited	1	14 oz.

Can be furnished with 9 in. brass chain. In ordering affix letter C to number, thus 2883 C, 2883 1/4 AC.


Specify number.



190

Sliding Door Lock

FOR SLIDING DISPLAY CASE OR CABINET DOORS


**Cylinder**1½ in. Diameter. For 1½ in. Wood.**Bolt**½ in. Diameter, ½ in. Throw.**Strike**Cup Type.**Operation**Push in Cylinder to Lock. Use Key to unlock.

No.	Material	Size Inches	Cylinder Cast Brass	2 Keys Nickel-silver Class	Changes	Packed in a Box	Weight Dozen
022915	All Brass	2½ x 1½	One	77	Unlimited	6	4 lbs.


Packed with screws.

Cabinet Locks

BALL BEARING CYLINDER

**0371CX, Right Hand***

Not Reversible

Selvage2¼ x ⅞ in.**Bolt**Broad and heavy, ⅝ in. throw.**Cylinder**1½ in. diameter. For 1½ in. wood. Can be furnished for other thicknesses of wood when so ordered.**Master-keying** ..Master-keyed in sets as desired with other master-keyed cylinder locks.**0686X****Selvage**½ x 2¼ in.**Bolt**Broad and heavy, ⅝ in. throw.**Cylinder**1½ in. diameter. For 1½ in. wood. Can be furnished for other thicknesses of wood when so ordered.**Master-keying** ..Master-keyed in sets as desired with other master-keyed cylinder locks.

No.	Material	Size Inches	Backset Inches	Cylinder Cast Brass	2 Keys Nickel-silver Class	Master-key Class	Changes	Packed in a Box	Weight Dozen
*0371CX	All Brass	2¼ x 2	1	One	77	077	Unlimited	1	5 lbs.
*0371DX	All Brass	2¼ x 2¼	1¼ Drop	One	77	077	Unlimited	1	5 lbs.
0686X	All Brass	2 x 2¼	1	One	77	077	Unlimited	1	4¼ lbs.

Packed with screws.


*Specify hand. Specify number and finish. See pages 1 and 2.



The Corbin Pin Tumbler Cylinder

191

WITH BALL BEARINGS



The pin-tumbler cylinder has done more to make security available to everyone who desires it than any other development in the locksmith's art. Its mechanism is superior to any other in general use in the protection it affords, and its form permits its adaptation for all the types of locks with which keys are used. There are few key rings upon which keys to cylinder locks are not found.




Fig. 1

Figure 1 shows the face of a Corbin cylinder used with mortise door locks. The cylinder is embedded in the door, the face only being visible and the key-hole forming the only point of attack. The keyway is of an irregular contour, the projections extending to the center of the slot. The plug which contains the keyway is cut from a solid bar, the irregular contour extending through its entire length, requiring a key

that will fit with exactness. The interlocking of the key with the channel cut in the plug prevents any tilting or up-and-down motion of the key. The highest degree of accuracy in form and fit is necessary, and nothing but a Corbin key can be made to operate a Corbin cylinder.

Figure 2 is a sectional view of a cylinder used with Corbin rim night latches. This also is embedded in the door, the front alone being visible.




Fig. 2

The spring pressed pins firmly bolt the plug to the shells. To operate, a key must be used which will raise the pins to a point where the divisions coincide with the surface

of the plug, permitting the key to rotate it. A very slight variation on any one of the five pins will prevent the key from turning the plug. It is easy to understand how such nicety will prevent the operation of the lock except by the key to which it is made.

Figure 3 shows the same cylinder with the key inserted, raising the pins and releasing the plug, permitting the cylinder to operate the lock. Each one of the five pins can




Fig. 3

be made in several different lengths, so that it is easy to understand the large number of key-changes, each distinct and different from any other, that can be provided.


The balls eliminate friction and wear at the point where the key enters. The first pin is balanced directly upon a ball, and when the key is inserted, the ball rolls in its place and imparts a directly upward movement to the pins. There is almost no resistance when a key is inserted or withdrawn. The use of balls is a Corbin invention and places the cylinders in a class by themselves.

The use of master-keys is becoming general wherever there are many doors through which it is desired to limit passage to groups or individuals. In a hotel, for instance, each room will have a guest key which is different from all others in the building; each floor will have a different master-key for its chambermaid; and the office will have a grand master-key or emergency key which will open all doors. In a hospital there will be one distinct system for the medical portion; another for the service portion, and an executive group different from either with grand master-keys to pass all. Office buildings, factories, universities, railroad systems and large institutions have carefully developed keying systems so arranged as to be capable of extension or changes. A new project can be master keyed or grand master keyed with provision made for every new additional building along the line to automatically find its place in the plan as soon as erected. So general has the use of master-keys become that even residences of modest proportions are frequently keyed so that the master's key will unlock all doors, while the servants carry keys which will admit them at the rear doors only.



Corbin Pin Tumbler Cylinders


BALL BEARING



260 1/2



253, 263



251

No.	Diameter		Material and Finish	For Use with	Weight Each with 2 Keys
	Head Inches	Barrel Inches			
251	1 3/8	1 3/32	Cast Brass or Bronze	Rim Dead bolts and night latches. Dummy cylinder.	4 1/2 oz.
252	1 3/8	1 3/32	Polished		
*253	1 3/8	1 3/32	Polished	Mortise locks and latches. Unit locks 900, 904 series. Same as No. 253 with clover leaf cam.	6 oz.
*260 1/2	1 3/8	1 3/32	Polished		
*263	1 3/8	1 3/32	Polished		
†460	1 3/8	1 3/32	Extruded Brass	For cylindrical locks, heavy duty.	3 1/2 oz.
†460 1/2	1 3/8	1 3/32	Extruded Brass	For cylindrical locks, master keyed.	3 1/2 oz.
†670	1 3/8	1 3/32	Extruded Brass	For cylindrical locks, standard duty.	3 1/2 oz.
†870	1 3/8	1 3/32	Extruded Brass	For cylindrical locks, light duty.	3 1/2 oz.

*Furnished 1, 1 1/4, 1 1/2, 1 3/4, 1 1/2, 1 5/8, 1 3/4, 2, 2 1/4, 2 1/2, 2 3/4, or 3 in. in length. State length required.

The length of mortise cylinders is measured under the head to outer edge of cam, see page 193.


†See cylindrical section for detail information.

Specify number and finish. See pages 1 and 2.




Cylinder Parts

193



In ordering cylinder parts, state number of cylinder with which parts are to be used; also, when possible, give number of lock.



THE LENGTH OF A CORBIN MORTISE CYLINDER

The catalogued length of a Corbin cylinder is the measurement from the lower edge of the face to the outer surface of the cam.

The one-inch cylinder is shown.

Lengths available:

No. 253 furnished 1, 1 $\frac{1}{8}$, 1 $\frac{1}{4}$, 1 $\frac{3}{8}$, 1 $\frac{1}{2}$, 1 $\frac{5}{8}$, 1 $\frac{3}{4}$, 2, 2 $\frac{1}{4}$, 2 $\frac{1}{2}$, 2 $\frac{3}{4}$, or 3 in. in length. State length required.

No. 263 furnished 1, 1 $\frac{1}{8}$, 1 $\frac{1}{4}$, 1 $\frac{3}{8}$, 1 $\frac{1}{2}$, 1 $\frac{5}{8}$, 1 $\frac{3}{4}$, 2, 2 $\frac{1}{4}$, 2 $\frac{1}{2}$, or 2 $\frac{3}{4}$ in. in length. State length required.

Cylinder Assembly Tools

No.	Description
CT 1	Plug Vise
CT 2	V Block
CT 3	Assembly Block
CT 4	Follower
CT 5	Pin Hole Reamer
CT 6	Tweezers
CT 7	Burring Tool
CT 8	Pliers, with 11 holes Drilled for 253 Cylinder Pins



Nickel-Silver Keys



77



73 1/4



74



077



073 1/4



074



074 1/4



074 1/2

CHANGE KEYS

(Current Series)

MASTER KEYS

Class No.	Description	Class No.	Description
77	For five pin cylinders Nos. 260 1/2, 251, 253, etc.	077	For five pin cylinders Nos. 260 1/2, 251, 253, etc.
73 1/4	For six pin cylinders Nos. 260 1/2, 251, 253, etc.	073 1/4	For six pin cylinders Nos. 260 1/2, 251, 253, etc.
*74	For six pin cylinders Nos. 260 1/2, 251, etc. and 253, not less than 1 1/4 inch in length	*074 *074 1/4 *074 1/2	{ For six pin cylinders Nos. 260 1/2, 251, etc. and 253, not less than 1 1/4 inch in length

*Furnished regularly with certain locks with special functions such as hotel locks, etc.



67



63 1/4



64



067



063 1/4

CHANGE KEYS

(Old Series)

MASTER KEYS

Class No.	Description	Class No.	Description
67	For five pin cylinders Nos. 260 1/2, 251, 253, etc.	067	For five pin cylinders Nos. 260 1/2, 251, 253, etc.
63 1/4	For six pin cylinders Nos. 260 1/2, 251, 253, etc.	063 1/4	For six pin cylinders Nos. 260 1/2, 251, 253, etc.
*64	For six pin cylinders Nos. 260 1/2, 251, and 253, etc. not less than 1 1/4 inch in length.		

*Furnished regularly with certain locks with special functions such as hotel locks, etc.

When key blanks are required, so state. When cut keys are required, specify change number (with prefixed letter, if any).

Key blanks packed three dozen in a box.



Nickel-Silver Keys

195



CHANGE KEYS

(Old Series)

MASTER KEYS

Class No.	Description	Class No.	Description
57	For five pin cylinders Nos. 251, 253.	057	For five pin cylinders Nos. 251, 253.
53 1/4	For six pin cylinders Nos. 251, 253.	053 1/4	For six pin cylinders Nos. 251, 253.
*54	For six pin cylinders Nos. 251 and 253, not less than 1 1/4 inch in length.		

*Used with certain locks with special functions such as hotel locks, etc.

When key blanks are required, so state. When cut keys are required, specify change number (with prefixed letter, if any).
Key blanks packed three dozen in a box.



196

Steel Keys

NICKEL PLATED



96 1/4



80 7/8



306



179 3/4



359 1/2

Class No.	For Locks	Class No.	For Locks
96 1/4 80 7/8 306	0186 133, 0251, 0261, 364, 365, 1365 123, 203, 274, 274A, 303, 383	179 3/4 359 1/2	131, 132, 685, 685 3/4 159 1/2, 0359, 359

When key blanks are required, so specify. When cut keys are required, specify class, change number (with prefixed letter, if any), and number of lock with which keys are to be used.


Key blanks packed three dozen in a box.

Iron Keys

NICKEL PLATED



179 1/4



011 1/4

Class No.	For Locks
179 1/4 011 1/4	0285, 01285, 285, 1285 961

Cut keys only. Specify change number required.

Steel Master Keys

NICKEL PLATED



080 7/8



195



0306

Class No.	For Locks
080 7/8 195 0306	133, 364, 365, 1365 132, 685 3/4 123, 203, 274, 274A, 303, 383



Strikes

197

FOR MORTISE LOCKS AND LATCHES



634


Type of
602, 0602,
603, 0603,
604



614, 0614



612



615

Type of
616, 620



0618

Type of
640, 641, 642



0636

No.	Size Inches	Lip to Center Inches	Material and Finish	For Locks or Latches Nos.
Wrought Brass or Bronze				
602	1 $\frac{7}{8}$ x $\frac{7}{8}$	1	Polished	10
603	2 $\frac{1}{4}$ x 1	1 $\frac{1}{4}$	Polished	29, 645, 659
604	2 x $\frac{7}{8}$	1	Polished	45
612	3 $\frac{3}{8}$ x $\frac{7}{8}$	1	Polished	685, 685 $\frac{3}{4}$
614	3 $\frac{1}{4}$ x $\frac{7}{8}$	1	Polished	285, 359
615	4 $\frac{1}{2}$ x 1 $\frac{5}{16}$	1	Polished	364
616	4 $\frac{1}{4}$ x 1 $\frac{1}{16}$	1	Polished	159 $\frac{1}{2}$, 159 $\frac{3}{4}$, 365
620	3 $\frac{5}{8}$ x 1 $\frac{1}{8}$	1 $\frac{1}{4}$	Polished	274, 274A
634	3 x 1	1 $\frac{1}{4}$	Polished	90, 177, 5192, 5193
640	5 x 1	1 $\frac{1}{4}$	Polished	5743
641	5 $\frac{5}{8}$ x 1 $\frac{3}{16}$	1 $\frac{1}{4}$	Polished	5262
642	5 x 1	1 $\frac{1}{4}$	Polished	5243
Wrought Steel				
0602	1 $\frac{7}{8}$ x $\frac{7}{8}$	1	Plated	01
0603	2 $\frac{1}{4}$ x 1	1 $\frac{1}{4}$	Plated	0645, 0659
0606	3 $\frac{7}{8}$ x 1 $\frac{1}{16}$...	Japanned (Cast Iron)	961
0614	3 $\frac{1}{4}$ x $\frac{7}{8}$	1	Plated	0285, 0359
0618	4 $\frac{7}{8}$ x 1	1 $\frac{1}{2}$	Plated	0186
0636	4 $\frac{1}{2}$ x 1	1 $\frac{1}{4}$	Plated	0251

Packed with screws.

Specify number and finish. See pages 1 and 2.

Wrought Boxes

FOR USE WITH LOCK STRIKES

Furnished for any mortise latch or lock when so ordered.



WROUGHT BOX
Symbol **WBX**



WROUGHT BOX
Symbol **WBX**




WROUGHT BOX
Symbol **WBX**

Specify number of latch or lock for which boxes are to be used.

Electric Door Openers

Regularly furnished for 6 to 12 volts D.C. or 12 to 24 volts A.C. When so ordered can be furnished for 24 volts D.C.




630

CaseIron, $2\frac{1}{8}$ x $3\frac{1}{8}$ x 1 in.
Front $4\frac{1}{2}$ x $1\frac{1}{4}$ in.




Pusher

 $1\frac{1}{4}$ x $1\frac{5}{8}$ x $\frac{1}{2}$ in.

430

Case $1\frac{7}{8}$ x $2\frac{3}{4}$ x 1 in.
Front $3\frac{1}{2}$ x $1\frac{3}{8}$ in.



621

CaseIron, $2\frac{1}{8}$ x $3\frac{1}{8}$ x 1 in.
Front $4\frac{1}{8}$ x $1\frac{1}{2}$ in.

No.	Front, Trip and Pusher	For Use with Locks	Packed in a Box	Weight Each
*430	Cast Brass or Bronze	*Heavy Duty Cylindrical	1	14 oz.
630	Polished	or Defender Cylindrical		
621	Polished	$1\frac{1}{2}$ " Door or over.	1	$1\frac{3}{8}$ lbs.
	Polished	Regular Cylinder Locks	1	$1\frac{3}{8}$ lbs.
		Unit Locks	1	

*For doors $1\frac{3}{4}$ in. and over. For $1\frac{3}{8}$ in. doors specify No. 630.

Packed with screws. State number of lock with which they are to be used.

Specify number and finish. See pages 1 and 2.

Lock Springs

199



Compression

No.	Gauge Wire	†Length Feet	Material	Used as
007	.036	3	Brass	Shoe spring.
008	.022	3	Brass	Latch spring for locks with type "A" construction.
009	.025	3	Phosphor Bronze	Latch spring for most locks with type "C" or "D" construction or for most cylinder locks.

†Can also be supplied in short pieces, when so ordered. Specify number of lock with which they are to be used.


Lock Springs



Extension

No.	Material	Used as
006	Brass	Lever spring for locks

Specify number of lock with which they are to be used.

Auxiliary Spring
FOR LEVER HANDLES


022½

Applied to wood under rose to hold lever handle in horizontal position.
Used under roses 1½ in. diameter and over.

No.	For Spindle	Material
022½ 25	5/16 in. 3/16 in.	Wrought Steel Brass Plated Brass Plated



25




Flat

No.	Width Inches	†Length Feet	Material
001	1/16	3	Phosphor Bronze
002	3/32	3	Steel
003	3/16	3	Steel
004	1/4	3	Steel

†Can also be supplied in short pieces, when so ordered. Specify number of lock with which they are to be used.

Thumb Knob Cylinders




48

For thumb knobs with 3/16 in. spindle.
Inserted in lock case in place of cylinder where it is desired to have lock operated by thumb knob in place of key.

No.	Size as Cylinder	Material
48	253	Wrought Steel Brass Plated

Cabinet Spindle Nut




22

Applied to thumb knobs with either 3/16 in. or 5/16 in. spindles, when so ordered.


No.	Diameter	Material
22	of Button 7/8 in.	Cast Brass or Bronze Polished

200


Wrought Cylinder Collars



151




153




553 1/4
ADJUSTABLE
TYPE
Type of 553

No.	Dia., Inches	Material and Finish	Height, Inches	For Cylinder
151	1 7/8	Wrought Brass or Bronze		251
153	1 7/16	Roll Polish	1/8	253, 263
553	1 11/16	Roll Polish	3/16	253, 263
553 1/4	1 11/16	Roll Polish	5/16	253, 263



75213

Cast Cylinder Collars



19613

No.	Dia., Inches	Material and Finish	Height, Inches	For Cylinder
75213	2	Cast Brass or Bronze		253
*19613	2	Polished	3/16	253
		Polished	1/4	

*Suffix 1/2 to number when required plain i.e. 19613 1/2.

Knob Screws



14



14 1/2



15



16



16 1/2, 17

No.	Size	Material and Finish	Used with	Packed in a Box	Weight Gross
14	3/4 in. 24 Thread	Steel, Plated	PY and Colonial Shank Knobs	1 Gross	1/2 lb.
14 1/2		Steel, Plated	Lever Handles	1 Gross	3/4 lb.
15	3/16 in. 32 Thread	Steel, Plated	Simplex and Glass Knobs	1 Gross	7/8 lb.
16	5/8 in. No. 9	Iron, Blued	For Pottery Knobs	1 Gross	3/8 lb.
16 1/2	*5/8 in. No. 9	Iron, Plated	Standard Shank Knobs	1 Gross	5/8 lb.
17	*5/8 in. No. 9	Bronze, Polished	Standard Shank Knobs	1 Gross	5/8 lb.

*Furnished 1/2 in. when so ordered.

Knob Washers



18

No.	For Spindle	Material	Packed in a Box
18	3/16 in.	Wrought Steel	1 lb.

Knob Plates

Applied to door under rose or escutcheon to hold knob rigid.




20

No.	Size Inches	For Spindle	Material	Weight Dozen
20	1 1/8 x 1 1/8	3/16 in.	Cast Iron	5/8 lb.

Specify number and finish. See pages 1 and 2.

Knob Spindles

201



20



25



45½, 045½

Used with locks operated by knob from one side only



056, 056¼



36



56

No.	Size Inches	Material	Standard Length Inches	Use	Packed in a Box	Weight Dozen
20	5/16	Wrought Steel	27/8	For 03463 screen door	2 Doz.	½ lb.
25	5/16	Wrought Steel	3¼	For 03457 screen door	2 Doz.	¾ lb.
36	5/16	Wrought Steel	4¼	For standard shank knobs	2 Doz.	1 lb.
56	5/16	Wrought Steel	5¼	For PY and TS type knobs	2 Doz.	1 lb.
056	5/16	Wrought Steel	3¾	For glass knobs	2 Doz.	¾ lb.
056¼	5/16	Wrought Steel	4½	For simplex knobs	2 Doz.	1 lb.
45½	5/16	Wrought Steel	3¾	For simplex knobs	2 Doz.	1 lb.
045½	5/16	Wrought Steel	2¾	For glass knobs	2 Doz.	¾ lb.



044



032



033, 034

No.	Size Inches	Swivel Centers Inches	Material	Length Inches	Use	Packed in a Box	Weight Dozen
032	5/16	3/8	Wrought Steel	5	For PY and TS type knobs	2 Doz.	1¼ lbs.
033	5/16	3/8	Wrought Steel	4	For glass knobs	2 Doz.	1¼ lbs.
034	5/16	3/8	Wrought Steel	5	For simplex knobs	2 Doz.	1½ lbs.
*044	5/16	3/16	Wrought Steel	5	For colonial shank	2 Doz.	1½ lbs.


*Specify length.

Specify number.

202

Knob Spindles


CLOSET



43¼



56½



30¼ to 040¼

No.	Size Inches	Material	Overall Length Inches	Turn Knob		Use	Packed in a Box	Weight Dozen
				Rose Size Inches	Material Turn Piece Cast Rose Wrought			
30¼	5/16	Wrought Steel	2 13/16	1 3/4 x 1 3/8	Cast Brass or Bronze	For Glass Knobs	2 Doz.	1 7/8 lbs.
40¼	5/16	Wrought Steel	3 3/4	1 3/4 x 1 3/8	Cast Brass or Bronze	For PY and TS type knobs	2 Doz.	2 1/4 lbs.
43¼	5/16	Wrought Steel	1 3/16	Cast Brass or Bronze	For PY and TS type knobs	2 Doz.	1 7/8 lbs.
030¼	5/16	Wrought Steel	2 13/16	1 3/4 x 1 3/8	Cast Iron Plated	For glass knobs	2 Doz.	1 7/8 lbs.
040¼	5/16	Wrought Steel	3 3/4	1 3/4 x 1 3/8	Cast Iron Plated	For PY and TS type knobs	2 Doz.	2 1/4 lbs.
56½	5/16	Wrought Steel	3 7/8	Wrought Steel	For rigid glass, PY or TS knobs	2 Doz.	14 oz.

Packed with screws.




5, 6



7

Knob Thimbles
FOR USE ON ESCUTCHEONS

8



9

No.	Diameter Inches	Height Inches	Material and Finish	Description
5	1 1/8	3/16	Wrought Steel Plated	Used on all wrought steel escutcheons for standard shank knobs, simplex knobs, glass knobs and lever handles.
6	1 1/8	3/16	Wrought Brass or Bronze Polished	
7	1 1/8	3/16	Cast Brass or Bronze Polished	Used on cast brass or bronze escutcheons for glass knobs and lever handles.
8	1 1/8	5/8	Cast Brass or Bronze Polished	Used on all escutcheons for cast shank knobs.
9	1 1/4	3/16	Cast Brass or Bronze Polished	Used on all TS screwless type knobs.


Specify number and finish. See pages 1 and 2.



Knob Attachments


203

METHODS OF MOUNTING




Plain or Standard Type

The knobs are attached to the spindle by screws which pass through the knob shanks and are screwed into the spindle, the knobs being drawn tight against the spindle. There are three holes in each end of the spindle, giving a range of adjustment of one inch. Washers introduced under the ends of the knob shanks eliminate end play.




Simplex Type

The shanks of both knobs and both ends of the spindle are threaded and the knobs are screwed down to make a close working contact. The knobs are held in place by cup point set screws which are screwed down firmly against the flat surface of the spindle. For use with one piece wrought knobs and glass knobs.




PY Screwless Type

The outer knob is fastened to the spindle by a pin which is covered by the thimble on the rose. The inner end of the spindle and the shank of the inner knob are threaded, and the knob is screwed down to make a close working contact. It is held in place by a cup point set screw, which screws down firmly against the flat surface of the spindle. There is a range of one inch in adjustment. The thimbles are long and bracketed onto the knob shanks, giving a smooth, easy action under close adjustment. For use with round one-piece wrought knobs with cast shank, and cast knobs, with exceptions noted on knob pages.



LH Type


For lever handles, with exceptions noted on lever handle pages; used also for unusually heavy service. The outer handle is fastened to the spindle by a pin which is covered by the thimble on the rose. The inner handle is secured by a set screw terminating in a dowel pin which passes through the spindle into the opposite side of the shank. Close adjustment is obtained by lengthening or shortening the spindle by means of the screw in the swivel. Thickness of door should be stated when ordering.



**TS Screwless Type
(Patented)**

The outer knob is fastened to the spindle by a pin which is covered by the thimble on the rose. The inner end of this spindle is threaded. With the rose in place the shank "A" is screwed down onto the spindle so that it will make a close working contact with the rose. The knob is then placed on the spindle and forced down into the shank with the cam surface "D" pressing back the spring "C" so that the knob will fit tightly against the shank. Holding the knob in this position give the shank a $\frac{1}{8}$ turn with the spanner wrench which engages a slot in the shank through the hole in the movable ring "B". This allows the springs "C" to enter groove "E" locking the knob firmly in place, after which the movable ring "B" should be turned with the fingers to conceal the slot in the shank.

Cannot be used with wrought shank knobs.



204

Rev. 6-1-57


Door Knobs

SPINDLE $\frac{5}{16}$ IN.

01623 1/2




1419 1/2, 01419 1/2


1419
Type of 1419W x 1109 Rose

No.	Diam. Inches	Material and Finish	Projec- tion Inches	Type Shank	Type Spindle	Rose			Packed in a Box	Weight Dozen Pairs
						No.	Diam. Inches	Material and Finish		
1419 1/2	2 1/4	Wrought Brass or Bronze								
1419	2 1/4	Polished	2 3/16	Simplex	056 1/4	1109	2	Brass or Bronze	6 pair	9 1/4 lbs.
1419W	2 1/4	Polished	2 3/16	PY	56	1118	2	Wrought, Polished	6 pair	12 3/4 lbs.
		Polished	2 1/32	PY	56	1109	2	Cast, Polished	6 pair	11 lbs.
								Wrought, Polished	6 pair	
01419 1/2	2 1/4	Wrought Steel								
01623 1/2	2 1/4	Plated	2 3/16	Simplex	056 1/4	01109	2	Wrought Steel	6 pair	7 1/2 lbs.
01623 1/2	2 1/4	Plated	2 1/4	Simplex	056 1/4	01109	2	Plated	6 pair	7 lbs.
J01623 1/2	2 1/4	Japanned	2 1/4	Simplex	056 1/4	01109	2	Plated	6 pair	7 lbs.
								Japanned	6 pair	

Packed with screws.



1422 to 01621



1519 1/2



1719, 1719 3/4

No.	Diam. Inches	Material and Finish	Projec- tion Inches	Type Shank	Type Spindle	Rose			Packed in a Box	Weight Dozen Pairs
						No.	Diam. Inches	Material and Finish		
1422	2	Brass or Bronze								
1621	1 3/4	Wrought, Polished	2	Simplex	056 1/4	1109	2	Brass or Bronze	6 pair	6 3/4 lbs.
1519 1/2	2 1/4	Wrought, Polished	1 13/16	Standard	36	1108	1 3/4 x 1 3/8	Wrought, Polished	6 pair	5 1/2 lbs.
		Cast, Polished	2 3/16	PY	56	1118	2	Cast, Polished	4 pair	15 1/4 lbs.
*1719	2 1/4	Wrought, Polished	2 7/16	TS	56	1122	2	Cast, Polished	4 pair	16 3/4 lbs.
*1719 1/2	2 1/4	Wrought, Polished	2 7/16	PY	56	1122	2	Cast, Polished	4 pair	16 3/4 lbs.
1719 3/4	2 1/4	Wrought, Polished	2 7/16	TS	56	1122	2	Cast, Polished	4 pair	15 1/4 lbs.
		Wrought Steel								
01422	2	Plated	2	Simplex	056 1/4	01109	2	Wrought Steel	6 pair	6 3/4 lbs.
01621	1 3/4	Plated	1 13/16	Standard	36	01108	1 3/4 x 1 3/8	Plated	6 pair	5 1/2 lbs.
								Plated	6 pair	


Packed with screws. *Steel lined.

Specify number and finish. See pages 1 and 2.




Door Knobs

205

SPINDLE $\frac{5}{16}$ IN.

1425, 01425



1830

No.	Diam. Inches	Material and Finish	Projec- tion Inches	Type Shank	Type Spindle	Rose			Packed in a Box	Weight Dozen Pairs
						No.	Diam. Inches	Material and Finish		
1425	2	Wrought Brass or Bronze								
1830	2	Polished	$1\frac{13}{16}$	Simplex	$056\frac{1}{4}$	1110	$1\frac{3}{4}$	Polished	2 Pair	$8\frac{3}{4}$ lbs.
		Polished	$2\frac{3}{8}$	French	056	1109	2	Polished	2 Pair	$9\frac{1}{2}$ lbs.
01425	2	Wrought Steel								
		Plated	$1\frac{13}{16}$	Simplex	$056\frac{1}{4}$	1110	$1\frac{3}{4}$	Plated	2 Pair	$7\frac{1}{2}$ lbs.

Packed with screws.

With Glass Tops



418


No.	Diam. Inches	Shank Material and Finish	Projec- tion Inches	Type Shank	Type Spindle	Rose			Packed in a Box	Weight Dozen Pairs
						No.	Diam. Inches	Material and Finish		
418	2	Wrought Brass or Bronze								
		Polished	$2\frac{3}{8}$	Simplex	056	1109	2	Polished	3 Pair	$11\frac{1}{2}$ lbs.

Packed with screws.

Specify number and finish. See pages 1 and 2.




Door Knobs


SPINDLES $\frac{3}{16}$ IN.

1918

Rose with Concealed Screws



1932




1954


Rose with Concealed Screws

No.	Diam. Inches	Material and Finish	Projec- tion Inches	Type Shank	Type Spindle	Rose			Packed in a Box	Weight Dozen Pairs
						No.	Diam. Inches	Material and Finish		
1918	2	Cast Brass or Polished	2	Colonial	044	1150	2	Cast Brass or Polished	2 Pair	16½ lbs.
1932	2	Polished	2 $\frac{3}{16}$	French	056 $\frac{1}{4}$	1130	1 $\frac{3}{4}$	Polished	2 Pair	14 lbs.
1954	3	Polished	2 $\frac{5}{8}$	Colonial	044	1147	2 $\frac{1}{2}$	Polished	2 Pair	30¾ lbs.


Packed with screws.



1960



1961

Screwless Knob
and Rose
1962

*Type of 1963

No.	Diam. Inches	Material and Finish	Projec- tion Inches	Type Shank	Type Spindle	Rose			Packed in a Box	Weight Dozen Pairs
						No.	Diam. Inches	Material and Finish		
1960	1 $\frac{7}{8}$	Cast Brass or Polished	2 $\frac{1}{16}$	PY	56	1160	2 $\frac{3}{8}$	Cast Brass or Polished	1	18 lbs.
1961	2	Polished	2 $\frac{7}{8}$	PY	56	1161	2 $\frac{1}{8}$	Polished	1	18 lbs.
1962	2	Polished	3	TS	56	1162	3	Polished	1	25½ lbs.
1963	2	Polished	3	TS	56	1163	3	Polished	1	25½ lbs.

Packed with screws.

*Same as 1962 except plain rose. See page 208 for screwless application.

Specify number and finish. See pages 1 and 2.




Lever Handles


Spindles $\frac{5}{16}$ in.

207

Rev. 6-1-57




2024, 02024




2020, 2021, 2022

No.	†Size Inches	Material and Finish	Projec- tion Inches	Type Shank	Type Spindle	Rose			Packed in a Box	Weight Each
						No.	Size Inches	Material and Finish		
2024	2	Cast Brass or Bronze						Brass or Bronze		
2020	2½	Polished	1½	½ in. plain	36	1108	1¾x1¾	Wrought, Polished	2 pair	4 oz.
2021	3	Polished	2¾	Simplex	056	1127	1¾	Cast, Polished	2 pair	7 oz.
2022	3¾	Polished	2¼	Simplex	056	1127	1¾	Cast, Polished	2 pair	8½ oz.
			3	Simplex	056	1118	2	Cast, Polished	2 pair	12 oz.
02024	2	Cast Iron						Wrought Steel		
		Plated	1½	½ in. plain	36	01108	1¾x1¾	Plated	2 pair	4 oz.

Packed with screws.




2025




7025, 07025

No.	†Size Inches	Material and Finish	Projec- tion Inches	Type Shank	Type Spindle	Rose			Packed in a Box	Weight Each
						No.	Diam. Inches	Material and Finish		
2025	2⅞	Cast Brass or Bronze						Cast Brass or Bronze		
7025	2⅞	Polished	1⅞	Simplex	056	1120	2	Polished	2 pair	8 oz.
		*Colonium Metal	1⅞	Simplex	056	1125	2	Colonium Metal	2 pair	8 oz.
		Old Iron finish						Old Iron finish		
07025	2⅞	Cast Iron						Cast Iron		
		*Plated	1⅞	Simplex	056	01125	2	Plated	2 pair	8 oz.


Packed with screws. *HPE finish only.



2009, Right Hand*



2782



2784

No.	†Size Inches	Material and Finish	Projec- tion Inches	Type Shank	Type Spindle	Rose			Packed in a Box	Weight Each
						No.	Diam. Inches	Material and Finish		
2009	3¼	Cast Brass or Bronze						Cast Brass or Bronze		
2782	4	Polished	2⅞	Simplex	056	1129	1¾	Polished	2 pair	10 oz.
2784	4½	Polished	2¼	Simplex	056	2782	3	Polished	2 pair	1 lb.
		Polished	2⅞	Simplex	056	2784	2¼	Polished	2 pair	⅞ lb.

Packed with screws. †Size of lever handle is the length measured from center of spindle to end of lever. *Specify hand.

Specify number and finish. See pages 1 and 2.




Knob Roses



1108, 01108





1109, 01109







01138

No.	Size Inches	Material and Finish	Height Inches	Use
1108 1109	1 3/4 x 1 3/8 2 Dia.	Wrought Brass or Bronze Polished Polished	5/16 1 3/32	1621 knob and 2024 lever. For simplex, french shank and glass knobs.
01108 01109	1 3/4 x 1 3/8 2 Dia.	Wrought Steel Plated Plated	3/16 1 3/32	01621 knobs and 02024 lever. For simplex knobs.
01138	1 3/4 Dia.	Cast Iron HPE Finish only	1/2	For cast iron simplex knobs.

Packed with screws.

1118
1117 same but no
screw holes


1122, 1124

1121, 1123
†Screwless†Metal Door
Application†Wood
Application1106
with built in
auxiliary spring

1120, 1127



1129, 1130



*1125, 01125

No.	Diameter Inches	Material and Finish	Height Inches	Use
1106	1 3/4	Cast Brass or Bronze Polished	5/8	For lever handles.
1117	2	Polished	3/4	For use with No. 20 plate and TS knob.
1118	2	Polished	3/4	For PY and simplex knobs.
1120	2	Polished	7/16	For lever handles.
1121	2	Polished	3/4	Screwless rose for TS screwless knobs.
1122	2	Polished	3/4	For TS screwless knobs.
1123	2 1/2	Polished	3/4	Screwless rose for TS screwless knobs.
1124	2 1/2	Polished	3/4	For TS screwless knobs.
1127	1 3/4	Polished	1 3/32	For lever handles.
1129	1 3/4	Polished	1 3/32	For lever handles.
1130	1 3/4	Polished	1 1/32	For french shank knobs.
*1125	2	Colonium metal *Old Iron finish	7/16	For simplex knobs and lever handles.
*01125	2	Cast Iron *Plated	7/16	For simplex knobs and lever handles.

Packed with screws.

*HPE finish only.

Specify number and finish. See pages 1 and 2.



Escutcheons

209

Rev. 6-1-57



2560, 02560
Type of 2660



*74140



2662

No.	Size Inches	Material and Finish	Keyhole	Packed in a Box	Weight Dozen
2660	1 $\frac{5}{8}$ x1 $\frac{1}{8}$	Cast Brass or Bronze Polished	Regular and Key Class 306	24	8 oz.
2662	1 $\frac{3}{4}$ x $\frac{3}{4}$	Polished	Regular	12	13 oz.
*74140	1 $\frac{3}{4}$ x1 $\frac{1}{16}$	Polished	Key Class 306	12	9 oz.
2560	1 $\frac{5}{8}$ x1 $\frac{1}{8}$	Wrought Brass or Bronze Polished	Regular	24	5 oz.
02560	1 $\frac{5}{8}$ x1 $\frac{1}{8}$	Wrought Steel Plated	Regular	24	5 oz.

Packed with screws.

*Can be furnished partial dished or fully dished when so ordered.


Thumb Knobs



2148



2142 - 2143




2140, 2145



2147



2144



2138, 2248

No.	Plate Size Inches	Material and Finish	Spindle Inches	Packed in a Box	Weight Dozen
*2138	1 $\frac{7}{8}$ x1 $\frac{1}{4}$	Cast Brass or Bronze Polished	$\frac{3}{16}$	12	3 lbs.
2142	1 $\frac{1}{2}$ Dia.	Polished	$\frac{3}{16}$	12
2143	1 $\frac{1}{2}$ Dia.	Polished	$\frac{5}{16}$	12
2145	1 $\frac{5}{8}$ x1 $\frac{1}{8}$	Polished	$\frac{3}{16}$	12	1 $\frac{1}{2}$ lbs.
2147	1 $\frac{1}{2}$ Dia.	Polished	$\frac{3}{16}$	12	1 $\frac{3}{4}$ lbs.
*2148	2 $\frac{3}{4}$ x1	Polished	$\frac{3}{16}$	12	2 $\frac{1}{4}$ lbs.
*2248	1 $\frac{5}{8}$ x1 $\frac{1}{4}$	Polished	$\frac{5}{16}$	12	3 $\frac{3}{16}$ lbs.
2140	1 $\frac{5}{8}$ x1 $\frac{1}{8}$	Wrought Brass or Bronze Polished	$\frac{3}{16}$	12	1 $\frac{1}{4}$ lbs.
2144	1 $\frac{1}{2}$ Dia.	Polished	$\frac{3}{16}$	12

Packed with screws.


*Knob size: No. 2138 and 2248 1 $\frac{3}{4}$ x1 $\frac{1}{8}$ in. No. 2148 1 $\frac{1}{2}$ x $\frac{5}{8}$ in.

Specify number and finish. See pages 1 and 2.



210


Flush Cup Handles

Spindle $\frac{3}{16}$ in.

1952



1950



1953

No.	Overall Diameter Inches	Material and Finish	Depth of Cup Inches	Projection Back of Flange Inches	Packed in a Box	Weight Dozen
1950	$1\frac{3}{4}$	Cast Brass or Bronze				
1952	3	Cup Wrought Brass or Bronze Polished Polished	$\frac{5}{16}$ $\frac{1}{2}$	$\frac{3}{8}$ $\frac{7}{16}$	6 6	2 $\frac{3}{8}$ lbs. 6 $\frac{3}{4}$ lbs.

Packed with screws.

No.	Plate Size Inches	Material and Finish	Cup Diameter Inches	Depth of Cup Inches	Projection Back of Plate Inches	Packed in a Box	Weight Dozen
1953	3 x 3	Cast Brass or Bronze Polished	2 $\frac{1}{2}$	$\frac{1}{2}$	$\frac{5}{8}$	6	8 $\frac{1}{2}$ lbs.

Packed with screws.

Specify number and finish. See pages 1 and 2.



Escutcheons

209

Rev. 6-1-57

2560, 02560
Type of 2660

*74140




2662

No.	Size Inches	Material and Finish	Keyhole	Packed in a Box	Weight Dozen
2660	1 $\frac{5}{8}$ x 1 $\frac{1}{8}$	Cast Brass or Bronze Polished	Regular and Key Class 306	24	8 oz.
2662	1 $\frac{3}{4}$ x $\frac{3}{4}$	Polished	Regular	12	13 oz.
*74140	1 $\frac{3}{4}$ x 1 $\frac{3}{16}$	Polished	Key Class 306	12	9 oz.
2560	1 $\frac{5}{8}$ x 1 $\frac{1}{8}$	Wrought Brass or Bronze Polished	Regular	24	5 oz.
02560	1 $\frac{5}{8}$ x 1 $\frac{1}{8}$	Wrought Steel Plated	Regular	24	5 oz.

Packed with screws.

*Can be furnished partial dished or fully dished when so ordered.


Thumb Knobs



2148



2142 - 2143




2140, 2145



2147



2144



2138, 2248

No.	Plate Size Inches	Material and Finish	Spindle Inches	Packed in a Box	Weight Dozen
*2138	1 $\frac{7}{8}$ x 1 $\frac{1}{4}$	Cast Brass or Bronze Polished	$\frac{3}{16}$	12	3 lbs.
2142	1 $\frac{1}{2}$ Dia.	Polished	$\frac{3}{16}$	12
2143	1 $\frac{1}{2}$ Dia.	Polished	$\frac{5}{16}$	12
2145	1 $\frac{5}{8}$ x 1 $\frac{1}{8}$	Polished	$\frac{3}{16}$	12	1 $\frac{1}{2}$ lbs.
2147	1 $\frac{1}{2}$ Dia.	Polished	$\frac{3}{16}$	12	1 $\frac{1}{4}$ lbs.
*2148	2 $\frac{3}{4}$ x 1	Polished	$\frac{3}{16}$	12	2 $\frac{1}{4}$ lbs.
*2248	1 $\frac{7}{8}$ x 1 $\frac{1}{4}$	Polished	$\frac{5}{16}$	12	3 $\frac{3}{16}$ lbs.
2140	1 $\frac{5}{8}$ x 1 $\frac{1}{8}$	Wrought Brass or Bronze Polished	$\frac{3}{16}$	12	1 $\frac{1}{4}$ lbs.
2144	1 $\frac{1}{2}$ Dia.	Polished	$\frac{3}{16}$	12

Packed with screws.

*Knob size: No. 2138 and 2248 1 $\frac{3}{4}$ x 1 $\frac{1}{8}$ in. No. 2148 1 $\frac{1}{2}$ x $\frac{5}{8}$ in.

Specify number and finish. See pages 1 and 2.





MODERN LOCKSETS

UNIT LOCKSETS

HEAVY DUTY CYLINDRICAL LOCKSETS



Defender STANDARD DUTY CYLINDRICAL LOCKSETS

Guardian RESIDENTIAL CYLINDRICAL LOCKSETS

TUBULAR LOCKSETS

MORTISE LOCKSETS

RIM LOCKSETS





 INDEX OF

Item	Page
UNIT LOCKS	213, 217
CYLINDRICAL	
Heavy Duty	218, 233
Standard Duty "Defender"	234, 244
Light Duty "Guardian"	245, 250
TUBULAR	
Lock Sets ..	251, 253
COMBINATION SETS	254, 255
CONVENTIONAL SETS	
Colonial	256
Rim	257
Cast Iron	257

"900" Series Unit Locks

213

Rev. 6-1-57

FOR PUBLIC, INSTITUTIONAL AND COMMERCIAL BUILDINGS, FINE RESIDENCES AND APARTMENTS



The Corbin "900" Series Unit Locks are a smaller lighter model of the Corbin heavy duty commercial Unit Locks, which have been extensively used for over fifty years on many of the finest Public and Commercial Buildings.

For security and long lasting satisfactory performance, Unit Locks have proved themselves to be the finest lock obtainable for building construction.

These locks are assembled at the factory and are shipped as a complete unit.

Latch bolts are of the pivoted swinging type for easy quiet closing.

The cylinder locks have secure pin tumbler locking mechanism with the key hole in the knob. Can be masterkeyed if desired.

Easy to install, no mortising is required, just two saw cuts, knock out the block, drill two holes for through bolts, slip the lock into place and apply the through bolts.

Uniform size of case for all functions making them interchangeable in the same mortise.

For illustration of sets available and details, see following pages.

214


Rev. 6-1-57

"900" Series Unit Locks


FOR PUBLIC, INSTITUTIONAL AND COMMERCIAL BUILDINGS, FINE RESIDENCES AND APARTMENTS

CAST BRASS, BRONZE OR ALUMINUM

(Factory Assembled)



View with jacket drawn back to show parts.

**Knob with Push Button**

Push Button is pushed in to lock and except where otherwise noted is released by a turn of key outside, knob inside or closing door.

**Knob with Turn Button**

Turn button is manually operated both to lock and unlock.

- Frame** One piece extruded brass for all locks.
- Case** $1\frac{3}{4} \times 3\frac{1}{4}$ in.
- Backset** $2\frac{1}{2}$ in.
- Front** Flat for $1\frac{3}{8}$ in. Door. Beveled $\frac{1}{8}$ in. 2 in. for $1\frac{3}{4}$ in. door.
- Latch Bolt** ... Swinging Type, $\frac{5}{8}$ in. throw. Can also be furnished $\frac{3}{4}$ in. throw. To order affix $\frac{3}{4}$ to lock number, thus: 900-951 $\frac{3}{4}$.
- Cylinder** Nos. 460 and 460 $\frac{1}{2}$ extruded brass. 5 pin for stock; 6 pin for master keyed jobs.
- Keys** Two Nickel Silver keys Class 77. Masterkey Class 077 for 5 pin cylinders. Class 73 $\frac{1}{4}$, Masterkey Class 073 $\frac{1}{4}$ for 6 pin cylinders. Can be masterkeyed with other Corbin cylinder locks.
- Hand** Reversible for right or left hand doors opening in. Can be furnished reverse bevel for doors opening out if so ordered.

* **Door Thickness** — Furnished for either $1\frac{3}{8}$ in. or $1\frac{3}{4}$ in. doors. State thickness required.

FINISHES AVAILABLE


- A — Polished Brass.
 EA — Dull Brass.
 DB — Dull Bronze.
 CR — Chromium Plated, Polished.
 DCR — Chromium Plated, Dull.
 DL — Dull Satin Aluminum.

**OPEN BACK STRIKE**
CAST BRASS, BRONZE OR ALUMINUM


Furnished only when ordered.

Size $3\frac{1}{2} \times 1\frac{1}{8}$ in.No. 925V for $1\frac{3}{4}$ in. doors with V bevel.No. 925S for $1\frac{3}{8}$ in. doors flat front.**Strikes**

900SA



901SA



2900S



2901S

WROUGHT BRASS, BRONZE OR ALUMINUM

Regular strikes for single doors with adjusting screw to compensate for door shrinkage. With curved lip. Dimension "B" measured from stop to end of lip $1\frac{1}{4}$ in. for $1\frac{3}{8}$ in. door, $2\frac{1}{8}$ in. for $1\frac{3}{4}$ in. door.

WROUGHT BRASS, BRONZE OR ALUMINUM

Regular strike for pairs of doors non-adjustable. With straight lip. Dimension "B" edge of strike to end of lip $1\frac{1}{16}$ in. for $1\frac{3}{8}$ in. doors, $1\frac{13}{16}$ in. for $1\frac{3}{4}$ in. doors.

*State whether for $1\frac{3}{8}$ or $1\frac{3}{4}$ in. door. Specify reverse bevel if for doors opening out.

"900" Series Unit Locks

214A


FOR PUBLIC, INSTITUTIONAL AND COMMERCIAL BUILDINGS, FINE RESIDENCES AND APARTMENTS

CAST BRASS, BRONZE OR ALUMINUM

(Factory Assembled)

Inside

Outside




No. 900

For Communicating Doors

Latch Bolt operated by knob from either side except when latch bolt has been dead locked and both knobs made rigid by turn of button in either knob.

Door can be opened only when turn buttons on both sides are in unlocked position.

Latch bolt is automatically dead-locked when door is closed.



No. 910


For Passage Doors

Latch Bolt operated by knobs from either side of door.

No. 910½

Fire Door Latch

Same as No. 910 but with ¾ in. throw latch bolt.



No. 915

Exit Latch

For doors used for exit only.


Latch bolt operated by knob from the inside at all times. Outside knob always rigid.

Latch bolt is automatically dead-locked when door is closed.

FUNCTIONS AVAILABLE

Inside

Outside



No. 902

Communicating Lock

For connecting doors.


Latch bolt operated by knobs from either side except when key in either knob locks opposite knob.

Latch bolt is automatically dead-locked when door is closed.

To prevent accidental lockout this lock should not be used on doors between rooms which have no other entrance.

Inside

Outside



No. 920


For Bedroom or Bathroom Door

Latch Bolt operated by knobs from either side of door except when outside knob has been locked by pushing in button in center of inside knob.

A turn of inside knob releases locking mechanism.

In case of emergency, door can be unlocked from the outside by pressure of small pointed object against the emergency device in center of outside knob.

Cannot be accidentally locked. If locking button in inside knob has been pushed in while door is open, contact of latch bolt with strike as door closes, automatically releases locking mechanism.




No. 921

Patio Lock

For Patio, Sun Deck or Basement doors or for doors that require locking only when room is occupied. Can also be used for bedroom or bathroom doors if emergency operation from outside is not required.

Latch bolt operated by knobs from either side except when outside knob is locked by pushing in button in inside knob.

Turning inside knob or closing door automatically releases locking button.



No. 920Y

Privacy Lock

For use on bathroom, bedroom or lavatory doors.

Latch bolt operated by knobs from either side except when outside knob is locked by pushing in button in inside knob.

Turning inside knob or closing door automatically releases locking button.

When locked, a spindle projects through center of outside knob, which can be pushed in to release locking mechanism in case of emergency.

For further description dimensions, etc., see page 214. Above numbers cover functions only. For sets complete with knobs and escutcheons in various designs see pages 215 to 217.

214B

"900" Series Unit Locks

FOR PUBLIC, INSTITUTIONAL AND COMMERCIAL BUILDINGS, FINE RESIDENCES AND APARTMENTS


CAST BRASS, BRONZE OR ALUMINUM

(Factory Assembled)

FUNCTIONS AVAILABLE

Inside

Outside


**No. 927****StatEROom or Hotel Lock**

For use on Corridor Doors.

Latch bolt operated by knob from inside and by key from the outside. Outside knob always rigid.

Pushing in button in inside knob shuts out all keys, except emergency key and projects a visual occupancy indicator in face of cylinder. Turning inside knob or closing door automatically releases locking button and shut out features and retracts indicator.

Latch bolt is automatically deadlocked when door is closed.

**No. 941****Patio, Exit or Privacy Lock**

Latch Bolt operated by knobs from either side of door except when outside knob has been locked by pushing in button in center of inside knob.


A turn of inside knob releases locking mechanism.

Cannot be accidentally locked. If locking button in inside knob has been pushed in while door is open, contact of latch bolt with strike as door closes, automatically releases locking mechanism.

Latch bolt is automatically deadlocked when door is closed.

Inside

Outside


**No. 929****Hotel Corridor Lock**

Latch bolt operated by knob from the inside and by key from the outside. Outside knob is always rigid.

Pushing in button in inside knob shuts out all keys except emergency key and projects a visual occupancy indicator in face of cylinder.

Turning inside knob or closing door automatically releases locking button and shutout features and retracts indicator unless button has been fixed in locked position by turning with a special spanner key.

Latch bolt is automatically deadlocked when door is closed.

**No. 944****Patio, Exit or Office Communicating Doors**


Latch Bolt operated by knobs from either side except when latch bolt is deadlocked and both knobs made rigid by a turn of button in inside knob.

To prevent accidental lockout this lock should not be used on doors to rooms which have no other entrance.

Latch bolt is automatically deadlocked when door is closed.

Inside


Outside

**No. 932****Fixed Knob Lock**

For passage doors which are always locked.

Latch bolt operated by key from either side. Both knobs always rigid.

Latch bolt is automatically deadlocked when door is closed.

**No. 951****For Entrance or Office Doors**

By key from the outside at all times, and by knobs from either side except when outside knob is locked by a turn of turn button in inside knob.

Retracting latch bolt by means of key from outside or knob from inside does not disturb locking mechanism which is controlled only by turn button in inside knob.

Latch bolt is automatically deadlocked when door is closed.

No. 951 3/4**Fire Door Lock**

Same as No. 951 except for 3/4 in. throw latch bolt.

For further description dimensions, etc., see page 214. Above numbers cover functions only. For sets complete with knobs and escutcheons in various designs see pages 215 to 217.

"900" Series Unit Locks

214C

FOR PUBLIC, INSTITUTIONAL AND COMMERCIAL BUILDINGS, FINE RESIDENCES AND APARTMENTS


CAST BRASS, BRDNZE DR ALUMINUM

(Factory Assembled)

FUNCTIONS AVAILABLE

Inside

Outside



No. 954

For Office, Apartment Vestibule Entrance or Public Lavatory Doors


Latch Bolt operated by key from outside at all times and by knob from either side except when outside knob is locked from inside by masterkey only unless otherwise ordered.

Latch bolt is automatically deadlocked when door is closed.

No. 954 3/4

Fire Door Lock

Same as No. 954 but 3/4 in. throw latch bolt.



No. 965

Dormitory Lock

For dormitory bedrooms or public rest room doors.

Latch bolt operated by 1/4 turn of key in counter-clockwise direction from outside at all times and by knobs from either side except when outside knob is locked by pushing in locking button in inside knob or turning key 1/4 turn in clockwise direction in outside knob. Inside knob is always free.


When outside knob is locked by push button from inside, a turn of inside knob a quarter counter-clockwise turn of key in outside knob or closing door releases locking button.

When outside knob is locked by key, locking mechanism can only be released by a counter-clockwise turn of key in outside knob.

Outside knob cannot be locked by key unless locking button is in released position.

Inside

Outside



No. 955


For Classroom Doors

Latch Bolt operated by knob from inside at all times and by knob from outside except when it is locked by key from outside.

Latch bolt is automatically deadlocked when door is closed.

No. 955 1/4

Same as No. 955 except that latch bolt can be held retracted by retracting latch bolt by means of outside knob and turning key while in this position.




No. 964

For Office, Apartment Vestibule Entrance or Public Lavatory Doors

Latch Bolt operated by key from the outside and knob from the inside. Outside knob rigid at all times.

To hold latch bolt retracted, turn inside knob to retract latch bolt and lock in this position by a full turn of key in inside knob.

Latch bolt automatically deadlocked when door is closed.



No. 957


For Closet and Storeroom Doors

Latch Bolt operated by key from the outside and knob from the inside. Outside knob is always rigid.

Latch bolt is automatically deadlocked when door is closed.

Inside

Outside




No. 956

Patio Lock

For doors to Patio, Sun Deck, etc.

Latch Bolt operated by Knobs from either side, except when outside knob is locked by key in inside knob.

Latch bolt is automatically deadlocked when door is closed.




No. 961

Inner Office or Privacy Lock

Latch Bolt operated by key from the outside at all times and by knobs from either side except when outside knob is locked by pushing in locking button in inside knob. A turn of key outside or knob inside releases locking button. Closing door when locking button is pushed in does not release locking mechanism.

Latch bolt is automatically deadlocked when door is closed.



No. 988

Store Door Lock

For store entrance or communicating doors.

Latch bolt operated by knobs from either side except when both knobs are locked by turning key in either knob. When both knobs are locked from either side, key from either side will unlock both knobs.

Latch bolt automatically deadlocks when door is closed.


For further description dimensions, etc., see page 214. Above numbers cover functions only. For sets complete with knobs and escutcheons in various designs see pages 215 to 217.

214D

"900" Series Unit Locks

FOR PUBLIC, INSTITUTIONAL AND COMMERCIAL BUILDINGS, FINE RESIDENCES AND APARTMENTS

FUNCTIONS AVAILABLE WITH DEAD BOLT, HAVING HARDENED STEEL INSERT.



No. 901D
Communicating or Closet Lock

Or for any door which is to be deadlocked from outside only. Can also be furnished to deadlock from inside only when so ordered.

Latch bolt operated by knobs from either side.

Dead bolt operated by key from one side only.

No. 922D
For Entrance, Store Door
or Communicating Doors


Latch bolt operated by knobs from either side.

Dead bolt operated by key from either side.

No. 923D
For Entrance, Store Door
or Communicating Doors

Latch bolt operated by knobs from either side.

Dead bolt operated by key from outside or turn button inside.



No. 924D

Patio or Exit Lock


Can also be used for bedroom or bathroom doors if emergency operation from outside is not required.

Latch bolt operated by knobs from either side.

Dead bolt operated by turn button in inside knob only.

For further description dimensions, etc., see page 214. Above numbers cover functions only. For sets complete with knobs and escutcheons in various designs see pages 215 to 217.

CYLINDERS




No. 460 Standard

No. 460½ with master ring.
Extruded Brass.

5 Pin. for stock 6 Pin for master keyed jobs.

Illustration shows cam for 95I lock. In ordering state number of lock with which cylinder is to be used so that correct cam can be furnished.

DUMMY TRIM



900 series unit locksets can be furnished with Dummy Trim, when so ordered.

For further description dimensions, etc., see page 214. Above numbers cover functions only. For sets complete with knobs and escutcheons in various designs see pages 215 to 217.

"900" Series Unit Locks

215


Rev. 6-1-57

FOR PUBLIC, INSTITUTIONAL AND COMMERCIAL BUILDINGS, FINE RESIDENCES AND APARTMENTS

Spartan Design No. 900


CAST BRASS, BRONZE OR ALUMINUM

(Factory Assembled)



900-951

Typical of all sets except 750-551.



750-551

Heavy duty set for entrance doors
over 1 3/4 to 2 1/4 in. thick.

COMPLETE SETS

Door	Set Number	Lock		Pair Knobs Diam. Inches	Two Escutcheons Size, Inches
		No.	See Page		
Communicating	900-900	900	214A	2 3/16	3 1/8
Communicating, Storeroom, Etc.	900-901D	901D	214D	2 3/16	3 1/8
Communicating	900-902	902	214A	2 3/16	3 1/8
Passage (Latch)	900-910	910	214A	2 3/16	3 1/8
Fire Door (Latch)	900-910 3/4	910 3/4	214A	2 3/16	3 1/8
Exit (Latch)	900-915	915	214A	2 3/16	3 1/8
Bathroom, Bedroom, Conference Room	900-920	920	214A	2 3/16	3 1/8
Bathroom, Bedroom	900-920Y	920Y	214A	2 3/16	3 1/8
Patio or Sun Deck	900-921	921	214A	2 3/16	3 1/8
Entrance or Communicating	900-922D	922D	214D	2 3/16	3 1/8
Entrance or Communicating	900-923D	923D	214D	2 3/16	3 1/8
Exit or Patio	900-924D	924D	214D	2 3/16	3 1/8
Stateroom or Hotel Corridor	900-927	927	214B	2 3/16	3 1/8
Hotel Corridor	900-929	929	214B	2 3/16	3 1/8
Fixed Knob Lock	900-932	932	214B	2 3/16	3 1/8
Patio, Sun Deck or Basement	900-941	941	214B	2 3/16	3 1/8
Exit or Patio	900-944	944	214B	2 3/16	3 1/8
Entrance or Office	900-951	951	214B	2 3/16	3 1/8
Fire Door	900-951 3/4	951 3/4	214B	2 3/16	3 1/8
Apartment Vestibule Entrance, Office or Public Toilet	900-954	954	214C	2 3/16	3 1/8
Fire Door	900-954 3/4	954 3/4	214C	2 3/16	3 1/8
Class Room	900-955	955	214C	2 3/16	3 1/8
Class Room	900-955 1/4	955 1/4	214C	2 3/16	3 1/8
Storeroom or Closet	900-957	957	214C	2 3/16	3 1/8
Office	900-961	961	214C	2 3/16	3 1/8
Apartment Vestibule Entrance, or Office	900-964	964	214C	2 3/16	3 1/8
Dormitory, Bedroom or Public Rest Room	900-965	965	214C	2 3/16	3 1/8
Store Door	900-988	988	214C	2 3/16	3 1/8
Entrance for Doors 1 3/4 to 2 1/4 thick	*750-551	551	2 1/4	5

One set in a box with screws.

State whether for 1 3/8 or 1 3/4 in. door. Specify reverse bevel if for doors opening out.

*State hand and thickness of door for set 750-551. This is a heavy duty unit lockset case 2 3/8 x 3 3/4 x 1 3/8 in. Backset 3 in., front beveled 1/4 in., in 2 in. Latch Bolt 5/8 in. throw. Operated by key from outside at all times and by knobs from either side except when outside knob is locked by stop in face. Auxiliary latch deadlocks latch bolt when door is closed.

Specify number and finish. See pages 1 and 2.

The Canadian Locksmith 2004




216

Rev. 6-1-57

"900" Series Unit Locks

FOR PUBLIC, INSTITUTIONAL AND COMMERCIAL BUILDINGS, FINE RESIDENCES AND APARTMENTS

**904-951**

Titan Design

No. 904

CAST BRASS, BRONZE OR ALUMINUM
(Factory Assembled)

COMPLETE SETS

Door	Set Number	Lock		Pair Knobs Diam. Inches	Two Escutcheons Size, Inches
		No.	See Page		
Communicating	904-900	900	214A	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Communicating, Storeroom, Etc.	904-901D	901D	214D	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Communicating	904-902	902	214A	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Passage (Latch)	904-910	910	214A	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Fire Door (Latch)	904-910³/₄	910 ³ / ₄	214A	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Exit (Latch)	904-915	915	214A	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Bath, Bedroom, Conference Room	904-920	920	214A	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Bathroom, Bedroom	904-920Y	920Y	214A	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Patio or Sun Deck	904-921	921	214A	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Entrance or Communicating	904-922D	922D	214D	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Entrance or Communicating	904-923D	923D	214D	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Exit or Patio	904-924D	924D	214D	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Stateroom or Hotel Corridor	904-927	927	214B	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Hotel Corridor	904-929	929	214B	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Fixed Knob Lock	904-932	932	214B	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Patio, Sun Deck or Basement	904-941	941	214B	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Exit or Patio	904-944	944	214B	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Entrance or Office	904-951	951	214B	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Fire Door	904-951³/₄	951 ³ / ₄	214B	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Apartment Vestibule Entrance, Office or Public Toilet	904-954	954	214C	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Fire Door	904-954³/₄	954 ³ / ₄	214C	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Class Room	904-955	955	214C	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Class Room	904-955¹/₄	955 ¹ / ₄	214C	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Storeroom or Closet	904-957	957	214C	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Office	904-961	961	214C	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Apartment Vestibule Entrance, or Office	904-964	964	214C	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Dormitory, Bedroom or Public Rest Room	904-965	965	214C	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄
Store Door	904-988	988	214C	2 ³ / ₁₆	3 ¹ / ₈ x 3 ¹ / ₄

One in a box with screws.

State whether for 1³/₈ or 1³/₄ in. door.

Specify reverse bevel if for door opening out.


Specify number and finish. See pages 1 and 2.**The Canadian Locksmith 2004**

"900" Series Unit Locks**216A**

FOR FINE COLONIAL RESIDENCES

**Windsor Design
No. 903**

CAST BRASS OR BRONZE

**903-951**

COMPLETE SETS

Door	Set Number	Lock		Pair Knobs Diam. Inches	Two Escutcheons Diam. Inches
			See Page		
Passage (Latch)	903-910	910	214A	2 $\frac{7}{16}$	3 $\frac{1}{8}$
Bath or Bedroom	903-920	920	214A	2 $\frac{3}{4}$	3 $\frac{1}{8}$
Patio or Sun Deck	903-921	921	214A	2 $\frac{5}{16}$	3 $\frac{1}{8}$
Patio, Sun Deck or Basement	903-941	941	214B	2 $\frac{3}{16}$	3 $\frac{1}{8}$
Entrance	903-951	951	214B	2 $\frac{3}{16}$	3 $\frac{1}{8}$

One in a box with screws.

State whether for 1 $\frac{3}{8}$ or 1 $\frac{3}{4}$ in. door.

Specify reverse bevel if for door opening out.

While the above Windsor Sets were designed primarily for fine colonial residences other than residential functions will be available if required.


Specify number and finish. See pages 1 and 2.

216B**"900" Series Unit Locks**

FOR PUBLIC, INSTITUTIONAL AND COMMERCIAL BUILDINGS, FINE RESIDENCES AND APARTMENTS

**Crestwood Design
No. 905****CAST BRASS, BRONZE OR ALUMINUM**

(Factory Assembled)

**905-951****COMPLETE SETS**

Door	Set Number	Lock		Pair Knobs Diam. Inches	Two Escutcheon Size, Inches
		No.	See Page		
Communicating	905-900	900	214A	2 1/4	3 1/8 x 3 1/4
Communicating, Storeroom, Etc.	905-901D	901D	214D	2 1/4	3 1/8 x 3 1/4
Communicating	905-902	902	214A	2 1/4	3 1/8 x 3 1/4
Passage (Latch)	905-910	910	214A	2 1/4	3 1/8 x 3 1/4
Fire Door (Latch)	905-910 3/4	910 3/4	214A	2 1/4	3 1/8 x 3 1/4
Exit (Latch)	905-915	915	214A	2 1/4	3 1/8 x 3 1/4
Bath, Bedroom, Conference Room	905-920	920	214A	2 1/4	3 1/8 x 3 1/4
Bathroom, Bedroom	905-920Y	920Y	214A	2 1/4	3 1/8 x 3 1/4
Patio or Sun Deck	905-921	921	214A	2 1/4	3 1/8 x 3 1/4
Entrance or Communicating	905-922D	922D	214D	2 1/4	3 1/8 x 3 1/4
Entrance or Communicating	905-923D	923D	214D	2 1/4	3 1/8 x 3 1/4
Exit or Patio	905-924D	924D	214D	2 1/4	3 1/8 x 3 1/4
Stateroom or Hotel Corridor	905-927	927	214B	2 1/4	3 1/8 x 3 1/4
Hotel Corridor	905-929	929	214B	2 1/4	3 1/8 x 3 1/4
Fixed Knob Lock	905-932	932	214B	2 1/4	3 1/8 x 3 1/4
Patio, Sun Deck or Basement	905-941	941	214B	2 1/4	3 1/8 x 3 1/4
Exit or Patio	905-944	944	214B	2 1/4	3 1/8 x 3 1/4
Entrance or Office	905-951	951	214B	2 1/4	3 1/8 x 3 1/4
Fire Door	905-951 3/4	951 3/4	214B	2 1/4	3 1/8 x 3 1/4
Apartment Vestibule Entrance, Office or Public Toilet	905-954	954	214C	2 1/4	3 1/8 x 3 1/4
Fire Door	905-954 3/4	954 3/4	214C	2 1/4	3 1/8 x 3 1/4
Class Room	905-955	955	214C	2 1/4	3 1/8 x 3 1/4
Class Room	905-955 1/4	955 1/4	214C	2 1/4	3 1/8 x 3 1/4
Storeroom or Closet	905-957	957	214C	2 1/4	3 1/8 x 3 1/4
Office	905-961	961	214C	2 1/4	3 1/8 x 3 1/4
Apartment Vestibule Entrance, or Office	905-964	964	214C	2 1/4	3 1/8 x 3 1/4
Dormitory, Bedroom or Public Rest Room	905-965	965	214C	2 1/4	3 1/8 x 3 1/4
Store Door	905-988	988	214C	2 1/4	3 1/8 x 3 1/4

One in a box with screws.

State whether for 1 3/8 or 1 3/4 in. door.

Specify reverse bevel if for door opening out.


Specify number and finish. See pages 1 and 2.

The Canadian Locksmith 2004



"900" Series Unit Locks**216C**

FOR PUBLIC, INSTITUTIONAL AND COMMERCIAL BUILDINGS, FINE RESIDENCES AND APARTMENTS

**908-951****Knollwood Design
No. 908****CAST BRASS, BRONZE OR ALUMINUM**
(Factory Assembled)**COMPLETE SETS**

Door	Set Number	Lock		Pair Knobs Diam. Inches	Two Escutcheons Size, Inches
		No.	See Page		
Communicating	908-900	900	214A	2 1/4	3 1/8 x 3 1/4
Communicating, Storeroom, Etc.	908-901D	901D	214D	2 1/4	3 1/8 x 3 1/4
Communicating	908-902	902	214A	2 1/4	3 1/8 x 3 1/4
Passage (Latch)	908-910	910	214A	2 1/4	3 1/8 x 3 1/4
Fire Door (Latch)	908-910 3/4	910 3/4	214A	2 1/4	3 1/8 x 3 1/4
Exit (Latch)	908-915	915	214A	2 1/4	3 1/8 x 3 1/4
Bath, Bedroom, Conference Room	908-920	920	214A	2 1/4	3 1/8 x 3 1/4
Bathroom, Bedroom	908-920Y	920Y	214A	2 1/4	3 1/8 x 3 1/4
Patio or Sun Deck	908-921	921	214A	2 1/4	3 1/8 x 3 1/4
Entrance or Communicating	908-922D	922D	214D	2 1/4	3 1/8 x 3 1/4
Entrance or Communicating	908-923D	923D	214D	2 1/4	3 1/8 x 3 1/4
Exit or Patio	908-924D	924D	214D	2 1/4	3 1/8 x 3 1/4
Stateroom or Hotel Corridor	908-927	927	214B	2 1/4	3 1/8 x 3 1/4
Hotel Corridor	908-929	929	214B	2 1/4	3 1/8 x 3 1/4
Fixed Knob Lock	908-932	932	214B	2 1/4	3 1/8 x 3 1/4
Patio, Sun Deck or Basement	908-941	941	214B	2 1/4	3 1/8 x 3 1/4
Exit or Patio	908-944	944	214B	2 1/4	3 1/8 x 3 1/4
Entrance or Office	908-951	951	214B	2 1/4	3 1/8 x 3 1/4
Fire Door	908-951 3/4	951 3/4	214B	2 1/4	3 1/8 x 3 1/4
Apartment Vestibule Entrance, Office or Public Toilet	908-954	954	214C	2 1/4	3 1/8 x 3 1/4
Fire Door	908-954 3/4	954 3/4	214C	2 1/4	3 1/8 x 3 1/4
Class Room	908-955	955	214C	2 1/4	3 1/8 x 3 1/4
Class Room	908-955 1/4	955 1/4	214C	2 1/4	3 1/8 x 3 1/4
Storeroom or Closet	908-957	957	214C	2 1/4	3 1/8 x 3 1/4
Office	908-961	961	214C	2 1/4	3 1/8 x 3 1/4
Apartment Vestibule Entrance, or Office	908-964	964	214C	2 1/4	3 1/8 x 3 1/4
Dormitory, Bedroom or Public Rest Room	908-965	965	214C	2 1/4	3 1/8 x 3 1/4
Store Door	908-988	988	214C	2 1/4	3 1/8 x 3 1/4

One in a box with screws.

State whether for 1 3/8 or 1 3/4 in. door.

Specify reverse bevel if for door opening out.


Specify number and finish. See pages 1 and 2.**The Canadian Locksmith 2004**

216D**"900" Series Unit Locks**

FOR PUBLIC, INSTITUTIONAL AND COMMERCIAL BUILDINGS, FINE RESIDENCES AND APARTMENTS

**Chalice Design
No. 909****CAST BRASS, BRONZE OR ALUMINUM**

(Factory Assembled)

**909-951****COMPLETE SETS**

Door	Set Number	Lock		Pair Knobs Diam. Inches	Two Escutcheons Size, Inches
		No.	See Page		
Communicating	909-900	900	214A	2 1/4	3 1/8 x 3 1/4
Communicating, Storeroom, Etc.	909-901D	901D	214D	2 1/4	3 1/8 x 3 1/4
Communicating	909-902	902	214A	2 1/4	3 1/8 x 3 1/4
Passage (Latch)	909-910	910	214A	2 1/4	3 1/8 x 3 1/4
Fire Door (Latch)	909-910 3/4	910 3/4	214A	2 1/4	3 1/8 x 3 1/4
Exit (Latch)	909-915	915	214A	2 1/4	3 1/8 x 3 1/4
Bath, Bedroom, Conference Room	909-920	920	214A	2 1/4	3 1/8 x 3 1/4
Bathroom, Bedroom	909-920Y	920Y	214A	2 1/4	3 1/8 x 3 1/4
Patio or Sun Deck	909-921	921	214A	2 1/4	3 1/8 x 3 1/4
Entrance or Communicating	909-922D	922D	214D	2 1/4	3 1/8 x 3 1/4
Entrance or Communicating	909-923D	923D	214D	2 1/4	3 1/8 x 3 1/4
Exit or Patio	909-924D	924D	214D	2 1/4	3 1/8 x 3 1/4
Stateroom or Hotel Corridor	909-927	927	214B	2 1/4	3 1/8 x 3 1/4
Hotel Corridor	909-929	929	214B	2 1/4	3 1/8 x 3 1/4
Fixed Knob Lock	909-932	932	214B	2 1/4	3 1/8 x 3 1/4
Patio, Sun Deck or Basement	909-941	941	214B	2 1/4	3 1/8 x 3 1/4
Exit or Patio	909-944	944	214B	2 1/4	3 1/8 x 3 1/4
Entrance or Office	909-951	951	214B	2 1/4	3 1/8 x 3 1/4
Fire Door	909-951 3/4	951 3/4	214B	2 1/4	3 1/8 x 3 1/4
Apartment Vestibule Entrance, Office or Public Toilet	909-954	954	214C	2 1/4	3 1/8 x 3 1/4
Fire Door	909-954 3/4	954 3/4	214C	2 1/4	3 1/8 x 3 1/4
Class Room	909-955	955	214C	2 1/4	3 1/8 x 3 1/4
Class Room	909-955 1/4	955 1/4	214C	2 1/4	3 1/8 x 3 1/4
Storeroom or Closet	909-957	957	214C	2 1/4	3 1/8 x 3 1/4
Office	909-961	961	214C	2 1/4	3 1/8 x 3 1/4
Apartment Vestibule Entrance, or Office	909-964	964	214C	2 1/4	3 1/8 x 3 1/4
Dormitory, Bedroom or Public Rest Room	909-965	965	214C	2 1/4	3 1/8 x 3 1/4
Store Door	909-988	988	214C	2 1/4	3 1/8 x 3 1/4

One in a box with screws.

State whether for 1 3/8 or 1 1/4 in. door.


Specify reverse bevel if for door opening out.

Specify number and finish. See pages 1 and 2.**The Canadian Locksmith 2004**

"900" Series Unit Locks**217**

Rev. 6-1-57

FOR PUBLIC, INSTITUTIONAL AND COMMERCIAL BUILDINGS, FINE RESIDENCES AND APARTMENTS

**911-951****Melody Design
No. 911****CAST BRASS, BRONZE OR ALUMINUM**

(Factory Assembled)

COMPLETE SETS

Door	Set Number	Lock		Pair Knobs Diam. Inches	Two Escutcheons Size, Inches
		No.	See Page		
Communicating	911-900	900	214A	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Communicating, Storeroom, Etc.	911-901D	901D	214D	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Communicating	911-902	902	214A	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Passage (Latch)	911-910	910	214A	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Fire Door (Latch)	911-910$\frac{3}{4}$	910 $\frac{3}{4}$	214A	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Exit (Latch)	911-915	915	214A	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Bath, Bedroom, Conference Room	911-920	920	214A	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Bathroom, Bedroom	911-920Y	920Y	214A	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Patio or Sun Deck	911-921	921	214A	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Entrance or Communicating	911-922D	922D	214D	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Entrance or Communicating	911-923D	923D	214D	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Exit or Patio	911-924D	924D	214D	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Stateroom or Hotel Corridor	911-927	927	214B	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Hotel Corridor	911-929	929	214B	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Fixed Knob Lock	911-932	932	214B	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Patio, Sun Deck or Basement	911-941	941	214B	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Exit or Patio	911-944	944	214B	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Entrance or Office	911-951	951	214B	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Fire Door	911-951$\frac{3}{4}$	951 $\frac{3}{4}$	214B	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Apartment Vestibule Entrance, Office or Public Toilet	911-954	954	214C	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Fire Door	911-954$\frac{3}{4}$	954 $\frac{3}{4}$	214C	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Class Room	911-955	955	214C	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Class Room	911-955$\frac{1}{4}$	955 $\frac{1}{4}$	214C	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Storeroom or Closet	911-957	957	214C	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Office	911-961	961	214C	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Apartment Vestibule Entrance, or Office	911-964	964	214C	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Dormitory, Bedroom or Public Rest Room	911-965	965	214C	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$
Store Door	911-988	988	214C	2 $\frac{1}{8}$	3 $\frac{1}{8}$ x 3 $\frac{1}{4}$

One in a box with screws.


State whether for 1 $\frac{3}{8}$ or 1 $\frac{3}{4}$ in. door.

Specify reverse bevel if for door opening out.

Specify number and finish. See pages 1 and 2.

The Canadian Locksmith 2004

Heavy Duty Cylindrical Locks



Corbin Cylindrical Locks combine several features that make them particularly suitable for schools, hospitals, office buildings, public buildings, apartments, etc. Their handsome appearance and high degree of security also suggest their use for fine residences, especially on exterior doors.

Corbin Cylindrical Locks utilize the same shifting roll-back latch operating principle and balanced knob action as Corbin Unit Locks. This, together with their compact, heavy-duty construction, assures many years of smooth, faultless operation with a minimum of maintenance.

A high degree of security is afforded by the heavy, solid brass latch bolt with full $\frac{5}{8}$ inch throw . . . to insure secure locking even on doors that shrink or warp. All sets with locking operation (except the No. 420 Privacy Set) also have the extra protection of an automatic deadlocking feature on latch bolt, when door is closed.

If the keys should be lost, the cylinder can be removed readily for fast, easy replacement or for rekeying.

For master-key systems, Corbin Cylindrical Locks offer you the same security and flexibility as other Corbin cylinder-type locks. When desired, Corbin Cylindrical Locks can be master-keyed in sets with other Corbin locks.

Corbin Cylindrical Locks are 100% reversible, but to change the hand of key-operated locksets requires that the cylinder be re-positioned by releasing and rotating the knob. While this can easily be done on the job, you can avoid it and insure minimum installation time if you will specify hand for all cylinder locks when placing your order with us.



Corbin is the only manufacturer to offer you every major type of lock—cylindrical locks, unit locks, tubular locks, and mortise locks. When you use Corbin locks, you have complete freedom to select any of these different types of locks for the various parts of a building and yet have all locks master-keyed as needed and harmonious in design.

Heavy Duty Cylindrical Locks

219


Rev. 6-1-57

DESCRIPTION



**Knob with
Push Button**


Push button is pushed in to lock and except where otherwise noted is released by a turn of key outside, knob inside or closing door.



**Knob with
Turn Button**

Turn button is manually operated both to lock and unlock.

Universal Button: Operates same as push button but has slot or spanner holes in head and can be fixed in locked position by turning with coin, screw driver, or spanner key as noted in description of function for locks with which it is used.



Plain Knob



**Thumb Turn For
Inside of Closet Sets**

Cylindrical Case:...Steel M and T Bronze Plate. $2\frac{1}{16}$ inch diameter for $2\frac{1}{8}$ inch hole in door.

Backset:Regular $2\frac{3}{4}$ inch. Can be furnished with Extension Units for 5-7-10 and 18 inch backset, see page 230.

Latch Unit:No. 445 with latch only. No. 0445 with latch and auxiliary bolt. 100% Reversible.

Case:.....Steel Zinc plated Dichromate Dip. $\frac{31}{32}$ inch diameter for 1 inch hole.

Front:.....Wrought Brass, Bronze or Aluminum. Size $2\frac{1}{4}$ x $1\frac{1}{8}$ inch beveled $\frac{1}{8}$ inch in 2 inches. Flat front to order. In ordering suffix **F** to number, thus **800-451F**.

Latch Bolt: Solid Brass. $\frac{5}{8}$ in. Throw, self-lubricating.

Box Strike:Wrought Brass, Bronze or Aluminum. Size $2\frac{3}{4}$ inch x $1\frac{1}{8}$ inch curved lip $1\frac{1}{4}$ inch to center. Can be furnished curved lip 1, $1\frac{1}{2}$, $1\frac{3}{4}$, 2, $2\frac{1}{2}$ and 3 inch to center when so ordered.

Standardize $1\frac{1}{8}$ in. series strikes can be supplied when so ordered. Open back strikes can be supplied when so ordered.

For reinforcement for hollow metal doors—see page 230
For different locks available—see pages 226, 228
For complete sets available—see pages 220, 225

Cylinders:Type No. 460 Standard and No. 460 $\frac{1}{2}$ Master Keyed. Extruded Brass Ball Bearing Pin tumbler type. See page 229 for numbers covering cylinders complete with the proper cams to operate the various locks. Five Pin will be furnished regularly on all stock sets. Six Pin on all master keyed jobs.

Keying:Two nickel silver keys Class 77 for 5 pin cylinder. Master Key Class 077. Two class 73 $\frac{1}{4}$ for 6 Pin cylinder. Master Key Class 073 $\frac{1}{4}$ can be master keyed if desired with other locks having same Class Master Key.

Thickness of door: Adjustable for doors $1\frac{1}{8}$ to 2 in. thick. For doors over 2 in. thick up to $2\frac{1}{2}$ in. thick, state thickness of door.

Hand of doors: ...Reversible—except that on all Cylinder Sets it is advisable to state hand of door so that factory can assemble lock with key hole in correct position saving contractor time when applying. As latch unit is reversible use Right Hand lock for both Right Hand and Right Hand Reverse Bevel doors and Left Hand lock for Left Hand and Left Hand Reverse Bevel doors, except on split finishes which require all locks to be ordered **RHRB** or **LHRB** for doors opening out so that finish of strike will match outside trim.

Packing:One set in a box with instructions for applying and Spanner Wrench.




220

Rev. 6-1-57


Heavy Duty Cylindrical Locks

COMPLETE SETS WITH KNOBS AND ROSES



Spartan Design No. 800

CAST BRASS, BRONZE OR ALUMINUM

Knob: $2\frac{5}{16}$ in. diameter. Projection on $1\frac{3}{4}$ in. Door $2\frac{1}{2}\frac{1}{16}$ in.**Rose:** $2\frac{5}{16}$ in. diameter.Use No. **80024** for knob and concealed screw rose to match for use as operating trim with mortise locks.No. **80024DT** when required as dummy trim for either mortise or cylindrical sets.

Spartan Design No. 830

WROUGHT BRASS, BRONZE OR ALUMINUM

Can also be furnished Stainless Steel trim **PS** or **DS** finish. If required with Stainless Steel chassis as well as trim, affix **SS** to number, thus: **PS830-451SS****Knob:** $2\frac{5}{16}$ in. diameter. Projection on $1\frac{3}{4}$ in. Door $2\frac{1}{2}\frac{1}{16}$ in. Reinforced with steel lining.**Rose:** $2\frac{5}{16}$ in. diameter.Use No. **83024** for knob and concealed screw rose to match for use as operating trim with mortise locks.No. **83024OT** when required as dummy trim for either mortise or cylindrical sets.

For Door	Set Number Cast Brass, Bronze or Aluminum	Set Number Wrought Brass, Bronze or Aluminum	Lock	
			No.	See Page
Communicating	800-400	830-400	400	226
Communicating	800-402	830-402	402	226
Communicating	800-404	830-404	404	226
Communicating Suite	800-405	830-405	405	226
Passage (Latch)	800-410	830-410	410	226
Exit (Latch)	800-415	830-415	415	226
Closet (Latch)	800-419	830-419	419	226
Bath or Bedroom, Conference Room	800-420	830-420	420	226
Hotel Corridor or Apartment	800-427	830-427	427	226
Hotel Corridor	800-429	830-429	429	227
Passage (Always Locked)	800-432	830-432	432	227
Private Office, etc.	800-441	830-441	441	227
Exit	800-444	830-444	444	227
Entrance or Office	800-451	830-451	451	227
Apartment Entrance, Office or Public Toilet	800-454	830-454	454	227
Classroom	800-455	830-455	455	227
Classroom	800-455 $\frac{1}{4}$	830-455 $\frac{1}{4}$	455 $\frac{1}{4}$	227
Institution	800-455 $\frac{3}{4}$	830-455 $\frac{3}{4}$	455 $\frac{3}{4}$	227
Patio	800-456	830-456	456	227
Exit or Storeroom	800-457	830-457	457	228
Closet, Pipe or Wire Shaft	800-459	830-459	459	228
Office	800-461	830-461	461	228
Exterior or Corridor	800-462	830-462	462	228
Rest Room or Service Station	800-463	830-463	463	228
Dormitory Bedroom or Public Rest Room	800-465	830-465	465	228
Closet	800-469	830-469	469	228
Store Entrance	800-488	830-488	488	228

Packed one set in a box.

Specify number and finish. See pages 1 and 2.



Heavy Duty Cylindrical Locks


COMPLETE SETS WITH KNOBS AND ROSES

221

Rev. 6-1-57


Harmony Design No. 806

CAST BRASS, BRONZE OR ALUMINUM

Knob:2 $\frac{3}{16}$ in. diameter. Projection on 1 $\frac{3}{4}$ in. Door 2 $\frac{1}{16}$ in.**Rose:**2 $\frac{5}{8}$ in. diameter.Use No. **80624** for knob and concealed screw rose to match for use as operating trim with mortise locks.No. **80624DT** when required as dummy trim for either mortise or cylindrical sets.

Harmony Design No. 836

WROUGHT BRASS, BRONZE OR ALUMINUM

Can also be furnished Stainless Steel trim, **PS** or **DS** finish. If required with Stainless Steel chassis as well as trim, suffix symbol **SS** to lock number, thus: **PS836-451SS****Knob:**2 $\frac{3}{16}$ in. diameter. Projection on 1 $\frac{3}{4}$ in. Door 2 $\frac{1}{16}$ in. Reinforced with steel lining.**Rose:**2 $\frac{5}{8}$ in. diameter.Use No. **83624** for knob and concealed screw rose to match for use as operating trim with mortise locks.No. **83624DT** when required as dummy trim for either mortise or cylindrical sets.

For Door	Set Number Cast Brass, Bronze or Aluminum	Set Number Wrought Brass, Bronze or Aluminum	Lock	
			No.	See Page
Communicating	806-400	836-400	400	226
Communicating	806-402	836-402	402	226
Communicating	806-404	836-404	404	226
Communicating Suite	806-405	836-405	405	226
Passage (Latch)	806-410	836-410	410	226
Exit (Latch)	806-415	836-415	415	226
Closet (Latch)	806-419	836-419	419	226
Bath or Bedroom, Conference Room	806-420	836-420	420	226
Hotel Corridor or Apartment	806-427	836-427	427	226
Hotel Corridor	806-429	836-429	429	227
Passage (Always Locked)	806-432	836-432	432	227
Private Office, etc.	806-441	836-441	441	227
Exit	806-444	836-444	444	227
Entrance or Office	806-451	836-451	451	227
Apartment Entrance, Office or Public Toilet	806-454	836-454	454	227
Classroom	806-455	836-455	455	227
Classroom	806-455 $\frac{1}{4}$	836-455 $\frac{1}{4}$	455 $\frac{1}{4}$	227
Institution	806-455 $\frac{3}{4}$	836-455 $\frac{3}{4}$	455 $\frac{3}{4}$	227
Patio	806-456	836-456	456	227
Exit or Storeroom	806-457	836-457	457	228
Closet, Pipe or Wire Shaft	806-459	836-459	459	228
Office	806-461	836-461	461	228
Exterior or Corridor	806-462	836-462	462	228
Rest Room or Service Station	806-463	836-463	463	228
Dormitory Bedroom or Public Rest Room	806-465	836-465	465	228
Closet	806-469	836-469	469	228
Store Entrance	806-488	836-488	488	228

Packed one set in a box.

Specify number and finish. See pages 1 and 2.



222

Rev. 6-1-57

Heavy Duty Cylindrical Locks

COMPLETE SETS WITH KNOBS AND ROSES

Chalice Design No. 809


CAST BRASS, BRONZE OR ALUMINUM

Knob: 2¼ in. diameter

Rose: 3¾ in. diameter

Use No. 80924 for knob with concealed screw rose to match for use as operating trim with mortise locks.

No. 80924DT when required as dummy trim with either mortise or cylindrical sets.



For Door	Set Number Cast Brass, Bronze or Aluminum	Lock	
		No.	See Page
Communicating	809-400	400	226
Communicating	809-402	402	226
Communicating	809-404	404	226
Communicating Suite	809-405	405	226
Passage (Latch)	809-410	410	226
Exit (Latch)	809-415	415	226
Closet (Latch)	809-419	419	226
Bath or Bedroom, Conference Room	809-420	420	226
Hotel Corridor or Apartment	809-427	427	226
Hotel Corridor	809-429	429	227
Passage (Always Locked)	809-432	432	227
Private Office, etc.	809-441	441	227
Exit	809-444	444	227
Entrance or Office	809-451	451	227
Apartment Vestibule Entrance, Office or Public Toilet	809-454	454	227
Classroom	809-455	455	227
Classroom	809-455¼	455¼	227
Institution	809-455¾	455¾	227
Patio	809-456	456	227
Exit or Storeroom	809-457	457	228
Closet, Pipe or Wire Shaft	809-459	459	228
Office	809-461	461	228
Exterior or Corridor	809-462	462	228
Rest Room or Service Station	809-463	463	228
Dormitory Bedroom or Public Rest Room	809-465	465	228
Closet	809-469	469	228
Store Entrance	809-488	488	228

Packed one set in a box.

Specify number and finish. See pages 1 and 2.




Heavy Duty Cylindrical Locks

223

Rev. 6-1-57

COMPLETE SETS WITH KNOBS AND ROSES



Melody Design No. 811

CAST BRASS, BRONZE OR ALUMINUM

Knob:2 $\frac{1}{8}$ in. diameterRose:3 $\frac{3}{4}$ in. diameterUse No. **81124** for knob with concealed screw rose to match for use as operating trim with mortise locks.No. **81124DT** when required as dummy trim with either mortise or cylindrical sets.

For Door	Set Number Cast Brass, Bronze or Aluminum	Lock	
		No.	Sec Page
Communicating	811-400	400	226
Communicating	811-402	402	226
Communicating	811-404	404	226
Communicating Suite	811-405	405	226
Passage (Latch)	811-410	410	226
Exit (Latch)	811-415	415	226
Closet (Latch)	811-419	419	226
Bath or Bedroom, Conference Room	811-420	420	226
Hotel Corridor or Apartment	811-427	427	226
Hotel Corridor	811-429	429	227
Passage (Always Locked)	811-432	432	227
Private Office, etc.	811-441	441	227
Exit	811-444	444	227
Entrance or Office	811-451	451	227
Apartment Vestibule Entrance, Office or Public Toilet	811-454	454	227
Classroom	811-455	455	227
Classroom	811-455$\frac{1}{4}$	455 $\frac{1}{4}$	227
Institution	811-455$\frac{3}{4}$	455 $\frac{3}{4}$	227
Patio	811-456	456	227
Exit or Storeroom	811-457	457	228
Closet, Pipe or Wire Shaft	811-459	459	228
Office	811-461	461	228
Exterior or Corridor	811-462	462	228
Rest Room or Service Station	811-463	463	228
Dormitory Bedroom or Public Rest Room	811-465	465	228
Closet	811-469	469	228
Store Entrance	811-488	488	228

Packed one set in a box.

Specify number and finish. See pages 1 and 2.



224



Rev. 6-1-57

Heavy Duty Cylindrical Locks


COMPLETE SETS WITH KNOBS AND ROSES

Windsor Design No. 803

CAST BRASS OR BRONZE



803A



803B

Knob: $2\frac{1}{16}$ in. DiameterKnob No. 803L diameter $2\frac{1}{8}$ in.
For use with large roses 803A
and 803B.**Rose:** $3\frac{1}{2}$ in. Diameter**Rose No. 803A**—5 in. Diameter**Rose No. 803B**—8 in. DiameterUse No. 80324 for Knob and concealed screw rose to match for use as operating trim for mortise locks.
No. 80324DT when required as dummy trim for either mortise or cylindrical sets.

For Door	Set Number Cast Brass or Bronze	Lock	
		No.	See Page
Communicating	803-400	400	226
Communicating	803-402	402	226
Communicating	803-404	404	226
Communicating Suite	803-405	405	226
Passage (Latch)	803-410	410	226
Exit (Latch)	803-415	415	226
Closet (Latch)	803-419	419	226
Bath or Bedroom, Conference Room	803-420	420	226
Hotel Corridor or Apartment	803-427	427	226
Hotel Corridor	803-429	429	227
Passage (Always Locked)	803-432	432	227
Private Office, etc.	803-441	441	227
Exit	803-444	444	227
Entrance or Office	803-451	451	227
Apartment Entrance, Office or Public Toilet	803-454	454	227
Classroom	803-455	455	227
Classroom	803-455 $\frac{1}{4}$	455 $\frac{1}{4}$	227
Institution	803-455 $\frac{3}{4}$	455 $\frac{3}{4}$	227
Patio	803-456	456	227
Exit or Storeroom	803-457	457	228
Closet, Pipe or Wire Shaft	803-459	459	228
Office	803-461	461	228
Exterior or Corridor	803-462	462	228
Rest Room or Service Station	803-463	463	228
Dormitory Bedroom or Public Rest Room	803-465	465	228
Closet	803-469	469	228
Store Entrance	803-488	488	228

Packed one set in a box.

Specify number and finish. See pages 1 and 2.




Heavy Duty Cylindrical Locks

227

Rev. 6-1-57

FUNCTIONS AVAILABLE



No. 429


Hotel Corridor Lock

Latch bolt operated by knob from the inside and by key from the outside. Outside knob always rigid.

Pushing in button in inside knob shuts out all keys except emergency key and projects a visual occupancy indicator in face of cylinder.

Turning inside knob or closing door automatically releases locking button and shutout features and retracts indicator unless button has been fixed in locked position by turning with a special spanner key.

Latch bolt is automatically deadlocked when door is closed.




No. 432

Fixed Knob Lock

For passage doors which are always locked.

Latch bolt operated by key from either side. Both knobs always rigid.

Latch bolt is automatically deadlocked when door is closed.



No. 441


Privacy Lock

For doors that require locking only when room is occupied.

Latch bolt operated by knobs from either side except when outside knob is locked by pushing in button in inside knob.

A turn of inside knob or closing door releases locking button preventing accidental lockout.

Latch bolt is automatically deadlocked when door is closed.




No. 444

Exit Lock

For doors used mostly for exit, and entrance not required when locked.

Latch bolt operated by knobs from either side except when outside knob is locked by turn button in inside knob.

Latch bolt is automatically deadlocked when door is closed.




No. 451

Entrance or Office Lock

For entrance, vestibule or office doors.

Latch bolt operated by key from the outside at all times and by knobs from either side except when outside knob is locked by turn button in inside knob.

Latch bolt is automatically deadlocked when door is closed.




No. 454

Vestibule or Office Lock

For apartment vestibule entrance, office or public toilet doors.

Latch bolt operated by key from outside at all times and by knobs from either side except when outside knob is locked by master key only in inside knob unless otherwise specified.

Latch bolt is automatically deadlocked when door is closed.



No. 455


Class Room Lock

For classroom or utility room doors.

Latch bolt operated by knobs from either side except when outside knob is locked by key in outside knob.

Latch bolt is automatically deadlocked when door is closed.

No. 455 1/4 same as No. 455 except that latch bolt can be held retracted by retracting latch bolt by means of outside knob and tuning key while in this position.




No. 455 1/4

Institution Lock

For Detention Room Doors.

Latch bolt operated by knob from either side, except when both knobs are locked by key in outside knob.

Latch bolt is automatically deadlocked when door is closed.



No. 456

Patio Lock

For doors to Patio, Sun Deck, etc.

Latch Bolt operated by Knobs from either side, except when outside knob is locked by key in inside knob.

Latch bolt is automatically deadlocked when door is closed.

For further description, dimensions, etc., see page 219.

Above numbers cover functions only. For complete sets with knobs and roses, see pages 220, 225.



228


Rev. 6-1-57

Heavy Duty Cylindrical Locks

FUNCTIONS AVAILABLE

Inside

Outside



No. 457


Utility or Storeroom Lock

For utility, storeroom or exit doors. Latch bolt operated by knob from inside and by key from the outside. Outside knob always rigid.

Latch bolt is automatically deadlocked when door is closed.

Inside

Outside



No. 459

Utility Closet Lock


For utility closets, pipe or wire shaft doors, etc.

Latch bolt operated by thumb turn from the inside and by key from the outside. Outside knob always rigid.

Latch bolt is automatically deadlocked when door is closed.

Inside

Outside



No. 461


Office Lock

For use on office doors.

Latch bolt operated by key from the outside at all times and by knobs from either side except when outside knob is locked by pushing in button in inside knob.

Turning key outside or knob inside automatically releases locking button. Closing door does not release locking button.

Latch bolt is automatically deadlocked when door is closed.



No. 462


Exterior or Corridor Lock

Latch bolt operated by key from the outside at all times and by knobs from either side except when outside knob is locked by pushing in button in inside knob.

Turning key outside or knob inside releases locking button. Closing door does not release locking button.

Locking button has slot in head and can be fixed in locked position by turning it with a coin or screw driver.

Latch bolt is automatically deadlocked when door is closed.



No. 463

Service Station Lock


For rest rooms or public station doors.

Latch bolt operated by key from outside at all times and by knobs from either side except when outside knob is locked by pushing in button in inside knob.

Turning key outside, knob inside or closing door automatically releases locking button.

Locking button has slot in head and can be fixed in locked position by turning it with a coin or screw driver.

Latch bolt is automatically deadlocked when door is closed.



No. 465

Dormitory Lock


For dormitory bedrooms or public rest room doors.

Latch Bolt operated by $\frac{1}{4}$ turn of key in counter-clockwise direction from outside at all times and by knobs from either side except when outside knob is locked by pushing in button in inside knob or turning key $\frac{1}{4}$ turn in clockwise direction in outside knob. Inside knob always free. When outside knob is locked by push button from inside, a turn of inside knob a quarter counter-clockwise turn of key in outside knob or closing door releases locking button.

When outside knob is locked by key, locking mechanism can only be released by a counter-clockwise turn of key in outside knob.

Outside knob cannot be locked by key unless locking button is in released position.

Latch bolt is automatically deadlocked when the door is closed.




No. 469

Closet Lock

For closet doors which require key operation.

Latch bolt operated by thumb turn from inside at all times and by knob from the outside except when outside knob has been locked by full turn of key.

Latch bolt automatically deadlocks when door is closed.



No. 488

Store Door Lock

For store entrance or communicating doors.

Latch bolt operated by knobs from either side except when both knobs are locked by turning key in either knob. When both knobs are locked from either side, key from either side will unlock both knobs.

Latch bolt automatically deadlocks when door is closed.

For further description, dimensions, etc., see page 219.

Above numbers cover functions only. For complete sets with knobs and roses, see pages 220, 225.



Heavy Duty Cylindrical Locks

229

Rev. 6-1-57

MISCELLANEOUS INFORMATION

CYLINDERS TYPES 460 COMPLETE WITH CAMS FOR THE VARIOUS LOCKS.



No. 460A

For use with locks Nos. 431, 432, 451, 454 out., 457, 459 and 488 out.




No. 460B

For use with locks Nos. 402, 454 ins., and 456.



No. 460C

For use with locks Nos. 404, 455, 455 1/4 and 469.




No. 460D

For use with locks Nos. 405, 455 3/4 and 465.




No. 460E

For use with locks Nos. 461, 462 and 463.



No. 460F

For use with locks Nos. 427 and 429.



No. 460G

For use with lock No. 465.

State Number of lock for which cylinder will be used.



No. 460M

For use with lock No. 488 ins.

TOOLS



No. 3

Tru-Arc Plier

When changing cylinder the Tru-Arc plier No. 3 is used to remove knob shank retaining ring which holds cylinder in knob.



Thimble Wrench

Use to tighten or loosen rose thimble. A plastic sleeve is attached to this wrench to prevent marring of finish.

Use other end to release knob retaining device.

Packed one in each stock set. One for 10 sets on contract work.




No. 2

Tru-Arc Plier

When rekeying or changing cylinder, the Tru-Arc Plier No. 2 is used to remove retaining ring which holds cylinder plug in cylinder shell.

INSTRUCTIONS FOR DISASSEMBLING CYLINDER FOR RE-KEYING.



FOLLOWER

1. Remove key from cylinder plug.
2. Remove retaining pin from cam and remove cam.
3. Use Tru-Arc plier No. 2 to remove retaining ring from cylinder plug.
4. Insert key in cylinder plug—use caution so that plug does not fall out of cylinder shell.
5. Place follower against end of cylinder plug and using slight pressure remove cylinder plug from shell. Keep follower in close contact with cylinder plug all the way through so that pins will not fall out of pin chambers in shell.
6. Reset to new keying and reverse above procedure to re-assemble.

NOTE: For No. 460A type cylinder ignore step No. 3. Cylinders No. 460B—460E in Step No. 2 line up hole in cam with pin.



230

Rev. 6-1-57

Heavy Duty Cylindrical Locks

MISCELLANEOUS INFORMATION


Extension Units



5 in.



7 in.



10 in.

No. 491*


For special backsets.

Regular latch unit $2\frac{3}{4}$ inch backset. Extension units which attach to regular latch unit to extend backset are available for 5", 7", 10" or 18" backset.

* State size.

Sleeves available for metal doors for special back sets keeping latch and extension unit in alignment.


Rabbeted Front



These locks can be supplied with rabbeted front and strike for doors with $\frac{1}{2}$ in. rabbet. In ordering, suffix **RAB** to number, thus **800-451RAB**. Backset on rabbet front locks $2\frac{3}{4}$ in. on long side of rabbet.

Large Rose

Cast Brass, Bronze or Aluminum


 $3\frac{5}{8}$ in. diameter.

Rose No. 80605

Can be used in place of regular rose with any heavy duty cylindrical set.

If ordered singly specify whether outside or inside rose is required.

Working Trim




Knobs with Concealed Screw Roses

Knobs with concealed screw roses to match the different cylindrical lock designs will be furnished for use as operating trim with mortise locks.

These knobs and roses can also be used as dummy trim with either cylindrical or mortise locksets.

See cylindrical design pages 220 and 225, for catalogue numbers for these knobs.

Reinforcing Unit



No. 492

For hollow metal doors.

This reinforcing unit is essential when cylindrical locks are to be installed in hollow metal doors. It is welded into the hollow metal stile by door manufacturer when the door is made.

Made for $1\frac{3}{8}$ " or $1\frac{1}{4}$ " doors.


State thickness of door.

Template blue prints for cutting metal doors for cylindrical locks will be available.

Square Rose

Wrought Brass, Bronze or Aluminum

Size 3 x 3 in.



No. 85104

Can be used in place of regular rose with any heavy duty cylindrical set.

If ordered singly specify whether outside or inside rose is required.

Specify number and finish. See pages 1 and 2.



Heavy Duty Cylindrical Locks


TOOLS

231

Rev. 6-1-57

Boring Jig

ALUMINUM



No. 040

For use in boring holes for lock case and latch unit for Heavy Duty Cylindrical Locksets regular $2\frac{3}{4}$ in. backset.

Instruction Plates




No. 100

Instruction plates are available at no additional charge for use on hotel doors. Furnished with black background and embossed aluminum letters. Plate measures $1\frac{1}{4}$ in. x $2\frac{3}{4}$ in. and are furnished with pins for attaching.



Bushing C


Latch Bushing C can be furnished for use in boring Latch hole only for special long backset Heavy Duty Locks.



No. 400MT

For use in marking centers when boring for Heavy Duty Cylindrical Locks.

Bit



No. 4103

For boring $2\frac{1}{2}$ diameter holes for the Heavy Duty Cylindrical Locks.

Furnished regularly for use in bit brace. Can be furnished for use in electric drill, when so ordered.

Aligning Tool



No. 042

For use in applying knobs and roses used as working trim for Mortise Locks.

If used when attaching roses the knobs will work freely without binding.




Heavy Duty Cylindrical Locks

INSTALLATION DETAILS FOR LOCKS Nos. 400, 402, 404, 405, 432 and 488.


① LAYOUT DOOR

Scribe center line of latch bolt on door. Mark center of latch at center of door edge. Apply template to center line and mark center of hole for lock case.




② DRILL DOOR

Drill $2\frac{1}{4}$ " hole thru stile as marked. Drill from both sides. Drill hole for latch as marked ($1\frac{1}{2}$ " hole). Mortise for latch front. Position latch.




③ POSITION STRIKE

Transfer vertical center line of latch from edge of door to jamb. Mortise jamb for strike with screw holes on center line and latch at center of strike opening. Screw strike home.




④ DETACH TRIM

Exert pressure against knob retainer on side facing latch retractor, using screw driver end of spanner wrench. At the same time a slight pressure of the thumb will release the knob. Remove Rose by unscrewing from sleeve.




⑤ ENGAGE UNITS

With latch unit in place and rose adjusted to come against knob as shown by arrow, install lock so that lock case engages with latch case prongs and interlock retractor with latch tail.



⑥ INSTALL AND ADJUST LOCK

1. With rose (A) against knob as shown and lock installed in door as far as it will go in direction of arrow, apply rose (B) to opposite side of door until thimble corresponds with door thickness indicated by grooves on shank of knob.
2. Fasten rose (A) by screwing rose adjusting thimble on threaded sleeve. Tighten with wrench provided. See view 7 for fastening rose.
3. Install knob (C) into sleeve and rotate knob slightly in both directions until locked in position.





Simply push knob into position, no catch to depress.

Rose held stationary by spurs as thimble is screwed firmly against rose.


⑦ FASTEN ROSE

See instructions, under ⑥



IMPORTANT

Cylinders are assembled in knobs for right or left hand doors as ordered. If it becomes necessary to change the hand of a lock so that cylinder will be right side up, see instructions at right.



TO CHANGE HAND OF LOCK

Unscrew case and cap tie screw and exert pressure with screw driver end of wrench against outside knob retainer on side facing latch retractor, releasing same so as to permit removal of knob. Withdraw key partly from cylinder, turn knob over and replace knob. Push knob retainer back as far as possible and lock it in place with tie screw.


Heavy Duty Cylindrical Locks

233

INSTALLATION DETAILS FOR ALL LOCKS EXCEPT Nos. 400, 402, 404, 405, 432 and 488.


① LAYOUT DOOR

Scribe center line of latch bolt on door. Mark center of latch at center of door edge. Apply template to center line and mark center of hole for lock case.




② DRILL DOOR

Drill 2 1/2" hole thru stile as marked. Drill from both sides. Drill hole for latch as marked (1" hole). Mortise for latch front. Position latch.




③ POSITION STRIKE

Transfer vertical center line of latch from edge of door to jamb. Mortise jamb for strike with screw holes on center line and latch at center of strike opening. Screw strike home.




④ DETACH INSIDE TRIM

Exert pressure against inside knob retainer on side facing latch retractor, using screw driver end of spanner wrench. At the same time a slight pressure of the thumb will release the knob. Remove rose by unscrewing rose adjusting thimble.




⑤ ADJUST LOCK

Adjust lock to fit door thickness by rotating outside rose in direction of arrow until top of rose thimble corresponds with door thickness indicated by grooves on shank of knob.




⑥ ENGAGE UNITS

With latch unit in place, install lock so that lock case engages with latch case prongs and interlock retractor with latch tail.





⑦ INSTALL ROSE

Attach inside rose by screwing thimble on threaded sleeve. Tighten with wrench provided.




⑧ INSTALL INSIDE KNOB

Slip shank of knob into sleeve and rotate knob slightly in both directions until locked in position.



IMPORTANT

Cylinders are assembled in knobs for right or left hand doors as ordered. If it becomes necessary to change the hand of a lock so that cylinder will be right side up, see instructions at right.



TO CHANGE HAND OF LOCK


Unscrew case and cap tie screw and exert pressure with screw driver end of wrench against outside knob retainer on side facing latch retractor, releasing same so as to permit removal of knob. Withdraw key partly from cylinder, turn knob over and replace knob. Push knob retainer back as far as possible and lock it in place with tie screw.

The Defender

STANDARD DUTY CYLINDRICAL LOCKS

For fine Residences and Commercial Buildings where normal frequency of operation is anticipated.

EXCLUSIVE FEATURES



Set illustrated is 430 651 with 670 cylinder and 77 Class Keys.

OTHER FEATURES

All exposed parts brass, bronze or aluminum.

Knobs with cylinders with Class 77 keys two-piece construction. Cylinder easily removable for rekeying. All other knobs sturdy one-piece construction.

Lock and Latch cases and interior working parts pressed steel zinc plated and diebromate dipped for rust resistance.

Double compression springs. Light latch springs for easy closing. Heavy retractor springs for positive knob return and balanced knob action.

Sturdy steel anchor plate quickly and securely fastens lock to door in perfect alignment.

Latch bolts solid brass $\frac{3}{8}$ in. throw.

Auxiliary bolt provided for locks with locking functions, dead locks latch bolt preventing forcing by end pressure when door is closed.

Adjustable for doors $1\frac{1}{8}$ to $1\frac{3}{4}$ in. thick, with allowance for undersize $1\frac{1}{8}$ in. mill doors.

All made to standard dimensions. All doors bored alike regardless of functions.

Precision manufacture provides complete interchangeability of parts.

Meet U. S. Government specifications Type 160.

PATENTED





The Defender

STANDARD DUTY CYLINDRICAL LOCKS

235

Rev. 6-1-57

DESCRIPTION



**Knob with
Push Button**

Push button is pushed in to lock and except where otherwise noted is released by a turn of key outside, knob inside or closing door.



**Knob with
Turn Button**

Turn button is manually operated both to lock and unlock.

Universal Button: Operates same as push button but has slot in head and can be fixed in locked position by turning with coin or screw driver, as noted in description of function for locks with which it is used.

Cylindrical Case:.... Steel M and T Bronze Plate. $2\frac{1}{8}$ in. diameter for $2\frac{1}{8}$ in. hole in door.

Latch Unit: 645, Plain Latch.
645 $\frac{1}{4}$, Plain Latch with throw-off.
0645 with Auxiliary Latch.
0645 $\frac{1}{4}$ with Auxiliary Latch and throw-off feature.

Case: Steel, Zinc Plated, Dichromate Dip, $2\frac{7}{32}$ in. diameter for $\frac{7}{8}$ in. hole in door.

Front: Wrought Brass, Bronze or Aluminum, $2\frac{1}{4}$ x1 in.
Beveled $\frac{1}{16}$ " in 2".
Reversible, can be used on doors with either flat edges or standard bevel $\frac{1}{8}$ in. in 2 inches.

Latch Bolt: Solid Brass, $\frac{3}{8}$ in. throw.

Backset: Regular 2 $\frac{3}{8}$ in. When so ordered, can be furnished 2 or 2 $\frac{3}{4}$ in. backset or with extension unit for 5 in. backset.

2 in. backset cannot be furnished with auxiliary latch. 2 $\frac{3}{4}$ in. backset locks will have front $1\frac{1}{8}$ in. wide beveled $\frac{1}{8}$ " in 2" and can be used in same mortise as heavy duty cylindrical locks.

Box Strike: Wrought Brass, Bronze or Aluminum, $2\frac{3}{4}$ x1 $\frac{1}{8}$ in. curved lip $1\frac{1}{4}$ in. to center. Can be furnished with lip 1, $1\frac{1}{2}$, $1\frac{3}{4}$ or 2 in. to center, when so ordered. Open back strikes can be supplied when so ordered.

Cylinder: No. 670 Extruded Brass ball bearing 5 pin tumblers with Class 77 Keys used in two piece Knobs all designs except Chalise and Melody.

No. 671 Same as No. 670 except shorter pin chamber for use with Chalise and Melody Designs only.

No. 672 Brass five pin tumblers. With Class 26 $\frac{1}{4}$ Keys. For use with one piece knobs in Wrought Designs.

Keying: Two keys furnished with each set. Sets with Class 77 keys can be master keyed with other types of 5 pin cylinder locks having class 77 keys. Sets with Class 26 $\frac{1}{4}$ keys can be master keyed only with other locks having Class 26 $\frac{1}{4}$ keys.

Thickness of Door:.. Adjustable for doors $1\frac{3}{8}$ to $1\frac{1}{4}$ in. thick. For doors over $1\frac{1}{4}$ in. thick up to $2\frac{1}{4}$ in. thick, with cast roses, state thickness of door.

Hand of Doors:..... Reversible—except that on all cylinder Sets with Class 77 keys it is advisable to state hand of door so that factory can assemble lock with key hole in correct position saving contractor time when applying. As latch unit is reversible use Right Hand lock for both Right Hand and Right Hand Reverse Bevel doors and Left Hand lock for Left Hand and Left Hand Reverse Bevel doors, except on split finishes which require all locks to be ordered RHRB or LHRB for doors opening out so that finish of strike will match outside trim.

Sets with 26 $\frac{1}{4}$ keys have keyway in horizontal position and can be applied to Right or Left Hand doors without change.

Packing: One set in a box with screws and instructions for applying.

For different locks available—see pages 240, 241



236

Rev. 6-1-57

The Defender

STANDARD DUTY CYLINDRICAL LOCKS


COMPLETE SETS WITH KNOBS AND ROSES



No. 430-651
With Keys
Class 77

Spartan Design No. 430

WROUGHT BRASS, BRONZE OR
ALUMINUM



No. 430-4651
With Keys
Class 26 1/4

Knobs Knobs with Cylinders No. 670 and Class 77
Keys two piece 2 1/8 in. diameter. All other
knobs one piece 2 in. diameter.

Rose 2 5/8 in. diameter.

Use No. 43024 for knob and concealed screw rose to match
for use as operating trim with mortise lock.

No. 43024OT when required as dummy trim for either
mortise or cylindrical sets.

For Door	Set Number	Lock	
		No.	Sec Page
Communicating	430-600	600	240
Passage (Latch)	430-610	610	240
Exit (Latch)	430-615	615	240
Bath, Bedroom, Conference Room	430-620	620	240
Private Office, Etc.	430-621	621	240
Entrance or Office	†430-631	631	240
Patio, Private Office, Etc.	430-641	641	240
Patio or Exit	430-644	644	240
Entrance or Office	†430-651	651	240
Class Room	†430-655	655	240
Exit or Store Room	†430-657	657	241
Office or Entrance	†430-661	661	241
Exterior or Corridor	†430-662	662	241
Rest Room or Service Station	†430-663	663	241
Entrance or Office	*430-4631	4631	240
Entrance or Office	*430-4651	4651	240
Class Room	*430-4655	4655	240
Exit or Store Room	*430-4657	4657	241
Office or Entrance	*430-4661	4661	241
Exterior or Corridor	*430-4662	4662	241
Rest Room or Service Station	*430-4663	4663	241

One set in a box with screws, template and instructions for installing.

All sets 20 in a case.

Weight per Case: Cylinder Sets, 39 Lbs., all others 34 Lbs.

† These Cylinder Sets with 77 Class Keys can be Masterkeyed with other types of Corbin Locks having Class 77 Keys.

* These Cylinder Sets with 26 1/4 Class Keys can be Masterkeyed only with other Locks having 26 1/4 Class Keys.

For Auxillary Roses and Handle which can be used under the regular 2 5/8 in. Roses of this design see Pages 242 and 250B.


Specify number and finish. See pages 1 and 2.



The Defender

STANDARD DUTY CYLINDRICAL LOCKS


COMPLETE SETS WITH KNOBS AND ROSES



No. 436-651
With Keys
Class 77

Harmony Design No. 436

WROUGHT BRASS, BRONZE
OR ALUMINUM



No. 436-4651
With Keys
Class 26¼

Knob:2½ in. diameter. Knobs with No. 670 cylinder and Class 77 keys two-piece; all others one piece.

Rose:2½ in. diameter.

Use No. 43624 for knob and concealed screw rose to match for use as operating trim with mortise lock.

No. 43624DT when required as dummy trim for either mortise or cylindrical sets.

For Door	Set Number	Lock	
		No.	See Page
Communicating	436-600	600	240
Passage (Latch)	436-610	610	240
Exit (Latch)	436-615	615	240
Bath, Bedroom, Conference Room	436-620	620	240
Private Office, Etc.	436-621	621	240
Entrance or Office	†436-631	631	240
Patio, Private Office, Etc.	436-641	641	240
Patio or Exit	436-644	644	240
Entrance or Office	†436-651	651	240
Class Room	†436-655	655	240
Exit or Storeroom	†436-657	657	241
Entrance or Office	†436-661	661	241
Exterior or Corridor	†436-662	662	241
Rest Room or Service Station	†436-663	663	241
Entrance or Office	*436-4631	4631	240
Entrance or Office	*436-4651	4651	240
Class Room	*436-4655	4655	240
Exit or Storeroom	*436-4657	4657	241
Office or Entrance	*436-4661	4661	241
Exterior or Corridor	*436-4662	4662	241
Rest Room or Service Station	*436-4663	4663	241

One set in a box with screws, template and instructions for installing.

All sets 20 in a case.

Weight per Case: Cylinder Sets, 39 Lbs., all others 34 Lbs.

† These Cylinder Sets with 77 Class Keys can be Masterkeyed with other types of Corbin Locks having Class 77 Keys.

* These Cylinder Sets with 26¼ Class Keys can be Masterkeyed only with other Locks having 26¼ Class Keys.

For Auxiliary Roses and Handle which can be used under the regular 2½ in. Roses of this design see Pages 242 and 250B.

Specify number and finish. See pages 1 and 2.




238

Rev. 6-1-57

The Defender

STANDARD DUTY CYLINDRICAL LOCKS

COMPLETE SETS WITH KNOBS AND ROSES



No. 439-651
With Keys
Class 77

Chalice Design No. 439


WROUGHT BRASS, BRONZE OR ALUMINUM

Knobs....2 in. diameter Knobs with 671
Cylinder and 77 Keys two piece; all
others one piece.

Roses....3¼ in. diameter.

Use No. 43924 for knob and concealed screw
rose to match for use as operating trim with
mortise lock.

No. 43924DT when required as dummy trim
for either mortise or cylindrical sets.



No. 439-4651
With Keys
Class 26¼

For Door	Set Number	Lock	
		No.	See Page
Communicating	439-600	600	240
Passage (Latch)	439-610	610	240
Exit (Latch)	439-615	615	240
Bath, Bedroom, Conference Room	439-620	620	240
Private Office, Etc.	439-621	621	240
Entrance or Office	†439-631	631	240
Patio	439-641	641	240
Patio	439-644	644	240
Entrance or Office	†439-651	651	240
Class Room	†439-655	655	240
Exit or Store Room	†439-657	657	241
Entrance or Office	†439-661	661	241
Exterior or Corridor	†439-662	662	241
Rest Room or Service Station	†439-663	663	241
Entrance or Office	*439-4631	4631	240
Entrance or Office	*439-4651	4651	240
Class Room	*439-4655	4655	240
Exit or Store Room	*439-4657	4657	241
Entrance or Office	*439-4661	4661	241
Exterior or Corridor	*439-4662	4662	241
Rest Room or Service Station	*439-4663	4663	241

One set in a box with screws, template and instructions for installing.

All sets 20 in a case.

Weight per Case: Cylinder Sets with Class 77 Keys, 49 Lbs.; Cylinder Sets with Class 26¼ Keys, 43 Lbs.; all other Sets, 39 Lbs.

† These Sets with 77 Class Keys can be Masterkeyed with other types of Corbin Locks having Class 77 Keys.


* These Sets with 26¼ Class Keys can be Masterkeyed only with other Locks having 26¼ Class Keys.

Specify number and finish. See pages 1 and 2.



The Defender

238A

STANDARD DUTY CYLINDRICAL LOCKS
COMPLETE SETS WITH KNOBS AND ROSESWindsor Design
No. 403

CAST BRASS OR BRONZE

Knob:2¼ in. diameter.

Rose:2½ in. diameter.

Use No. 40324 for knob and concealed screw rose to match for use as operating trim with mortise lock.

No. 40324DT when required as dummy trim for either mortise or cylindrical sets.

For Door	Set Number Cast Brass or Bronze	Lock	
		No.	See Page
Communicating	403-600	600	240
Passage (Latch)	403-610	610	240
Exit (Latch)	403-615	615	240
Bath, Bedroom, Conference Room	403-620	620	240
Private Office, Etc.	403-621	621	240
Entrance or Office	403-631	631	240
Private Office, Etc.	403-641	641	240
Exit	403-644	644	240
Entrance or Office	403-651	651	240
Class Room	403-655	655	240
Exit or Store Room	403-657	657	241
Office	403-661	661	241
Exterior or Corridor	403-662	662	241
Rest Room or Service Station	403-663	663	241

Packed one set in a box. Weight: Cylinder Sets, 3 Lbs. Each; all other Sets, 2¾ Lbs. each.

Cylinder sets in this design furnished only with Keys Class 77 and can be master keyed with other types of Corbin 5 Pin cylinder locks having Class 77 Keys.

Specify number and finish. See pages 1 and 2.




238B

The Defender

STANDARD DUTY CYLINDRICAL LOCKS

COMPLETE SETS WITH KNOBS AND ROSES

Melody Design
No. 411CAST BRASS, BRONZE OR
ALUMINUM

411-651

Knobs:2 in. diameter two-piece.

Roses:3¼ in. diameter.

Use No. 41124 for knob and concealed screw rose to match for use as operating trim with mortise lock.

No. 41124DT when required as dummy trim for either mortise or cylindrical sets.

For Door	Set Number	Lock	
		No.	See Page
Communicating	411-600	600	240
Passage (Latch)	411-610	610	240
Exit (Latch)	411-615	615	240
Bath, Bedroom, Conference Room	411-620	620	240
Private Office, Etc.	411-621	621	240
Entrance or Office	*411-631	631	240
Patio, Private Office, Etc.	411-641	641	240
Patio or Exit	411-644	644	240
Entrance or Office	*411-651	651	240
Class Room	*411-655	655	240
Exit or Store Room	*411-657	657	241
Entrance or Office	*411-661	661	241
Exterior or Corridor	*411-662	662	241
Rest Room or Service Station	*411-663	663	241

One set in a box with screws, template and instructions for installing.

* Cylinder Sets in this design furnished only with 671 Cylinder and 77 Class Keys and can be Masterkeyed with other types of locks having Class 77 Keys.


Specify number and finish. See pages 1 and 2.




The Defender

238C


STANDARD DUTY CYLINDRICAL LOCKS



No. 411S-H Stratawood
Horizontal Grain
Diameter 2 in.




No. 411S-V Stratawood
Vertical Grain
Diameter 2 in.




No. 411C Cocabola
No. 411R Rosewood
Diameter 2 in.

Melody Design
Wood Knobs

Projection 2 $\frac{3}{8}$ in. on 1 $\frac{3}{8}$ in. door.




No. 439MPB Mother of Pearl
Black Frieze
2 in. Diameter



No. 411MPG Mother of Pearl
Gold Frame
2 in. Diameter


Projection 2 $\frac{3}{8}$ in. on 1 $\frac{3}{8}$ in. door.

Melody Design
Ceromic Knobs



No. 439C Cocabola
No. 439R Rosewood
Diameter 2 in.

Wood Knobs



No. 439MPB Mother of Pearl
Black Frieze
Diameter 2 in.

Ceramic Knob

Projection 2 $\frac{3}{8}$ in. on 1 $\frac{3}{8}$ in. door.

Cholice Design

Wood and Ceramic Knobs for interior use only. Cannot be furnished with cylinder in knob.

All with wrought shank and furnished regularly with No. 439 Chalice Rose Wrought Brass, Bronze, or Aluminum, 3 $\frac{1}{4}$ in. diameter.

To order in sets, prefix knob number to lock number, see pages 240, 241.

Example: **A411C-610** Passage Door Latch Set with 411C Cocabola Knob both sides with polished brass shanks and roses.

DB439R-651 Entrance Door Set with Dull Bronze Metal Knob and Rose 439 Chalice Design outside and 439R Rosewood Knob with Dull Bronze Shank and Rose inside.

Specify number and finish. See pages 1 and 2.



The Defender

STANDARD DUTY CYLINDRICAL LOCKS

COMPLETE SETS WITH KNOBS AND ROSES

239

Rev. 6-1-57

Crestwood Design No. 405


CAST BRASS, BRONZE OR ALUMINUM

Knob: 2 in. diameter.

Rose: 3 in. diameter.

Use No. **40524** for knob and concealed screw rose to match for use as operating trim with mortise lock.

No. **40524DT** when required as dummy trim for either mortise or cylindrical sets.



For Door	Set Number Cast Brass, Bronze or Aluminum	Lock	
		No.	See Page
Communicating	405-600	600	240
Passage (Latch)	405-610	610	240
Exit (Latch)	405-615	615	240
Bath, Bedroom, Conference Room	405-620	620	240
Private Office, Etc.	405-621	621	240
Entrance or Office	405-631	631	240
Private Office, Etc.	405-641	641	240
Exit	405-644	644	240
Entrance or Office	405-651	651	240
Class Room	405-655	655	240
Exit or Store Room	405-657	657	241
Office	405-661	661	241
Exterior or Corridor	405-662	662	241
Rest Room or Service Station	405-663	663	241

Packed one set in a box. Weight: Cylinder Sets, 2 $\frac{3}{8}$ Lbs. Each; all other Sets, 2 $\frac{5}{8}$ Lbs. Each.

Cylinder sets in this design furnished only with Keys Class 77 and can be master keyed with other types of Corbin 5 Pin cylinder locks having Class 77 Keys.

Specify number and finish. See pages 1 and 2.



240


Rev. 6-1-57

The Defender

STANDARD DUTY CYLINDRICAL LOCKS

FUNCTIONS AVAILABLE

Inside Outside


**No. 600****Communicating Lock**

For connecting doors.

Latch bolt operates by knobs from either side except when turn button in either knob locks both knobs.

Latch bolt is automatically dead locked when door is closed.

To prevent accidental lockout this lock should not be used on doors between rooms which have no other entrance.


**No. 620****Privacy Lock**

For use on bathroom, bedroom, lavatory or conference room doors.

Latch bolt operated by knobs from either side except when outside knob is locked by pushing in button in inside knob.

Turning inside knob or closing door automatically releases locking button.

In case of emergency pressure of emergency key or other pointed instrument against emergency device in center of outside knob releases locking mechanism.

**No. 644****Exit Lock**

For doors used mostly for exit, and entrance not required when locked.


Latch bolt operated by knobs from either side except when outside knob is locked by turn button in inside knob.

Latch bolt is automatically deadlocked when door is closed.

For further description, dimensions, etc., see page 235.


Above numbers cover functions only. For complete set with knobs and roses, see pages 236-239.

Inside Outside

**No. 610****Passage Door Lock**

For any door that does not require locking.


Latch bolt operated by knobs from either side at all times.

**No. 631 With Class 77 Keys**
No. 4631 With Class 26 1/4 Keys**Entrance of Office Lock**

For entrance, vestibule or office doors.

Latch bolt operated by key from the outside at all times and by knobs from either side except when outside knob is locked by turn button in inside knob.

Without Auxiliary Latch to deadlock Latch Bolt.


**No. 651 With Class 77 Keys**
No. 4651 With Class 26 1/4 Keys**Entrance or Office Lock**

For entrance, vestibule or office doors.

Latch bolt operated by key from the outside at all times and by knobs from either side except when outside knob is locked by turn button in inside knob.

Latch bolt is automatically deadlocked when door is closed.


Inside Outside

**No. 615****Exit Latch**

For doors used for exit only.

Latch bolt operated by knob from the inside at all times. Outside knob always rigid.

Latch bolt is automatically deadlocked when door is closed.

**No. 641*****No. 621****Patio or Sun Deck Lock**


For doors that require locking only when room is occupied or for doors to sun deck, basement or inner office. Can also be used for bedroom or bathroom doors if emergency operation from outside is not required.

Latch bolt operated by knobs from either side except when outside knob is locked by pushing in button in inside knob.

A turn of inside knob or closing door releases locking button preventing accidental lockout.

Latch bolt is automatically deadlocked when door is closed.

*Without auxiliary.

**No. 655 With Class 77 Keys**
No. 4655 With Class 26 1/4 Keys
Class Room Lock

For Class Room or Utility Room doors.

Latch bolt operated by knobs from either side except when outside knob is locked by key in outside knob.

Latch bolt is automatically deadlocked when door is closed.


The Defender

241

Rev. 6-1-57

STANDARD DUTY CYLINDRICAL LOCKS

FUNCTIONS AVAILABLE




No. 657 With Class 77 Keys
No. 4657 With Class 26 1/4 Keys
Utility or Storeroom Lock

For utility, storeroom or exit doors.

Latch bolt operated by knob from inside and key from the outside. Outside knob always rigid.

Latch bolt is automatically deadlocked when door is closed.




No. 661 With Class 77 Keys
No. 4661 With Class 26 1/4 Keys
Office Lock

For use on office doors.

Latch bolt operated by key from the outside at all times and by knobs from either side except when the outside knob is locked by pushing in button in inside knob.

Turning key outside or knob inside automatically releases locking button. Closing door does not release locking button.

Latch bolt is automatically deadlocked when door is closed.




No. 662 With Class 77 Keys
No. 4662 With Class 26 1/4 Keys
Exterior or Corridor Lock

Latch bolt operated by key from the outside at all times and by knobs from either side except when outside knob is locked by pushing in button in inside knob.

Turning key outside or knob inside releases locking button. Closing door does not release locking button.

Locking button has slot in head and can be fixed in locked position by turning it with a coin or screw driver.

Latch bolt is automatically deadlocked when door is closed.



No. 663 With Class 77 Keys
No. 4663 With Class 26 1/4 Keys
Service Station Lock

For rest rooms or public station doors.


Latch bolt operated by key from outside at all times and by knobs from either side except when outside knob is locked by pushing in button in inside knob.

Turning key outside, knob inside or closing door automatically releases locking button.

Locking button has slot in head and can be fixed in locked position by turning it with a coin or screw driver.


Latch bolt is automatically deadlocked when door is closed.

Cylinder



No. 670

Extruded Brass ball bearing 5 Pin tumblers with Class 77 Keys used in two piece knobs all designs except Chalice and Melody.



No. 671

Extruded Brass ball bearing 5 Pin tumblers with Class 77 Keys used with Chalice and Melody Designs only.



No. 672

Brass 5 Pin tumblers with Class 26 1/4 Keys. For use in one piece knobs, wrought designs only.

All cylinders easily removable for rekeying if desired.

For further description, dimensions, etc., see page 235.

Above numbers cover functions only. For complete sets with knobs and roses, see pages 236-239.



242


Rev. 6-1-57

The Defender

STANDARD DUTY CYLINDRICAL LOCKS

Auxiliary Roses

WROUGHT BRASS, BRONZE AND ALUMINUM




431A

5½ in. dia.



431B

5½ in. dia.




431C

5½ in. dia.

These auxiliary roses can be used under regular 2¾ in. rose of any standard duty cylindrical lockset—5 in. backset. For other auxiliary roses and auxiliary handles see page 250B.

Flush Handle




FT1

Wrought Brass, Bronze or Aluminum with cast Turn Piece. 2¾ in. diameter.

This flush turn can be used in place of free acting plain inside knob with Latch 610 and Lock 655. Recommended for use on Closet Doors and Communicating Doors in hotel suites where clearance is insufficient to accommodate projection of knob.

In ordering suffix **FT1** to Lock No. thus: 430-610**FT1**.

Working Trim




Knobs with concealed screw roses to match the different cylindrical lock designs will be furnished for use as operating trim with mortise locks.

These knobs and roses can also be used as dummy trim with either cylindrical or mortise locksets.

See Standard Duty Cylindrical Locks, design pages 236-239 for catalogue numbers for these knobs.

Square Rose



No. 45104


Wrought Brass, Bronze or Aluminum

Size 3 in. x 3 in.

Can be used in place of regular rose with any standard duty cylindrical set.

If ordered singly specify whether outside or inside rose is required.


Strikes



645S

Regular Strike

Wrought Brass, Bronze or Aluminum. Size 2¾ x 1½ in. Curved lip 1¼ in. to center. Can be furnished with curved lip 1, 1½, 1¾ or 2 in. to center when so ordered.



645OB

Open Back Strike

Cast Brass, Bronze or Aluminum. Size 2¾ x 1½ in. Furnished for doors 1¾ to 2¼ in. thick. State thickness of door.

Specify number and finish. See pages 1 and 2.




The Defender

STANDARD DUTY CYLINDRICAL LOCKS

243

Rev. 6-1-57


Rabbeted Front



These locks can be supplied with rabbeted front and strike for doors with $\frac{1}{2}$ in. rabbet. In ordering, suffix **RAB** to number thus **430-651 RAB**.

Regular size $2\frac{1}{4} \times 1 \times \frac{1}{2}$ in. Beveled $\frac{1}{8}$ " in 2". Regular backset $2\frac{3}{8}$ in. longside of rabbet. On $2\frac{3}{4}$ in. special backset locks front will be $1\frac{1}{8}$ in. wide with strike to suit.

Mortising Tool For Latch Fronts




No. 061

For use in accurate mortising of doors for regular $2\frac{1}{4} \times 1$ in. front for the Defender Standard Duty Cylindrical Locks.

Boring Jig


ALUMINUM



No. 060

For use in boring holes for lock case and latch unit for The Defender Standard Duty Cylindrical Locksets regular $2\frac{3}{8}$ in. backset.

Reinforcing Unit



No. 492

For hollow metal doors.

This reinforcing unit is essential when cylindrical locks are to be installed in hollow metal doors. It is welded into the hollow metal stile by door manufacturer when the door is made.

Made for $1\frac{3}{8}$ " or $1\frac{1}{4}$ " doors.

State thickness of door.

Template blue prints for cutting metal doors for cylindrical locks will be available.

Extension Unit




No. 691-5"

Above Extension Unit when attached to regular $2\frac{3}{8}$ " backset latch unit will extend backset to 5 in.

When ordered for hollow metal doors sleeve will be provided to hold latch unit and extension unit together.

Bit



No. 4103

For boring $2\frac{1}{8}$ in. diameter holes for the case of Defender Standard Duty Cylindrical Locks.

Can be used with either bit brace or electric drill.



The Defender


STANDARD DUTY CYLINDRICAL LOCKS

INSTALLATION DETAILS


ADJUSTABLE FOR DOORS 1 1/4" TO 1 3/4"

1 LAYOUT DOOR


Scribe vertical center line on door edge for latch. Mark center horizontally on edge of door. Apply template to high edge of door bevel at intersection of lines, and mark center of hole for lock case.

**2 BORE HOLES IN DOOR**


Bore 2 1/2" hole thru stile as marked. Bore from both sides. Bore 7/8" hole for latch as marked. Mortise for latch front and position latch.

**3 POSITION STRIKE**


Transfer vertical center line of latch from edge of door to jamb. Mortise jamb for strike with screw holer on center line and latch at center of strike opening. Screw strike home.

**4 DETACH INSIDE TRIM**


Remove inside rose from rose liner to position shown. Depress knob retainer with screw-driver and with pressure against rose, push knob off tubular spindle.

**5 ADJUST LOCK**


Adjust lock for door thickness by rotating outside rose. Lock is suitable for doors 1 1/4" to 1 3/4" thick.

**6 ENGAGE UNITS**



With latch unit in place, install lock so that lock case engages with latch case prong and latch tail interlock with retractor. Unit should interlock freely, do not force. If necessary correct lock case hole for free engagement.

**7 ATTACH ROSE LINER**

Attach inside rose liner with machine screws and tighten securely to door. Latch should depress freely under easy finger pressure and knob should retract latch bolt.

**8 INSTALL INSIDE KNOB**

Slip rose over tubular spindle to position shown and tighten rose by snapping it over spring clip. Then slide knob on tubular spindle with depression on knob sleeve or rhank lined up with narrow slot in tubular spindle. Push knob or for it will go and rattle knob sharply with palm of hand to snap over knob retainer. Check installation by operating both knobs.


**A**

This information for use only for cylinder locksets with keyway in vertical position.

Cylinder locksets with keyway in horizontal position can be applied to right or left hand doors without change.

IMPORTANT

Cylinders with keyway in vertical position are assembled in knob for right or left hand door as ordered. If it becomes necessary to change the hand of a lock so that cylinder will be right side up, see instructions of right.

**TO CHANGE HAND OF LOCK**


- (1) Remove key from lock.
- (2) With lock held in position shown in (Fig. 1) and with latch retractor facing you, unscrew rose and turn knob 1/2 turn toward you to expose knob retainer to slot in threaded flange.
- (3) Depress knob retainer with screw-driver and at the same time pull off knob.
- (4) Turn knob over 1/2 turn and with slot in knob sleeve in line with slot in tubular spindle shown (Fig. 2) push knob on until it comes to a stop, then with a slight turn toward you continue to push knob until it hits knob retainer.
- (5) Turn knob toward you 1/2 turn or before to expose knob retainer and depress retainer with screw-driver and push knob into position.
- (6) Try pulling knob off to be sure knob retainer is engaged.

PATENTS APPLIED FOR

Residential Cylindrical Locks

245

Rev. 6-1-57



OUTSTANDING FEATURES

The ideal lock for residential use. Especially desirable for the budget priced home.

Easy to install; simply bore two holes and mortise for front and strike. All functions have the same size case, front and strike making them interchangeable in the same mortise.

Precision manufacture provides complete interchangeability of parts.

All exposed parts Wrought Brass, Bronze or Aluminum.

Knobs screwless self aligning with snap-on catch or retainer with screwless roses. On cylinder sets the outside knob retainer is inaccessible, without use of key, preventing forced entry.

Knobs with large cylinders and 77 keys two-piece construction. Other knobs sturdy wrought one-piece construction.

Balanced knob action with coil compression type springs.

Meets Government Specifications type 150 and 150Y.

Cases and interior parts heavy pressed steel, zinc plated and dichromate dipped for rust resistance, and projection welded for strength.

Extremely sturdy steel inner frame and case assembly assures positive alignment of parts.

Heavy steel anchor plate, with bayonet slots for quick assembly, securely fastens lock to door in perfect alignment.

Latch Bolts extruded brass with $\frac{3}{8}$ inch throw. Locking functions are available with an auxiliary latch which automatically deadlocks the latch bolt against end pressure when door is closed.

Cylinders Extruded Brass ball bearing 5 pin tumbler type with Class 77 keys. Can be master keyed with other Corbin locks having 077 Class master key.

Cylinders brass 5 pin tumbler type with 26 $\frac{1}{4}$ class keys, can be master keyed only with other locks having class 26 $\frac{1}{4}$ keys.


Cylinders can be easily removed for replacement or re-keying if desired.

100% reversible. Adjustable for doors 1 $\frac{3}{8}$ to 1 $\frac{3}{4}$ in. thick.

Patents Applied For



Residential Cylindrical Locks




**Knob with
Push Button**

Push button is pushed in to lock and except where otherwise noted is released by a turn of knob inside or closing door.



**Knob with
Turn Button**

Turn button is manually operated both to lock and unlock.



**Dummy Trim
No. 23024DT**

Knob and Rose with concealed screws for use as Dummy Trim.

DESCRIPTION

Cylindrical Case:...Steel M and T Bronze Plate $1\frac{1}{16}$ in. diameter for 2 in. hole in door.

Backset:..... $2\frac{3}{8}$ in. (Backset of hole in door $2\frac{3}{8}$ in., as $1\frac{1}{16}$ in. diameter lock case is mounted off center in 2 in. diameter hole).

Latch Unit:.....Reversible.

No. 845 with plain latch.

No. 845 $\frac{1}{4}$ plain latch with throw-off feature.

No. 0845 with auxiliary latch.

Case: Steel, Zinc plated, Dichromate dip, $2\frac{7}{32}$ in. diameter for $\frac{7}{8}$ in. hole in door.

***Front:** Wrought Brass, Bronze or Aluminum. Size $2\frac{1}{4}$ x 1 in. Beveled $\frac{1}{16}$ in. in 2 inches. For use on either flat front door or door with front beveled $\frac{1}{8}$ in. in 2 in.

Latch Bolt: Solid Brass, $\frac{3}{8}$ in. throw.



***STRIKE
No. 845S**

**WROUGHT BRASS, BRONZE OR
ALUMINUM**

Size $2\frac{1}{4}$ x $1\frac{1}{4}$ in. curved lip $1\frac{1}{4}$ in. to center

Cylinder:.....No. 870 Extruded Brass, ball bearing 5 pin tumbler type.

Keying:.....Two nickel silver keys Class 77 with each lock. Can be master keyed in sets with other Corbin cylinder locks having 077 Class master key.

Cylinder:.....No. 872 brass 5 pin tumbler type for wrought sets for stock.

Keying:.....Two nickel silver keys Class 26 $\frac{1}{4}$ —can be master keyed only with other locks having Class 26 $\frac{1}{4}$ keys.

Thickness of Door: Adjustable for doors $1\frac{3}{8}$ to $1\frac{3}{4}$ in. thick with allowance for undersize $1\frac{3}{8}$ in. mill doors.

Can also be furnished for doors $1\frac{3}{4}$ to 2 in. thick. In ordering affix **E** to number, thus: **751E**.

Hand of Door:....**REVERSIBLE**—except that on cylinder sets, with Class 77 keys it is advisable to specify hand of door so that factory can assemble locks with keyway in correct position saving contractor time when applying. All other sets can be applied to right or left hand doors without change.

Packing:.....One set in a box, with screws and instructions for applying.

*Front and strike can be furnished with corners rounded to $\frac{1}{4}$ in. radins for machine mortising. In ordering affix **RC** to number, thus: **851RC**.




Residential Cylindrical Locks

COMPLETE SETS WITH KNOBS AND ROSES

247

Rev. 6-1-57



230-751

Keys class 77. Keyway in vertical position.


Spartan Design No. 230

**WROUGHT BRASS, BRONZE OR
ALUMINUM**

Knobs...Knobs with cylinder and class 77 keys, two piece 2½ in. diam. Knobs with cylinder and class 26¼ keys and knobs without cylinder one piece 2 in. diam.

Roses...2½ in. diam.

Uses No. **23024 OT** for Knobs and Roses to be used as dummy trim.



230-4751

Keys class 26¼. Keyway in horizontal position.

Door	Set Number	Lock Number	See Page	Knobs Diameter	Roses Diameter
Inside (Latch)	230-710	710	249	2"	2⅝"
Bedroom or bathroom	230-720	720	249	2"	2⅝"
Patio, sun deck, etc.	230-721	721	249	2"	2⅝"
Entrance or office	*230-731	731	249	2⅛"	2⅝"
Patio, sun deck, etc.	230-741	741	249	2"	2⅝"
Entrance or office	*230-751	751	249	2⅛"	2⅝"
Exterior or office	*230-761	761	249	2⅛"	2⅝"
Exterior or office	*230-771	771	249	2⅛"	2⅝"
Entrance or office	†230-4731	4731	249	2"	2⅝"
Entrance or office	†230-4751	4751	249	2"	2⅝"
Exterior or office	†230-4761	4761	249	2"	2⅝"
Exterior or office	†230-4771	4771	249	2"	2⅝"

One set in a box with screws, template and instructions for installing.

All sets 20 in a case, weight per case; cylinder sets 32 lbs; all others 24 lbs.

*These sets with Class 77 keys can be master keyed with all other Corbin locks having Class 77 keys.

†These sets with Class 26¼ keys can be master keyed only with other locks having Class 26¼ keys.

For large Auxiliary Roses which can be used under the regular 2½ in. Roses of above sets see Pages 242 and 250B.

Specify number and finish. See pages 1 and 2.




248

Rev. 6-1-57

Residential Cylindrical Locks

COMPLETE SETS WITH KNOBS AND ROSES



No. 240-4751

Mayfair Design

No. 240

WROUGHT BRASS, BRONZE OR ALUMINUM

Knobs.....One piece 1 $\frac{7}{8}$ in. diam.

Roses.....2 $\frac{5}{8}$ in. diam.

Use No. 24024 DT for Knobs and
Roses to be used as dummy trim.

Door	Set Number	Lock Number	See Page	Knobs Diameter	Roses Diameter
Inside (Latch)	240-710	710	249	1 $\frac{7}{8}$ "	2 $\frac{5}{8}$ "
Bedroom or bathroom	240-720	720	249	1 $\frac{7}{8}$ "	2 $\frac{5}{8}$ "
Patio, sun deck, etc.	240-721	721	249	1 $\frac{7}{8}$ "	2 $\frac{5}{8}$ "
Patio, sun deck, etc.	240-741	741	249	1 $\frac{7}{8}$ "	2 $\frac{5}{8}$ "
Entrance or office	*240-4731	4731	249	1 $\frac{7}{8}$ "	2 $\frac{5}{8}$ "
Entrance or office	*240-4751	4751	249	1 $\frac{7}{8}$ "	2 $\frac{5}{8}$ "
Exterior or office	*240-4761	4761	249	1 $\frac{7}{8}$ "	2 $\frac{5}{8}$ "
Exterior or office	*240-4771	4771	249	1 $\frac{7}{8}$ "	2 $\frac{5}{8}$ "

One set in a box with screws, template and instructions for installing.

All sets 20 in a case, weight per case cylinder sets 32 lbs; all others 24 lbs.

*These sets with Class 26 $\frac{1}{4}$ keys, can be master keyed only with other locks having Class 26 $\frac{1}{4}$ keys.

Locksets with 77 Class keys cannot be furnished in this design.

For large Auxiliary Roses which can be used under the regular 2 $\frac{5}{8}$ in. diam. Roses of above sets see Pages 242 and 250B.

Specify number and finish. See pages 1 and 2.




Residential Cylindrical Locks

249

Rev. 6-1-57


FUNCTIONS AVAILABLE



No. 710
Passage Door Latch

For any door that does not require locking.

Latch bolt operated by knobs from either side at all times.




No. 720
Bedroom or Bathroom Lock

For use on bathroom, bedroom, lavatory or conference room doors.

Latch bolt operated by knobs from either side except when outside knob is locked by pushing in button in inside knob.

Turning inside knob or closing door automatically releases locking button.

In case of emergency pressure of pointed instrument against emergency device in center of outside knob releases locking mechanism.




No. 741
Patio Lockset

For Patio, Sun Deck or Basement doors or for doors that require locking only when room is occupied.

Latch bolt operated by knobs from either side except when outside knob is locked by pushing in button in inside knob.

A turn of inside knob releases locking button. Closing door does not release locking button.

Latch bolt is automatically deadlocked when door is closed.




***No. 731** — with class 77 keys.
†No. 4731 — with class 26¼ keys.

Entrance or Exterior Lockset

For entrance, vestibule or office doors.

Latch bolt operated by key from the outside at all times and by knobs from either side except when outside knob is locked by turn button in inside knob.




***No. 751** — with class 77 keys.
†No. 4751 — with class 26¼ keys.

Entrance or Exterior Lockset

For entrance, vestibule or office doors.

Latch bolt operated by key from the outside at all times and by knobs from either side except when outside knob is locked by turn button in inside knob.

Latch bolt is automatically deadlocked when door is closed.



***No. 761** — with class 77 keys.
†No. 4761 — with class 26¼ keys.

Exterior or Office Doorlock

Latch bolt operated by key from the outside at all times and by knobs from either side except when outside knob is locked by pushing in button in inside knob.

Turning key outside or knob inside automatically releases locking button. Closing door does not release locking button.

Latch bolt is automatically deadlocked when door is closed.

***No. 771** — with class 77 keys.
†No. 4771 — with class 26¼ keys.

Same as above but without auxiliary latch to deadlock latch bolt.

Front and strike can be furnished with corners rounded to ¼ in. radius for machine mortising. In ordering affix **RC** to number, thus: **751 RC**.

For use on cupboard, pipe or wire shaft doors where projection of inside knob would interfere with closing of door use **No. 709** for latch like **710** but with plain plate inside no knob and **No. 779** for lock like **No. 751** but outside knob always rigid latch bolt operated by key from outside and plain plate only inside, no inside knob. Caution: Do not use these sets on closets which a person could enter and accidentally lock themselves in.

*Locks Nos. **731**, **751**, **761**, and **771** have keyway in vertical position and can be reversed for opposite hand or door by removing outside knob and replacing it in reversed position. They can be master keyed with all other Corbin locks having Class 77 keys.

†Locks Nos. **4731**, **4751**, **4761** and **4771** have keyway in horizontal position and can be applied to right or left hand doors without change. They can be master keyed only with other locks having keys Class 26¼.

For further description, dimensions, etc., see page 246.

Above numbers cover functions only. For complete sets with knobs and roses, see pages 247 and 248.



250

Rev. 6-1-57

Residential Cylindrical Locks

Cylinders



No. 870

For use with Residential Cylindrical Locks. Extruded Brass, ball bearing 5 pin tumbler type. 2 nickel silver keys, class 77.




No. 872

For use with Residential Cylindrical Locksets for stock. Brass, 5 pin tumbler type.

2 nickel silver keys, Class 26 1/4.

Extension Units




No. 791 — 5 in.

For Residential Locksets

For use in conjunction with regular latch unit to extend backset to 5 in.

Mortising Tool For Latch Fronts




No. 061

For use in accurate mortising of doors for the 2 1/4 x 1 in. front for the Residential Cylindrical Locks.

Boring Jig


ALUMINUM



No. 080

For use in boring holes for lock case and latch unit for the Residential Cylindrical Locksets.

Bits



No. 7103

For boring 2 in. diameter holes for the case of Residential Cylindrical Locks.

Can be used in either bit brace or electric drill.



Residential Cylindrical Locks


250A

INSTALLATION DETAILS

ADJUSTABLE FOR DOORS $1\frac{3}{8}"$ to $1\frac{3}{4}"$ **1 LAYOUT DOOR**


Scribe vertical center line on door edge for latch. Mark center horizontally on edge of door. Apply template to high edge of door bevel and intersection of lines, and mark center of hole for lock case.

CAUTION—Use template, do not measure. If boring jig is used, follow instructions with jig.


**2 BORE HOLES IN DOOR**

Bore 2" hole thru stile as marked from template, bore from both sides. Bore $\frac{7}{8}"$ hole for latch as marked. Mortise for latch front and position latch.

Bore (2" hole) from both sides of door. **CAUTION**—Bore hole as marked from template, do not measure.

**3 POSITION STRIKE**


Transfer vertical center line of latch from edge of door to jamb. Mortise jamb for strike with screw holes on center line and latch of center of strike opening. Screw




On locks with deadlocking plunger, be sure that plunger rides on strike. Plunger prevents forcing of latch when door is closed.

**4 DETACH INSIDE TRIM**


Depress inside knob retainer with screwdriver and exert pressure with thumb and forefinger to start release of knob, after which knob can be pulled off of tubular spindle.

**5 ENGAGE UNITS**

With latch unit in place, install lock so that lock case engages with latch case prongs and latch tail interlocks with retractor. Units should interlock freely, do not force. If necessary correct lock case hole for free engagement.


**6 DOOR THICKNESS**

Screws which fasten into lock case to secure inside rose attaching plate to door can be adjusted to suit door thickness.



**7 ATTACH ROSE PLATE**

(1) Adjust fastening screws to measure $\frac{1}{2}$ inch under head of screw to face of door.

(2) Place inside rose plate with large holes in screw slots over head of fastening screws and with word (Front) toward front of door as shown. Turn plate clockwise and tighten screws securely.

**8 INSTALL INSIDE KNOB**



Slip rose over tubular spindle so that screw driver slot is toward hinge side of door and snap rose over plate. Line up knob retainer slot with knob retainer and push knob into position. Check installation by operating both knobs.

**A**

This information for use only for cylinder locksets with keyway in vertical position. Cylinder locksets with keyway in horizontal position can be applied to right or left hand doors without change.

IMPORTANT

Cylinders with keyway in vertical position are assembled in knobs for right or left hand doors as ordered. If it becomes necessary to change the hand of a lock so that cylinder will be right side up, see at right.

**TO CHANGE HAND OF LOCK**

- (1) Lock outside knob by depressing and turning thumb piece in inside knob.
- (2) Turn key one quarter turn and at the same time depress knob retainer with a small nail and pull knob off. (Fig. 1)
- (3) Remove key.
- (4) Turn knob one half turn and with knob retainer hole in line with knob retainer (Fig. 2) replace on spindle. Push knob down on spindle until it touches knob retainer.
- (5) Depress retainer and push knob as far as possible on spindle.
- (6) Reinsert key and turn one quarter turn. Push knob further on spindle with key turned to engage knob retainer with slot in knob. Try to remove knob in order to check knob retainer engagement.


PATENTED




250B

Auxiliary Roses

FOR USE WITH RESIDENTIAL, DEFENDER OR HEAVY
DUTY CYLINDRICAL LOCKSETS, BRASS, BRONZE
OR ALUMINUM (ALUMILITED)




Corona Design
No. 401G
Cast Metal
Size $7\frac{1}{8}$ x $3\frac{1}{2}$ in.




Polaris Design
No. 401E
Cast Metal
Size 10 x $7\frac{1}{2}$ in.

Nos. 231A and 401G can be used with regular $2\frac{3}{8}$ or $2\frac{3}{4}$ in. backsets. All others require lock 5 in. backset or over.

Except for Nos. 401F and 801F these Auxiliary Roses are used under regular $2\frac{3}{8}$ in. diameter Roses of cylinder locksets.



Sunburst Design
No. 401F for Defender sets.
No. 801F for heavy duty sets
Cast Metal
Size 7 x $4\frac{1}{2}$ in.
Used in place of outside Rose.




Rancho Design
No. 431D

Wrought Metal

Size 8 x 8 in. on the diamond.

Can also be used on the square.

Size $5\frac{5}{8}$ x $5\frac{5}{8}$ in. on the square.



No. 231A
Wrought Metal
Size $3\frac{3}{4}$ in. diam.

FOR OTHER AUXILIARY ROSES SEE PAGE 242


Auxiliary Handle

No. 232P

Cast Brass, Bronze or Aluminum

Size $9\frac{1}{8}$ x $3\frac{1}{4}$ in. Projection $2\frac{1}{4}$ in. For use under the regular $2\frac{3}{8}$ in. outside rose of entrance or exterior door sets when entrance handle type trim is desired.

Has no function except to act as door pull.



Tubular Latches

251


Rev. 6-1-57

REVERSIBLE



WBX

Wrought Box
Furnished only
when ordered



Strike

640 to 0650

Case Cast Iron, $1\frac{1}{16}$ in. diameter, $3\frac{1}{8}$ in. long.


Front $2\frac{1}{4}$ x 1 in.

Backset $2\frac{3}{16}$ in.


Latch Bolt Cast Iron.

Hub $\frac{1}{16}$ in.


Strike $2\frac{1}{4}$ x $\frac{7}{8}$ in. Curved Lip $1\frac{1}{8}$ " to center.



No. 1109
2 in. dia. Plain




No. 1158 Rose
2 in. dia. With
Hole for emer-
gency device




No. 1157 Rose
2 in. dia. With
Locking Lever

No.	Front	Operation
640 0640	Wrought Brass or Bronze Polished Wrought Steel, Sprayed	By knobs from either side
650 0650	Same as No. 640 and 0640 except for Locking Spring in Case, which is operated by Lever on inside Rose which can be turned to lock both Knobs when room is occupied. These locks are provided with an emergency device which can be inserted in hole in outside Rose and turned to release locking mechanism from the outside in case of necessity.	


DETAILS OF THE VARIOUS SETS AVAILABLE WITH TUBULAR LATCHES



Inside Set
Latch No. 640, 0640




Closet Set
Latch No. 640, 0640



Bedroom or Bathroom Set
With Emergency Feature
Lock No. 650, 0650

Mortise $2\frac{1}{4}$ " x 1" — $\frac{1}{8}$ " deep for front



Showing door bored for Lock No. 650.

Latch No. 640 requires the same mortise except without $\frac{3}{8}$ in. hole for locking device.

Template instructions for installing packed with each set. For complete sets see following pages.

Specify number and finish. See pages 1 and 2.




Tubular Latch Sets

WROUGHT BRASS OR BRONZE


REVERSIBLE

253

Rev. 6-1-57



200F-640



202-640

Type of 302-640

Door	Set No.	Latch		Pair Knobs		Roses			Packed in a Box	Weight Dozen Sets
		No.	See Page	No.	Dia. Inches	Outside No.	Inside No.	Dia. Inches		
Inside	200F-640	640	251	418	2	1109	1109	2	1	14¼ lbs.
Closet	200F-640½	640	251	418 x 040¼ Spindle	2	1109	None	2	1	12 lbs.
Bathroom or Bedroom	200F-650	650	251	418	2	1158	1157	2	1	14¼ lbs.
Inside	202-640	640	251	1422	2	1109	1109	2	1	12 lbs.
Closet	202-640½	640	251	1422 x 040¼ Spindle	2	1109	None	2	1	10 lbs.
Bathroom or Bedroom	202-650	650	251	1422	2	1158	1157	2	1	12 lbs.

Packed with screws. 2½ dozen in a case.

WROUGHT STEEL

Door	Set No.	Latch		Pair Knobs		Roses			Packed in a Box	Weight Dozen Sets
		No.	See Page	No.	Dia. In.	Outside No.	Inside No.	Dia. In.		
Inside	*302-640	0640	251	01422	2	01109	01109	2	1	12 lbs.
Bathroom or Bedroom	*302-650	0650	251	01422	2	01158	01157	2	1	12 lbs.

Packed with screws. 2½ dozen in a case.


*Latch fronts and strike furnished EAS and DES sprayed finishes only.

Specify number and finish. See pages 1 and 2.



254 Combination Handle and Rim Lock Set

CAST BRASS OR BRONZE



75383

WITH HANDLES BOTH SIDES

Set No.	Rim Latch	See Page	Mortise Latch	See Page	One Pair Handles Cast Brass or Bronze	Weight Per Set
753-177	356	188	177	172	75383	6½ lbs.
753-2R6	3R6	187	177	172	75383	6½ lbs.
753-247	Rim Lock 1447	184	177	172	75383	6¾ lbs.


Operates:—Mortise Latch No. 177, by thumb piece of handle from either side.

Night Latch No. 356, by Key from outside and Turn Knob inside. The stop in case holds Bolt retracted.

Night Latch No. 3R6, by Key from outside and Turn Knob inside. The stop in case holds the Bolt retracted.

Rim Dead Lock No. 1447, by Key from outside and Turn Knob inside.

One in a box, with screws.



Edge view applied.



0792

Thumb Latches

Grip No. 04421

No.	Size Plate Inches	Material and Finish	Weight Each
0792	10x2¾	Cast Iron With Wrought Steel Plate Plated	2 lbs.

One in a box, with screws.

Specify number and finish. See pages 1 and 2.



Combination Rim and Mortise Locksets 255

FOR DOORS OPENING IN


Wrought Brass or Bronze

OPERATES


Mortise Latches Nos. 01 and 45, by Knobs from either side.

Night Latch No. 356, by Key from outside and Turn Knob inside. Stop in case holds Bolt retracted.

Night Latch No. 3R6, by Key from outside and Turn Knob inside. The stop in case holds the Bolt retracted.




Outside



Inside

Set No.	Rim Latch	See Page	Mortise Latch	See Page	Pair Knobs and Rose	One Escutcheon	Weight Per Set
702-045	356	188	45	180	1419½ (2¼ in. dia.)	70230 (9 x 2½ in.)	3½ lbs.
702-3R6	3R6	187	01	179	1419½ (2¼ in. dia.)	70230 (9 x 2½ in.)	3 lbs.

One in a box, with screws.

520-045
520-3R6529-045
529-3R6

Set No.	Rim Latch	See Page	Mortise Latch	See Page	Pair Knobs and Rose	One Escutcheon	Weight Per Set
520-045	356	188	45	180	1425 (2" Dia.)	2621 (8½ x 2⅜ in.)	3½ lbs.
520-3R6	3R6	187	01	179	1425 (2" Dia.)	2621 (8½ x 2⅜ in.)	3 lbs.
529-045	356	188	45	180	1492 x 1490 (2¼" dia. outside) (2" dia. inside)	2991 (9 x 2½ in.)	3½ lbs.
529-3R6	3R6	187	01	179	1492 x 1490 (2¼" dia. outside) (2" dia. inside)	2991 (9 x 2½ in.)	3 lbs.

One in a box, with screws.

Specify number and finish. See pages 1 and 2.




256

Rev. 6-1-57

Mortise Locksets

WROUGHT BRASS, BRONZE OR STEEL





100-842 104-842



1419 1/2

100-130
Type of 300-048


1422

104-130
Type of 304-048

153-130



418



153-438

Wrought Brass or Bronze

Door	Set No.	Lock		Pair Knobs		2 Roses		2 Escutcheons		Packed in a Box	Weight Doz. Sets
		No.	See Page	No.	Dia. In.	No.	Dia. Inches	No.	Size In		
Inside (Latch)	100-012	10	179	1419 1/2	2 1/4	1109	2			1	13 1/2 lbs.
Inside	100-130	285	173	1419 1/2	2 1/4	1109	2	2560	1 5/8 x 1 1/8	1	21 lbs.
	100-158	685	174	1419 1/2	2 1/4	1109	2	2560	1 5/8 x 1 1/8	1	24 lbs.
Bathroom	100-438	359	178	1419 1/2	2 1/4	1109	2	2140x2560	1 5/8 x 1 1/8	1	21 lbs.
Communicating	100-464	159 3/4	178	1419 1/2	2 1/4	1109	2	2-2140	1 5/8 x 1 1/8	1	25 1/2 lbs.
Vestibule	100-742	7331	162	1419 1/2	2 1/4	1109	2			1	40 1/2 lbs.
Front	100-842	5243	165	1419 1/2	2 1/4	1109	2	1-2140	1 5/8 x 1 1/8	1	45 lbs.
Inside (Latch)	104-012	10	179	1422	2	1109	2			1	12 3/4 lbs.
Inside	104-130	285	173	1422	2	1109	2	2560	1 5/8 x 1 1/8	1	20 3/4 lbs.
	104-158	685	174	1422	2	1109	2	2560	1 5/8 x 1 1/8	1	23 1/4 lbs.
Bathroom	104-438	359	178	1422	2	1109	2	2140x2560	1 5/8 x 1 1/8	1	20 1/4 lbs.
Communicating	104-464	159 3/4	178	1422	2	1109	2	2-2140	1 5/8 x 1 1/8	1	24 3/4 lbs.
Vestibule	104-742	7331	162	1419 1/2 x 1422	2 1/4 x 2	1109	2			1	39 3/4 lbs.
Front	104-842	5243	165	1419 1/2 x 1422	2 1/4 x 2	1109	2	1-2140	1 5/8 x 1 1/8	1	44 1/4 lbs.
Inside (Latch)	153-012	10	179	418	2	1109	2			1	15 3/4 lbs.
Inside	153-130	285	173	418	2	1109	2	2560	1 5/8 x 1 1/8	1	24 lbs.
Bathroom	153-438	359	178	418	2	1109	2	2140x2560	1 5/8 x 1 1/8	1	22 1/2 lbs.
Wrought Steel											
Inside (Latch)	300-004	01	179	01419 1/2	2 1/4	01109	2			1	13 1/2 lbs.
Inside	300-048	0285	173	01419 1/2	2 1/4	01109	2	02560	1 5/8 x 1 1/8	1	21 lbs.
Inside (Latch)	304-004	01	179	01422	2	01109	2			1	12 3/4 lbs.
Inside	304-048	0285	173	01422	2	01109	2	02560	1 5/8 x 1 1/8	1	18 3/4 lbs.

Packed with screws.

Specify number and finish. See pages 1 and 2.




Mortise Locksets

257

CAST IRON
IMITATION HALF POLISHED IRON
IPE FINISH ONLY



641-048



641-3R6

641-004
641-074


Door	Set No.	Lock		Knobs 2 in. Dia.	Escutcheons 6½ x 2 in.	Weight Dozen Sets
		No.	See page			
Inside (Latch)	641-004	01	179	64122	64131	24 lbs.
Inside	641-048	0285	173	64122	64131	31¾ lbs.
Bathroom	641-074	0359	178	64122x01422	64131x60032	30 lbs.

One in a box, with screws.

Set No.	Rim Latch	See page	Mortise Latch	See Page	Pair Knobs and Rose	One Escutcheon	Weight Per Set
641-3R6	3R6	187	01	179	Cast Iron 64122 2 in. Dia.	Cast Iron 64130 9¼x2¾ in.	3¾ lbs.

One in a box, with screws.

Rim Lock Sets



961



J01623½



3318



3366, 3367

Set No.	Lock						Pair Knobs			One Escutcheon			Weight Dozen Sets
	No.	Material and Finish	Size Inches	Lock Bolts	One Key Class	See Page	No.	Dia. In.	Material	No.	Size In.	Material	
3318	961	Cast Iron	4x3¼	Iron	011¼	196	J01623½	2¼	Wrought Steel	01103	2 Dia.	Wrought Steel	21¾ lbs.
3366	961	Japanned	4x3¼	Iron	011¼	196	J01623½	2¼	Japanned	60032	6x2	Japanned	24 lbs.
3367	961	Japanned	4x3¼	Iron	011¼	196	J01623½	2¼	Plated	60032	6x2	Plated	24 lbs.

One in a box, with screws.

Specify number and finish. See pages 1 and 2.





CANADA


WROUGHT DESIGNS

CANADA DESIGN

PORTLAND DESIGN

MIAMI DESIGN

BARRE DESIGN





INDEX OF

Wrought Designs

Number		Page
600SteelCANADA	261, 262
700SolidCANADA	261, 262
602SteelPORTLAND	263, 264
702SolidPORTLAND	263, 264
320SteelMIAMI	265
520SolidMIAMI	265
428SteelMIAMIGlass Knobs	266
128SolidMIAMIGlass Knobs	266
329SteelBARRE	267, 268
529SolidBARRE	267, 268
498SteelBARREGlass Knobs	269
198SolidBARREGlass Knobs	269


Canada Design

WROUGHT BRASS, BRONZE OR STEEL

261



01623 1/2 x 60032

4476
04476

70081

2353
02353

1419 1/2 x 70030



70061

3315
03315

Number		Size, Inches	Description
Wrought Brass or Bronze	Wrought Steel		
1419 1/2	01419 1/2	2 3/4 Dia.	Door Knob (seamless) simplex
70030	01623 1/2	2 3/4 Dia.	Door Knob (two piece) simplex
70031	60030	9 x 2 1/2	Escutcheon
	7 1/2 x 2 1/4	Escutcheon
70032	60032	6 x 2	Escutcheon
70033	60033	3 7/8 x 1 7/8	Escutcheon
70061		3 7/8 x 1 7/8	Electric Push Button
3315	03315	1 1/2 x 3	Flush Sash Lift (See page 73)
70081	12 x 3	Store Door Handle (See page 139)
*2353	*02353	Push Plate (See Page 130)
4476	04476	Door Pull (See Page 127)

Packed with screws. *Specify size.


Specify number and finish. See pages 1 and 2.



262

Canada Design


WROUGHT BRASS, BRONZE OR STEEL



700-806, 600-806



700-130, 600-048



700-842

Locksets—Wrought Brass or Bronze

Door	Set No.	Lock		Knobs	Escutcheons		Weight Dozen Sets
		No.	See Page		Outside	Inside	
Inside (Latch)	700-012	10	179	1419½	70033	70033	13½ lbs.
Inside	700-130	285	173	1419½	70032	70032	24 lbs.
	700-158	685	174	1419½	70032	70032	27 lbs.
Bathroom	700-426	359	178	One E 1419½	None	E70032	18 lbs.
	700-438	359	178	1419½	70032	70032	26¼ lbs.
Vestibule	700-742	7331	162	1419½	70030	70031	48 lbs.
Front	700-806	0251	171	1419½	70030	70032	38¼ lbs.
	700-842	5243	165	1419½	70030	70031	48 lbs.

One in a box, with screws.

Locksets—Wrought Steel

Door	Set No.	Lock		Knobs	Escutcheons		Weight Dozen Sets
		No.	See Page		Outside	Inside	
Inside (Latch)	600-004	01	179	01419½	60033	60033	13½ lbs.
	600-004½	01	179	01623½	60033	60033	13½ lbs.
Inside	600-048	0285	173	01419½	60032	60032	24 lbs.
	600-048½	0285	173	01623½	60032	60032	24 lbs.
Bathroom	600-072	0359	178	One E 01419½	None	E60032	18 lbs.
	600-072½	0359	178	One E 01623½	None	E60032	18 lbs.
	600-074	0359	178	01419½	60032	60032	26¼ lbs.
	600-074½	0359	178	01623½	60032	60032	26¼ lbs.
Front	600-806	0251	171	01419½	60030	60032	36 lbs.
	600-806½	0251	171	01623½	60030	60032	36 lbs.
	600-810	0261	171	01419½	60030	60032	36 lbs.
	600-810½	0261	171	01623½	60030	60032	36 lbs.
	*600B-806	0251	171	1419½x01419½	70030	60032	36 lbs.
	*600B-810	0261	171	1419½x01419½	70030	60032	36 lbs.

One in a box, with screws.

*Outside trim Wrought Brass or Bronze.

Specify number and finish. See pages 1 and 2.



Portland Design

263

WROUGHT BRASS, BRONZE OR STEEL



1419 1/2 x 70231
01419 1/2 x 60231




4470
04470




70281



2352
02352



1419 1/2 x 70230



2305

Number		Size, Inches	Description
Wrought Brass or Bronze	Wrought Steel		
1419 1/2	01419 1/2	2 1/4 Dia.	Door Knob (Seamless) Simplex
70230	60230	9 x 2 1/2	Escutcheon
70231	60231	7 x 2 1/4	Escutcheon
70233	60233	3 1/4 x 1 1/2	Escutcheon
70261	////	3 1/4 x 1 1/2	Electric Push Button (See Page 141)
70264	////	3 1/4 x 1 1/2	Bell Turn (See Page 92)
70281	////	14 x 3	Store Door Handle
* 2352	*02352	////	Push Plate (See Page 130)
4470	04470	////	Door Pull (See Page 127)
2305	////	6 3/4 x 2 1/2	Letter Drop Plate (See Page 142)


Packed with screws. *Specify size.

Specify number and finish. See pages 1 and 2.




Portland Design


WROUGHT BRASS, BRONZE OR STEEL



702-806, 602-806



702-130, 602-048



702-842

Locksets — Wrought Brass or Bronze

Door	Set No.	Lock		Knobs	Escutcheons		Weight Dozen Sets
		No.	See Page		Outside	Inside	
Inside (Latch)	702-012	10	179	1419½	70233	70233	13½ lbs.
Inside	702-130	285	173	1419½	70231	70231	24 lbs.
	702-158	685	174	1419½	70231	70231	24 lbs.
	702-438	359	178	1419½	70231	70231	26¼ lbs.
Bathroom	702-742	7331	162	1419½	70230	70231	48 lbs.
Vestibule	702-806	0251	171	1419½	70230	70231	38¼ lbs.
Front	702-842	5243	165	1419½	70230	70231	48 lbs.

One in a box, with screws.

Locksets — Wrought Steel

Door	Set No.	Lock		Knobs	Escutcheons		Weight Dozen Sets
		No.	See Page		Outside	Inside	
Inside (Latch)	602-004	01	179	01419½	60233	60233	13½ lbs.
Inside	602-048	0285	173	01419½	60231	60231	24 lbs.
Bathroom	602-074	0359	178	01419½	60231	60231	26¼ lbs.
Front	602-806	0251	171	01419½	60230	60231	37½ lbs.
	602-810	0261	171	01419½	60230	60231	36 lbs.
	*602B-806	0251	171	1419½ x 01419½	70230	60231	38¼ lbs.
	*602B-810	0261	171	1419½ x 01419½	70230	60231	36 lbs.

One in a box, with screws.

*Outside trim Wrought Brass or Bronze.


Specify number and finish. See pages 1 and 2.




Miami Design

265


WROUGHT BRASS, BRONZE OR STEEL



520-842



520-130, 320-048



520-806, 320-806

Articles

No. Brass or Bronze	No. Steel	Size, Inches	Description
1425	01425	2	Door Knob, Simplex
2620	3620	7 $\frac{1}{16}$ x 1 $\frac{3}{4}$	Escutcheon
2621	3621	8 $\frac{1}{2}$ x 2 $\frac{3}{16}$	Escutcheon

Locksets—Wrought Brass or Bronze

Door	Set No.	Lock		Knobs	Escutcheons		Weight Dozen Sets
		No.	See Page		Outside	Inside	
Inside (Latch)	520-012	10	179	1425	2620	2620	15 $\frac{3}{4}$ lbs.
Inside	520-130	285	173	1425	2620	2620	21 $\frac{3}{4}$ lbs.
	520-158	685	174	1425	2620	2620	24 lbs.
Bathroom	520-438	359	178	1425	2620	2620	21 $\frac{3}{4}$ lbs.
Vestibule	520-742	7331	162	1425	2621	2621	45 lbs.
Front	520-806	0251	171	1425	2621	2620	33 $\frac{3}{4}$ lbs.
	520-842	5243	165	1425	2621	2621	48 lbs.

One in a box, with screws.

Locksets—Wrought Steel

Door	Set No.	Lock		Knobs	Escutcheons		Weight Dozen Sets
		No.	See Page		Outside	Inside	
Inside (Latch)	320-004	01	179	01425	3620	3620	15 $\frac{3}{4}$ lbs.
Inside	320-048	0285	173	01425	3620	3620	21 $\frac{3}{4}$ lbs.
Bathroom	320-074	0359	178	01425	3620	3620	21 $\frac{3}{4}$ lbs.
Front	320-806	0251	171	01425	3621	3620	33 $\frac{3}{4}$ lbs.
	320-810	0261	171	01425	3621	3620	32 $\frac{1}{4}$ lbs.
	*320B-806	0251	171	1425 x 01425	2621	3620	33 $\frac{3}{4}$ lbs.
	*320B-810	0261	171	1425 x 01425	2621	3620	32 $\frac{1}{4}$ lbs.

One in a box, with screws *Outside trim Wrought Brass or Bronze.


Specify number and finish. See pages 1 and 2.




Barre Design

267


WROUGHT BRASS, BRONZE OR STEEL



1490 x 2991

1492 x 2990
01492 x 3990



52986



52991



52980

1490 x 2991
01490 x 39911492 x 2990
01492 x 3990

Number		Size, Inches	Description
Wrought Brass or Bronze	Wrought Steel		
1490	01490	2 1/4 Dia.	Door Knob (Seamless), Simplex
1492	01492	2 Dia.	Door Knob (Seamless), Simplex
2991	3991	9 x 2 1/2	Escutcheon
2990	3990	6 1/4 x 1 7/8	Escutcheon
52980	15 x 3	Store Door Handle (See Page 139)
52986	15 x 3	Door Pull (Grip No. 4451)
52991	15 x 3	Push Plate


Packed with screws.

Specify number and finish. See pages 1 and 2.





Barre Design

WROUGHT BRASS, BRONZE OR STEEL



529-842

529-130
329-048529-806
329-806

Locksets—Wrought Brass or Bronze

Door	Set No.	Lock		Knobs	Escutcheons		Weight Dozen Sets
		No.	See Page		Outside	Inside	
Inside (Latch)	529-012	10	179	1492	2990	2990	15¾ lbs.
Inside	529-130	285	173	1492	2990	2990	22¼ lbs.
	529-158	685	174	1492	2990	2990	24 lbs.
	529-438	359	178	1492	2990	2990	22¼ lbs.
Bathroom	529-742	7331	162	1492	2991	2990	45¾ lbs.
Vestibule	529-806	0251	171	1490 x 1492	2991	2990	34½ lbs.
Front	529-842	5243	165	1430 x 1492	2991	2990	43 lbs.

One in a box, with screws.

Locksets — Wrought Steel

Door	Set No.	Lock		Knobs	Escutcheons		Weight Dozen Sets
		No.	See Page		Outside	Inside	
Inside (Latch)	329-004	01	179	01492	3990	3990	16 lbs.
Inside	329-048	0285	173	01492	3990	3990	22½ lbs.
Bathroom	329-074	0359	178	01492	3990	3990	22½ lbs.
Front	329-806	0251	171	01490 x 01492	3991	3990	34½ lbs.
	329-810	0261	171	01490 x 01492	3991	3990	32¼ lbs.
	*329B-806	0251	171	1490 x 01492	2991	3990	34½ lbs.
	*329B-810	0261	171	1490 x 01492	2991	3990	32¼ lbs.


One in a box, with screws. *Outside trim Wrought Brass or Bronze.

Specify number and finish. See pages 1 and 2.




Barre Design

WROUGHT BRASS, BRONZE OR STEEL
WITH POLYGON TYPE GLASS KNOBS



198-842

198-130
498-048198-806
498-806

Locksets—Wrought Brass or Bronze

Door	Set No.	Lock		Knobs	Escutcheons		Weight Dozen Sets
		No.	See Page		Outside	Inside	
Inside (Latch)	198-012	10	179	418	2990	2990	18¾ lbs.
Inside	198-130	285	173	418	2990	2990	25½ lbs.
	198-158	685	174	418	2990	2990	27 lbs.
Bathroom	198-438	359	178	418	2990	2990	25½ lbs.
Vestibule	198-742	7331	162	418	2991	2990	45 lbs.
Front	198-806	0251	171	1490 x 418	2991	2990	33¾ lbs.
	198-842	5243	165	1490 x 418	2991	2990	48 lbs.

One in a box, with screws.

Locksets—Wrought Steel

Door	Set No.	Lock		Knobs	Escutcheons		Weight Dozen Sets
		No.	See Page		Outside	Inside	
Inside (Latch)	498-004	01	179	418	3990	3990	18¾ lbs.
Inside	498-048	0285	173	418	3990	3990	25½ lbs.
Bathroom	498-074	0359	178	418	3990	3990	25½ lbs.
Front	498-806	0251	171	01490 x 418	3991	3990	34½ lbs.
	498-810	0261	171	01490 x 418	3991	3990	32¼ lbs.
	*498B-806	0251	171	1490 x 418	2991	3990	36 lbs.
	*498B-810	0261	171	1490 x 418	2991	3990	36 lbs.

One in a box, with screws. *Outside trim Wrought Brass or Bronze.

Specify number and finish. See pages 1 and 2.



CAST DESIGNS

PLAZA DESIGN

CANADA DESIGN

STANDARD DESIGN

GOTHAM DESIGN

FIDELITY DESIGN

SOMERSET DESIGN

CANTERBURY DESIGN

TITAN DESIGN

WARDEN DESIGN





 INDEX OF

Cast Designs

Number		Page
739PLAZA	273
740CANADA	274, 275
741STANDARD	276, 277
745GOTHAM	278, 279
788FIDELITY ..	280, 281
807SOMERSET	282
862CANTERBURY	283
767TITAN	284
541WARDEN	285


Plaza Design

CAST BRASS OR BRONZE

273



739-158



73986



73990



739-842

No.	Size Inches	Description	No.	Size Inches	Description
1419	2¼	Door Knob Wrought Brass or Bronze PY Type	73986	12x3	Door Pull (See page 126)
1519½	2¼	Door Knob Cast Brass or Bronze PY Type	73990	12x3	Push Plate (See page 129)
73930	8 x 2½	Escutcheon	73991	15x3½	Push Plate (See page 129)
73932	6½ x 2½	Escutcheon			

Locksets

Door	Set No.	Lock		Knobs	Escutcheon	
		No.	See Page		Outside	Inside
Inside	739-130	285	173	1519½	73932	73932
	739-130¼	285	173	1419	73932	73932
	739-158	685	174	1519½	73932	73932
	739-158¼	685	174	1419	73932	73932
	739-438	359	178	1519½	73932	73932
Bathroom	739-438¼	359	178	1419	73932	73932
	739-464	159¾	178	1519½	73932	73932
Communicating	739-464¼	159¾	178	1419	73932	73932
	739-522	7551	162	1519½	73930	73930
Office	739-522¼	7551	162	1419	73930	73930
	739-742	7331	162	1519½	73930	73932
Vestibule	739-742¼	7331	162	1419	73930	73932
	739-842	5243	165	1519½	73930	73932
Front	739-842¼	5243	165	1419	73930	73932

One in a box, with screws.

Specify number and finish. See pages 1 and 2.



274

Canada Design


CAST BRASS OR BRONZE



1519½ x 74031



4485



74081



2343



1519½ x 74030

No.	Size Inches	Description
1419	2¼	Door Knob Wrought Brass or Bronze PY Type.
1519½	2¼	Door Knob Cast Brass or Bronze PY Type.
74030	9 x 2½	Escutcheon
74031	7½ x 2¼	Escutcheon
74081	15 x 3	Store Door Handle (See page 140)
*2343	Push Plate (See page 129)
4485	Door Pull (See page 126)

Packed with screws. *Specify size.

Specify number and finish. See pages 1 and 2.




Plaza Design

273

CAST BRASS OR BRONZE



739-158



73986



73990



739-842

No.	Size Inches	Description	No.	Size Inches	Description
1419	2¼	Door Knob Wrought Brass or Bronze PY Type	73986	12x3	Door Pull (See page 126)
1519½	2¼	Door Knob Cast Brass or Bronze PY Type	73990	12x3	Push Plate (See page 129)
73930	8 x 2½	Escutcheon	73991	15x3½	Push Plate (See page 129)
73932	6½ x 2½	Escutcheon			

Locksets

Door	Set No.	Lock		Knobs	Escutcheon	
		No.	See Page		Outside	Inside
Inside	739-130	285	173	1519½	73932	73932
	739-130¼	285	173	1419	73932	73932
	739-158	685	174	1519½	73932	73932
	739-158¼	685	174	1419	73932	73932
Bathroom	739-438	359	178	1519½	73932	73932
	739-438¼	359	178	1419	73932	73932
Communicating	739-464	159¾	178	1519½	73932	73932
	739-464¼	159¾	178	1419	73932	73932
Office	739-522	7551	162	1519½	73930	73930
	739-522¼	7551	162	1419	73930	73930
Vestibule	739-742	7331	162	1519½	73930	73932
	739-742¼	7331	162	1419	73930	73932
Front	739-842	5243	165	1519½	73930	73932
	739-842¼	5243	165	1419	73930	73932

One in a box, with screws.

Specify number and finish. See pages 1 and 2.




Canada Design

CAST BRASS OR BRONZE


275



740-522



740-158



740-842

Locksets

Door	Set No.	Lock		Knobs	Escutcheons	
		No.	See Page		Outside	Inside
Inside	740-130	285	173	1519½	74031	74031
	740-130¼	285	173	1419	74031	74031
	740-158	685	174	1519½	74031	74031
	740-158¼	685	174	1419	74031	74031
Bathroom	740-438	359	178	1519½	74031	74031
	740-438¼	359	178	1419	74031	74031
Communicating	740-464	159¾	178	1519½	74031	74031
	740-464¼	159¾	178	1419	74031	74031
Office	740-522	7551	162	1519½	74030	74030
	740-522¼	7551	162	1419	74030	74030
Vestibule	740-742	7331	162	1519½	74030	74031
	740-742¼	7331	162	1419	74030	74031
Front	740-842	5243	165	1519½	74030	74031
	740-842¼	5243	165	1419	74030	74031

One in a box, with screws.

Specify number and finish. See pages 1 and 2.

276

Standard Design

CAST BRASS OR BRONZE



1519½ x 74131



74186



74180



74190



1519½ x 74130

No.	Size Inches	Description
1419	2¼	Door Knob Wrought Brass or Bronze PY Type
1519½	2¼	Door Knob Cast Brass or Bronze PY Type
74130	8 x 2½	Escutcheon
74131	7 x 2¼	Escutcheon
74140	1¾ x 1⅝	Key Escutcheon
74180	15 x 3	Store Door Handle (See page 140)
74181	16 x 4	Store Door Handle (See page 140)
74186	12 x 3	Door Pull (See page 126)
74190	12 x 3	Push Plate (See page 129)
74192	15 x 3½	Push Plate (See page 129)
74193	16 x 4	Push Plate (See page 129)
74194	20 x 4	Push Plate (See page 129)


Packed with screws.

Specify number and finish. See pages 1 and 2.

Standard Design

CAST BRASS OR BRONZE

277



741-522



741-158



741-842

Locksets

Door	Set No.	Lock		Knobs	Escutcheons	
		No.	See Page		Outside	Inside
Inside	741-130	285	173	1519½	74131	74131
	741-130¼	285	173	1419	74131	74131
	741-158	685	174	1519½	74131	74131
	741-158¼	685	174	1419	74131	74131
Bathroom	741-438	359	178	1519½	74131	74131
	741-438¼	359	178	1419	74131	74131
Communicating	741-464	159¾	178	1519½	74131	74131
	741-464¼	159¾	178	1419	74131	74131
Office	741-522	7551	162	1519½	74130	74130
	741-522¼	7551	162	1419	74130	74130
Vestibule	741-742	7331	162	1519½	74130	74131
	741-742¼	7331	162	1419	74130	74131
Front	741-842	5243	165	1519½	74130	74131
	741-842¼	5243	165	1419	74130	74131

One in a box, with screws.

Specify number and finish. See pages 1 and 2.




278

Gotham Design

CAST BRASS OR BRONZE




74587



74522 x 74530



74586



74522 x 74531



74513



74522 x 74505



74549



74570



74540

No.	Size Inches	Description	No.	Size Inches	Description
74505	2 x 1 $\frac{3}{4}$	Knob Rose	*74570	3 $\frac{3}{4}$ x 10 $\frac{1}{4}$	Letter Drop
74513	2 $\frac{1}{16}$ x 1 $\frac{1}{16}$	Cylinder Collar	*74571	3 $\frac{3}{4}$ x 10 $\frac{1}{4}$	Letter Drop with Back Plate
74514	3 x 2 $\frac{1}{4}$	Cylinder Collar	74580	16 x 3	Store Door Handle, (See page 140)
74522	2 $\frac{1}{4}$ Dia.	Door Knob PY Type	74583	9 $\frac{1}{8}$ x 2 $\frac{1}{4}$	Sectional Door Handle, (See page 136)
74530	9 x 2 $\frac{1}{2}$	Escutcheon	74586	14 x 3	Door Pull (Grip 4436)
74531	7 x 2 $\frac{1}{4}$	Escutcheon	74587	8 $\frac{7}{8}$ x 2 $\frac{1}{4}$	Sectional Door Pull (Grip 4436)
74540	1 $\frac{3}{4}$ x 1 $\frac{1}{4}$	Escutcheon	74590	16 x 3	Push Plate
74549	1 $\frac{1}{2}$ x 1 $\frac{1}{4}$	Thumb Knob ($\frac{3}{16}$ " Spindle)	74591	14 x 3	Push Plate
74561	1 $\frac{3}{4}$ x 1 $\frac{1}{4}$	Push Button			

*Packed with screws. *Opening 1 $\frac{1}{2}$ x 7 in.


Specify number and finish. See pages 1 and 2.



Gotham Design

279


CAST BRASS OR BRONZE



745-522



745-158



745-842

Locksets

Door	Set No.	Lock		Knobs	Escutcheons	
		No.	See Page		Outside	Inside
Inside	745-130	285	173	74522	74531	74531
	745-158	685	174	74522	74531	74531
Bathroom	745-438	359	178	74522	74531	74531
Communicating	745-464	159 $\frac{3}{4}$	178	74522	74531	74531
Office	745-522	7551	162	74522	74530	74530
Vestibule	745-742	7331	162	74522	74530	74531
Front	745-842	5243	165	74522	74530	74531

One in a box, with screws.

Specify number and finish. See pages 1 and 2.


280

Fidelity Design


CAST BRASS OR BRONZE



78822 x 78831




78886



78890



78822 x 78830



78870



78822 x 78803

No.	Size Inches	Description
78803	2 1/4	Knob Rose
78822	2 1/4	Door Knob PY Type
78830	8 1/2 x 2 5/8	Escutcheon
78831	7 1/2 x 2 1/4	Escutcheon
*78870	2 1/2 x 8	Letter Box Plate
*78871	2 1/2 x 8	Letter Box Plate and Border
78880	16 x 4	Store Door Handle (See Page 140)
78886	16 x 4	Door Pull (Grip 4455)
78890	16 x 4	Push Plate

*Packed with screws. *With opening 5-3/16 x 15/16 in.

Specify number and finish. See pages 1 and 2.




Fidelity Design

281


CAST BRASS OR BRONZE



788-522



788-158



788-842

Locksets

Door	Set No.	Lock		Knobs	Escutcheons	
		No.	See Page		Outside	Inside
Inside	788-130	285	173	78822	78831	78831
	788-158	685	174	78822	78831	78831
Communicating	788-464	159 $\frac{3}{4}$	178	78822	78831	78831
Office	788-522	7551	162	78822	78830	78830
Vestibule	788-742	7331	162	78822	78830	78831
Front	788-842	5243	165	78822	78830	78831

One in a box, with screws.


Specify number and finish. See pages 1 and 2.



282

Somerset Design

CAST BRASS OR BRONZE



80768




80722 x 80730



80713



80784



80790



80722 x 80731



80722 x 80703



80761



80749



80770



80740



80798

No.	Size Inches	Description	No.	Size Inches	Description
80703	2	Knob Rose	80768	7 1/4 x 4	Door Knocker
80713	4 7/8 x 2	Cylinder Collar	*80770	8 1/2 x 2 3/8	Letter Box Plate
80722	2	Door Knob Simplex	*80771	8 1/2 x 2 3/8	Letter Box Plate and Border
80730	9 1/2 x 2 3/4	Escutcheon	80784	10 x 2	Entrance Door Handle (See Page 136)
80731	8 x 2 1/2	Escutcheon	80790	12 x 3	Push Plate
80740	2 x 1	Key Escutcheon	80798	20	Hinge Plate 4 in. Butt Stock
80749	2 x 1	Thumb Knob	80798	30	Hinge Plate 4 in. Butt Stock
80761	3 x 1	Electric Push Button			

Packed with screws.

Locksets

Door	Set No.	Lock		Knobs	Escutcheons	
		No.	See Page		Outside	Inside
Inside	807-158 807-842	685	174	80722 80722	80731	80731
Front		5243	165		80730	80731

One in a box, with screws. *With opening 4 1/2 x 1 in. †Sectional Handle Lockset 807-880. See page 136.


Specify number and finish. See pages 1 and 2.




Canterbury Design

283


CAST BRASS OR BRONZE



86290



86222x86229



86222x86231



86286

No.	Size Inches	Description
86222	2 1/4	Door Knob PY Type
86229	12 1/2 x 3 1/4	Escutcheon
86231	9 1/4 x 2 3/4	Escutcheon
86280	18 x 3 3/4	Store Door Handle (See Page 140)
86286	18 x 3 3/4	Door Pull (Grip 4455)
86290	18 x 3 3/4	Push Plate

Packed with screws.

Locksets

Door	Set No.	Lock		Knobs	Escutcheons	
		No.	See Page		Outside	Inside
Inside	862158	685	174	86222	86231	86231
Vestibule	862742	7331	162	86222	86229	86231
Front	862-842	5243	165	86222	86229	86231

One in a box with screws.

Specify number and finish. See pages 1 and 2.




284

Titan Design

CAST BRASS, BRONZE
OR ALUMINUM


76790



76722 x 76703



76713



76722 x 76730

For 900 Series Unit Locksets
to match. See 904 Design on
Page 217.



76786

No.	Size Inches	Description
76703	2 1/4	Knob Rose—Concealed Screw Type—For PY Knobs.
76706	2 1/4	Knob Rose same as No. 76703 but for Knobs with TS Type Screwless Shanks.
76713	2 1/4	Cylinder Collar.
76722	2 1/4	Door Knob—PY Shanks—Projection 2 3/8 in. Can be finished with TS Type Shanks when so ordered.
76730	8 x 2 1/2	Escutcheon.
76786	14 x 3	Door Pull (Grip 4334)
76790	14 x 3	Push Plate.

Packed with screws.

Locksets

Door	Set No.	Lock		Knobs	Escutcheons	
		No.	See Page		Outside	Inside
Inside	767-158	685	174	76722	76730	76730
Bathroom	767-438	359	178	76722	76730	76730
Communicating	767-464	159 3/4	178	76722	76730	76730
Office	767-522	7551	162	76722	76730	76730
Vestibule	767-742	7331	162	76722	76730	76730
Front	767-842	5243	165	76722	76730	76730

One in a box, with screws.

Specify number and finish. See pages 1 and 2.




Canterbury Design

CAST BRASS OR BRONZE


283



86290



86222x86229



86222x86231



86286

No.	Size Inches	Description
86222	2 1/4	Door Knob PY Type
86229	12 1/2 x 3 1/4	Escutcheon
86231	9 1/4 x 2 3/4	Escutcheon
86280	18 x 3 3/4	Store Door Handle (See Page 140)
86286	18 x 3 3/4	Door Pull (Grip 4455)
86290	18 x 3 3/4	Push Plate

Packed with screws.

Locksets

Door	Set No.	Lock		Knobs	Escutcheons	
		No.	See Page		Outside	Inside
Inside	862-158	685	174	86222	86231	86231
Vestibule	862-742	7331	162	86222	86229	86231
Front	862-842	5243	165	86222	86229	86231

One in a box with screws.

Specify number and finish. See pages 1 and 2.



Warden Design

COLONIUM METAL, HAMMERED

285




*54184




54161



54122 x 54131



54168



54198

No.	Size Inches	Description
54113	4 $\frac{1}{8}$ x 2 $\frac{3}{8}$	Cylinder Collar
54122	2	Door Knob PY Type
54131	6 $\frac{1}{2}$ x 2	Escutcheon
54161	4 $\frac{1}{8}$ x 2 $\frac{3}{8}$	Electric Push Button
54168	7 x 3	Door Knocker
54184	11 $\frac{3}{4}$ x 2 $\frac{1}{2}$	Entrance Door Handle (See Page 137)
54198	18	Hinge Plate 4 in. Butt Stock
54198	24	Hinge Plate 4 in. Butt Stock

Packed with screws.

Lockset

Door	Set No.	Lock		Knobs	Escutcheons	
		No.	Sec Page		Outside	Inside
Inside	541-158	685	174	54122	54131	54131

One in a box, with screws. *Sectional Handle Lockset 541-880. See page 137.

Specify number and finish. See pages 1 and 2.





CABINET LOCKS PADLOCKS KEYS

CHEST LOCKS

DRAWER LOCKS

CUPBOARD LOCKS

SLIDING DOOR LOCKS

WARDROBE LOCKS



PADLOCKS

SUITCASE LOCKS

FRICTION CATCHES

MISCELLANEOUS
CABINET HARDWARE

KEY BLANKS





Cabinet Locks, Padlocks, Keys

Corbin Lock Company of Canada Limited

BELLEVILLE, ONTARIO

CANADA

General Information

289

The catalog illustrates those items which comprise our regular stock merchandise, however, many items shown can be furnished with special features, such as keying, finish or new application.

We cannot show in this catalog all the items we manufacture on special order. If you do not find illustrated, the lock or hardware item suitable for your requirements, please write to us, giving all pertinent information necessary for us to determine your exact needs. In the development of a product on which you expect to use a special locking arrangement, etc., it is best to contact us while in the early stages of development. Our engineers can at that time perhaps suggest an item already being produced, thereby saving you time and expense for the production of an entirely new device. Our sales engineers are especially trained to work with you in developing special locking devices. They will contact you promptly upon request.

Send your locking problem to Corbin Lock Company of Canada, Ltd.

Sales Policies

In order to give our customers the best product with efficient service at a desirable price, we wish to outline the following policies which are in force for the purpose of bringing about a mutually fair and satisfactory business relationship.

ORDERS. We reserve the right to decline the whole or part of orders in which the price or quantity of goods is not satisfactory to us. Orders will be filled to the extent of our stock on hand, and any balance forwarded as soon as possible.

SHIPMENTS. Shipments are F.O.B. Factory. All goods are at the risk of the purchaser after delivery to the transportation medium. Deliveries are contingent upon transportation and manufacturing conditions beyond our control.

The weights given in our catalog are supplied as a guide in estimating transportation and tariff charges. They include the weight of cartons and any wrapping material used therein but do not include the weight of wooden cases or of packing material. They are subject to the ordinary variations in manufacture and the changes that may be made in methods of manufacture.

CANCELLATION. Bona fide orders for our regular stock goods accepted by us for immediate shipment may be cancelled prior to shipment only.

Orders for our regular stock goods for deferred shipment or goods manufactured to other than stock specifications are not subject to cancellation.

RETURNED GOODS. We make every effort to manufacture perfect merchandise to conform to either our stock or to our customers' special specifications. Having shipped these goods, they become the property of the purchaser.

We desire to have any defects or errors for which we are responsible, called to our attention for rectification. **Returned goods of any description will not be accepted unless authorized by us.**

If returned goods are not found, after rigid reinspection, to contain a defect in material or workmanship, or any deviation from the customer's specification, we are not responsible. Expenses incurred in inspecting, checking, handling, repapering and re-packing, will cause the resulting allowance to be unsatisfactory to our customer.

No.	Article	Page	No.	Article	Page
75	Strike	312	359½	Key Blank	338
09	Name Plate	328	0370B	Cupboard Lock	307
010	" "	328	0370½B	" "	307
105	Strike	312	581X	Locker Lock	310
011	Name Plate	328	582X	" "	311
11S	Strike	312	585	Drawer Lock	304
011¼	Cut Key	338	0585	" "	304
012	Name Plate	328	590	" "	302
018	" "	328	0590	" "	302
020	" "	328	590¾	" "	304
26S	Strike	312	0590¾	" "	304
26½S	"	312	592½	" "	302
34	Chest Lock	297	0592½	" "	302
41S	Strike	312	0601	" "	303
046	Desk Lock	298	625	" "	305
47¾C	" "	298	0666	" "	300
49S	Strike	312	0666½	" "	300
49½S	"	312	0676	" "	303
50	Cabinet Lock Board	296	699	" "	303
52S	Strike	312	0699	" "	303
53¼	Key Blank	337	701B	Wardrobe Lock	310
54	" "	337	702B	" "	310
57	" "	337	704L	" "	310
63¼	" "	337	0737	" "	308
64	" "	337	0738	Drawer Lock	301
67	" "	337	749	Wardrobe Lock	309
70	Padlock Board	296	0749	" "	309
73¼	Key Blank	337	750	" "	309
74	" "	337	0750	" "	309
77	" "	337	0751	" "	309
80	Chest Lock	297	755	" "	308
80⅞	Key Blank	338	0755	" "	308
P95	Padlock	324	803	Drawer Lock	305
P95¼	"	324	878	"	305
P95C	"	324	900	Padlock	320
P95¼C	"	324	900C	"	320
P95E	"	323	0900	"	320
P95¼E	"	323	0900C	"	320
P95H	"	323	902	"	320
P95¼H	"	323	902C	"	320
P95L	"	323	0902	"	320
P95¼L	"	323	0902C	"	320
96¼	Key Blank	338	904	"	320
0140	Chest Lock	297	904C	"	320
0142P	" "	297	904¼	"	320
0168	Desk Lock	298	904¼C	"	320
179¼	Key Blank	338	0904	"	320
179¾	" "	338	0904C	"	320
L215A	Adapta Lock	299	0904¼	"	320
L215B	" "	299	0904¼C	"	320
L215C	" "	299	904H	"	323
306	Key Blank	338	904W	"	323

General Information

289

The catalog illustrates those items which comprise our regular stock merchandise, however, many items shown can be furnished with special features, such as keying, finish or new application.

We cannot show in this catalog all the items we manufacture on special order. If you do not find illustrated, the lock or hardware item suitable for your requirements, please write to us, giving all pertinent information necessary for us to determine your exact needs. In the development of a product on which you expect to use a special locking arrangement, etc., it is best to contact us while in the early stages of development. Our engineers can at that time perhaps suggest an item already being produced, thereby saving you time and expense for the production of an entirely new device. Our sales engineers are especially trained to work with you in developing special locking devices. They will contact you promptly upon request.

Send your locking problem to Corbin Lock Company of Canada, Ltd.

Sales Policies

In order to give our customers the best product with efficient service at a desirable price, we wish to outline the following policies which are in force for the purpose of bringing about a mutually fair and satisfactory business relationship.

ORDERS. We reserve the right to decline the whole or part of orders in which the price or quantity of goods is not satisfactory to us. Orders will be filled to the extent of our stock on hand, and any balance forwarded as soon as possible.

SHIPMENTS. Shipments are F.O.B. Factory. All goods are at the risk of the purchaser after delivery to the transportation medium. Deliveries are contingent upon transportation and manufacturing conditions beyond our control.

The weights given in our catalog are supplied as a guide in estimating transportation and tariff charges. They include the weight of cartons and any wrapping material used therein but do not include the weight of wooden cases or of packing material. They are subject to the ordinary variations in manufacture and the changes that may be made in methods of manufacture.

CANCELLATION. Bona fide orders for our regular stock goods accepted by us for immediate shipment may be cancelled prior to shipment only.

Orders for our regular stock goods for deferred shipment or goods manufactured to other than stock specifications are not subject to cancellation.

RETURNED GOODS. We make every effort to manufacture perfect merchandise to conform to either our stock or to our customers' special specifications. Having shipped these goods, they become the property of the purchaser.

We desire to have any defects or errors for which we are responsible, called to our attention for rectification. **Returned goods of any description will not be accepted unless authorized by us.**


If returned goods are not found, after rigid reinspection, to contain a defect in material or workmanship, or any deviation from the customer's specification, we are not responsible. Expenses incurred in inspecting, checking, handling, repapering and re-packing, will cause the resulting allowance to be unsatisfactory to our customer.

No.	Article	Page	No.	Article	Page
904X	Padlock	323	02114	Box Hinge	333
906	"	321	02285	Sliding Door Lock	306
906C	"	321	02290S	Strike	312
906 $\frac{1}{4}$	"	321	02291	Sliding Door Lock	306
906 $\frac{1}{4}$ C	"	321	2575	Strike	336
0906	"	321	2578	"	336
0906C	"	321	2614	Escutcheon	312
0906 $\frac{1}{4}$	"	321	2652	"	312
0906 $\frac{1}{4}$ C	"	321	2879	Padlock	317
906H	"	323	2879A	"	317
908	"	321	2879AC	"	317
908C	"	321	2879C	"	317
908 $\frac{1}{4}$	"	321	2880	"	317
908 $\frac{1}{4}$ C	"	321	2880A	"	317
0908	"	321	2880AC	"	317
0908C	"	321	2880C	"	317
0908 $\frac{1}{4}$	"	321	2880 $\frac{1}{4}$	"	317
0908 $\frac{1}{4}$ C	"	321	2880 $\frac{1}{4}$ A	"	317
1751	Stay Hinge	331	2880 $\frac{1}{4}$ AC	"	317
1771 $\frac{1}{2}$	Suit Case Catch	335	2880 $\frac{1}{4}$ C	"	317
1771 $\frac{3}{4}$	" " "	335	2880AH	"	322
1778 $\frac{1}{2}$	" " "	335	2881	"	317
1778 $\frac{3}{4}$	" " "	335	2881A	"	317
1809 $\frac{1}{2}$	" " "	335	2881AC	"	317
1809 $\frac{3}{4}$	" " "	335	2881C	"	317
1835	General Utility Lock Box	312	2881 $\frac{1}{4}$	"	317
1893 $\frac{1}{4}$ H	Card Holder	329	2881 $\frac{1}{4}$ A	"	317
1894 $\frac{1}{4}$ H	" "	329	2881 $\frac{1}{4}$ AC	"	317
1902 $\frac{1}{4}$	" "	330	2881 $\frac{1}{4}$ C	"	317
1903 $\frac{1}{4}$ H	" "	330	2881AH	"	322
1906 $\frac{1}{4}$ H	" "	330	2881AW	"	322
1909 $\frac{1}{4}$	Box Pull	331	2881AX	"	322
1911 $\frac{1}{4}$ H	Card Holder	329	2882	"	318
1912 $\frac{1}{4}$ H	" "	329	2882A	"	318
1913A	" "	329	2882AC	"	318
1913 $\frac{1}{4}$ H	" "	329	2882C	"	318
1914 $\frac{1}{4}$ H	" "	329	2882 $\frac{1}{4}$	"	318
1919 $\frac{1}{4}$	Box Pull	331	2882 $\frac{1}{4}$ A	"	318
1925A	Card Holder	330	2882 $\frac{1}{4}$ AC	"	318
1925 $\frac{1}{4}$ H	" "	330	2882 $\frac{1}{4}$ C	"	318
1929 $\frac{1}{4}$	Box Pull	331	2882AH	"	322
1932 $\frac{1}{4}$ H	Card Holder	328	2883	"	318
1935A	" "	328	2883A	"	318
1935 $\frac{1}{4}$ H	" "	328	2883AC	"	318
02065	Drawer Lock	301	2883C	"	318
02065 $\frac{1}{2}$	" "	302	2883 $\frac{1}{4}$	"	318
02066	" "	301	2883 $\frac{1}{4}$ A	"	318
02067	Wardrobe Lock	308	2883 $\frac{1}{4}$ AC	"	318
02109	Box Hinge	333	2883 $\frac{1}{4}$ C	"	318
02111	" "	333	2883AH	"	322
02112	" "	333	2885A	"	319
2114	" "	333	2885AC	"	319

No.	Article	Page	No.	Article	Page
2885¼A	Padlock	319	4145½C	Key Blank	341
2885¼AC	"	319	4151	" "	341
2886A	"	319	4152	" "	341
2886AC	"	319	4163½	" "	339
2886¼A	"	319	4179	" "	339
2886¼AC	"	319	4197¼AC	" "	339
2951G	"	326	4202	" "	342
2951GC		326	4359K	" "	342
03002	Hinge Hasp	332	4409K	" "	342
3004	" "	332	4491	" "	342
03004	" "	332	4740	" "	341
3005	" "	332	4773	" "	341
03005	" "	332	4780	" "	342
3032	Safety Hinge Hasp	332	4784	" "	342
03032	" " "	332	5558	" "	339
03234	Friction Catch	336	5862	" "	339
3236	" "	336	6031	" "	341
3237	" "	336	8618C	" "	339
3238	" "	336	8632C	" "	339
3239	" "	336	8658BPM	" "	339
03700	Case Corner	334	8658BP5	" "	339
03703	" "	334	8658BV	" "	339
03715	" "	334	8687C	" "	339
4103B	Key Blank	340	9101A	Key Machine	343
4106	" "	340	9913X	Padlock	324
4116B	" "	340	9913¼X	"	324
4120B	" "	340	9913XC	"	324
4120T	" "	340	9913¼XC	"	324
4122½	" "	340	9913XH	"	325
4122½B	" "	340	9913XK	"	325
4127B	" "	340	9913XP	"	325
4127½B	" "	340	9913XR	"	325
4128B	" "	340	9914X	"	324
4130B	" "	340	9914¼X	"	324
4131A	" "	341	9914XC	"	324
4131B	" "	341	9914¼XC	"	324
4132A	" "	340	9954	"	326
4140T	" "	341	15630	Flush Panel Board Lock and Catch Combined	311
4141B	" "	341			
4144B	" "	341			
4145½B	" "	340	15631	Flush Panel Board Catch	311

Cabinet Locks


Pin Tumbler



Until proper key is inserted, plug is locked in shell by pins and cannot be rotated.




Proper key lines up pins evenly at top of plug and plug can now be rotated.




A turn of the key rotates the plug which in turn operates the lock mechanism.

Corbin Pin Tumbler Cylinders are still, after many years, the finest locking device known for doors, drawers, etc. requiring security in a high degree plus smooth, easy operation. The number of keys changes available and the precision with which they are manufactured makes them essential to the best installations.

Pin Tumbler – Master-keyed




The service key aligns pins at the surface of the plug permitting rotation of the plug and operation of the locking mechanism.




The master-key aligns pins at the outside surface of the master-ring permitting rotation of the plug and operation of the locking mechanism.

The Corbin method of master-keying cylinder locks by means of a master-ring is an exclusive Corbin feature giving far greater security and greater diversity in master-key systems. The master-ring which encircles the plug contains a complete set of pins for the master-key.

Disc Tumbler



Until proper key is inserted plug is locked in shell by projecting discs and cannot be rotated.




Proper keys retracts discs into plug and plug can now be rotated to operate lock.


Corbin disc cylinders offer a limited number of key changes for installations where cost does not permit the use of pin tumbler cylinders. They are remarkably free from the imperfections frequently found in locks of this type.

Types of Locking Mechanisms

Lever Locks




Until proper key is inserted, levers are not aligned preventing retraction of bolt.



Proper key places levers in alignment permitting bolt to be retracted by turn of key.

Lever locks are made in varying grades and degrees of security, the number of key changes depending on the number of levers used. Corbin lever locks are made for applications of all kinds and can be master-keyed in most cases.

Warded Locks




In warded locks the key is cut to correspond with one or more wards which project from the sides of the lock case. Locks of this type are suitable where a high degree of security is not essential.

Hand of Locks

When ordering locks which are available for either right hand or left hand doors, it is necessary to specify the hand required. Otherwise right hand locks will be furnished.




The above illustration shows a right hand door and a right hand lock is shown below. (Swings to the right.)



Above is a left hand door and a left hand lock is shown below. (Swings to the left.)



Right Hand Lock



Left Hand Lock

Keying Information

295

CABINET LOCKS KEYED ALIKE WITHOUT EXTRA CHARGE

FLAT KEYED LEVER AND DISC TUMBLER CABINET LOCKS

Drawer			Wardrobe		Sliding Door
0585	0592½	699	0749	0751	02285
585	592½	02065	749	0755	
0590	0601	02065½	0750	0750	
590	0676	02066	750	02067	
0590¾	0676				
590¾	0699				

CABINET LOCKS FURNISHED THICKNESS OF WOOD AS LISTED WITHOUT EXTRA CHARGE

FLAT KEYED LEVER TYPE

Drawer		Chest and Desk	Cupboard and Wardrobe	Sliding Door
0590¾	0585	0140 }	0749	02285 ⅞ in.
590¾	585	0142P { ¾ and ⅞ in.	749	
0590	0592½		0750 { ¾ and ⅞ in.	0751
590	592½		750	0755 ⅞ in.
0601	0676	046 ⅞ in.	581x { ¼ and ¾ in.	0750
	*0699		582x {	
	*699			

*Also furnished ½ in. wood.

DISC TUMBLER CABINET LOCKS

02065 { ¾ and ⅞ in.	02067 ¾ and ⅞ in.
02066 {	
02065½ ⅞ in.	

PIN TUMBLER CABINET LOCKS

0666 { ¾ and ⅞ in.	0168 ¾ and ⅞ in.	0370 B { ¾ and ⅞ in.	02291 ⅞ in.
0666½ {		0370½B {	
0738 {		0737 {	

CABINET LOCKS INTERKEYED IN SETS TO SPECIAL ORDER

CAN BE KEYED ALIKE, ALIKE IN SETS, ALL DIFFERENT AND MASTER KEYED IN GROUPS AS FOLLOWS:

FLAT KEYED LEVER TYPE

	Drawer	Desk	Cupboard and Wardrobe	Sliding Door
Group 1	0601		0751, 0755, 0750	
Group 2	0590, 590		0749, 749	
Group 3	0592½, 592½		0750, 750	

DISC TUMBLER TYPE

Group 4	02065			
	02066		02067	
	02065½			


PIN TUMBLER TYPE

Group 5	L215A			02291
	L215B	0168	0370B	
	L215C		0370½B	
	0666		0737	
	0666½			
	0738			

CAUTION:—Be sure specifications are complete and include any locks to be ordered later as otherwise the inclusion of additional numbers may be difficult or impossible without rebuilding original locks.

Cabinet Locks

Display Assortments



No. 50

CABINET LOCK BOARD

11¾ x 17¾ in.
Red and Black
Mounted With

Drawer	Cupboard	Wardrobe	Chest
590	02067	701B	34
592½		702B	0142P
0666		749	
699		750	
02066			



No. 70

PADLOCK BOARD

18 x 4½ in.
Royal Blue
Mounted With

900	9913X
904	P95
	9954

Chest Locks

297


Ward Construction - Double Link

NOT SELF LOCKING

No.	Size Inches	Material	Selvage to Key/Pin	Regular Key Changes	Key Blank	Weight Dozen
34	2 1/2 x 1 1/2	Steel	7/8"	6	4780	1 1/16 lbs.

Keys.....1 key to each lock.

Packed.....One half dozen in a box, with screws, 1/2"-3-F.H.



34

Secure Lever - Double Link

SELF LOCKING

No.	Size Inches	Material	Selvage to Key/Pin	Hook Tumblers	Regular Key Changes	Key Blank	Weight Dozen
80	2 3/8 x 1 3/4	Steel	7/8"	4	12	4491	2 3/8 lbs.

Brass.....


Escutcheon, No. 2614.

Keys.....1 double bitted key to each lock.

Packed.....One half dozen in a box with screws, 1/2"-4-F.H.

SPECIAL PRICE INFORMATION

Alike.....Additional charge for quantities of less than 12 dozen.



80

NOT SELF LOCKING

No.	Size Inches	Material	Selvage to Center of Tube	Made Regular for Wood	Also Made for Wood No Extra Charge	Regular Key Changes	Possible Key Changes	Master-keyed Key Changes
0140	1 1/2 x 1 1/4	All Brass	3/4"	3/4"	7/8"	12	620	250
0142P	2 x 1 1/2	All Brass	7/8"	3/4"	7/8"	12	252	60

Tube.....Nos. 0140-0142P, 1 1/2 inches in diameter.

Levers.....3.

Keys.....2 flat steel nickel plated keys to each lock.

Key Blank...No. 0140, 4103B. No. 0142P, 4106.

Packed.....One dozen in a box, with screws, 1/2"-3-F.H.

Weight Doz. No. 0140 1 lb.
No. 0142P 1 1/2 lbs.


SPECIAL PRICE INFORMATION

Wood.....Additional charge for thicknesses of wood, not listed above, for quantities less than 12 dozen.

Alike.....Additional charge for quantities of less than 12 dozen.

All Different..More than regular key changes at an extra charge.

Masterkeyed..Extra charge.



0142P

Desk Locks

Secure Lever

HOOK BOLT — NOT SELF LOCKING

No.	Size Inches	Material	Selvage to Center of Tube	Made Regular for Wood	Levers	Regular Key Changes	Possible Key Changes	Master-keyed Key Changes
046	2 x 1 3/4	All Brass	7/8"	7/8"	2	12	2500	252

Tube..... 1/2 inch in diameter.
Bolt..... 1/4 inch throw, retracts when unlocked.
Selvage..... 2 x 7/16 inches.
Strike..... Brass, No. 11S, regularly furnished.
Keys..... 2 flat steel nickel plated keys to each lock.
Key Blank..... 4151.
Packed..... One dozen in a box, with screws, 3/4"-4 F.H.
Weight..... (Dozen) 2 lbs.

SPECIAL PRICE INFORMATION

Wood..... Additional charge for thicknesses of wood, not listed above, for quantities less than 12 dozen.
Alike..... Additional charge for quantities of less than 12 dozen.
All Different..... More than regular key changes at an extra charge.
Masterkeyed..... Extra charge.

FULL MORTISE — HOOK BOLT — SELF LOCKING For Rolling Top Desks

No.	Size Inches	Material	Selvage to Center of Key hole	Levers	Regular Key Changes	Key Blank
47 3/4 C	3 x 1 1/2	Steel, Brass Selvage	1"	4	12	4204

Bolt..... Does not draw back into case.
Selvage..... 3 x 19/32 inches.
Strike..... Brass, No. 41S, regularly furnished, 3/4"-5 F.H. screws.
Brass Escutcheon..... 2652 plain buffed. 3/4"-2 R.H. screws.
Keys..... 2 steel nickel plated keys to each lock.

Packed..... One dozen in a box with screws, 3/4"-5 F.H.
Weight..... (Dozen) 3 3/4 lbs.

SPECIAL PRICE INFORMATION

Alike..... Additional charge for quantities of less than 12 dozen.

Pin Tumbler Cylinder

HOOK BOLT — NOT SELF LOCKING


No.	Size Inches	Material	Selvage to Center of Cylinder	Made Regular for Wood	Also Made for Wood No Extra Charge	Key Changes	Key Blanks	Weight Dozen
0168	2x1 1/2	All Brass	3/4"	7/8"	3/4"	3/4" wood 1200 7/8" wood and over 4000	3/4" wood No. 8632C 7/8" wood and over No. 8618C	2 3/4 lbs.

Cylinder..... 3/4 inch in diameter.
Bolt..... 1/4 inch throw, retracts when unlocked.
Selvage..... 2 x 3/8 inches.
Strike..... Brass, No. 7S, regularly furnished.
Keys..... 2 nickel silver keys to each lock. 1 key each when locks are alike.
Packed..... One lock in a box, with screws. 3/4"-4 F.H.




INTER-KEYING See Page 295

SPECIAL PRICE INFORMATION


Wood..... Additional charge for thicknesses of wood, not listed above, for quantities less than 12 dozen.
Alike..... Additional charge for quantities of less than 12 doz.
All Different..... No extra charge.
Masterkeyed..... Extra charge.



046



47 3/4 C




0168



Adapta-Lock

299

9 WAY — LOCK ENSEMBLE
MEETS 95% OF THE DEMAND FOR CABINET AND DRAWER LOCKS




215
(Lock only)




Selvage to
Center of
Cylinder 1 in.



Selvage to
Center of
Cylinder
 $\frac{7}{8}$ in.



Selvage
to center of
cylinder 1 in.



L215A

DNE LDCK can be used in three different positions.

THREE INTERCHANGEABLE CYLINDERS—easily adjustable to varying thicknesses of wood.

EASILY ADAPTABLE TO:


54 major applications.

6 different thicknesses of wood $\frac{3}{4}$ " to $1\frac{3}{4}$ ", in $\frac{1}{8}$ in. steps.


Right or left hand cabinet doors or drawers simply by releasing a slide and rotating cylinder.

Locks or cylinders can be ordered separately.

Locks furnished with cylinder adjusting tool.



215A
Adjustable for
wood $\frac{3}{4}$ · $\frac{7}{8}$ · 1 in.



215B
Adjustable for
wood $\frac{7}{8}$ · 1 · $1\frac{1}{8}$ in.



215C
Adjustable for
wood $1\frac{1}{8}$ · $1\frac{1}{4}$ · $1\frac{3}{8}$ in.

Complete Lock with Cylinder No.	Material	Lock only		Cylinder		Adjustable for thickness of wood inches	Changes		Key Blank	Weight Dozen
		No.	Size Inches	No.	Pins		Regular	Master- Keyed		
L215A	All Brass	215	2x1 $\frac{3}{8}$	215A	4	$\frac{3}{4}$ · $\frac{7}{8}$ · 1	2500	500	8632C	4 $\frac{1}{4}$ lbs.
L215B	All Brass	215	2x1 $\frac{1}{2}$	215B	5	$\frac{7}{8}$ · 1 · $1\frac{1}{8}$	13500	2500	8618C	4 $\frac{5}{8}$ lbs.
L215C	All Brass	215	2x1 $\frac{3}{4}$	215C	5	$1\frac{1}{8}$ · $1\frac{1}{4}$ · $1\frac{3}{8}$	13500	2500	8618C	5 lbs.

Cylinder.....1 inch in diameter.

Dead Bolt.... $\frac{7}{16}$ inch throw, $\frac{7}{8}$ x $\frac{3}{16}$ inches.

Selvage.....2 x $1\frac{1}{2}$ inches.

Strike.....Brass No. 7S if so ordered at an additional price.

Keys.....2 nickel silver keys to each lock. 1 key each when locks are alike.

Packed.....Nos. L215A and L215B six to a box, L215C 3 to a box with screws $\frac{5}{8}$ " · 4-F.H.

INTER-KEYING

See Page 295

SPECIAL PRICE INFORMATION

Alike.....Additional charge for quantities of less than 12 dozen.


All Different..No extra charge.

Masterkeyed..Extra charge.

1 adjusting tool

Drawer Locks

Pin Tumbler Cylinder




0666

No.	Size Inches	Material	Selvage to Center of Cylinder	Made Regular for Wood	Also Made for Wood No Extra Charge	Key Changes	Key Blanks	Weight Dozen
0666	2 x 1 5/8	All Brass	7/8"	7/8"	3/4"	3/4" wood 1200 7/8" wood and over 4000	3/4" wood No. 8632C 7/8" wood and over No. 8618C	3 lbs.

Cylinder 7/8 inch in diameter.
 Dead Bolt 5/16 in. throw, 7/8 x 7/32 ins.
 Selvage 2 x 13/32 inches.
 Strike Brass, No. 7S, if so ordered at an additional price.
 Keys 2 nickel silver keys to each lock. 1 key each when locks are alike.
 Packed One lock in a box, with screws, 5/8"-4-F.H.

INTER-KEYING
 See Page 295

SPECIAL PRICE INFORMATION
Wood Additional charge for thicknesses of wood, not listed above, for quantities less than 12 dozen.
Alike Additional charge for quantities of less than 12 dozen.
All Different No extra charge.
Masterkeyed Extra charge.



0666 1/2

No.	Size Inches	Material	Selvage to Center of Cylinder	Made Regular for Wood	Also Made for Wood No Extra Charge	Key Changes	Key Blanks	Weight Dozen
0666 1/2	2 x 1 5/8	All Brass	7/8"	7/8"	3/4"	3/4" wood 1200 7/8" wood and over 4000	3/4" wood No. 8632C 7/8" wood and over No. 8618C	3 lbs.

Cylinder 7/8 inch in diameter.
 Latch Bolt 7/32 inch throw.
 Selvage 2 x 13/32 inches.
 Strike Brass, No. 26 1/2 S, regularly furnished.
 Keys 2 nickel silver keys to each lock. 1 key each when locks are alike.
 Packed One lock in a box, with screws, 5/8"-4-F.H.


INTER-KEYING
 See Page 295

SPECIAL PRICE INFORMATION
Wood Additional charge for thicknesses of wood, not listed above, for quantities less than 12 dozen.
Alike Additional charge for quantities of less than 12 dozen.
All Different No extra charge.
Masterkeyed Extra charge.

Drawer Locks

Pin Tumbler Cylinder

No.	Size Inches	Material	Selvage to Center of Cylinder	Made Regular for Wood	Also Made for Wood No Extra Charge	Key Changes	Key Blanks	Weight Dozen
0738	1 5/8 x 1 1/4	All Brass	5/8"	7/8"	3/4"	3/4" wood and over 4000	5/8" wood No. 8632C 3/4" wood and over No. 8618C	3 1/2 lbs.



0738

Cylinder..... 5/8 inch in diameter.
Dead Bolt..... 3/4 inch throw, 5/8 x 7/32 inches.
Bolt shoots up or down.
Strike..... Brass, No. 52S, if so ordered at an additional price.
Keys..... 2 nickel silver keys to each lock. 1 key each when locks are alike.
Packed..... One lock in a box with screws, 1" x 5-R.H.


INTER-KEYING
See Page 295

SPECIAL PRICE INFORMATION

Wood..... Additional charge for thicknesses of wood, not listed above, for quantities less than 12 dozen.
Alike..... Additional charge for quantities of less than 12 dozen.
All Different... No extra charge.
Masterkeyed... Extra charge.

Disc Tumbler

No.	Size Inches	Material	Selvage to Center of Cylinder	Made Regular for Wood	Regular Key Changes	Possible Key Changes	Master-keyed Key Changes
02065	2 1/4 x 1 1/4	Back Plate Brass	3/4"	7/8"	200	200	200



02065

Cylinder
Brass Plated Die Cast, 3/8 inch in diameter.
Dead Bolt..... 23/64 inch throw, 5/8 x 3/16 ins.
Selvage..... 2-1/64 x 3/8 inch.
Disc Tumblers. 6.
Keys..... 2 brass nickel plated keys to each lock. 1 key each when locks are alike.
Key Blank..... 8658BV. Regular stock goods.
Packed..... One ~~half~~ dozen in a box, with screws, 3/4" x 5-F.H.
Weight..... (Dozen) 2 7/8 lbs.

INTER-KEYING
See Page 295


SPECIAL PRICE INFORMATION

Wood..... 3/4-1-1/8. Extra charge.
Alike..... No extra charge.
Masterkeyed... Extra charge.

KEY BLANKS FOR MASTERKEYED LOCKS

Service Key... No. 8658BPS.
Masterkey..... No. 8658BPM.

No.	Size Inches	Material	Selvage to Center of Cylinder	Made Regular for Wood	Also Made for Wood No Extra Charge	Regular Key Changes	Master-Keyed Key Changes
02066	2 x 1 1/4	Back Plate Steel, Brass Plated	3/4"	7/8"	3/4"	200	200



02066

Cylinder
Brass Plated Die Cast, 3/8 inch in diameter.
Dead Bolt..... 11/32 inch throw, 5/8 x 3/16 ins.
Disc Tumblers. 6.
Keys..... 2 brass nickel plated keys for each lock. 1 key each when locks are alike.
Key Blank..... 8658BV. Regular stock goods.
Packed..... One ~~half~~ dozen in a box with screws, 3/4" x 5-F.H.
Weight..... (Dozen) 3 1/8 lbs.

INTER-KEYING
See Page 295


SPECIAL PRICE INFORMATION

Wood..... 1 1/8 in. thickness of wood furnished at additional charge in quantities of less than 12 doz.
Alike..... No extra charge.
Masterkeyed... Extra charge.

KEY BLANKS FOR MASTERKEYED LOCKS

Service Key... No. 8658BPS.
Masterkey..... No. 8658BPM.

Drawer Locks Disc Tumbler



02065 1/2

No.	Size Inches	Material	Selvage to Center of Cylinder	Made Regular for Wood	Regular Key Changes	Possible Key Changes	Master-keyed Key Changes
02065 1/2	2 1/16 x 1 1/16	Back Plate Brass	3/4"	7/8"	200	200	200


Cylinder.....Brass Plated Die Cast, 7/8 inch in diameter.
Latch Bolt.....23/64 inch throw.
Selvage.....2-1/64 x 3/8 inch.
Disc Tumblers.....6.
Strike.....Brass No. 26S.
Keys.....2 brass nickel plated keys to each lock. 1 key each when locks are alike.
Key Blank.....8658BV. Regular stock goods.
Packed.....One dozen in a box, with screws, 3/4" 3-F.H.
Weight.....(Dozen) 3 1/4 lbs.

INTER-KEYING
See Page 295

SPECIAL PRICE INFORMATION
Wood.....3/4"—1 1/4". Extra charge.
Alike.....No extra charge.
Masterkeyed...Extra charge.

KEY BLANKS FOR MASTERKEYED LOCKS
Service Key...No. 8658BPS.
Masterkey....No. 8658BPM.

Secure Lever




0592 1/2

No.	Size Inches	Material	Selvage to Center of Tube	Made Regular for Wood	Levers	Regular Key Changes	Possible Key Changes	Master-keyed Key Changes
592 1/2	2 x 1 5/8	Steel, Brass Tube	7/8"	7/8"	2	12	620	620
0592 1/2	2 x 1 5/8	All Brass	7/8"	7/8"	2	12	620	620

Tube.....5/8 inch in diameter.
Dead Bolt.....1/4 inch throw, 7/8 x 3/32 inches.
Selvage.....2 x 15/32 inches.
Keys.....2 flat steel nickel plated keys to each lock.
Key Blank.....4120B.
Packed.....One dozen in a box, with screws, 3/4" 3-F.H.
Weight.....(Dozen) 2 lbs.

INTER-KEYING
See Page 295

SPECIAL PRICE INFORMATION
Wood.....Additional charge for thicknesses of wood, not listed above, for quantities less than 12 dozen.
Alike.....No extra charge.
All Different...More than regular key changes at an extra charge.
Masterkeyed...Extra charge.



0590

No.	Size Inches	Material	Selvage to Center of Tube	Made Regular for Wood	Also made for Wood No extra Charge	Levers	Regular Key Changes	Possible Key Changes	Master-keyed Key Changes
590	1 3/4 x 1 1/2	Steel, Brass Tube	3/4"	7/8"	3/4"	2	12	1290	210
0590	1 3/4 x 1 1/2	All Brass	3/4"	7/8"	3/4"	2	12	1290	210

Tube.....17/32 inch in diameter.
Dead Bolt.....1/4 in. throw, 11/16 x 1/8 inch.
Selvage.....1 3/4 x 3/8 inches.
Keys.....2 flat steel nickel plated keys to each lock.
Key Blank.....4141B.
Packed.....One dozen in a box, with screws, 3/4" 3-F.H.
Weight.....(Dozen) 1 1/2 lbs.

INTER-KEYING
See Page 295

SPECIAL PRICE INFORMATION
Wood.....Additional charge for thicknesses of wood not listed above for quantities less than 12 doz.
Alike.....No extra charge.
All Different...More than regular key changes at an extra charge.
Masterkeyed...Extra charge.

Drawer Locks

303

Secure Lever


No.	Size Inches	Material	Selvage to Center of Tube	Made Regular for Wood	Also Made for Wood No Extra Charge	Levers	Regular Key Changes	Possible Key Changes	Master-keyed Key Changes
0601	2 1/4 x 1 3/4	All Brass	7/8"	7/8"	3/4"	3	200	200	200

Tube.....Cut for cupboard and drawer, 19/32 inch in diameter.
Dead Bolt.....9/32 in. throw, 13/16x3/16 ins.
Selvage.....2 1/4 x 7/32 inches.
Strike.....Brass, No. 11S, if so ordered at an additional price.
Keys.....2 flat steel nickel plated keys to each lock.
Key Blank.....4120B.
Packed.....One ~~dozen~~ dozen in a box, with screws, 5/8"-3-F.H.
Weight.....(Dozen), 2 1/2 lbs.

INTER-KEYING
See Page 295

SPECIAL PRICE INFORMATION

Wood.....Additional charge for thicknesses of wood not listed above in quantities of less than 12 dozen.
Alike.....No extra charge.
All Different.....More than regular key changes at an extra charge.
Masterkeyed.....Extra charge.



0601


No.	Size Inches	Material	Selvage to Center of Tube	Made Regular for Wood	Levers	Regular Key Changes	Possible Key Changes	Master-keyed Key Changes
0676	2 1/4 x 1 3/4	All Brass	7/8"	7/8"	3	96	1290	1290

Tube.....9/16 in. in diameter, Cast Brass Cap.
Dead Bolt.....1/4 inch throw, 27/32 x 5/32 ins.
Selvage.....2 x 1/2 inch.
Keys.....2 flat steel nickel plated keys to each lock.
Key Blank.....6031.
Packed.....One ~~dozen~~ dozen in a box with screws, 5/8"-3-F.H.
Weight.....(Dozen) 2 3/4 lbs.

INTER-KEYING
See Page 295

SPECIAL PRICE INFORMATION

Wood.....Furnished 7/8 in. wood only.
Alike.....No extra charge.
All Different.....More than regular key changes at an extra charge.
Masterkeyed.....Extra charge.




0676

No.	Size Inches	Material	Selvage to Center of Tube	Made Regular for Wood	Also Made for Wood No Extra Charge	Regular Key Changes	Possible Key Changes
699	1 5/8 x 1 7/8	Steel, Brass Tube	1 1/8"	7/8"	1/2"	36	492
0699	1 5/8 x 1 7/8	All Brass	1 1/8"	7/8"	1/2"	36	492

Tube.....1/2 inch in diameter.
Dead Bolt.....1/4 inch throw, 5/8 x 1/8 inches.
Levers.....2.
Strike.....No. 49 1/2S regularly furnished for No. 699 Steel, screws 1/2"-3-F.H.
Keys.....No. 49S regularly furnished for No. 0699 Brass, screws 1/2"-3-F.H.
Key Blank.....4151.
Packed.....One ~~dozen~~ dozen in a box, with screws, 5/8"-3-F.H.
Weight.....(Dozen) 2 1/2 lbs.


SPECIAL PRICE INFORMATION

Wood.....Additional charge for thicknesses of wood, not listed above, for quantities less than 12 dozen.
Alike.....No extra charge.
All Different.....More than regular key changes at an extra charge.



0699

Drawer Locks



No. 0590 3/4


No.	Size Inches	Material	Selvedge to Center of Tube	Made Regular for Wood	Also Made for Wood No Extra Charge	Regular Key Changes	Possible Key Changes	Master-keyed Key Changes
590 3/4	1 3/4 x 1 1/2	Steel, Brass Tube	3/4"	7/8"	3/4"	12	1290	210
0590 3/4	1 3/4 x 1 1/2	All Brass	3/4"	7/8"	3/4"	12	1290	210

Tube..... 17/32 inch in diameter.
 Latch Bolt..... 1/4 inch throw.
 Selvedge..... 1 3/4 x 3/8 inches.
 Levers..... 2.
 Strike..... Brass, No 26S, regularly furnished.
 Keys..... 2 flat steel nickel plated keys to each lock.
 Key Blank..... 4740.
 Packed..... One ~~dozen~~ dozen in a box, with screws, 5/16-4 F.H.
 Weight..... (Dozen) 1 3/4 lbs.

INTER-KEYING
See Page 295

SPECIAL PRICE INFORMATION

Wood..... Additional charge for thicknesses of wood, not listed above, for quantities less than 12 dozen.
 Alike..... No extra charge.
 All Different... More than regular key changes at an extra charge.
 Masterkeyed... Extra charge.



0585

No.	Size Inches	Material	Selvedge to Center of Tube	Made Regular for Wood	Regular Key Changes	Possible Key Changes
585	2 1/8 x 2	Steel, Brass Tube	7/8"	7/8"	12	12
0585	2 1/8 x 2	All Brass	7/8"	7/8"	12	12

Tube..... 1/2 inch in diameter.
 Dead Bolt..... 1/4 inch throw, 11/16 x 1/2 inch.
 Selvedge..... 1-3/16 x 3/8 inches.
 Levers..... 2.
 Keys..... 2 flat steel nickel plated keys to each lock.
 Key Blank..... 4141B.
 Packed..... One dozen in a box, with screws, 5/16-3 F.H.
 Weight..... (Dozen) 1 7/8 lbs.

SPECIAL PRICE INFORMATION

Wood..... 7/8 inch only.
 Alike..... No extra charge.

Drawer Locks

305


Secure Lever

No.	Size Inches	Material	Selvage to Center of Tube	Made Regular for Metal	Also Made for Metal No Extra Charge	Levers	Regular Key Changes	Possible Key Changes	Master-keyed Key Changes
878	1½ x 1	Steel	½"	½"	¼", ⅜"	2	12	252	60

Tube.....Brass, 9/16 inch in diameter.
Dead Bolt.....7/32 inch throw, ½ x 3/32 inches.
Keys.....2 flat steel nickel plated keys to each lock. Key can be withdrawn only when locked.
Key Blank.....4116B.
Packed.....One dozen in a box.
Weight.....(Dozen) 1 lb.

SPECIAL PRICE INFORMATION

Metal.....Additional charge for thicknesses of metal, not listed above, for quantities less than 12 dozen.
Alike.....No extra charge.
All Different.....More than regular key changes at an extra charge.
Masterkeyed...Extra charge.




878

Ward Construction

No.	Size Inches	Material	Selvage to Center of Tube	Made Regular for Metal	Regular Key Changes	Key Blank	Weight Dozen
803	1¼ x ⅞	Steel	⅜"	⅜"	1	4179	⅝ lb.

Tube.....Brass, ⅜ inch in diameter.
Dead Bolt.....3/16 inch throw, 5/16 x 3/22 ins.

Keys.....1 flat steel nickel plated key to each lock.
Packed.....Six dozen in a box.




803

No.	Size Inches	Material	Selvage to Key Pin	Regular Key Changes	Key Blank	Weight Dozen
625	2¼ x 1½	Steel	¾"	1	4359K	1¼ lbs.

Dead Bolt.....¼ inch throw, ½ x ¼ inch.
Keys.....1 key to each lock.

Key Hole.....Double cut for cupboard and drawer.
Packed.....One dozen in a box, with screws, ⅜"-3-R.H.




625

Sliding Door Locks

Pin Tumbler Cylinder

PUSH BOLT TYPE



02291

No.	Size Inches	Material	Made Regular for Wood	Also Made for Wood Extra Charge	Key Changes	Key Blank
02291	2 x 1	All Brass	7/8"	1 1/8"	7/8, 1 1/8" wood 4000	8618C

Cylinder.....1 inch in diameter.

Bolt.....7/16 inch throw, diameter, 11/32 inch.

Cup Strike...Brass No. 02290S regularly furnished.

Keys.....2 nickel silver keys to each lock, 1 key each when locks are alike.

Packed.....One half dozen in a box, with screws, 5/8"-5-F.H.

Weight.....(Dozen) 3 3/4 lbs.

Note—To lock, push end of cylinder. To unlock use key.

INTER-KEYING

See Page 295

SPECIAL PRICE INFORMATION


Wood.....No other thicknesses of wood furnished except those listed above.

Alike.....Additional charge for quantities of less than 12 dozen.

All Different.No extra charge.

Masterkeyed.Extra charge.

Ward Construction



02285

No.	Size Inches	Material	Made Regular for Wood	Also Made for Wood Extra Charge	Regular Key Changes	Key Blank	Weight Dozen
02285	2 x 5/8	All Brass, Burnished, Brass Finish	7/8"	1 1/8"	6	4773	1 1/4 lbs.

Tube.....9/16 inch in diameter.

Bolt.....7/16 inch throw, diameter, 11/32 inch.

Cup Strike...Brass, No. 02290S, regularly furnished.

Keys.....2 flat steel nickel plated keys to each lock.

Packed.....One half dozen in a box, with screws, 5/8"-4-F.H.

Note—To lock, push end of cylinder. To unlock, use key.

SPECIAL PRICE INFORMATION

Wood.....No other thicknesses of wood furnished except those listed above.

Alike.....No extra charge.

Cupboard Locks

Pin Tumbler Cylinder


No.	Size Inches	Material	Selvage to Center of Cylinder	Made Regular for Wood	Also Made for Wood No Extra Charge	Key Changes	Key Blanks	Weight Dozen
0370B	2 x 1 $\frac{5}{8}$	All Brass	1"	$\frac{7}{8}$ "	$\frac{3}{4}$ "	$\frac{3}{4}$ " wood 1200 $\frac{7}{8}$ " wood and over 4000	$\frac{3}{4}$ " wood No. 8632C $\frac{7}{8}$ " wood and over No. 8618C	3 lbs.

Cylinder..... $\frac{3}{8}$ inch in diameter.
Dead Bolt..... $\frac{5}{16}$ inch throw, $\frac{7}{8}$ x $\frac{7}{32}$ inches.
Selvage.....2 x $\frac{3}{8}$ inches.
Hand.....Regularly furnished right hand, left when specified.
Strike.....Brass, No. 7S, if so ordered, at an additional price.
Keys.....2 nickel silver keys to each lock, 1 key each when locks are alike.
Packed.....One lock in a box, with screws, $\frac{5}{8}$ "-4-F.H.

INTER-KEYING See Page 295

SPECIAL PRICE INFORMATION

Wood.....Additional charge for thicknesses of wood, not listed above, for quantities less than 12 dozen.
Alike.....Additional charge for quantities of less than 12 dozen.
All Different....No extra charge.
Masterkeyed....Extra charge.



0370B


No.	Size Inches	Material	Selvage to Center of Cylinder	Made Regular for Wood	Also Made for Wood No Extra Charge	Key Changes	Key Blanks	Weight Dozen
0370 $\frac{1}{2}$ B	2x1 $\frac{5}{8}$	All Brass	1"	$\frac{7}{8}$ "	$\frac{3}{4}$ "	$\frac{3}{4}$ " wood 1200 $\frac{7}{8}$ " wood and over 4000	$\frac{3}{4}$ " wood No. 8632C $\frac{7}{8}$ " wood and over No. 8618C	3 lbs.

Cylinder..... $\frac{3}{8}$ inch in diameter.
Latch Bolt.....Cast bronze, $\frac{5}{16}$ in. throw.
Selvage.....2 x $\frac{3}{8}$ inches.
Hand.....Regularly furnished right hand, left when specified.
Strike.....Brass, No. 26 $\frac{1}{2}$ S, regularly furnished.
Keys.....2 nickel silver keys to each lock, 1 key each when locks are alike.
Packed.....One lock in a box, with screws, $\frac{5}{8}$ "-4-F.H.

INTER-KEYING See Page 295

SPECIAL PRICE INFORMATION

Wood.....Additional charge for thicknesses of wood, not listed above, for quantities less than 12 dozen.
Alike.....Additional charge for quantities of less than 12 dozen.
All Different....No extra charge.
Masterkeyed....Extra charge.




0370 $\frac{1}{2}$ B

308

Wardrobe Locks

Pin Tumbler Cylinder



0737

No.	Size Inches	Material	Selvage to Center of Cylinder	Made Regular for Wood	Also Made for Wood No Extra Charge	Key Changes	Key Blanks	Weight Dozen
0737	1 5/8 x 1 1/4	All Brass	5/8"	7/8"	3/4"	3/4" wood and over 4000	3/4" wood and over No. 8618C	3 1/2 lbs.


Cylinder..... 3/4 inch in diameter.
Dead Bolt..... Brass, 3/4 inch throw, 3/4 x 3/16 inches. Shoots right and left for either hand door.
Strike..... Brass, No. 52S, if so ordered, at an additional price.
Keys..... 2 nickel silver keys to each lock. 1 key each when locks are alike.
Packed..... One lock in a box, with screws, 1" x 5-R.H.

INTER-KEYING
See Page 295

SPECIAL PRICE INFORMATION

Wood..... Additional charge for thicknesses of wood, not listed above, for quantities less than 12 dozen.
Alike..... Additional charge for quantities of less than 12 dozen.
All Different... No extra charge.
Masterkeyed... Extra charge.

Disc Tumbler



02067

No.	Size Inches	Material	Selvage to Center of Cylinder	Made Regular for Wood	Also Made for Wood No Extra Charge	Regular Key Changes	Master-Keyed Key Changes
02067	2 x 1 1/4	Back Plate Steel, Brass Plated	3/4"	7/8"	3/4"	200	200

Cylinder..... Brass Plated. Die Cast, 3/4 inch in diameter.
Dead Bolt..... 11/32 inch throw, 5/8 x 3/16 ins.
Disc Tumblers..... 5.
Keys..... 2 brass nickel plated keys for each lock. 1 key each when locks are alike.
Key Blank..... 8658BV, Regular stock goods.
Packed..... One ~~lock~~ dozen in a box, with screws, 3/4" x 5-F.H.
Weight..... (Dozen) 3 1/4 lbs.

SPECIAL PRICE INFORMATION


Wood..... 1 1/2 in. thickness of wood furnished at additional charge for quantities of less than 12 doz.
Alike..... No extra charge.
Masterkeyed... Extra charge

KEY BLANKS FOR MASTERKEYED LOCKS

Service Key.... No. 8658BPS.
Masterkey..... No. 8658BPM.

INTER-KEYING
See Page 295

Secure Lever



0755

No.	Size Inches	Material	Selvage to Center of Tube	Made Regular for Wood	Regular Key Changes	Possible Key Changes	Master-keyed Key Changes
755	2 x 1 5/8	Steel, Brass Tube	3/4"	7/8"	All Different	16800	2394
0755	2 x 1 5/8	All Brass	3/4"	7/8"	All Different	16800	2394

Tube..... 11/16 inch in diameter.
Dead Bolt..... Brass, 3/4 inch throw, 3/4 x 3/16 inches. Shoots right and left for either hand door.
Levers..... 5.
Strike..... Brass, No. 52S, regularly furnished, 3/4" x 4-F.H. screws.
Keys..... 2 flat steel nickel plated keys to each lock.
Key Blank..... 4131A.
Packed..... One-half dozen in a box, with screws, 1" x 6-R.H.
Weight..... (Dozen) 4 3/4 lbs.

INTER-KEYING
See Page 295

SPECIAL PRICE INFORMATION

Wood..... Additional charge for thicknesses of wood not listed above in quantities of less than 12 dozen.
Alike..... No extra charge.
All Different... No extra charge.
Masterkeyed... Extra charge.

Cupboard Locks

307

Pin Tumbler Cylinder

No.	Size Inches	Material	Selvage to Center of Cylinder	Made Regular for Wood	Also Made for Wood No Extra Charge	Key Changes	Key Blanks	Weight Dozen
0370B	2 x 1 $\frac{5}{8}$	All Brass	1"	$\frac{7}{8}$ "	$\frac{3}{4}$ "	$\frac{3}{4}$ " wood 1200 $\frac{7}{8}$ " wood and over 4000	$\frac{3}{4}$ " wood No. 8632C $\frac{7}{8}$ " wood and over No. 8618C	3 lbs.

Cylinder..... $\frac{7}{8}$ inch in diameter.

Dead Bolt..... $\frac{5}{16}$ inch throw, $\frac{7}{8}$ x $\frac{7}{32}$ inches.

Selvage.....2 x $\frac{5}{8}$ inches.

Hand.....Regularly furnished right hand, left when specified.

Strike.....Brass, No. 7S, if so ordered, at an additional price.

Keys.....2 nickel silver keys to each lock. 1 key each when locks are alike.

Packed.....One lock in a box, with screws, $\frac{5}{8}$ "-4 F.H.

INTER-KEYING

See Page 295


SPECIAL PRICE INFORMATION

Wood.....Additional charge for thicknesses of wood, not listed above, for quantities less than 12 dozen.

Alike.....Additional charge for quantities of less than 12 dozen.

All Different....No extra charge.

Masterkeyed....Extra charge.



0370B

No.	Size Inches	Material	Selvage to Center of Cylinder	Made Regular for Wood	Also Made for Wood No Extra Charge	Key Changes	Key Blanks	Weight Dozen
0370 $\frac{1}{2}$ B	2x1 $\frac{5}{8}$	All Brass	1"	$\frac{7}{8}$ "	$\frac{3}{4}$ "	$\frac{3}{4}$ " wood 1200 $\frac{7}{8}$ " wood and over 4000	$\frac{3}{4}$ " wood No. 8632C $\frac{7}{8}$ " wood and over No. 8618C	3 lbs.

Cylinder..... $\frac{7}{8}$ inch in diameter.

Latch Bolt.....Cast bronze, $\frac{5}{16}$ in. throw.

Selvage.....2 x $\frac{5}{8}$ inches.

Hand.....Regularly furnished right hand, left when specified.

Strike.....Brass, No. 26 $\frac{1}{2}$ S, regularly furnished.

Keys.....2 nickel silver keys to each lock. 1 key each when locks are alike.

Packed.....One lock in a box, with screws, $\frac{5}{8}$ "-4 F.H.

INTER-KEYING

See Page 295


SPECIAL PRICE INFORMATION

Wood.....Additional charge for thicknesses of wood, not listed above, for quantities less than 12 dozen.

Alike.....Additional charge for quantities of less than 12 dozen.

All Different....No extra charge.

Masterkeyed....Extra charge.



0370 $\frac{1}{2}$ B

Wardrobe Locks

Secure Lever


No.	Size Inches	Material	Selvage to Center of Tube	Made Regular for Wood	Regular Key Changes	Possible Key Changes	Master-keyed Key Changes
0751	2 $\frac{7}{8}$ x1 $\frac{5}{8}$	All Brass	$\frac{3}{4}$ "	$\frac{7}{8}$ "	12	7770	1290

Tube.....21/32 inch in diameter.
 Dead Bolt.....Brass, $\frac{3}{8}$ inch throw, $\frac{3}{4}$ x $\frac{3}{16}$ inches. Shoots right and left for either hand door.
 Levers.....2.
 Strike.....No. 52S, if so ordered at an additional price.
 Keys.....2 flat steel nickel plated keys to each lock.
 Key Blank.....4131B.
 Packed.....One half dozen in a box, with screws, $\frac{5}{8}$ " 3-F.H.
 Weight.....(Dozen) 3 lbs.

INTER-KEYING
 See Page 295

SPECIAL PRICE INFORMATION

Wood.....Additional charge for thicknesses of wood, not listed above, for quantities less than 12 dozen.
 Alike.....No extra charge.
 All Different.....More than regular key changes at an extra charge.
 Masterkeyed.....Extra charge.



0751


No.	Size Inches	Material	Selvage to Center of Tube	Made Regular for Wood	Also Made for Wood No Extra Charge	Regular Key Changes	Possible Key Changes	Master-keyed Key Changes
750	2 $\frac{3}{4}$ x1 $\frac{1}{4}$	Steel, Brass Tube	$\frac{5}{8}$ "	$\frac{7}{8}$ "	$\frac{3}{4}$ "	12	7770	1290
0750	2 $\frac{3}{4}$ x1 $\frac{1}{4}$	All Brass	$\frac{5}{8}$ "	$\frac{7}{8}$ "	$\frac{3}{4}$ "	12	7770	1290

Tube..... $\frac{5}{8}$ inch in diameter.
 Dead Bolt.....Brass, 5/16 in. throw, 11/16x5/32 inches. Shoots right and left for either hand door.
 Levers.....2.
 Strike.....No. 52S, if so ordered at an additional price.
 Keys.....2 flat steel nickel plated keys to each lock.
 Key Blank.....4127B.
 Packed.....One half dozen in a box, with screws, $\frac{5}{8}$ " 3-F.H.
 Weight.....(Dozen) 2 $\frac{1}{2}$ lbs.

INTER-KEYING
 See Page 295

SPECIAL PRICE INFORMATION

Wood.....Additional charge for thicknesses of wood, not listed above, for quantities less than 12 dozen.
 Alike.....No extra charge.
 All Different.....More than regular key changes at an extra charge.
 Masterkeyed.....Extra charge.



0750


No.	Size Inches	Material	Selvage to Center of Tube	Made Regular for Wood	Also Made for Wood No Extra Charge	Regular Key Changes	Possible Key Changes	Master-keyed Key Changes
749	1 $\frac{7}{8}$ x $\frac{7}{8}$	Steel, Brass Tube	$\frac{1}{16}$ "	$\frac{7}{8}$ "	$\frac{3}{4}$ "	12	1290	210
0749	1 $\frac{7}{8}$ x $\frac{7}{8}$	All Brass	$\frac{1}{16}$ "	$\frac{7}{8}$ "	$\frac{3}{4}$ "	12	1290	210

Tube.....17/32 inch in diameter.
 Dead Bolt.....Brass, 5/32 inch throw, 7/16x $\frac{1}{8}$ inches. Shoots right and left for either hand door.
 Levers.....2.
 Strike.....No. 49S, if so ordered, at an additional price.
 Keys.....2 flat steel nickel plated keys to each lock.
 Key Blank.....4144B.
 Packed.....One half dozen in a box, with screws, $\frac{1}{2}$ " 3-F.H.
 Weight.....(Dozen) 1 $\frac{1}{8}$ lbs.

INTER-KEYING
 See Page 295

SPECIAL PRICE INFORMATION

Wood.....Additional charge for thicknesses of wood, not listed above, for quantities less than 12 dozen.
 Alike.....No extra charge.
 All Different.....More than regular key changes at an extra charge.
 Masterkeyed.....Extra charge.




0749

310

Wardrobe Locks

Ward Construction




704L

No.	Size Inches	Material	Selvedge to Center of Key Pin	Ward	Regular Key Changes	Key Blank	Weight Dozen
704L	3 x 1 5/8	Steel	1 3/16"	1	1	4409K	2 5/8 lbs.

Dead Bolt..... 1/2 inch throw, 3/4 x 1/8 inches. Shoots right and left for either hand door.

Keys..... 1 malleable key.

Key Hole..... Cut for drawer and wardrobe.
Packed..... One dozen in a box, with screws, 5/8"-5-R.H.



702B

No.	Size Inches	Material	Selvedge to Center of Key Pin	Ward	Regular Key Changes	Key Blank	Weight Dozen
701B	2 x 1	Steel	1/2"	1	1	4359K	1 1/4 lbs.
702B	2 1/2 x 1 1/4	Steel	5/8"	1	1	4359K	1 1/2 lbs.

Dead Bolt..... No. 701B, 5/16 inch throw, 9/16 x 1/8 inches. Shoots right and left for either hand door.


No. 702B, 1/4 inch throw, 9/16 x 1/8 inches. Shoots right and left for either hand door.

Keys..... 1 malleable key.

Key Hole..... Cut for wardrobe and drawer.
Packed..... One dozen in a box, with screws.
701B-5/8"-3-R.H. screws
702B-5/8"-4-R.H. screws

Locker Locks

Secure Lever



581X

No.	Size Inches	Material	Selvedge to Center of Tube	Made Regular for Metal	Also Made for Metal No Extra Charge	Levers	Regular Key Changes	Possible Key Changes	Master-keyed Key Changes
581X	1 1/2 x 1 5/8	Steel, Cad'm Plated	7/8"	1/4"	3/4"	3	12	4090	4090

Tube..... Brass, 5/8 inch in diameter.

Latch Bolt..... Cast bronze, 7/32 inch throw.

Keys..... 2 flat steel nickel plated keys to each lock.

Key Blank..... 4120T.

Packed..... One dozen in a box.

Weight..... (Dozen) 3 1/2 lbs.

SPECIAL PRICE INFORMATION

Metal..... Additional charge for thicknesses of metal, not listed above, for quantities less than 12 dozen.

Alike..... Additional charge for quantities of less than 12 dozen.

All Different.... More than regular key changes at an extra charge.

Masterkeyed.... Extra charge.

Locker Locks

Secure Lever

No.	Size Inches	Material	Selvage to Center of Tube	Made Regular for Metal	Also Made for Metal No Extra Charge	Levers	Regular Key Changes	Possible Key Changes	Master-keyed Key Changes
582X	1½ x 1½	Steel, Cad'm Plated	⅞"	¼"	¾"	3	12	4090	4090

Tube.....Brass, ⅝ inch in diameter.

Dead Bolt.....Brass, 5/16 inch throw, ¾ x ¼ inches.

Keys.....2 flat steel nickel plated keys to each lock.

Key Blank.....4120T.

Packed.....One dozen in a box.

Weight.....(Dozen) 3½ lbs.


SPECIAL PRICE INFORMATION

Metal.....Additional charge for thicknesses of metal not listed above, for quantities less than 12 dozen.

Alike.....Additional charge for quantities of less than 12 dozen.

All Different.....More than regular key changes at an extra charge.

Masterkeyed.....Extra charge.



582X

Flush Panel Board Lock and Catch Combined

Secure Lever

LATCH BOLT — NOT SELF LOCKING

No.	Size Inches	Material	Made Regular for Metal	Backset	Levers	Regular Key Changes	Possible Key Changes	Key Blank
15630	3⅝ x 1½	Wrought Steel, Cad'm Plated	⅛"	1⅝"	1	1	5	4120B

Tube.....Brass, nickel plated, ¾ inch in diameter.

Latch Lip Bolt.....Spring, 3/16 inch throw, so constructed that it does not require the use of a strike on steel doors.

Hand.....Regularly furnished right hand, left hand when specified.


Ring Pull.....Brass forging, nickel plated, operates bolt when unlocked allowing the lock to be used as a catch.

Backset.....From edge of bolt (when retracted) to center of cylinder.

Keys.....2 flat steel nickel plated keys to each lock.

Packed.....One dozen in a box.

Weight.....(Dozen) 3½ lbs.



15630

Flush Panel Board Catch

LATCH BOLT

No.	Size Inches	Material	Made Regular for Metal	Backset	Weight Dozen
15631	1½ x 1½	Wrought Steel, Cadmium Plated	⅛"	1⅝"	2 lbs.


Latch Lip Bolt.....Spring 3/16 inch throw, so constructed that it does not require the use of a strike on steel doors.

Hand.....Regularly furnished right hand, left hand when specified.

Ring Pull.....Brass forging, nickel plated, operates the bolt.

Backset.....From edge of bolt (when retracted) to center of ring pull.

Packed.....One dozen in a box.




15631

312

General Utility Box Locks

Secure Lever



No.	Size Inches	Material	Levers	Regular Key Changes	Key Blank	Weight Dozen
1835	3¼ x 2¼	Steel, Brass Plated, Bright Finish	1	1	4140A	3 lbs.

Keys.....1 flat steel key, nickel plated to each lock. Packed..... One half dozen in a box.

Strikes

SIZE
OPENING



10S Wrought Brass

2½" x ½"
⅞" x ⅝"



11S Wrought Brass

2½" x 1⅜"
⅞" x ⅝"



26S Wrought Brass

1¾" x ⅞"
¾" x ⅝"

SIZE
OPENING



26½S Wrought Brass

1¾" x ⅞"
1⅞" x 1⅜"



41S Wrought Brass

2¾" x 2⅞"
1⅜" x ⅝"



49S Wrought Brass

49½S Wrought Steel

1½" x 1⅜"

SIZE
OPENING



52S Wrought Brass

2½" x 1⅜"



7S Wrought Brass

1⅞" x 1⅜"
⅞" x ⅝"




02290S Wrought Brass

½" x ⅞"
Diameter ⅞" out. ⅜" ins.

Escutcheons



2614 Brass, polished



2652 Brass, polished

Comparative List Cabinet Locks

313

Corbin Numbers Arranged Numerically

CORBIN	YALE	EAGLE
94 <i>Cansel</i>	S4	166
046		01896
47 $\frac{3}{4}$ C	S208	1984C
80 <i>Cansel</i>	S82	583
0140	SA160	6099
0142P	SA162	02126 $\frac{1}{2}$
0168	5541	03061
0370B	5511	03163
0370 $\frac{1}{2}$ B	5511S	03183
581x	R380 $\frac{1}{4}$	2220 $\frac{1}{2}$
582x	R381 $\frac{1}{2}$ L	2220
585		6094 $\frac{3}{4}$
0585		6094
590	R295C	1921
0590	RA295C	01921
590 $\frac{3}{4}$	R290	1921 $\frac{1}{2}$
0590 $\frac{3}{4}$	RA290	01921 $\frac{1}{4}$
592 $\frac{1}{2}$	R300	1816
0592 $\frac{1}{2}$	RA300	01816
0601	RA311	6001
622	R462	71
0666	5551 $\frac{1}{4}$	03202
0666 $\frac{1}{2}$	5551 $\frac{1}{4}$ S	03272
0676	RA396	01902
699	R360	1848
0699	RA360	01848
702B	W3 $\frac{1}{4}$	415 $\frac{1}{4}$
704	W7	510
0737	5611	03130
0738	519	
749	W100	1055
0749	WA100	1056
750	W102	7098
0750	WA102	6098
751	W103	7074
0751	WA103	6074
755 <i>Cansel</i>	W120	1986
0755 <i>0244</i>	WA120	01986
803	R279N	2173G
878 <i>Cansel</i>	R357 $\frac{1}{4}$	2152
1835	TS805A	
02065	9402	0701
02066	9660	711
02067	9780	721
02291	529	03377
15630	2430	
15631	2435	

The Finest Padlock in the World



EXTRUDED BRASS PIN-TUMBLER PADLOCKS

For generations, the Corbin Pin Tumbler Extruded Brass Padlock has and will continue to represent the highest of skill in workmanship with the finest of materials designed to outlast time.

The construction of these precision machined padlocks incorporates unique features (Corbin Patented)—Roller Bolt—Master Ring and others which assure smoother, easier, longer lasting operation and the utmost in locking security.

Truly, Corbin is your answer for the "finest padlocks that money can buy."

- | | | |
|-------------------------|--------------------|-----------------|
| • ATTRACTIVE APPEARANCE | • SUPERIOR QUALITY | • LONGER LIFE |
| • GREATEST SECURITY | • DURABILITY | • DEPENDABILITY |

CORBIN LOCK COMPANY OF CANADA, LTD.

BELLEVILLE — ONTARIO

**JUST LOOK
AT ALL THESE**

Features!




EXTRUDED BRASS BODIES

Shaped under tremendous hydraulic pressure, from ingots of heated brass. The metal is extremely tough, with no porosities or fractures.

HEAVY SPRINGS AND PINS

Originated by CORBIN are used in the Extruded Brass Padlocks. This increases the security, by resisting attempts to open by picking tools.




CHOICE OF SHACKLES

Hardened Steel, zinc plated, dichromate—rust resistant—saw and file proof, also brass shackles.

THE ROLLER BOLT

Securely holds the shackle in locked position. The patented Stainless Steel "Rollerbolt" deadlocks in shackle notch, prevents lock being "rapped" open.



THE INTERIOR VIEW OF CORBIN EXTRUDED BRASS PADLOCKS

The Pin Tumbler rust-proof mechanism consists of a series of pins of various lengths which are actuated by the bitting (or notching) of the key.

When the key is inserted in the irregular keyway of the Extruded Brass Padlock, it raises the pins to a length which brings a series of breaks (or divisions) in alignment with the surface of the plug, thereby releasing and permitting the key to turn it.

When the plug is turned, the cam operates the bolt and releases the shackle. The masterkey mechanism consists of a master ring which encircles the plug, and the pins extending through it into the plug.

When the masterkey is inserted, a new series of breaks (or divisions) in the pins come into play on the outer surface of the master ring, releasing it and permitting the ring and plug to rotate together, thus making it possible to release the shackle.

Thus in material and mechanism, Corbin combines superior features and maximum protection to present the utmost in Padlock Security.

Extruded Metal Padlocks

Pin Tumbler Cylinder

Made from a solid block of Extruded Brass, machined out to receive mechanism.

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Pin Tumblers	Regular Key Changes	Key Blank	Weight Dozen
	Width	Height	Case	Shackle	Diam. Inches	Height of Opening Inches				
2879	1 7/8	1 7/8	Extruded Brass, Satin Finish	Brass, Lacquered	1 3/64	1 5/32	4	All Different	4197 3/4 AC	2 1/2 lbs.
2879A	Same as No. 2879 but with hardened steel, zinc plated, dichromate shackle.									



2879

Keys..... Two nickel silver keys to each lock. **Packed.....** One lock in a box.
Chain..... Can be furnished with 9 inch chain. **Six in a carton.**
 In ordering affix "C" to number, thus:
 2879C, 2879AC.

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Pin Tumblers	Regular Key Changes	Key Blank	Weight Dozen
	Width	Height	Case	Shackle	Diam. Inches	Height of Opening Inches				
2880	1 3/8	1 1/4	Extruded Brass, Satin Finish	Brass, Lacquered	1 7/64	2 1/32	4	All Different	8632C	4 lbs.
2880 1/4	Same as No. 2880 but master-keyed with limited changes. Master-key blank No. 8632M.									
2880A	Same as No. 2880 but with hardened steel, zinc plated, dichromate shackle.									
2880 1/4 A	Same as No. 2880 1/4 but with hardened steel, zinc plated, dichromate shackle.									



2880

Keys..... Two nickel silver keys to each lock. **Packed.....** One lock in a box.
Chain..... Can be furnished with 9 inch chain. **Six in a carton.**
 In ordering affix "C" to number, thus:
 2880C, 2880 1/4 C, 2880AC, 2880 1/4 AC.

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Pin Tumblers	Regular Key Changes	Key Blank
	Width	Height	Case	Shackle	Diam. Inches	Height of Opening Inches			
2881	1 1/2	1 3/8	Extruded Brass, Satin Finish	Brass, Lacquered	5/16	5/8	5	All Different	8618C
2881 1/4	Same as No. 2881 but master-keyed, 1400 changes. Master-key blank No. 8618M.								
2881A	Same as No. 2881 but with hardened steel, zinc plated, dichromate shackle.								
2881 1/4 A	Same as No. 2881 1/4 but with hardened steel, zinc plated, dichromate shackle.								



2881

Keys..... Two nickel silver keys to each lock. **Weight.....** (Dozen) 5 1/2 lbs.
Chain..... Can be furnished with 9 inch chain. **Packed.....** One lock in a box.
 In ordering affix "C" to number, thus: **Six in a carton.**
 2881C, 2881 1/4 C, 2881AC, 2881 1/4 AC.

Extruded Metal Padlocks

Pin Tumbler Cylinder

Made from a solid block of Extruded Brass, machined out to receive mechanism.



2882

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Pin Tumblers	Regular Key Changes	Key Blank
	Width	Height	Case	Shackle	Diam. Inches	Height of Opening Inches			
2882	1 3/4	1 1/16	Extruded Brass, Satin Finish	Brass, Lacquered	1 1/32	3/4	5	All Different	77
2882 1/4	Same as No. 2882 but master-keyed, 6000 changes. Master-key blank No. 077.								
2882A	Same as No. 2882 but with hardened steel, zinc plated, dichromate shackle.								
2882 1/4 A	Same as No. 2882 1/4 but with hardened steel, zinc plated, dichromate shackle.								

Keys..... Two nickel silver keys to each lock.

Weight.... (Dozen) 8 3/8 lbs.

Chain..... Can be furnished with 9 inch chain.
In ordering affix "C" to number, thus:
2882C, 2882 1/4 C, 2882AC, 2882 1/4 AC.

Packed.... One lock in a box.
Six in a carton.



2883

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Pin Tumblers	Regular Key Changes	Key Blank
	Width	Height	Case	Shackle	Diam. Inches	Height of Opening Inches			
2883	2	1 5/8	Extruded Brass, Satin Finish	Brass, Lacquered	1 1/32	1 3/16	5	All Different	77
2883 1/4	Same as No. 2883 but master-keyed, 6000 changes. Master-key blank No. 077.								
2883A	Same as No. 2883 but with hardened steel, zinc plated, dichromate shackle.								
2883 1/4 A	Same as No. 2883 1/4 but with hardened steel, zinc plated, dichromate shackle.								

Keys..... Two nickel silver keys to each lock.

Weight.... (Dozen) 10 3/8 lbs.

Chain..... Can be furnished with 9 inch chain.
In ordering affix "C" to number, thus:
2883C, 2883 1/4 C, 2883AC, 2883 1/4 AC.

Packed.... One lock in a box.
Six in a carton.

Extruded Metal Padlocks

319

Pin Tumbler Cylinder

Made from a solid block of Extruded Brass, machined out to receive mechanism.

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Pin Tumblers	Regular Key Changes
	Width	Height	Case	Shackle	Diam. Inches	Height of Opening Inches		
2885A	2½	1⅞	Extruded Brass, Satin Finish	Hardened Steel, Zinc Plated Dichromate	1⅞ ₃₂	1⅞ ₃₂	5	All Different
2885¼A	Same as No. 2885A but master-keyed 6000 changes. Master-key blank No. 077.							



2885A

Keys...... Two nickel silver keys to each lock.
Chain...... Can be furnished with 9 inch chain.
 In ordering affix "C" to number, thus:
 2885AC, 2885¼AC.
Key Blank...... 77.
Weight...... (Dozen) 16⅞ lbs.
Packed...... One lock in a box. Six in a carton.

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Pin Tumblers	Regular Key Changes
			Case	Shackle	Diam. Inches	Height of Opening Inches		
	Width	Height						
2886A	3	2¼	Extruded Brass, Satin Finish	Hardened Steel, Zinc Plated Dichromate	⅞	1⅞	6	All Different
2886¼A	Same as No. 2886A but master-keyed 12,000 changes. Master-keyed blank No. 073¼.							



2886A


Keys...... Two nickel silver keys to each lock.
Chain...... Can be furnished with 9 inch chain.
 In ordering affix "C" to number, thus:
 2886AC, 2886¾AC.
Key Blank...... 73¼.
Weight...... (Dozen) 30¼ lbs.
Packed...... One lock in a box.

320

Solid Brass Padlocks

Pin Tumbler Cylinder

Made from a solid block of Extruded Brass, machined out to receive mechanism.



900

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Pin Tumblers	Regular Key Changes	Key Blank	Weight Dozen
			Case	Shackle	Diam. Inches	Height of Opening Inches				
	Width	Height								
0900	1 1/8	1 1/8	Solid Brass, Satin Finish	Brass, Lacquered	1 3/16	1 3/32	4	All Different	4197 1/4 AC	2 1/8 lbs.
900	Same as No. 0900 but with hardened steel, zinc plated, dichromate shackle.									

Keys.....Two nickel silver keys to each lock.
Chain.....Can be furnished with 9 inch chain.
In ordering affix "C" to number, thus:
0900C, 900C.

Packed.....One lock in a box.
Six in a carton.



902

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Pin Tumblers	Regular Key Changes	Key Blank	Weight Dozen
	Width	Height	Case	Shackle	Diam. Inches	Height of Opening Inches				
0902	1 3/8	1 1/4	Solid Brass, Satin Finish	Brass, Lacquered	1 7/16	2 1/32	4	All Different	8632C	4 lbs.
902	Same as No. 0902 but with hardened steel, zinc plated, dichromate shackle.									

Keys.....Two nickel silver keys to each lock.
Chain.....Can be furnished with 9 inch chain.
In ordering affix "C" to number, thus:
0902C, 902C.

Packed.....One lock in a box.
Six in a carton.



904

No.	Overall Size of Case Inches		Material and Finish		Shackle		Num- ber of Pin Tum- blers	Regular Key Changes	Key Blank
			Case	Shackle	Diam. Inches	Height of Open- ing Inches			
	Width	Height							
0904	1½	1⅜	Solid Brass, Satin Finish	Brass, Lacquered	5⁄16	1⅞ ₃₂	5	All Different	8618C
0904¼	Same as No. 0904 but master-keyed, limited changes, Master-key blank No. 8618M.								
904	Same as No. 0904 but with hardened steel, zinc plated, dichromate shackle.								
904¼	Same as No. 0904¼ but with hardened steel, zinc plated, dichromate shackle.								

Keys.....Two nickel silver keys to each lock.
Chain.....Can be furnished with 9 inch chain.
In ordering affix "C" to number, thus:
0904C, 0904 1/4 C, 904C, 904 1/4 C.

Weight.....(Dozen) 5 1/2 lbs.
Packed.....One lock in a box.
Six in a carton.

Solid Brass Padlocks

321

Pin Tumbler Cylinder

Made from a solid block of Extruded Brass, machined out to receive mechanism.

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Pin Tumblers	Regular Key Changes	Key Blank
			Case	Shackle	Diam. Inches	Height of Opening Inches			
	Width	Height							
0906	1¾	1⅞	Solid Brass, Satin Finish	Brass, Lacquered	11/32	¾	5	All Different	77
0906¼	Same as No. 0906 but master-keyed, limited changes. Master key blank No. 077.								
906	Same as No. 0906 but with hardened steel, zinc plated, dichromate shackle.								
906¼	Same as No. 0906¼ but with hardened steel, zinc plated, dichromate shackle.								



906

Keys.....Two nickel silver keys to each lock.
Chain.....Can be furnished with 9 inch chain.
 In ordering affix "C" to number, thus:
 0906C, 0906 1/4 C, 906C, 906 1/4 C.
Weight.....(Dozen) 8 5/8 lbs.
Packed.....One lock in a box. Six in a carton.

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Pin Tumblers	Regular Key Changes	Key Blank
			Case	Shackle	Diam. Inches	Height of Opening Inches			
	Width	Height							
0908	2	1 $\frac{5}{8}$	Solid Brass, Satin Finish	Brass, Lacquered	1 $\frac{1}{32}$	1 $\frac{3}{16}$	5	All Different	77
0908 $\frac{1}{4}$	Same as No. 0908 but master-keyed, limited changes. Master-key blank No. 077.								
908	Same as No. 0908 but with hardened steel, zinc plated, dichromate shackle.								
908 $\frac{1}{4}$	Same as No. 0908 $\frac{1}{4}$ but with hardened steel, zinc plated, dichromate shackle.								



908

Keys.....Two nickel silver keys to each lock.
Chain.....Can be furnished with 9 inch chain.
 In ordering affix "C" to number, thus:
 0908C, 0908 1/4 C, 908C, 908 1/4 C.
Weight.....(Dozen) 10 3/8 lbs.
Packed.....One lock in a box. Six in a carton.

322

Extruded Metal Padlocks

Pin Tumbler Cylinder

Made from a solid block of Extruded Brass, machined out to receive mechanism.



2880AH

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Pin Tumblers	Regular Key Changes	Key Blank	Weight Dozen
	Width	Height	Case	Shackle	Diam. Inches	Height of Opening Inches				
2880AH	1 $\frac{3}{8}$	1 $\frac{1}{4}$	Extruded Brass, Satin Finish	Hardened Steel, Zinc Plated Dichromate	1 $\frac{7}{64}$	2 $\frac{1}{2}$	4	All Different	8632C	4 $\frac{7}{8}$ lbs.
2882AH	1 $\frac{3}{4}$	1 $\frac{1}{16}$	Extruded Brass, Satin Finish	Hardened Steel, Zinc Plated Dichromate	1 $\frac{1}{32}$	2 $\frac{1}{2}$	5	All Different	77	9 $\frac{3}{4}$ lbs.
2883AH	2	1 $\frac{5}{8}$	Extruded Brass, Satin Finish	Hardened Steel, Zinc Plated Dichromate	1 $\frac{1}{32}$	2 $\frac{9}{16}$	5	All Different	77	11 $\frac{1}{2}$ lbs.

Keys..... Two nickel silver keys to each lock.

Packed..... One lock in a box. Six in a carton.
Can be Master-keyed.



2881AH

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Pin Tumblers	Regular Key Changes	Key Blank	Weight Dozen
	Width	Height	Case	Shackle	Diam. Inches	Height of Opening Inches				
2881AH	1 $\frac{1}{2}$	1 $\frac{3}{8}$	Extruded Brass, Satin Finish	Hardened Steel, Zinc Plated Dichromate	$\frac{3}{16}$	2 $\frac{1}{2}$	5	All Different	8618C	7 lbs.
2881AW	Same as No. 2881AH but with height of shackle opening 1 $\frac{1}{4}$ ".									6 $\frac{1}{4}$ lbs.
2881AX	Same as No. 2881AH but with height of shackle opening 1 $\frac{3}{4}$ ".									6 $\frac{3}{4}$ lbs.

Keys..... Two nickel silver keys to each lock.

Packed..... One lock in a box. Six in a carton.
Can be Master-keyed

Solid Brass Padlocks Pin Tumbler Cylinder

Made from a solid block of Extruded Brass, machined out to receive mechanism.

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Pin Tumblers	Regular Key Changes	Key Blank	Weight Dozen
	Width	Height	Case	Shackle	Diam. Inches	Height of Opening Inches				
904H	1½	1¾	Solid Brass, Satin Finish	Hardened Steel, Zinc Plated Dichromate	⅝	2½	5	All Different	8618C	6½ lbs.
904W	Same as No. 904H but with height of shackle opening 1¼".									6¼ lbs.
904X	Same as No. 904H but with height of shackle opening 1¾".									6¾ lbs.

Keys.....Two nickel silver keys to each lock.
Packed.....One lock in a box. Six in a carton.
Can be Master-keyed


No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Pin Tumblers	Regular Key Changes	Key Blank	Weight Dozen
	Width	Height	Case	Shackle	Diam. Inches	Height of Opening Inches				
906H	1¾	1⅞	Solid Brass, Satin Finish	Hardened Steel, Zinc Plated Dichromate	11/32	2½	5	All Different	77	9¾ lbs.

Keys.....Two nickel silver keys to each lock.
Packed.....One lock in a box. Six in a carton.
Can be Master-keyed



Die Cast Padlocks Pin Tumbler Cylinder

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Pin Tumblers	Regular Key Changes	Key Blank	Weight Dozen
	Width	Height	Case	Shackle	Diam. Inches	Height of Opening Inches				
P95H	1¾	1⅞	Solid Die Cast, Black Wrinkle Japan	Hardened Steel, Zinc Plated Dichromate	9/32	1	5	All Different 4000	8618C	4¾ lbs.
P95E	Same as No. P95H but with height of shackle opening 1½"									5¼ lbs.
P95L	Same as No. P95H but with height of shackle opening 2"									5½ lbs.

Keys.....Two nickel silver keys to each lock.
Masterkeying... Can be masterkeyed if desired with limited key changes.
Masterkey blank No. 8618CM.
In ordering add ¼ to number, thus:
P95¼H, P95¼E, P95¼L.
Packed.....One-half dozen in a box.
Can be Master-keyed



904H



906H



P95H

324

Die Cast Padlocks Pin Tumbler Cylinder



P95

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Pin Tumblers	Regular Key Changes	Key Blank	Weight Dozen
			Case	Shackle	Diam. Inches	Height of Opening Inches				
P95	1 3/4	1 3/16	Solid Die Cast Black Wrinkle Japan	Hardened Steel Zinc Plated Dichromate	9/32	7/8	5	All Different 4900	8618C	4 3/4 lbs.
P95 1/4	Same as No. P95 but master-keyed with limited changes. Key blank No. 8618C. Master-key blank No. 8618CM.									

Keys.....Two nickel silver keys to each lock.
Chain.....Can be furnished with 9 inch steel chain.
In ordering affix "C" to number, thus: P95C, P95 1/4 C.
Packed.....One-half dozen in a box.

Disc Tumbler



9913X

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Disc Tumblers	Regular Key Changes	Regular Stock Goods Key Blank
			Case	Shackle	Diam. Inches	Height of Opening Inches			
9913X	1 1/16	1 1/2	Solid Die Cast, Gray Wrinkle Japan	Hardened Steel, Zinc Plated Dichromate	1/4	3/4	5	200	8658BV
9913 1/4 X	Same as No. 9913X but master-keyed, 200 changes.								

Keys.....Two brass nickel plated keys to each lock.
Chain.....Can be furnished with 9 inch chain.
In ordering affix "C" to number, thus: 9913XC, 9913 1/4 XC.
Weight.....(Dozen) 4 1/2 lbs.
Packed.....One-half dozen in a box.

Key Blanks for Masterkeyed Locks

Service KeyNo. 8658BPS MasterkeyNo. 8658BPM

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Disc Tumblers	Regular Key Changes	Regular Stock Goods Key Blank
			Case	Shackle	Diam. Inches	Height of Opening Inches			
9914X	1 3/4	1 5/8	Solid Die Cast, Gray Wrinkle Japan	Hardened Steel, Zinc Plated Dichromate	9/32	7/8	5	200	3658BV
9914 1/4 X	Same as No. 9914X but master-keyed 200 changes.								

Keys.....Two brass nickel plated keys to each lock.
Chain.....Can be furnished with 9 inch chain.
In ordering affix "C" to number, thus: 9914XC, 9914 1/4 XC.
Weight.....(Dozen) 6 lbs. Packed.....One-half dozen in a box.
Key Blanks for Masterkeyed Locks
Service KeyNo. 8658BPS MasterkeyNo. 8658BPM



9914X

Die Cast Padlocks

325


Disc Tumbler

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Disc Tumblers	Regular Key Changes	Regular Stock Goods Key Blank	Weight Dozen
			Case	Shackle	Diam. Inches	Height of Open- ing Inches				
	Width	Height								
9913XH	1 $\frac{1}{16}$	1 $\frac{1}{2}$	Solid Die Cast, Gray Wrinkle Japan	Hardened Steel, Zinc Plated Dichromate	$\frac{1}{4}$	1 $\frac{1}{4}$	5	200	8658BV	5 lbs.
9913XK	Same as No. 9913XH but with height of shackle opening 5".									5 $\frac{3}{4}$ lbs.
9913XP	Same as No. 9913XH but with height of shackle opening 2 $\frac{3}{4}$ ".									5 $\frac{1}{8}$ lbs.

Keys.....Two brass, nickel plated keys to each lock.
Packed.....One-half dozen in a box.

KEY BLANKS FOR MASTERKEYED LOCKS

Service Key.....No. 8658BPS. Masterkey.....No. 8658BPM.




9913XK

No.	Overall Size of Case Inches		Material and Finish		Shackle		Number of Disc Tumblers	Regular Key Changes	Regular Stock Goods Key Blank	Weight Dozen
	Width	Height	Case	Shackle	Diam. Inches	Height of Opening Inches				
9913XR	1 $\frac{1}{16}$	1 $\frac{1}{2}$	Solid Die Cast, Gray Wrinkle Japan	Hardened Steel, Zinc Plated Dichromate	$\frac{1}{4}$	2 $\frac{3}{4}$	5	200	8658BV	5 lbs.

Keys.....Two brass, nickel plated keys to each lock.
Packed.....One-half dozen in a box.
Brass Clevis.....Steel nickel plated ring and brass tag.

KEY BLANKS FOR MASTERKEYED LOCKS


Service Key.....No. 8658BPS Masterkey.....No. 8658BPM



9913XR

Wrought Steel Padlocks

Secure Lever



2951G

No.	Overall Size of Case Inches		Material and Finish		Shackle	Regular Key Changes	Possible Key Changes	Master-keyed Key Changes
	Width	Height	Case	Shackle				
2951G	2½	2¾	Steel, Cadmium Plated	Malleable Iron, Cadmium Plated	15/16	12	4 Lcv. 252 6 Lev. 4090	4090

Interior Parts, All Brass.

Keys.....Two nickel plated steel keys to each lock.

Chain.....Can be furnished with chain. In ordering affix "C" to number, 2951GC with 15 inch steel cadmium plated chain.

Levers.....4.

Key Blank...5558.

Weight.....(Dozen) 9¾ lbs.

Packed.....One-half dozen in a box.

Masterkeyed, Extra charge.

Die Cast Padlocks

Ward Mechanism



9954

No.	Overall Size of Case Inches		Material and Finish		Shackle		Regular Key Changes	Key Blank	Weight Dozen
	Width	Height	Case	Shackle	Diam. Inches	Height of Opening Inches			
9954	1½	1¾	Die Cast,	Steel, Nickel Plated	¾	25/32	4	8715	2¾ lbs.


Keys.....Two corrugated steel keys to each lock.

Packed.....One-half dozen in a box.

Chain.....Can be furnished with 9 inch chain. In ordering affix "C" to number, thus: 9954C.

Padlock Chain Assemblies

FOR ROUND WIRE SHACKLE PADLOCKS



Type for 9913X, 9914X and P95



Type for Extruded Metal Padlocks

The above type of Padlock Chain is for attaching to round wire padlock shackles without the necessity of drilling and riveting.

The chains are 9 inches in length, attached with a clevis, these chains can be supplied in brass, or cadmium plated steel.

The chain and clevis are supplied assembled and may be easily applied to the padlock by slipping the clevis over the toe end of the shackle to its normal position where it can be properly adjusted, so as to prevent it slipping around the bend of the shackle. **PACKED ONE DOZEN IN A BOX.**

328


Name Plates



011

No.	Overall Size Inches	Material and Finish	Card Space Inches	Gauge of Metal	Weight Gross
09	2 x 1/2	Wrought Brass, Dipped and Lacquered	1 5/8 x 7/16	.012	5/8 lb.
010	2 1/2 x 1/2	" " " " "	2 1/8 x 7/16	.012	3/4 lb.
011	3 x 1/2	" " " " "	2 5/8 x 7/16	.012	1 lb.
012	3 1/2 x 1/2	" " " " "	3 3/8 x 7/16	.012	1 1/8 lbs.

Regularly packed *12* dozen in a box, without pins.



020

No.	Overall Size Inches	Material and Finish	Card Space Inches	Gauge of Metal	Weight Gross
018	2 1/2 x 3/4	Wrought Brass, Dipped and Lacquered	2 1/8 x 1 1/16	.012	1 3/8 lbs.
020	3 1/2 x 3/4	" " " " "	3 3/8 x 1 1/16	.012	1 15/16 lbs.

Regularly packed *12* dozen in a box, without pins.

Card Holders



1912 1/4 H

No.	Overall Size Inches	Material and Finish	Card Space Inches	Gauge of Metal	Weight Gross
1912 1/4 H	2 1/2 x 1 1/4	Brass, Dipped and Lacquered....	1 15/16 x 1	.022	1 5/8 lbs.

Regularly packed three dozen in a box, without pins.



1935 1/4 H

No.	Overall Size Inches	Material and Finish	Card Space Inches	Gauge of Metal	Weight Gross
1935 1/4 H	3 x 1 1/4	Brass, Dipped and Lacquered....	2 7/16 x 1	.022	2 3/4 lbs.
1935 A	3 x 1 1/4	Steel, Bright Finish	2 7/16 x 1	.035	3 lbs.

Regularly packed three dozen in a box, without pins.



1932 1/4 H

No.	Overall Size Inches	Material and Finish	Card Space Inches	Gauge of Metal	Weight Gross
1932 1/4 H	2 1/4 x 1 3/16	Brass, Dipped and Lacquered. ...	1 11/16 x 5/8	.022	1 lb.

Regularly packed three dozen in a box, without pins or screws.

Card Holders

No.	Overall Size Inches	Material and Finish	Card Space Inches	Gauge of Metal	Weight
1911 $\frac{1}{4}$ H	2 $\frac{3}{8}$ x 1 $\frac{1}{4}$	Brass, Dipped and Lacquered	1 $\frac{11}{16}$ x 1 $\frac{1}{8}$.022	1 $\frac{3}{4}$ lbs. <i>gross</i>



1911 $\frac{1}{4}$ H

Regularly packed three dozen in a box, without pins.

No.	Overall Size Inches	Material and Finish	Card Space Inches	Gauge of Metal	Weight Gross
1913 $\frac{1}{4}$ H	3 $\frac{3}{16}$ x 1 $\frac{1}{2}$	Brass, Dipped and Lacquered	2 $\frac{13}{16}$ x 1 $\frac{1}{4}$.028	3 lbs.
1913A	3 $\frac{3}{16}$ x 1 $\frac{1}{2}$	Steel, Bright Finish	2 $\frac{13}{16}$ x 1 $\frac{1}{4}$.035	4 lbs.



1913 $\frac{1}{4}$ H

Regularly packed three dozen in a box, without pins.


No.	Overall Size Inches	Material and Finish	Card Space Inches	Gauge of Metal	Weight Gross
1893 $\frac{1}{4}$ H	4 $\frac{1}{4}$ x 1	Brass, Dipped and Lacquered	3 $\frac{5}{8}$ x $\frac{7}{8}$.028	3 $\frac{1}{8}$ lbs.



1893 $\frac{1}{4}$ H

Regularly packed three dozen in a box, without pins.


No.	Overall Size Inches	Material and Finish	Card Space Inches	Gauge of Metal	Weight Gross
1914 $\frac{1}{4}$ H	3 $\frac{13}{16}$ x 2 $\frac{1}{2}$	Brass, Dipped and Lacquered	2 $\frac{13}{16}$ x 2 $\frac{1}{16}$.032	4 lbs.



1914 $\frac{1}{4}$ H

Regularly packed three dozen in a box, without pins or screws.

No.	Overall Size Inches	Material and Finish	Card Space Inches	Gauge of Metal	Weight Gross
1894 $\frac{1}{4}$ H	5 $\frac{1}{8}$ x 2 $\frac{1}{4}$	Brass, Dipped and Lacquered	4 $\frac{1}{2}$ x 1 $\frac{1}{8}$.028	4 $\frac{1}{4}$ lbs.



1894 $\frac{1}{4}$ H

Regularly packed three dozen in a box, without pins or screws.

Card Holders and Pulls



1906 1/4 H

No.	Overall Size Inches	Material and Finish	Card Space Inches	Gauge of Metal	Weight Gross
1906 1/4 H	1 13/16 x 7/8	Brass, Dipped and Lacquered.....	1 13/16 x 3/4	.028	2 lbs.


Regularly packed three dozen in a box, without pins or screws.



1902 1/4 H

No.	Overall Size Inches	Material and Finish	Card Space Inches	Gauge of Metal	Weight Gross
1902 1/4 H	2 1/2 x 1 1/4	Brass, Dipped and Lacquered.....	1 13/16 x 1 1/16	.028	3 lbs.


Regularly packed three dozen in a box, without pins or screws.



1925 1/4 H

No.	Overall Size Inches	Material and Finish	Card Space Inches	Gauge of Metal	Weight Gross
1925 1/4 H	3 x 1 1/4	Brass, Dipped and Lacquered.....	2 7/16 x 1	.028	4 7/8 lbs.
1925 A	3 x 1 1/4	Steel, Bright Finish.....	2 7/16 x 1	.035	5 lbs.

Regularly packed three dozen in a box, without pins or screws.



1903 1/4 H

No.	Overall Size Inches	Material and Finish	Card Space Inches	Gauge of Metal	Weight Gross
1903 1/4 H	3 3/16 x 1 1/2	Brass, Dipped and Lacquered.....	2 7/8 x 1 1/4	.028	5 lbs.

Regularly packed three dozen in a box, without pins or screws.

Box Pulls

331

No.	Overall Size Inches	Material and Finish	Pro-jection Inches	Clear-ance Inches	Gauge of Metal	Weight Gross
1929 $\frac{1}{4}$	2 $\frac{1}{16}$ x $\frac{3}{8}$	Wrought Steel, Brass Plated.	$\frac{43}{64}$	$\frac{5}{8}$.049	2 $\frac{3}{16}$ lbs.



1929 $\frac{1}{4}$

Regularly packed one gross in a box, without screws.

No.	Overall Size Inches	Material and Finish	Pro-jection Inches	Clear-ance Inches	Gauge of Metal	Weight
1919 $\frac{1}{4}$	2 $\frac{5}{8}$ x $\frac{3}{8}$	Wrought Steel, Brass Plated.	$\frac{3}{4}$	$\frac{45}{64}$.049	3 lbs. <i>per gross.</i>



1919 $\frac{1}{4}$

Regularly packed one gross in a box, without screws.

No.	Overall Size Inches	Material and Finish	Pro-jection Inches	Clear-ance Inches	Gauge of Metal	Weight
1909 $\frac{1}{4}$	3 $\frac{1}{2}$ x $\frac{3}{8}$	Wrought Steel, Brass Plated.	$\frac{51}{64}$	$\frac{3}{4}$.049	3 $\frac{1}{2}$ lbs. <i>per gross</i>



1909 $\frac{1}{4}$

Regularly packed one gross in a box, without screws.

Stay and Support Hinges

No.	Size Length Overall Open Inches	Material and Finish	Width Inches	Gauge of Metal	Weight Dozen Pairs
1751	7 $\frac{3}{4}$	Steel, Brass Plated	$\frac{3}{8}$.058	1 $\frac{5}{8}$ lbs.



1751


Regularly packed one dozen pairs in a box, without screws.
Screw holes countersunk for $\frac{5}{8}$ "-4-F.H. screws.

Suit Case Catches

335


No.	Overall Size Inches	Material and Finish	Gauge of Metal	Packed in a Box	Weight Gross
1809 $\frac{1}{2}$	$1\frac{15}{16} \times 1\frac{7}{16}$	Steel , Brass Plated025	6 dozen	5 lbs.
1809 $\frac{3}{4}$	$1\frac{15}{16} \times 1\frac{7}{16}$	" Nickel Plated025	6 dozen	5 lbs.

Regularly packed, without screws.

1809 $\frac{1}{2}$


No.	Overall Size Inches	Material and Finish	Gauge of Metal	Packed in a Box	Weight Gross
1771 $\frac{1}{2}$	$2\frac{3}{4} \times 1\frac{1}{2}$	Steel , Brass Plated032	6 dozen	$\frac{3}{4}$ lb.
1771 $\frac{3}{4}$	$2\frac{3}{4} \times 1\frac{1}{2}$	" Nickel Plated032	6 dozen	$\frac{3}{4}$ lb.

Regularly packed, without screws.

1771 $\frac{1}{2}$


No.	Overall Size Inches	Material and Finish	Gauge of Metal	Packed in a Box	Weight Gross
1778 $\frac{1}{2}$	$3\frac{5}{8} \times 1\frac{15}{16}$	Steel , Brass Plated025	3 dozen	$1\frac{3}{4}$ lbs.
1778 $\frac{3}{4}$	$3\frac{5}{8} \times 1\frac{15}{16}$	" Nickel Plated025	3 dozen	$1\frac{3}{4}$ lbs.

Regularly packed, without screws.

1778 $\frac{1}{2}$

336

Friction Catches




3236

No.	Length Inches	Material and Finish	Diam- eter Inches	Adjust- ment Inches	Regular Strike No.	Weight Dozen
3236	$\frac{3}{8}$	All Brass, with Steel Ball Center.	$\frac{1}{4}$	$\frac{1}{16}$	2571	1 $\frac{1}{2}$ oz.

Six dozen in a box, with screws, ~~$\frac{1}{4}$ "-3-F.H.~~


3/8" - 2 F.H.



3237

No.	Length Inches	Material and Finish	Diam- eter Inches	Adjust- ment Inches	Regular Strike No.	Weight Dozen
3237	$\frac{1}{2}$	All Brass, with Steel Ball Center.	$\frac{3}{8}$	$\frac{1}{4}$	2568	4 $\frac{3}{4}$ oz.
3238	$\frac{3}{4}$	All Brass, with Steel Ball Center.	$\frac{3}{8}$	$\frac{1}{4}$	2568	5 oz.


Can be furnished with flat brass strike no lip No. 2575, if so desired.
Three dozen in a box, with screws, $\frac{1}{2}$ "-3-F.H.



3239

No.	Length Inches	Material and Finish	Diam- eter Inches	Adjust- ment Inches	Regular Strike No.	Weight Dozen
3239	1	All Brass, with Steel Ball Center	$\frac{5}{8}$	$\frac{3}{8}$	2577	1 lb.


Can be furnished with brass lip strike No. 2578, if so desired.
One dozen in a box, with screws, $\frac{5}{8}$ "-8-F.H.



3232

No.	Size Inches	Material and Finish	Regular Strike No.	Gauge of Metal	Weight Dozen
3232	2 $\frac{3}{8}$ x $\frac{3}{4}$	Wrought Brass, Polished045	14 oz.

Three dozen in a box, with screws, $\frac{1}{2}$ "-5-F.H.



E03234

No.	Catch Inches	Material and Finish Wrought Steel		Spring Strike Inches	Packed in a Box	Weight Dozen
		Catch	Spring Strike			
E03234	1 $\frac{1}{4}$ x $\frac{3}{8}$	Nickel Plated	Nickel Plated	$\frac{3}{4}$ x 1 $\frac{3}{8}$	3 Doz.	8 oz.


Three dozen in a box, with screws, $\frac{1}{4}$ "-4-R.H.

Suit Case Catches

335

No.	Overall Size Inches	Material and Finish	Gauge of Metal	Packed in a Box	Weight Gross
1809½	1½ ¹⁵ / ₁₆ x 1 ⁷ / ₁₆	Steel, Brass Plated025	6 dozen	5 lbs.
1809¾	1½ ¹⁵ / ₁₆ x 1 ⁷ / ₁₆	" Nickel Plated025	6 dozen	5 lbs.


Regularly packed, without screws.



1809½

No.	Overall Size Inches	Material and Finish	Gauge of Metal	Packed in a Box	Weight Gross
1771½	2¾ x 1½	Steel, Brass Plated032	6 dozen	4 lbs. 3¼ lb.
1771¾	2¾ x 1½	" Nickel Plated032	6 dozen	3¼ lb.

Regularly packed, without screws.



1771½

No.	Overall Size Inches	Material and Finish	Gauge of Metal	Packed in a Box	Weight Gross
1778½	3⅝ x 1 ¹⁵ / ₁₆	Steel, Brass Plated025	3 dozen	1¾ lbs.
1778¾	3⅝ x 1 ¹⁵ / ₁₆	" Nickel Plated025	3 dozen	1¾ lbs.

Regularly packed, without screws.



1778½

Box Hinges

333

No.	Size Open Inches	Material and Finish	Length of Joint	Gauge of Metal	Weight Dozen Pairs
02111	1 $\frac{5}{8}$ x $\frac{1}{2}$	Brass, Dipped and Lacquered	$\frac{3}{16}$ in.	.022	3 oz.



02111

Regularly packed three dozen pairs in a box, without screws.

No.	Size Open Inches	Material and Finish	Length of Joint	Gauge of Metal	Weight Dozen Pairs
02114	1 $\frac{3}{16}$ x 1 $\frac{1}{8}$	Brass, Dipped and Lacquered	$\frac{3}{4}$ in.	.025	$\frac{5}{8}$ lb.
2114	1$\frac{7}{16}$ x 1$\frac{1}{8}$	Steel, Brass Plated	$\frac{3}{4}$ in.	.025	$\frac{5}{8}$ lb.



02114

Regularly packed three dozen pairs in a box, without screws.

No.	Size Open Inches	Material and Finish	Length of Joint	Gauge of Metal	Weight Dozen Pairs
02112	2 $\frac{5}{8}$ x $\frac{5}{8}$	Brass, Dipped and Lacquered	$\frac{5}{8}$ in.	.025	5 oz.



02112

Regularly packed three dozen pairs in a box, without screws.

No.	Size Open Inches	Material and Finish	Length of Joint	Gauge of Metal	Weight Dozen Pairs
02109	2 $\frac{7}{8}$ x $\frac{1}{2}$	Brass, Dipped and Lacquered	$\frac{1}{2}$ in.	.049	$\frac{5}{8}$ lb.




02109

Regularly packed three dozen pairs in a box, without screws.

334

Case Corners



03700

No.	Overall Size Inches	Material and Finish	Gauge of Metal	Packed in a Box	Weight Gross
03700	1¼x1¼x½	Brass, Dipped and Lacquered.025	6 dozen	1¼ lbs.

Regularly packed, without pins or screws.



03715

No.	Overall Size Inches	Material and Finish	Gauge of Metal	Packed in a Box	Weight Gross
03715	1¾x1¾x¾	Brass, Dipped and Lacquered.025	6 dozen	3½ lbs.

Regularly packed, without pins or screws.



03703

No.	Overall Size Inches	Material and Finish	Gauge of Metal	Packed in a Box	Weight Gross
03703	1⅞x1⅞x1⅞	Brass, Dipped and Lacquered.032	6 dozen	6⅝ lbs.

Regularly packed, without pins or screws.

Nickel Silver Key Blanks

GENUINE CORBIN BLANKS

337



77



*077



73 1/4



74



*073 1/4



67



*067



63 1/4



64



*063 1/4



57



*057



53 1/4



54



*053 1/4


*Cut keys only.

THREE DOZEN IN A BOX.

338

Wrought Steel Key Blanks

NICKEL-PLATED



†Cast Iron


Cast Iron Key



*Cut Keys Only

Master Key Blanks


WROUGHT STEEL NICKEL PLATED




THREE DOZEN IN A BOX

Nickel Silver Key Blanks

339



Brass Key Blanks Nickel Plated



THREE DOZEN IN A BOX



SAFETY FIRST... AND LAST
WHEN CORBIN LOCKED

340


Flat Steel Cabinet Key Blanks




4103B




4106



4116B



4120B




4120T



4122½

Number	4103B	4106	4116B	4120B	4120T	4122½
Thickness	.035	.049	.049	.049	.065	.065
Width	.200	.220	.265	.300	.300	.300



4122½B




4127B



4127½B



4128B



4130B



4145½B

Number	4122½B	4127B	4127½B	4128B	4130B	4145½B
Thickness	.049	.042	.042	.042	.049	.042
Width	.300	.300	.300	.300	.312	.245


The above keys are furnished regularly bright, but not polished or plated.

SIX DOZEN IN A BOX.



Flat Steel Cabinet Key Blanks

341



Number	4131A	4131B	4132A	4140T	4141B	4144B
Thickness	.072	.049	.072	.058	.042	.042
Width	.312	.312	.312	.245	.245	.245




Number	4145 1/2 C	4773	4151	4152	6031	4740
Thickness	.049	.058	.049	.049	.065	.042
Width	.245		.345	.345	.275	.250

The above blanks are furnished regularly bright, but not polished or plated.
SIX DOZEN IN A BOX.

342 Malleable Iron Cabinet Key Blanks



4359K



4491




4780




4784

Cabinet Key Blanks



4204
Wrought Steel

Cabinet Key




4409K
Malleable Iron

THREE DOZEN IN A BOX

Automatic Key Duplicator

343

COMPLETE WITH CUTTERS



9101A

FOR DUPLICATING PIN TUMBLER KEYS AND FLAT KEYS

The machine is 9½ inches long, 7 inches wide and 5½ inches high overall.

The operation is simple. The key which is to be duplicated is clamped in the upper vise on the traveling carriage, and the key blank in the lower vise. The carriage is then moved slowly from left to right as each cut is completed by cutter. Cutter can be operated either by hand or belt.

The revolving cutter duplicates exactly the cuts in the key which is used as a pattern.

Detailed instructions for operation, adjustment, change of cutters, etc., are furnished with each machine.

Packed one in a case, weight 17 lbs. each.

Equipment

Furnished with milling cutter for pin tumbler keys, gauges for pin tumbler keys with only one shoulder and small wires of various size for keys irregular in form for blocking up so they will fit securely in vise.

Wires can also be used under small keys to bring them high enough to cut without cutting into vise.

Two saws .035 and .060 thick with guides are furnished for cutting flat keys.